



TITLE V/STATE OPERATING PERMIT

Issue Date: May 23, 2019 Effective Date: November 30, 2022
Revision Date: November 30, 2022 Expiration Date: May 31, 2024

Revision Type: Amendment

In accordance with the provisions of the Air Pollution Control Act, the Act of January 8, 1960, P.L. 2119, as amended, and 25 Pa. Code Chapter 127, the Owner, [and Operator if noted] (hereinafter referred to as permittee) identified below is authorized by the Department of Environmental Protection (Department) to operate the air emission source(s) more fully described in this permit. This Facility is subject to all terms and conditions specified in this permit. Nothing in this permit relieves the permittee from its obligations to comply with all applicable Federal, State and Local laws and regulations.

The regulatory or statutory authority for each permit condition is set forth in brackets. All terms and conditions in this permit are federally enforceable applicable requirements unless otherwise designated as "State-Only" or "non-applicable" requirements.

TITLE V Permit No: 36-05025

Federal Tax Id - Plant Code: 72-0378240-1

Owner Information

Name: TEXAS EASTERN TRANS LP

Mailing Address: SUITE 1100, 915 N ELDRIDGE PKWY

HOUSTON, TX 77079-2703

Plant Information

Plant: TEXAS EASTERN TRANS LP/MARIETTA

Location: 36 Lancaster County 36925 East Donegal Township

SIC Code: 4922 Trans. & Utilities - Natural Gas Transmission

Responsible Official

Name: ROBERT STEEDE

Title: VP ENVIRO COMPLIANCE

Phone (713) 627 - 5731 Email: Robert.Steede@enbridge.com

Permit Contact Person

Name: PHILLIP WIEDENFELD, P.E.
Title: ENVIRONMENTAL SUPERVISOR

Phone: (713) 627 - 6608 Email: phillip.wiedenfeld@enbridge.com

[Signature]

WILLIAM R. WEAVER, SOUTHCENTRAL REGION AIR PROGRAMMANAGER



SECTION A. Table of Contents

Section A. Facility/Source Identification

Table of Contents Site Inventory List

Section B. General Title V Requirements

#001	Definitions
#()()	Denninons

- #002 Prohibition of Air Pollution
- #003 Property Rights
- #004 Permit Expiration
- #005 Permit Renewal
- #006 Transfer of Ownership or Operational Control
- #007 Inspection and Entry
- #008 Compliance Requirements
- #009 Need to Halt or Reduce Activity Not a Defense
- #010 Duty to Provide Information
- #011 Reopening and Revising the Title V Permit for Cause
- #012 Reopening a Title V Permit for Cause by EPA
- #013 Operating Permit Application Review by the EPA
- #014 Significant Operating Permit Modifications
- #015 Minor Operating Permit Modifications
- #016 Administrative Operating Permit Amendments
- #017 Severability Clause
- #018 Fee Payment
- #019 Authorization for De Minimis Emission Increases
- #020 Reactivation of Sources
- #021 Circumvention
- #022 Submissions
- #023 Sampling, Testing and Monitoring Procedures
- #024 Recordkeeping Requirements
- #025 Reporting Requirements
- #026 Compliance Certification
- #027 Operational Flexibility
- #028 Risk Management
- #029 Approved Economic Incentives and Emission Trading Programs
- #030 Permit Shield
- #031 Reporting
- #032 Report Format

Section C. Site Level Title V Requirements

- C-I: Restrictions
- C-II: Testing Requirements
- C-III: Monitoring Requirements
- C-IV: Recordkeeping Requirements
- C-V: Reporting Requirements
- C-VI: Work Practice Standards
- C-VII: Additional Requirements
- C-VIII: Compliance Certification
- C-IX: Compliance Schedule

Section D. Source Level Title V Requirements

- D-I: Restrictions
- D-II: Testing Requirements
- D-III: Monitoring Requirements
- D-IV: Recordkeeping Requirements
- D-V: Reporting Requirements



SECTION A. Table of Contents

D-VI: Work Practice Standards D-VII: Additional Requirements

Note: These same sub-sections are repeated for each source!

Section E. Source Group Restrictions

E-I: Restrictions

E-II: Testing Requirements E-III: Monitoring Requirements E-IV: Recordkeeping Requirements E-V: Reporting Requirements

E-VI: Work Practice Standards

E-VII: Additional Requirements

Section F. Alternative Operating Scenario(s)

F-I: Restrictions

F-II: Testing Requirements F-III: Monitoring Requirements F-IV: Recordkeeping Requirements F-V: Reporting Requirements F-VI: Work Practice Standards F-VII: Additional Requirements

Section G. Emission Restriction Summary


Section H. Miscellaneous





SECTION A. Site Inventory List

Source ID	Source Name	Capacity/	Throughput	Fuel/Material
038	AREA FUGITIVE EMISSIONS			
043	SOLAR MARS 100-T15000S TURB (30507/13,699HP)	107.200	MCF/HR	Natural Gas
044	CATERPILLAR EMERGENCY GEN 30536	4.700	MCF/HR	Natural Gas
045	PARTS WASHER, 16 GAL			
046	SOLAR TURBINE 2 (7,700 HP)	68.400	MMBTU/HR	
		67.100	MCF/HR	NATURAL GAS
047	SOLAR TURBINE 3 (7,700 HP)	68.400	MMBTU/HR	
		67.100	MCF/HR	NATURAL GAS
C046	OXIDATION CATALYST, TURBINE 2			
C047	OXIDATION CATALYST, TURBINE 3			
FM001	NATURAL GAS PIPELINE			
S43	STACK, SOLAR MARS			
S44	STACK, CATEPILLAR GEN			
S46	STACK, SOLAR TURBINE 2			
S47	STACK, SOLAR TURBINE 3			
Z38	STACK, FUGITIVE EMISSIONS			



36-05025 TEXAS EASTERN TRANS LP/MARIETTA



SECTION B. General Title V Requirements

#001 [25 Pa. Code § 121.1]

Definitions

Words and terms that are not otherwise defined in this permit shall have the meanings set forth in Section 3 of the Air Pollution Control Act (35 P.S. § 4003) and 25 Pa. Code § 121.1.....

#002 [25 Pa. Code § 121.7]

Prohibition of Air Pollution

No person may permit air pollution as that term is defined in the act.

#003 [25 Pa. Code § 127.512(c)(4)]

Property Rights

This permit does not convey property rights of any sort, or any exclusive privileges.

#004 [25 Pa. Code § 127.446(a) and (c)]

Permit Expiration

This operating permit is issued for a fixed term of five (5) years and shall expire on the date specified on Page 1 of this permit. The terms and conditions of the expired permit shall automatically continue pending issuance of a new Title V permit, provided the permittee has submitted a timely and complete application and paid applicable fees required under 25 Pa. Code Chapter 127, Subchapter I and the Department is unable, through no fault of the permittee, to issue or deny a new permit before the expiration of the previous permit. An application is complete if it contains sufficient information to begin processing the application, has the applicable sections completed and has been signed by a responsible official.

#005 [25 Pa. Code §§ 127.412, 127.413, 127.414, 127.446(e), 127.503 & 127.704(b)]

Permit Renewal

- (a) An application for the renewal of the Title V permit shall be submitted to the Department at least six (6) months, and not more than 18 months, before the expiration date of this permit. The renewal application is timely if a complete application is submitted to the Department's Regional Air Manager within the timeframe specified in this permit condition.
- (b) The application for permit renewal shall include the current permit number, the appropriate permit renewal fee, a description of any permit revisions and off-permit changes that occurred during the permit term, and any applicable requirements that were promulgated and not incorporated into the permit during the permit term. The fees shall be made payable to "The Commonwealth of Pennsylvania Clean Air Fund" and submitted with the fee form to the respective regional office.
- (c) The renewal application shall also include submission of proof that the local municipality and county, in which the facility is located, have been notified in accordance with 25 Pa. Code § 127.413. The application for renewal of the Title V permit shall also include submission of compliance review forms which have been used by the permittee to update information submitted in accordance with either 25 Pa. Code § 127.412(b) or § 127.412(j).
- (d) The permittee, upon becoming aware that any relevant facts were omitted or incorrect information was submitted in the permit application, shall promptly submit such supplementary facts or corrected information during the permit renewal process. The permittee shall also promptly provide additional information as necessary to address any requirements that become applicable to the source after the date a complete renewal application was submitted but prior to release of a draft permit.

#006 [25 Pa. Code §§ 127.450(a)(4) & 127.464(a)]

Transfer of Ownership or Operational Control

- (a) In accordance with 25 Pa. Code § 127.450(a)(4), a change in ownership or operational control of the source shall be treated as an administrative amendment if:
 - (1) The Department determines that no other change in the permit is necessary;
- (2) A written agreement has been submitted to the Department identifying the specific date of the transfer of permit responsibility, coverage and liability between the current and the new permittee; and,
 - (3) A compliance review form has been submitted to the Department and the permit transfer has been approved by





the Department.

(b) In accordance with 25 Pa. Code § 127.464(a), this permit may not be transferred to another person except in cases of transfer-of-ownership which are documented and approved to the satisfaction of the Department.

#007 [25 Pa. Code § 127.513, 35 P.S. § 4008 and § 114 of the CAA]

Inspection and Entry

- (a) Upon presentation of credentials and other documents as may be required by law for inspection and entry purposes, the permittee shall allow the Department of Environmental Protection or authorized representatives of the Department to perform the following:
- (1) Enter at reasonable times upon the permittee's premises where a Title V source is located or emissions related activity is conducted, or where records are kept under the conditions of this permit;
 - (2) Have access to and copy or remove, at reasonable times, records that are kept under the conditions of this permit;
- (3) Inspect at reasonable times, facilities, equipment including monitoring and air pollution control equipment, practices, or operations regulated or required under this permit;
- (4) Sample or monitor, at reasonable times, substances or parameters, for the purpose of assuring compliance with the permit or applicable requirements as authorized by the Clean Air Act, the Air Pollution Control Act, or the regulations promulgated under the Acts.
- (b) Pursuant to 35 P.S. § 4008, no person shall hinder, obstruct, prevent or interfere with the Department or its personnel in the performance of any duty authorized under the Air Pollution Control Act.
- (c) Nothing in this permit condition shall limit the ability of the EPA to inspect or enter the premises of the permittee in accordance with Section 114 or other applicable provisions of the Clean Air Act.

#008 [25 Pa. Code §§ 127.25, 127.444, & 127.512(c)(1)]

Compliance Requirements

- (a) The permittee shall comply with the conditions of this permit. Noncompliance with this permit constitutes a violation of the Clean Air Act and the Air Pollution Control Act and is grounds for one (1) or more of the following:
 - (1) Enforcement action
 - (2) Permit termination, revocation and reissuance or modification
 - (3) Denial of a permit renewal application
- (b) A person may not cause or permit the operation of a source, which is subject to 25 Pa. Code Article III, unless the source(s) and air cleaning devices identified in the application for the plan approval and operating permit and the plan approval issued to the source are operated and maintained in accordance with specifications in the applications and the conditions in the plan approval and operating permit issued by the Department. A person may not cause or permit the operation of an air contamination source subject to 25 Pa. Code Chapter 127 in a manner inconsistent with good operating practices.
- (c) For purposes of Sub-condition (b) of this permit condition, the specifications in applications for plan approvals and operating permits are the physical configurations and engineering design details which the Department determines are essential for the permittee's compliance with the applicable requirements in this Title V permit.

#009 [25 Pa. Code § 127.512(c)(2)]

Need to Halt or Reduce Activity Not a Defense

It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.



#010 [25 Pa. Code §§ 127.411(d) & 127.512(c)(5)]

Duty to Provide Information

- (a) The permittee shall furnish to the Department, within a reasonable time, information that the Department may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit, or to determine compliance with the permit.
- (b) Upon request, the permittee shall also furnish to the Department copies of records that the permittee is required to keep by this permit, or for information claimed to be confidential, the permittee may furnish such records directly to the Administrator of EPA along with a claim of confidentiality.

#011 [25 Pa. Code §§ 127.463, 127.512(c)(3) & 127.542]

Reopening and Revising the Title V Permit for Cause

- (a) This Title V permit may be modified, revoked, reopened and reissued or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance does not stay a permit condition.
- (b) This permit may be reopened, revised and reissued prior to expiration of the permit under one or more of the following circumstances:
- (1) Additional applicable requirements under the Clean Air Act or the Air Pollution Control Act become applicable to a Title V facility with a remaining permit term of three (3) or more years prior to the expiration date of this permit. The Department will revise the permit as expeditiously as practicable but not later than 18 months after promulgation of the applicable standards or regulations. No such revision is required if the effective date of the requirement is later than the expiration date of this permit, unless the original permit or its terms and conditions has been extended.
- (2) Additional requirements, including excess emissions requirements, become applicable to an affected source under the acid rain program. Upon approval by the Administrator of EPA, excess emissions offset plans for an affected source shall be incorporated into the permit.
- (3) The Department or the EPA determines that this permit contains a material mistake or inaccurate statements were made in establishing the emissions standards or other terms or conditions of this permit.
- (4) The Department or the Administrator of EPA determines that the permit must be revised or revoked to assure compliance with the applicable requirements.
- (c) Proceedings to revise this permit shall follow the same procedures which apply to initial permit issuance and shall affect only those parts of this permit for which cause to revise exists. The revision shall be made as expeditiously as practicable.
- (d) Regardless of whether a revision is made in accordance with (b)(1) above, the permittee shall meet the applicable standards or regulations promulgated under the Clean Air Act within the time frame required by standards or regulations.

#012 [25 Pa. Code § 127.543]

Reopening a Title V Permit for Cause by EPA

As required by the Clean Air Act and regulations adopted thereunder, this permit may be modified, reopened and reissued, revoked or terminated for cause by EPA in accordance with procedures specified in 25 Pa. Code § 127.543.

#013 [25 Pa. Code § 127.522(a)]

Operating Permit Application Review by the EPA

The applicant may be required by the Department to provide a copy of the permit application, including the compliance plan, directly to the Administrator of the EPA. Copies of title V permit applications to EPA, pursuant to 25 PA Code §127.522(a), shall be submitted, if required, to the following EPA e-mail box:

R3_Air_Apps_and_Notices@epa.gov

Please place the following in the subject line: TV [permit number], [Facility Name].

36-05025



SECTION B. General Title V Requirements

#014 [25 Pa. Code § 127.541]

Significant Operating Permit Modifications

When permit modifications during the term of this permit do not qualify as minor permit modifications or administrative amendments, the permittee shall submit an application for significant Title V permit modifications in accordance with 25 Pa. Code § 127.541. Notifications to EPA, pursuant to 25 PA Code §127.522(a), if required, shall be submitted, to the following EPA e-mail box:

R3_Air_Apps_and_Notices@epa.gov

Please place the following in the subject line: TV [permit number], [Facility Name].

#015 [25 Pa. Code §§ 121.1 & 127.462]

Minor Operating Permit Modifications

The permittee may make minor operating permit modifications (as defined in 25 Pa. Code §121.1), on an expedited basis, in accordance with 25 Pa. Code §127.462 (relating to minor operating permit modifications). Notifications to EPA, pursuant to 25 PA Code §127.462(c), if required, shall be submitted, to the following EPA e-mail box:

R3_Air_Apps_and_Notices@epa.gov

Please place the following in the subject line: TV [permit number], [Facility Name].

#016 [25 Pa. Code § 127.450]

Administrative Operating Permit Amendments

(a) The permittee may request administrative operating permit amendments, as defined in 25 Pa. Code §127.450(a). Copies of request for administrative permit amendment to EPA, pursuant to 25 PA Code §127.450(c)(1), if required, shall be submitted to the following EPA e-mail box:

R3_Air_Apps_and_Notices@epa.gov

Please place the following in the subject line: TV [permit number], [Facility Name].

(b) Upon final action by the Department granting a request for an administrative operating permit amendment covered under §127.450(a)(5), the permit shield provisions in 25 Pa. Code § 127.516 (relating to permit shield) shall apply to administrative permit amendments incorporated in this Title V Permit in accordance with §127.450(c), unless precluded by the Clean Air Act or the regulations thereunder.

#017 [25 Pa. Code § 127.512(b)]

Severability Clause

The provisions of this permit are severable, and if any provision of this permit is determined by the Environmental Hearing Board or a court of competent jurisdiction, or US EPA to be invalid or unenforceable, such a determination will not affect the remaining provisions of this permit.

#018 [25 Pa. Code §§ 127.704, 127.705 & 127.707]

Fee Payment

- (a) The permittee shall pay fees to the Department in accordance with the applicable fee schedules in 25 Pa. Code Chapter 127, Subchapter I (relating to plan approval and operating permit fees). The applicable fees shall be made payable to "The Commonwealth of Pennsylvania Clean Air Fund" with the permit number clearly indicated and submitted to the respective regional office.
- (b) Emission Fees. The permittee shall, on or before September 1st of each year, pay applicable annual Title V emission fees for emissions occurring in the previous calendar year as specified in 25 Pa. Code § 127.705. The permittee is not required to pay an emission fee for emissions of more than 4,000 tons of each regulated pollutant emitted from the facility.
- (c) As used in this permit condition, the term "regulated pollutant" is defined as a VOC, each pollutant regulated under Sections 111 and 112 of the Clean Air Act and each pollutant for which a National Ambient Air Quality Standard has been promulgated, except that carbon monoxide is excluded.





- (d) Late Payment. Late payment of emission fees will subject the permittee to the penalties prescribed in 25 Pa. Code § 127.707 and may result in the suspension or termination of the Title V permit. The permittee shall pay a penalty of fifty percent (50%) of the fee amount, plus interest on the fee amount computed in accordance with 26 U.S.C.A. § 6621(a)(2) from the date the emission fee should have been paid in accordance with the time frame specified in 25 Pa. Code § 127.705(c).
- (e) The permittee shall pay an annual operating permit maintenance fee according to the following fee schedule established in 25 Pa. Code § 127.704(d) on or before December 31 of each year for the next calendar year.
- (1) Eight thousand dollars (\$8,000) for calendar years 2021—2025.
- (2) Ten thousand dollars (\$10,000) for calendar years 2026—2030.
- (3) Twelve thousand five hundred dollars (\$12,500) for the calendar years beginning with 2031.

#019 [25 Pa. Code §§ 127.14(b) & 127.449]

Authorization for De Minimis Emission Increases

- (a) This permit authorizes de minimis emission increases from a new or existing source in accordance with 25 Pa. Code §§ 127.14 and 127.449 without the need for a plan approval or prior issuance of a permit modification. The permittee shall provide the Department with seven (7) days prior written notice before commencing any de minimis emissions increase that would result from either: (1) a physical change of minor significance under § 127.14(c)(1); or (2) the construction, installation, modification or reactivation of an air contamination source. The written notice shall:
 - (1) Identify and describe the pollutants that will be emitted as a result of the de minimis emissions increase.
- (2) Provide emission rates expressed in tons per year and in terms necessary to establish compliance consistent with any applicable requirement.

The Department may disapprove or condition de minimis emission increases at any time.

- (b) Except as provided below in (c) and (d) of this permit condition, the permittee is authorized during the term of this permit to make de minimis emission increases (expressed in tons per year) up to the following amounts without the need for a plan approval or prior issuance of a permit modification:
- (1) Four tons of carbon monoxide from a single source during the term of the permit and 20 tons of carbon monoxide at the facility during the term of the permit.
- (2) One ton of NOx from a single source during the term of the permit and 5 tons of NOx at the facility during the term of the permit.
- (3) One and six-tenths tons of the oxides of sulfur from a single source during the term of the permit and 8.0 tons of oxides of sulfur at the facility during the term of the permit.
- (4) Six-tenths of a ton of PM10 from a single source during the term of the permit and 3.0 tons of PM10 at the facility during the term of the permit. This shall include emissions of a pollutant regulated under Section 112 of the Clean Air Act unless precluded by the Clean Air Act or 25 Pa. Code Article III.
- (5) One ton of VOCs from a single source during the term of the permit and 5.0 tons of VOCs at the facility during the term of the permit. This shall include emissions of a pollutant regulated under Section 112 of the Clean Air Act unless precluded by the Clean Air Act or 25 Pa. Code Article III.
- (c) In accordance with § 127.14, the permittee may install the following minor sources without the need for a plan approval:
- (1) Air conditioning or ventilation systems not designed to remove pollutants generated or released from other sources.
 - (2) Combustion units rated at 2,500,000 or less Btu per hour of heat input.





- (3) Combustion units with a rated capacity of less than 10,000,000 Btu per hour heat input fueled by natural gas supplied by a public utility, liquefied petroleum gas or by commercial fuel oils which are No. 2 or lighter, viscosity less than or equal to 5.82 c St, and which meet the sulfur content requirements of 25 Pa. Code § 123.22 (relating to combustion units). For purposes of this permit, commercial fuel oil shall be virgin oil which has no reprocessed, recycled or waste material added.
 - (4) Space heaters which heat by direct heat transfer.
 - (5) Laboratory equipment used exclusively for chemical or physical analysis.
 - (6) Other sources and classes of sources determined to be of minor significance by the Department.
- (d) This permit does not authorize de minimis emission increases if the emissions increase would cause one or more of the following:
- (1) Increase the emissions of a pollutant regulated under Section 112 of the Clean Air Act except as authorized in Subparagraphs (b)(4) and (5) of this permit condition.
- (2) Subject the facility to the prevention of significant deterioration requirements in 25 Pa. Code Chapter 127, Subchapter D and/or the new source review requirements in Subchapter E.
- (3) Violate any applicable requirement of the Air Pollution Control Act, the Clean Air Act, or the regulations promulgated under either of the acts.
- (4) Changes which are modifications under any provision of Title I of the Clean Air Act and emission increases which would exceed the allowable emissions level (expressed as a rate of emissions or in terms of total emissions) under the Title V permit.
- (e) Unless precluded by the Clean Air Act or the regulations thereunder, the permit shield described in 25 Pa. Code § 127.516 (relating to permit shield) shall extend to the changes made under 25 Pa. Code § 127.449 (relating to de minimis emission increases).
- (f) Emissions authorized under this permit condition shall be included in the monitoring, recordkeeping and reporting requirements of this permit.
- (g) Except for de minimis emission increases allowed under this permit, 25 Pa. Code § 127.449, or sources and physical changes meeting the requirements of 25 Pa. Code § 127.14, the permittee is prohibited from making physical changes or engaging in activities that are not specifically authorized under this permit without first applying for a plan approval. In accordance with § 127.14(b), a plan approval is not required for the construction, modification, reactivation, or installation of the sources creating the de minimis emissions increase.
- (h) The permittee may not meet de minimis emission threshold levels by offsetting emission increases or decreases at the same source.

#020 [25 Pa. Code §§ 127.11a & 127.215]

Reactivation of Sources

- (a) The permittee may reactivate a source at the facility that has been out of operation or production for at least one year, but less than or equal to five (5) years, if the source is reactivated in accordance with the requirements of 25 Pa. Code §§ 127.11a and 127.215. The reactivated source will not be considered a new source.
- (b) A source which has been out of operation or production for more than five (5) years but less than 10 years may be reactivated and will not be considered a new source if the permittee satisfies the conditions specified in 25 Pa. Code § 127.11a(b).

#021 [25 Pa. Code §§ 121.9 & 127.216]

Circumvention

(a) The owner of this Title V facility, or any other person, may not circumvent the new source review requirements of 25 Pa. Code Chapter 127, Subchapter E by causing or allowing a pattern of ownership or development, including the



phasing, staging, delaying or engaging in incremental construction, over a geographic area of a facility which, except for the pattern of ownership or development, would otherwise require a permit or submission of a plan approval application.

(b) No person may permit the use of a device, stack height which exceeds good engineering practice stack height, dispersion technique or other technique which, without resulting in reduction of the total amount of air contaminants emitted, conceals or dilutes an emission of air contaminants which would otherwise be in violation of this permit, the Air Pollution Control Act or the regulations promulgated thereunder, except that with prior approval of the Department, the device or technique may be used for control of malodors.

#022 [25 Pa. Code §§ 127.402(d) & 127.513(1)]

Submissions

(a) Reports, test data, monitoring data, notifications and requests for renewal of the permit shall be submitted to the:

Regional Air Program Manager

PA Department of Environmental Protection

(At the address given on the permit transmittal letter, or otherwise notified)

(b) Any report or notification for the EPA Administrator or EPA Region III should be addressed to:

Enforcement & Compliance Assurance Division Air, RCRA and Toxics Branch (3ED21) Four Penn Center 1600 John F. Kennedy Boulevard Philadelphia, PA 19103-2852

The Title V compliance certification shall be emailed to EPA at R3_APD_Permits@epa.gov.

(c) An application, form, report or compliance certification submitted pursuant to this permit condition shall contain certification by a responsible official as to truth, accuracy, and completeness as required under 25 Pa. Code § 127.402(d). Unless otherwise required by the Clean Air Act or regulations adopted thereunder, this certification and any other certification required pursuant to this permit shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate and complete.

#023 [25 Pa. Code §§ 127.441(c) & 127.463(e); Chapter 139; & 114(a)(3), 504(b) of the CAA]

Sampling, Testing and Monitoring Procedures

- (a) The permittee shall perform the emissions monitoring and analysis procedures or test methods for applicable requirements of this Title V permit. In addition to the sampling, testing and monitoring procedures specified in this permit, the Permittee shall comply with any additional applicable requirements promulgated under the Clean Air Act after permit issuance regardless of whether the permit is revised.
- (b) The sampling, testing and monitoring required under the applicable requirements of this permit, shall be conducted in accordance with the requirements of 25 Pa. Code Chapter 139 unless alternative methodology is required by the Clean Air Act (including §§ 114(a)(3) and 504(b)) and regulations adopted thereunder.

#024 [25 Pa. Code §§ 127.511 & Chapter 135]

Recordkeeping Requirements

- (a) The permittee shall maintain and make available, upon request by the Department, records of required monitoring information that include the following:
 - (1) The date, place (as defined in the permit) and time of sampling or measurements.
 - (2) The dates the analyses were performed.
 - (3) The company or entity that performed the analyses.
 - (4) The analytical techniques or methods used.





- (5) The results of the analyses.
- (6) The operating conditions as existing at the time of sampling or measurement.
- (b) The permittee shall retain records of the required monitoring data and supporting information for at least five (5) years from the date of the monitoring sample, measurement, report or application. Supporting information includes the calibration data and maintenance records and original strip-chart recordings for continuous monitoring instrumentation, and copies of reports required by the permit.
- (c) The permittee shall maintain and make available to the Department upon request, records including computerized records that may be necessary to comply with the reporting, recordkeeping and emission statement requirements in 25 Pa. Code Chapter 135 (relating to reporting of sources). In accordance with 25 Pa. Code Chapter 135, § 135.5, such records may include records of production, fuel usage, maintenance of production or pollution control equipment or other information determined by the Department to be necessary for identification and quantification of potential and actual air contaminant emissions. If direct recordkeeping is not possible or practical, sufficient records shall be kept to provide the needed information by indirect means.

#025 [25 Pa. Code §§ 127.411(d), 127.442, 127.463(e) & 127.511(c)]

Reporting Requirements

- (a) The permittee shall comply with the reporting requirements for the applicable requirements specified in this Title V permit. In addition to the reporting requirements specified herein, the permittee shall comply with any additional applicable reporting requirements promulgated under the Clean Air Act after permit issuance regardless of whether the permit is revised.
- (b) Pursuant to 25 Pa. Code § 127.511(c), the permittee shall submit reports of required monitoring at least every six (6) months unless otherwise specified in this permit. Instances of deviations (as defined in 25 Pa. Code § 121.1) from permit requirements shall be clearly identified in the reports. The reporting of deviations shall include the probable cause of the deviations and corrective actions or preventative measures taken, except that sources with continuous emission monitoring systems shall report according to the protocol established and approved by the Department for the source. The required reports shall be certified by a responsible official.
- (c) Every report submitted to the Department under this permit condition shall comply with the submission procedures specified in Section B, Condition #022(c) of this permit.
- (d) Any records, reports or information obtained by the Department or referred to in a public hearing shall be made available to the public by the Department except for such records, reports or information for which the permittee has shown cause that the documents should be considered confidential and protected from disclosure to the public under Section 4013.2 of the Air Pollution Control Act and consistent with Sections 112(d) and 114(c) of the Clean Air Act and 25 Pa. Code § 127.411(d). The permittee may not request a claim of confidentiality for any emissions data generated for the Title V facility.

#026 [25 Pa. Code § 127.513]

Compliance Certification

- (a) One year after the date of issuance of the Title V permit, and each year thereafter, unless specified elsewhere in the permit, the permittee shall submit to the Department and EPA Region III a certificate of compliance with the terms and conditions in this permit, for the previous year, including the emission limitations, standards or work practices. This certification shall include:
- (1) The identification of each term or condition of the permit that is the basis of the certification.
- (2) The compliance status.
- (3) The methods used for determining the compliance status of the source, currently and over the reporting period.
- (4) Whether compliance was continuous or intermittent.
- (b) The compliance certification shall be postmarked or hand-delivered no later than thirty days after each anniversary of the date of issuance of this Title V Operating Permit, or on the submittal date specified elsewhere in the permit, to the Department in accordance with the submission requirements specified in Section B, Condition #022 of this permit. The Title V compliance certification shall be emailed to EPA at R3_APD_Permits@epa.gov.



#027 [25 Pa. Code § 127.3]

Operational Flexibility

The permittee is authorized to make changes within the Title V facility in accordance with the following provisions in 25 Pa. Code Chapter 127 which implement the operational flexibility requirements of Section 502(b)(10) of the Clean Air Act and Section 6.1(i) of the Air Pollution Control Act:

- (1) Section 127.14 (relating to exemptions)
- (2) Section 127.447 (relating to alternative operating scenarios)
- (3) Section 127.448 (relating to emissions trading at facilities with federally enforceable emissions caps)
- (4) Section 127.449 (relating to de minimis emission increases)
- (5) Section 127.450 (relating to administrative operating permit amendments)
- (6) Section 127.462 (relating to minor operating permit amendments)
- (7) Subchapter H (relating to general plan approvals and operating permits)

#028 [25 Pa. Code §§ 127.441(d), 127.512(i) and 40 CFR Part 68]

Risk Management

- (a) If required by Section 112(r) of the Clean Air Act, the permittee shall develop and implement an accidental release program consistent with requirements of the Clean Air Act, 40 CFR Part 68 (relating to chemical accident prevention provisions) and the Federal Chemical Safety Information, Site Security and Fuels Regulatory Relief Act (P.L. 106-40).
- (b) The permittee shall prepare and implement a Risk Management Plan (RMP) which meets the requirements of Section 112(r) of the Clean Air Act, 40 CFR Part 68 and the Federal Chemical Safety Information, Site Security and Fuels Regulatory Relief Act when a regulated substance listed in 40 CFR § 68.130 is present in a process in more than the listed threshold quantity at the Title V facility. The permittee shall submit the RMP to the federal Environmental Protection Agency according to the following schedule and requirements:
- (1) The permittee shall submit the first RMP to a central point specified by EPA no later than the latest of the following:
- (i) Three years after the date on which a regulated substance is first listed under § 68.130; or,
- (ii) The date on which a regulated substance is first present above a threshold quantity in a process.
- (2) The permittee shall submit any additional relevant information requested by the Department or EPA concerning the RMP and shall make subsequent submissions of RMPs in accordance with 40 CFR § 68.190.
- (3) The permittee shall certify that the RMP is accurate and complete in accordance with the requirements of 40 CFR Part 68, including a checklist addressing the required elements of a complete RMP.
- (c) As used in this permit condition, the term "process" shall be as defined in 40 CFR § 68.3. The term "process" means any activity involving a regulated substance including any use, storage, manufacturing, handling, or on-site movement of such substances or any combination of these activities. For purposes of this definition, any group of vessels that are interconnected, or separate vessels that are located such that a regulated substance could be involved in a potential release, shall be considered a single process.
- (d) If the Title V facility is subject to 40 CFR Part 68, as part of the certification required under this permit, the permittee shall:
- (1) Submit a compliance schedule for satisfying the requirements of 40 CFR Part 68 by the date specified in 40 CFR § 68.10(a); or,
- (2) Certify that the Title V facility is in compliance with all requirements of 40 CFR Part 68 including the registration and submission of the RMP.





- (e) If the Title V facility is subject to 40 CFR Part 68, the permittee shall maintain records supporting the implementation of an accidental release program for five (5) years in accordance with 40 CFR § 68.200.
- (f) When the Title V facility is subject to the accidental release program requirements of Section 112(r) of the Clean Air Act and 40 CFR Part 68, appropriate enforcement action will be taken by the Department if:
- (1) The permittee fails to register and submit the RMP or a revised plan pursuant to 40 CFR Part 68.
- (2) The permittee fails to submit a compliance schedule or include a statement in the compliance certification required under Section B, Condition #026 of this permit that the Title V facility is in compliance with the requirements of Section 112(r) of the Clean Air Act, 40 CFR Part 68, and 25 Pa. Code § 127.512(i).

#029 [25 Pa. Code § 127.512(e)]

Approved Economic Incentives and Emission Trading Programs

No permit revision shall be required under approved economic incentives, marketable permits, emissions trading and other similar programs or processes for changes that are provided for in this Title V permit.

#030 [25 Pa. Code §§ 127.516, 127.450(d), 127.449(f) & 127.462(g)]

Permit Shield

- (a) The permittee's compliance with the conditions of this permit shall be deemed in compliance with applicable requirements (as defined in 25 Pa. Code § 121.1) as of the date of permit issuance if either of the following applies:
 - (1) The applicable requirements are included and are specifically identified in this permit.
- (2) The Department specifically identifies in the permit other requirements that are not applicable to the permitted facility or source.
- (b) Nothing in 25 Pa. Code § 127.516 or the Title V permit shall alter or affect the following:
- (1) The provisions of Section 303 of the Clean Air Act, including the authority of the Administrator of the EPA provided thereunder.
 - (2) The liability of the permittee for a violation of an applicable requirement prior to the time of permit issuance.
 - (3) The applicable requirements of the acid rain program, consistent with Section 408(a) of the Clean Air Act.
 - (4) The ability of the EPA to obtain information from the permittee under Section 114 of the Clean Air Act.
- (c) Unless precluded by the Clean Air Act or regulations thereunder, final action by the Department incorporating a significant permit modification in this Title V Permit shall be covered by the permit shield at the time that the permit containing the significant modification is issued.

#031 [25 Pa. Code §135.3]

Reporting

- (a) The permittee shall submit by March 1 of each year an annual emissions report for the preceding calendar year. The report shall include information for all active previously reported sources, new sources which were first operated during the preceding calendar year, and sources modified during the same period which were not previously reported. All air emissions from the facility should be estimated and reported.
- (b) A source owner or operator may request an extension of time from the Department for the filing of an annual emissions report, and the Department may grant the extension for reasonable cause.

#032 [25 Pa. Code §135.4]

Report Format

Emissions reports shall contain sufficient information to enable the Department to complete its emission inventory. Emissions reports shall be made by the source owner or operator in a format specified by the Department.





SECTION C. Site Level Requirements

I. RESTRICTIONS.

Emission Restriction(s).

001 [25 Pa. Code §123.1]

Prohibition of certain fugitive emissions

The permittee shall not allow the emission into the outdoor atmosphere of any fugitive air contaminant from a source other than the following:

- (a) Construction or demolition of buildings or structures.
- (b) Grading, paying and maintenance of roads and streets.
- (c) Use of roads and streets. Emissions from material in or on trucks, railroad cars and other vehicular equipment are not considered as emissions from use of roads and streets.
- (d) Clearing of land.
- (e) Stockpiling of materials.
- (f) Open burning operations.
- (g) Sources and classes of sources other than those identified in above part (a) through (e), for which the operator has obtained a determination from the Department that fugitive emissions from the source, after appropriate control, meet the following requirements:
- (1) The emissions are of minor significance with respect to causing air pollution;
- (2) The emissions are not preventing or interfering with the attainment or manitenance of any ambient air standard.

002 [25 Pa. Code §123.2]

Fugitive particulate matter

The permittee shall not allow the emission of particulate matter into the outdoor atmosphere from a source specified in 25 Pa. Code Section 123.1 if the emissions are visible at the point the emissions pass outside the permittee's property.

003 [25 Pa. Code §123.31]

Limitations

The permittee shall not allow the emission into the outdoor atmosphere of any malodorous air contaminants from any source in such a manner that the malodors are detectable outside the permittee's property.

004 [25 Pa. Code §123.41]

Limitations

The permittee shall not allow the emission into the outdoor atmosphere of visible air contaminants in such a manner that the opacity of the emission is either of the following:

- (a) Equal to or greater than 20 percent for a period or periods aggregating more than three minutes in any one hour.
- (b) Equal to or greater than 60 percent at any time.

005 [25 Pa. Code §123.42]

Exceptions

The emission limitations of §123.41 shall not apply when:

- (a) The presence of uncombined water is the only reason for failure of the emission to meet the limitation.
- (b) The emission results from the operation of equipment used solely to train and test persons in observing the opacity of visible emissions.
- (c) The emission results from sources specified in Section C, Condition #001 (relating to prohibition of certain fugitive



SECTION C. Site Level Requirements

emissions).

006 [25 Pa. Code §127.512]

Operating permit terms and conditions.

The permittee shall limit the facility's actual emissions to below the following levels based on any consecutive 12-month period:

- a) 100 tons of NOx
- b) 50 tons of VOC
- c) 25 tons of any combination of HAPS
- d) 10 tons of a single HAP

II. TESTING REQUIREMENTS.

007 [25 Pa. Code §127.441]

Operating permit terms and conditions.

The Department reserves the right to require exhaust stack testing of the sources referenced in this permit to measure emissions for purposes including verification of permit condition compliance and estimation of annual emissions.

008 [25 Pa. Code §127.441]

Operating permit terms and conditions.

- (a) Unless otherwise approved in writing by DEP, the permittee shall do the following:
- (1) Conduct performance testing in accordance with the provisions of 25 Pa Code Section 139 and the Department's Source Testing Manual and any applicable federal regulations.
- (2) Submit to DEP a test protocol for review and approval at least 90 calendar days prior to commencing an emissions testing program, and not conduct the test that is the subject of the protocol until the protocol has been approved by DEP.
- (3) If DEP finds deficiencies in the protocol, the permittee shall provide a response to DEP addressing the deficiencies within 30 days of being notified of the deficiencies.
- (4) Complete the performance test within 90 days of DEP's approval of the test protocol.
- (b) Pursuant to 25 Pa. Code § 139.3 at least 15 calendar days prior to commencing an emission testing program, the permittee shall notify the appropriate Regional Office and the Division of Source Testing and Monitoring of the date and time of the performance test. Notification shall not be made without prior receipt of a protocol acceptance letter from the Department.
- (c) Pursuant to 25 Pa. Code Section 139.53(a)(3) within 15 calendar days after completion of the on-site testing portion of an emission test program, if a complete test report has not yet been submitted, an electronic mail notification shall be sent to the Department's Division of Source Testing and Monitoring and the appropriate Regional Office indicating the completion date of the on-site testing.
- (d) A complete test report shall be submitted to the Department no later than 60 calendar days after completion of the onsite testing portion of an emission test program.
- (e) Pursuant to 25 Pa. Code Section 139.53(b) a complete test report shall include a summary of the emission results on the first page of the report indicating if each pollutant measured is within permitted limits and a statement of compliance or non-compliance with all applicable permit conditions. The summary results will include, at a minimum, the following information:
- 1. A statement that the owner or operator has reviewed the report from the emissions testing body and agrees with the findings.





SECTION C. **Site Level Requirements**

- 2. Permit number(s) and condition(s) which are the basis for the evaluation.
- 3. Summary of results with respect to each applicable permit condition.
- 4. Statement of compliance or non-compliance with each applicable permit condition.
- (f) Pursuant to 25 Pa. Code § 139.3 all submittals shall meet all applicable requirements specified in the most current version of the Department's Source Testing Manual.
- (g) All testing shall be performed in accordance with the provisions of Chapter 139 of the Rules and Regulations of the Department of Environmental Protection.
- (h) Pursuant to 25 Pa. Code Section 139.53(a)(1) and 139.53(a)(3) all submittals, besides notifications, shall be accomplished through PSIMS*Online available through https://www.depgreenport.state.pa.us/ecomm/Login.jsp when it becomes available. If internet submittal cannot be accomplished, submittal shall be made as follows:

Regional Office:

Digital copy (only): RA-epscstacktesting@pa.gov

Bureau of Air Quality:

Digital copy (only): RA-epstacktesting@pa.gov

(i) The permittee shall insure all federal reporting requirements contained in the applicable subpart of 40 CFR are followed, including timelines more stringent than those contained herein. In the event of an inconsistency or any conflicting requirements between state and the federal, the most stringent provision, term, condition, method or rule shall be used by default.

009 [25 Pa. Code §139.1]

Sampling facilities.

Upon request by the Department, the permittee shall provide adequate sampling ports, safe sampling platforms and adequate utilities for the performance by the Department of tests on such source. The Department will set forth, in the request, the time period in which the facilities shall be provided as well as the specifications for such facilities.

MONITORING REQUIREMENTS.

010 [25 Pa. Code §123.43]

Measuring techniques

Visible air contaminants may be measured using either of the following:

- (a) A device approved by the Department and maintained to provide accurate opacity measurements.
- (b) Observers, trained and certified in EPA Method 9 to measure plume opacity with the naked eye or with the aid of any devices approved by the Department.

[25 Pa. Code §127.441]

Operating permit terms and conditions.

The permittee shall conduct a weekly inspection around the plant periphery during the daylight hours when the plant is in production to detect visible emissions, fugitive visible emissions and malodorous emissions as follows:

- (a) Visible emissions in excess of the limits stated in Section C, Condition #004. Visible emissions may be measured according to the methods specified in Section C, Condition #010. As an alternative, plant personnel who observe such visible emissions shall report each incident to the Department within four hours of the occurrence and arrange for a certified observer to read the visible emissions.
- (b) Presence of fugitive visible emissions beyond the plant property boundaries, as stated in Section C, Condition #002.
- c) Presence of malodorous air contaminants beyond the plant property boundaries as stated in Section C, Condition #003.



SECTION C. Site Level Requirements

IV. RECORDKEEPING REQUIREMENTS.

012 [25 Pa. Code §127.441]

Operating permit terms and conditions.

The permittee shall maintain a logbook for recording exceedances of malodorous air contaminants, visible emissions and fugitive visible emissions. The logbook shall include the name of the company representative, date and time of the monitoring and the wind direction.

V. REPORTING REQUIREMENTS.

013 [25 Pa. Code §127.511]

Monitoring and related recordkeeping and reporting requirements.

- (a) The permittee shall report malfunctions which occur at the Title V facility to the Department. As defined in 40 CFR Section 60.2 and incorporated by reference in 25 Pa. Code Chapter 122, a malfunction is any sudden, infrequent, and not reasonably preventable failure of air pollution control equipment, process equipment, or a process to operate in a normal or usual manner. Telephone reports can be made to the Air Quality Program at (610) 916-0100 during normal business hours, or to the Department's Emergency Hotline at any time. The Emergency Hotline phone number is changed/updated periodically. The current Emergency Hotline phone number can be found at
- https://www.dep.pa.gov/About/Regional/SouthcentralRegion/Pages/default.aspx. Failures that are caused in part by poor maintenance or careless operation are not malfunctions. Malfunctions shall be reported as follows:
- (1) Malfunctions which occur at the Title V facility and which pose an imminent danger to public health, safety, welfare and the environment, shall be immediately reported to the Department by telephone. The telephone report of such malfunctions shall occur no later than two hours after the incident. The permittee shall submit a written report of instances of such malfunctions to the Department within three (3) days of the telephone report.
- (2) Unless otherwise required by this permit, any other malfunction that is not subject to the reporting requirements of subsection (a)(1), above, shall be reported to the Department, in writing, within five (5) days of discovery of the malfunction.

014 [25 Pa. Code §135.3]

Reporting

- (a) The permittee shall submit an annual emissions report to the Department. The report for a given calendar year is due no later than March 1 of the following year, and shall be submitted to the Department's Reading District Supervisor unless otherwise specified.
- (b) The permittee may request an extension of time from the Department for filing of the report specified in part (a), above, and the Department may grant the extension for reasonable cause.

VI. WORK PRACTICE REQUIREMENTS.

015 [25 Pa. Code §123.1]

Prohibition of certain fugitive emissions

The permittee shall take all reasonable actions to prevent particulate matter from a source identified in Section C, Condition #001 from becoming airborne. These actions shall include, but not be limited to, the following:

- (a) Use, where possible, of water or chemicals for control of dust in the demolition of buildings or structures, construction operations, the grading of roads, or the clearing of land.
- (b) Application of asphalt, oil, water or suitable chemicals on dirt roads, material stockpiles and other surfaces which may give rise to airborne dusts.
- (c) Paving and maintenance of roadways.
- (d) Prompt removal of earth or other material from paved streets onto which earth or other material has been transported by trucking or earth moving equipment, erosion by water, or other means

Page 18

[25 Pa. Code §123.1(c)].





SECTION C. Site Level Requirements

016 [25 Pa. Code §127.512]

Operating permit terms and conditions.

The permittee shall operate and maintain all sources and any air cleaning devices identified in this operating permit in accordance with the manufacturer's recommendations/specifications, as well as in a manner consistent with good operating practices.

VII. ADDITIONAL REQUIREMENTS.

017 [25 Pa. Code §127.511]

Monitoring and related recordkeeping and reporting requirements.

Per Site Level Category VIII 'COMPLIANCE CERTIFICATION' below, the permittee may forward the annual compliance certification report electronically to EPA, in lieu of the hard copy version, to the email address: R3_APD_Permits@epa.gov

018 [25 Pa. Code §127.511]

Monitoring and related recordkeeping and reporting requirements.

COMPLIANCE CERTIFICATION

The permittee shall submit within thirty days of 01/01/2023 a certificate of compliance with all permit terms and conditions set forth in this Title V permit as required under condition #024 of section B of this permit, and annually thereafter.

019 [25 Pa. Code §129.14]

Open burning operations

- (a) No person shall conduct open burning of materials in such a manner that:
 - (1) The emissions are visible, at any time, at the point such emissions pass outside the permittee's property.
 - (2) Malodorous air contaminants from the open burning are detectable outside the permittee's property.
 - (3) The emissions interfere with the reasonable enjoyment of life or property.
 - (4) The emissions cause damage to vegetation or property.
 - (5) The emissions are or may be deleterious to human or animal health.
- (b) Exceptions: The requirements of subsections (a), above, do not apply where the open burning operations result from:
- (1) A fire set to prevent or abate a fire hazard, when approved by the Department and set by or under the supervision of a public officer.
 - (2) A fire set for the purpose of instructing personnel in fire fighting, when approved by the Department.
 - (3) A fire set for the prevention and control of disease or pests, when approved by the Department.
 - (4) A fire set solely for recreational or ceremonial purposes.
 - (5) A fire set solely for cooking food.
- (c) This permit does not constitute authorization to burn solid waste pursuant to Section 610(3) of the Solid Waste Management Act, 35 P.S. Section 6018.610(3), or any other provision of the Solid Waste Management Act.

VIII. COMPLIANCE CERTIFICATION.

No additional compliance certifications exist except as provided in other sections of this permit including Section B (relating to Title V General Requirements).

IX. COMPLIANCE SCHEDULE.

No compliance milestones exist.

*** Permit Shield In Effect ***


DEP Auth ID: 1404295 DEP PF ID: Page 19





Source ID: 038 Source Name: AREA FUGITIVE EMISSIONS

Source Capacity/Throughput:



I. RESTRICTIONS.

Emission Restriction(s).

001 [25 Pa. Code §127.512]

Operating permit terms and conditions.

[Additional authority for this permit condition is also derived from of 25 Pa. Code §129.97(c)]

The permittee shall limit the annual emissions of volatile organic compounds (VOC) to not more than 20 tpy during any 12-month rolling period from all gas releases as detailed in Condition 002.

002 [25 Pa. Code §127.512]

Operating permit terms and conditions.

Source ID 038 consists of all the fugitive volatile organic compound emission sources at the facility. Actual emissions from the following equipment at the facility shall be limited as follows:

- (a) There are three case vents at Marietta Station, one associated with each natural gas compressor. The VOC emissions from each case vent is limited to less than 2.7 tpy per 12-month rolling period;
- (b) There are three compressor seal vents (seal degassing vent for centrifugal compressors, and rod packing vents for reciprocating compressors) at Marietta Station, one associated with each natural gas compressor. The VOC emissions from each seal vent is limited to less than 2.7 tpy per 12-month rolling period;
- (c) Station pigging operations VOC emissions are limited to less than 2.7 tons per 12-month rolling period;
- (d) Station blowdown VOC emissions are limited to less than 2.7 tons per 12-month rolling period;
- (e) Pipeline blowdown VOC emissions at the Marietta Station are limited to less than 2.7 tons per 12-month rolling period
- (f) The permittee shall calculate VOC emissions using AP-42 emission factors, EPA accepted estimation methodologies, manufacturer supplied emission factors, mass material balance, performance (stack) test data, or other method(s) acceptable to the Department.
- (g) The permitee shall keep adequate records to demonstrate compliance with the above limits. If total station emissions are less than 2.7 tons per 12-month rolling period, it is sufficient to keep records showing this.
- (h) The permittee shall perform monthly audio, visual, and olfactory (AVO) inspections to ensure the fugitive air contaminant emissions are minimized. Any leak detected during the monthly AVO inspection shall be repaired within 15 calendar days of detection unless facility shutdowns or ordering of replacement parts are necessary for repair of the leaks.
- (i) The permittee shall keep a logbook of the following for the AVO inspections, which logbook shall be kept for 5 years and made available to the Department upon request:
- (1) the date of each inspection,
- (2) initials or name(s) of the person(s) conducting each inspection,
- (3) the date each leak is detected,
- (4) the specific location of the leak,
- (5) the repair performed to eliminate the leak,
- (6) the date the leak is repaired,
- (7) the action/inspection taken to determine that the leak is repaired, and
- (8) the initials or name(s) of the person(s) repairing the leak.

DEP Auth ID: 1404295 DEP PF ID: Page 20



II. TESTING REQUIREMENTS.

No additional testing requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

III. MONITORING REQUIREMENTS.

No additional monitoring requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

IV. RECORDKEEPING REQUIREMENTS.

No additional record keeping requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

V. REPORTING REQUIREMENTS.

No additional reporting requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

VI. WORK PRACTICE REQUIREMENTS.

003 [25 Pa. Code §127.512]

Operating permit terms and conditions.

[Additional authority for this permit condition is also derived from of 25 Pa. Code §129.97(c)]

The permittee shall operate and maintain the sources in accordance with the manufacturer's specifications and with good operating practices.

VII. ADDITIONAL REQUIREMENTS.

No additional requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

*** Permit Shield in Effect. ***

36-05025




SECTION D. Source Level Requirements

Source ID: 043 Source Name: SOLAR MARS 100-T15000S TURB (30507/13,699HP)

Source Capacity/Throughput: 107.200 MCF/HR Natural Gas

Conditions for this source occur in the following groups: SG02

SG04



I. RESTRICTIONS.

Emission Restriction(s).

001 [25 Pa. Code §123.13]

Processes

The permittee shall not allow the emissions into the outdoor atmosphere of particulate matter from Source ID 043 in a manner that the concentration of particulate matter in the effluent gas exceeds 0.04 grain per dry standard cubic foot.

002 [25 Pa. Code §123.21]

General

(b) No person may permit the emission into the outdoor atmosphere of sulfur oxides from a source in a manner that the concentration of the sulfur oxides, expressed as SO2, in the effluent gas exceeds 500 parts per million, by volume, dry basis.

003 [25 Pa. Code §127.441]

Operating permit terms and conditions.

In accordance with operating permit No. 36-02025A, the NOx emission from the Source ID 043 shall not exceed 25 ppmvd corrected to 15 percent oxygen at rated load. This emission limit assures compliance with the 40 CFR, Part 60, Subpart GG.

004 [25 Pa. Code §127.441]

Operating permit terms and conditions.

[Additional authority for this permit Condition is derived from operating permit No. 36-02025A]

Annual NOx emissions from Source ID 043 (Solar Mars Gas Turbine) and Source ID 044 (Caterpillar Emergency Generator) shall be less than 40 TPY based on twelve months running total.

II. TESTING REQUIREMENTS.

005 [25 Pa. Code §127.441]

Operating permit terms and conditions.

For those sources utilizing portable analyzers, the company shall submit a complete operating procedure including calibration, quality assurance /quality control, and emissions calculation methods to the Department at least 60 days prior to the test. The accuracy of the portable analyzer readings shall be verified by operation and recording of readings during the EPA method stack testing. Results from the stack tests using portable analyzers shall be retained by the company at the test location and provided annually with the emissions statements and at other times as requested by the Department.

The conversion from ppm to lbs/hr shall be determined using the equation below provided the following conditions are adhered to:

- (a) Readings are corrected to 3 percent oxygen (15.1percent excess air)
- (b) Readings are determined volumetrically

DEP Auth ID: 1404295 DEP PF ID: Page 22



Equation: ppm NOx * 0.001208 * mmbtu/hr = lbs/hr NOx

006 [25 Pa. Code §127.512]

Operating permit terms and conditions.

In performing any required testing, the permittee shall comply with the provisions of 40 CFR 60.335. Additionally:

Unless otherwise approved in writing by DEP a minimum of one (1) stack test in accordance with 40 CFR Part 60, Section 60.335, and 25 Pa. Code, Chapter 139 and the Department's latest version of Source Testing Manual shall be performed on Source ID 043, during the five year operating permit term, to verify the emisson rate for NOx as NO2. A pre-approval for the stack test protocol is required from the Department.

III. MONITORING REQUIREMENTS.

No additional monitoring requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements) and/or Section E (Source Group Restrictions).

IV. RECORDKEEPING REQUIREMENTS.

007 [25 Pa. Code §127.511]

Monitoring and related recordkeeping and reporting requirements.

Facility shall keep the following records for Source ID 043, and shall retain these for five years and make them available to the Department's representative when requested:

- (a) Monthly and yearly records of running hours.
- (b) Amount of fuel consumed on both a monthly and 12-month rolling total basis.

V. REPORTING REQUIREMENTS.

008 [25 Pa. Code §127.441]

Operating permit terms and conditions.

[Additional authority for this permit Condition is derived from operating permit No. 36-02025A]

The following information shall be submitted on a calendar year basis to the Reading District Supervisor by March 1 of the following year:

- (a) Source and facility annual NOx emissions based on a 12-month rolling total.
- (b) Source operating hours and natural gas usage computed monthly and annually. The fuel usage may be combined for Source IDs 043 and 044.

VI. WORK PRACTICE REQUIREMENTS.

No additional work practice requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements) and/or Section E (Source Group Restrictions).

VII. ADDITIONAL REQUIREMENTS.

009 [25 Pa. Code §127.441]

Operating permit terms and conditions.

The NOx emission standards referenced in above Condition #003 does not apply during startup and shutdown of the gas

DEP Auth ID: 1404295 DEP PF ID: Page 23



turbine. Startup and shutdown periods are limited to a maximum of one hour each.

*** Permit Shield in Effect. ***

DEP Auth ID: 1404295

DEP PF ID:

36-05025




SECTION D. Source Level Requirements

Source ID: 044 Source Name: CATERPILLAR EMERGENCY GEN 30536

Source Capacity/Throughput: 4.700 MCF/HR Natural Gas

Conditions for this source occur in the following groups: SG06



I. RESTRICTIONS.

Emission Restriction(s).

001 [25 Pa. Code §123.13]

Processes

The permittee shall not allow the emission into the outdoor atmosphere of particulate matter (PM) from Source ID 044 in a manner that the concentration of PM in the effuent gas exceeds 0.04 grain per dry standard cubic foot.

002 [25 Pa. Code §123.21]

General

The permittee shall not allow the emission into the outdoor atmosphere of sulfur dioxide from a source in a manner that the concentration of sulfur oxides, expressed as SO2, in the effluent gas exceeds 500 parts per million, by volume, dry basis.

003 [25 Pa. Code §127.441]

Operating permit terms and conditions.

[Additional authority for this permit Condition is derived from operating permit No. 36-02025A]

Annual NOx emissions from the Source ID 044 (Caterpillar Emergency Generator) combined with Source ID 043 (Solar Mars Gas Turbine) shall be less than 40 TPY based on any consecutive twelve month period.

Operation Hours Restriction(s).

004 [25 Pa. Code §127.441]

Operating permit terms and conditions.

The permittee shall limit the hours of operation to less than 500 hours for any 12 consecutive month period.

II. TESTING REQUIREMENTS.

No additional testing requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements) and/or Section E (Source Group Restrictions).

III. MONITORING REQUIREMENTS.

No additional monitoring requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements) and/or Section E (Source Group Restrictions).

IV. RECORDKEEPING REQUIREMENTS.

005 [25 Pa. Code §127.441]

Operating permit terms and conditions.

[Additional authority for this permit condition is derived from 25 Pa. Code §129.100(d)]

The permittee shall monthly record and maintain records of the hours of operation of the emergency generator. For each

DEP Auth ID: 1404295 DEP PF ID: Page 25



month the permittee shall calculate and record the hours of operation of the generator in the most recent twelve consecutive month period.

V. REPORTING REQUIREMENTS.

006 [25 Pa. Code §127.441]

Operating permit terms and conditions.

[Additional authority for this permit Condition is derived from operating permit No. 36-02025A]

The following information shall be submitted on a calendar year basis to the Reading District Supervisor by March I of the following year:

- (a) Source and facility annual NOx emissions based on a 12-month rolling total.
- (b) Source operating hours and natural gas usage computed monthly and annually. The fuel usage may be combined for Source IDs 043 and 044.

VI. WORK PRACTICE REQUIREMENTS.

007 [25 Pa. Code §127.441]

Operating permit terms and conditions.

[Additional authority for this permit condition is derived from 25 Pa. Code §129.97(c)(8)]

The source shall be maintained and operated in accordance with the manufacturer's specifications and with good operating practices.

VII. ADDITIONAL REQUIREMENTS.

No additional requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements) and/or Section E (Source Group Restrictions).

*** Permit Shield in Effect. ***





Source ID: 045 Source Name: PARTS WASHER, 16 GAL

Source Capacity/Throughput:

I. RESTRICTIONS.

Emission Restriction(s).

001 [25 Pa. Code §129.63]

Degreasing operations

- (a) Cold cleaning machines. Except for those subject to the Federal National emissions standards for hazardous air pollutants (NESHAP) for halogenated solvent cleaners under 40 CFR Part 63 (relating to National emission standards for hazardous air pollutants for source categories), this subsection applies to cold cleaning machines that use 2 gallons or more of solvents containing greater than 5% VOC content by weight for the cleaning of metal parts.
 - (1) Immersion cold cleaning machines shall have a freeboard ratio of 0.50 or greater.

II. TESTING REQUIREMENTS.

No additional testing requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

III. MONITORING REQUIREMENTS.

No additional monitoring requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

IV. RECORDKEEPING REQUIREMENTS.

002 [25 Pa. Code §129.63]

Degreasing operations

(a)(6) A person who operates a cold cleaning machine shall maintain for at least 2 years and shall provide to the Department, on request, the information specified in paragraph (5). An invoice, bill of sale, certificate that corresponds to a number of sales, Material Safety Data Sheet (MSDS), or other appropriate documentation acceptable to the Department may be used to comply with this section.

V. REPORTING REQUIREMENTS.

No additional reporting requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

VI. WORK PRACTICE REQUIREMENTS.

003 [25 Pa. Code §129.63]

Degreasing operations

- (a)(2) Immersion cold cleaning machines and remote reservoir cold cleaning machines shall:
- (i) Have a permanent, conspicuous label summarizing the operating requirements in paragraph (3). In addition, the label shall include the following discretionary good operating practices:
- (A) Cleaned parts should be drained at least 15 seconds or until dripping ceases, whichever is longer. Parts having cavities or blind holes shall be tipped or rotated while the part is draining. During the draining, tipping or rotating, the parts should be positioned so that solvent drains directly back to the cold cleaning machine.
- (B) When a pump-agitated solvent bath is used, the agitator should be operated to produce a rolling motion of the solvent with no observable splashing of the solvent against the tank walls or the parts being cleaned.
 - (C) Work area fans should be located and positioned so that they do not blow across the opening of the degreaser unit.





- (ii) Be equipped with a cover that shall be closed at all times except during cleaning of parts or the addition or removal of solvent. For remote reservoir cold cleaning machines which drain directly into the solvent storage reservoir, a perforated drain with a diameter of not more than 6 inches shall constitute an acceptable cover.
- (a)(3) Cold cleaning machines shall be operated in accordance with the following procedures:
- (i) Waste solvent shall be collected and stored in closed containers. The closed containers may contain a device that allows pressure relief, but does not allow liquid solvent to drain from the container.
- (ii) Flushing of parts using a flexible hose or other flushing device shall be performed only within the cold cleaning machine. The solvent spray shall be a solid fluid stream, not an atomized or shower spray.
- (iii) Sponges, fabric, wood, leather, paper products and other absorbent materials may not be cleaned in the cold cleaning machine.
 - (iv) Air agitated solvent baths may not be used.
 - (v) Spills during solvent transfer and use of the cold cleaning machine shall be cleaned up immediately.
- (a)(4) After December 22, 2002, a person may not use, sell or offer for sale for use in a cold cleaning machine any solvent with a vapor pressure of 1.0 millimeter of mercury (mm Hg) or greater and containing greater than 5% VOC by weight, measured at 20°C (68°F) containing VOCs.
- (a)(5) On and after December 22, 2002, a person who sells or offers for sale any solvent containing VOCs for use in a cold cleaning machine shall provide, to the purchaser, the following written information:
 - (i) The name and address of the solvent supplier.
 - (ii) The type of solvent including the product or vendor identification number.
- (iii) The vapor pressure of the solvent measured in mm hg at 20°C (68°F).
- (a)(7) Paragraph (4) does not apply:
 - (i) To cold cleaning machines used in extreme cleaning service.
- (ii) If the owner or operator of the cold cleaning machine demonstrates, and the Department approves in writing, that compliance with paragraph (4) will result in unsafe operating conditions.
 - (iii) To immersion cold cleaning machines with a freeboard ratio equal to or greater than 0.75.

VII. ADDITIONAL REQUIREMENTS.

No additional requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

*** Permit Shield in Effect. ***

36-05025



SECTION D. **Source Level Requirements**


Source ID: 046 Source Name: SOLAR TURBINE 2 (7,700 HP)

> Source Capacity/Throughput: 68.400 MMBTU/HR

> > 67.100 MCF/HR NATURAL GAS

Conditions for this source occur in the following groups: SG01

SG03 SG05



RESTRICTIONS.

No additional requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements) and/or Section E (Source Group Restrictions).

II. **TESTING REQUIREMENTS.**

No additional testing requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements) and/or Section E (Source Group Restrictions).

MONITORING REQUIREMENTS. III.

No additional monitoring requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements) and/or Section E (Source Group Restrictions).

RECORDKEEPING REQUIREMENTS. IV.

No additional record keeping requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements) and/or Section E (Source Group Restrictions).

REPORTING REQUIREMENTS. ٧.

No additional reporting requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements) and/or Section E (Source Group Restrictions).

VI. WORK PRACTICE REQUIREMENTS.

No additional work practice requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements) and/or Section E (Source Group Restrictions).

VII. ADDITIONAL REQUIREMENTS.

No additional requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements) and/or Section E (Source Group Restrictions).

*** Permit Shield in Effect. ***

DEP Auth ID: 1404295 DEP PF ID: Page 29

36-05025



SECTION D. **Source Level Requirements**


Source ID: 047 Source Name: SOLAR TURBINE 3 (7,700 HP)

> Source Capacity/Throughput: 68.400 MMBTU/HR

> > 67.100 MCF/HR NATURAL GAS

Conditions for this source occur in the following groups: SG01

SG03 SG05



RESTRICTIONS.

No additional requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements) and/or Section E (Source Group Restrictions).

II. **TESTING REQUIREMENTS.**

No additional testing requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements) and/or Section E (Source Group Restrictions).

MONITORING REQUIREMENTS. III.

No additional monitoring requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements) and/or Section E (Source Group Restrictions).

RECORDKEEPING REQUIREMENTS. IV.

No additional record keeping requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements) and/or Section E (Source Group Restrictions).

REPORTING REQUIREMENTS. ٧.

No additional reporting requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements) and/or Section E (Source Group Restrictions).

VI. WORK PRACTICE REQUIREMENTS.

No additional work practice requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements) and/or Section E (Source Group Restrictions).

VII. ADDITIONAL REQUIREMENTS.

No additional requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements) and/or Section E (Source Group Restrictions).

*** Permit Shield in Effect. ***

DEP Auth ID: 1404295 DEP PF ID: Page 30





Group Name: SG01

Group Description: NSPS Subpart OOOOa

Sources included in this group

ID	Name
046	SOLAR TURBINE 2 (7,700 HP)
047	SOLAR TURBINE 3 (7,700 HP)

I. RESTRICTIONS.

No additional requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

II. TESTING REQUIREMENTS.

No additional testing requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

III. MONITORING REQUIREMENTS.

No additional monitoring requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

IV. RECORDKEEPING REQUIREMENTS.

No additional record keeping requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

V. REPORTING REQUIREMENTS.

No additional reporting requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

VI. WORK PRACTICE REQUIREMENTS.

No additional work practice requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

VII. ADDITIONAL REQUIREMENTS.

001 [25 Pa. Code §127.512]

Operating permit terms and conditions.

Subpart OOOOa - Standards of Performance for Crude Oil and Natural Gas Facilities for which Construction, Modification or Reconstruction Commenced After September 18, 2015

Source:

81 FR 35898, June 3, 2016, unless otherwise noted.

§ 60.5360a What is the purpose of this subpart?

- (a) This subpart establishes emission standards and compliance schedules for the control of the pollutant greenhouse gases (GHG). The greenhouse gas standard in this subpart is in the form of a limitation on emissions of methane from affected facilities in the crude oil and natural gas source category that commence construction, modification, or reconstruction after September 18, 2015. This subpart also establishes emission standards and compliance schedules for the control of volatile organic compounds (VOC) and sulfur dioxide (SO2) emissions from affected facilities in the crude oil and natural gas source category that commence construction, modification or reconstruction after September 18, 2015. The effective date of the rule is August 2, 2016.
- (b) Prevention of Significant Deterioration (PSD) and title V thresholds for Greenhouse Gases.





- (1) For the purposes of 40 CFR 51.166(b)(49)(ii), with respect to GHG emissions from affected facilities, the "pollutant that is subject to the standard promulgated under section 111 of the Act" shall be considered to be the pollutant that otherwise is subject to regulation under the Act as defined in 40 CFR 51.166(b)(48) and in any State Implementation Plan (SIP) approved by the EPA that is interpreted to incorporate, or specifically incorporates, § 51.166(b)(48).
- (2) For the purposes of 40 CFR 52.21(b)(50)(ii), with respect to GHG emissions from affected facilities, the "pollutant that is subject to the standard promulgated under section 111 of the Act" shall be considered to be the pollutant that otherwise is subject to regulation under the Clean Air Act as defined in 40 CFR 52.21(b)(49).
- (3) For the purposes of 40 CFR 70.2, with respect to greenhouse gas emissions from affected facilities, the "pollutant that is subject to any standard promulgated under section 111 of the Act" shall be considered to be the pollutant that otherwise is "subject to regulation" as defined in 40 CFR 70.2.
- (4) For the purposes of 40 CFR 71.2, with respect to greenhouse gas emissions from affected facilities, the "pollutant that is subject to any standard promulgated under section 111 of the Act" shall be considered to be the pollutant that otherwise is "subject to regulation" as defined in 40 CFR 71.2.
- § 60.5365a Am I subject to this subpart?

You are subject to the applicable provisions of this subpart if you are the owner or operator of one or more of the onshore affected facilities listed in paragraphs (a) through (j) of this section for which you commence construction, modification, or reconstruction after September 18, 2015.

- (a) [N/A NO WELL]
- (b) [N/A NO CENTRIFUGAL COMPRESSOR WITH WET SEALS]
- (c) [N/A NO RECIPROCATING COMPRESSORS]
- (d) [N/A PNEUMATIC CONTROLLER NOT USED]
- (e) [N/A EACH STORAGE VESSEL VOC PTE LESS THAN 6 TPY]
- (f) The group of all equipment within a process unit is an affected facility.
- (1) [N/A PROJECT IS A MODIFICATION]
- (2) & (3) [N/A NOT AN ONSHORE NATURAL GAS PROCESSING PLANT]
- (g) [N/A NOT A SWEETENING UNIT]
- (h) [N/A NOT A PNEUMATIC PUMP FACILITY]
- (i) [N/A NO WELL]
- (j) The collection of fugitive emissions components at a compressor station, as defined in § 60.5430a, is an affected facility. For purposes of § 60.5397a, a "modification" to a compressor station occurs when:
- (1) [N/A ONLY REPLACEMENT COMPRESSORS]; or
- (2) One or more compressors at a compressor station is replaced by one or more compressors of greater total horsepower than the compressor(s) being replaced. When one or more compressors is replaced by one or more compressors of an equal or smaller total horsepower than the compressor(s) being replaced, installation of the replacement compressor(s) does not trigger a modification of the compressor station for purposes of § 60.5397a.
- § 60.5370a When must I comply with this subpart?





- (a) You must be in compliance with the standards of this subpart no later than August 2, 2016 or upon startup, whichever is later.
- (b) At all times, including periods of startup, shutdown, and malfunction, owners and operators shall maintain and operate any affected facility including associated air pollution control equipment in a manner consistent with good air pollution control practice for minimizing emissions. Determination of whether acceptable operating and maintenance procedures are being used will be based on information available to the Administrator which may include, but is not limited to, monitoring results, opacity observations, review of operating and maintenance procedures, and inspection of the source. The provisions for exemption from compliance during periods of startup, shutdown and malfunctions provided for in 40 CFR 60.8(c) do not apply to this subpart.
- (c) [N/A NO PERMIT EXEMPTION]

§60.5375a What GHG and VOC standards apply to well affected facilities?

[N/A - NO WELL]

§60.5380a What GHG and VOC standards apply to centrifugal compressor affected facilities?

[N/A - NO CENTRIFUGAL COMPRESSOR WITH WET SEALS]

§60.5385a What GHG and VOC standards apply to reciprocating compressor affected facilities?

[N/A - NO RECIPROCATING COMPRESSORS]

§60.5390a What GHG and VOC standards apply to pneumatic controller affected facilities?

[N/A - PNEUMATIC CONTROLLER NOT USED]

§60.5393a What GHG and VOC standards apply to pneumatic pump affected facilities?

[N/A - NOT A PNEUMATIC PUMP FACILITY]

§60.5395a What VOC standards apply to storage vessel affected facilities?

[N/A - EACH STORAGE VESSEL VOC PTE LESS THAN 6 TPY]

§ 60.5397a What fugitive emissions GHG and VOC standards apply to the affected facility which is the collection of fugitive emissions components at a well site and the affected facility which is the collection of fugitive emissions components at a compressor station?

For each affected facility under § 60.5365a(i) and (j), you must reduce GHG (in the form of a limitation on emissions of methane) and VOC emissions by complying with the requirements of paragraphs (a) through (j) of this section. These requirements are independent of the closed vent system and cover requirements in § 60.5411a.

- (a) You must monitor all fugitive emission components, as defined in § 60.5430a, in accordance with paragraphs (b) through (g) of this section. You must repair all sources of fugitive emissions in accordance with paragraph (h) of this section. You must keep records in accordance with paragraph (i) of this section and report in accordance with paragraph (j) of this section. For purposes of this section, fugitive emissions are defined as: Any visible emission from a fugitive emissions component observed using optical gas imaging or an instrument reading of 500 ppm or greater using Method 21.
- (b) You must develop an emissions monitoring plan that covers the collection of fugitive emissions components at well sites and compressor stations within each company-defined area in accordance with paragraphs (c) and (d) of this section.
- (c) Fugitive emissions monitoring plans must include the elements specified in paragraphs (c)(1) through (8) of this section, at a minimum.





- (1) Frequency for conducting surveys. Surveys must be conducted at least as frequently as required by paragraphs (f) and (g) of this section.
- (2) Technique for determining fugitive emissions (i.e., Method 21 at 40 CFR part 60, appendix A-7, or optical gas imaging).
- (3) Manufacturer and model number of fugitive emissions detection equipment to be used.
- (4) Procedures and timeframes for identifying and repairing fugitive emissions components from which fugitive emissions are detected, including timeframes for fugitive emission components that are unsafe to repair. Your repair schedule must meet the requirements of paragraph (h) of this section at a minimum.
- (5) Procedures and timeframes for verifying fugitive emission component repairs.
- (6) Records that will be kept and the length of time records will be kept.
- (7) If you are using optical gas imaging, your plan must also include the elements specified in paragraphs (c)(7)(i) through (vii) of this section.
- (i) Verification that your optical gas imaging equipment meets the specifications of paragraphs (c)(7)(i)(A) and (B) of this section. This verification is an initial verification and may either be performed by the facility, by the manufacturer, or by a third party. For the purposes of complying with the fugitives emissions monitoring program with optical gas imaging, a fugitive emission is defined as any visible emissions observed using optical gas imaging.
- (A) Your optical gas imaging equipment must be capable of imaging gases in the spectral range for the compound of highest concentration in the potential fugitive emissions.
- (B) Your optical gas imaging equipment must be capable of imaging a gas that is half methane, half propane at a concentration of 10,000 ppm at a flow rate of =60g/hr from a quarter inch diameter orifice.
- (ii) Procedure for a daily verification check.
- (iii) Procedure for determining the operator's maximum viewing distance from the equipment and how the operator will ensure that this distance is maintained.
- (iv) Procedure for determining maximum wind speed during which monitoring can be performed and how the operator will ensure monitoring occurs only at wind speeds below this threshold.
- (v) Procedures for conducting surveys, including the items specified in paragraphs (c)(7)(v)(A) through (C) of this section.
- (A) How the operator will ensure an adequate thermal background is present in order to view potential fugitive emissions.
- (B) How the operator will deal with adverse monitoring conditions, such as wind.
- (C) How the operator will deal with interferences (e.g., steam).
- (vi) Training and experience needed prior to performing surveys.
- (vii) Procedures for calibration and maintenance. At a minimum, procedures must comply with those recommended by the manufacturer.
- (8) If you are using Method 21 of appendix A-7 of this part, your plan must also include the elements specified in paragraphs (c)(8)(i) and (ii) of this section. For the purposes of complying with the fugitive emissions monitoring program using Method 21 a fugitive emission is defined as an instrument reading of 500 ppm or greater.
- (i) Verification that your monitoring equipment meets the requirements specified in Section 6.0 of Method 21 at 40 CFR part 60, appendix A-7. For purposes of instrument capability, the fugitive emissions definition shall be 500 ppm or greater methane using a FID-based instrument. If you wish to use an analyzer other than a FID-based instrument, you must



develop a site-specific fugitive emission definition that would be equivalent to 500 ppm methane using a FID-based instrument (e.g., 10.6 eV PID with a specified isobutylene concentration as the fugitive emission definition would provide equivalent response to your compound of interest).

- (ii) Procedures for conducting surveys. At a minimum, the procedures shall ensure that the surveys comply with the relevant sections of Method 21 at 40 CFR part 60, appendix A-7, including Section 8.3.1.
- (d) Each fugitive emissions monitoring plan must include the elements specified in paragraphs (d)(1) through (4) of this section, at a minimum, as applicable.
- (1) Sitemap.
- (2) A defined observation path that ensures that all fugitive emissions components are within sight of the path. The observation path must account for interferences.
- (3) If you are using Method 21, your plan must also include a list of fugitive emissions components to be monitored and method for determining location of fugitive emissions components to be monitored in the field (e.g. tagging, identification on a process and instrumentation diagram, etc.).
- (4) Your plan must also include the written plan developed for all of the fugitive emission components designated as difficult-to-monitor in accordance with paragraph (g)(3)(i) of this section, and the written plan for fugitive emission components designated as unsafe-to-monitor in accordance with paragraph (g)(3)(i) of this section.
- (e) Each monitoring survey shall observe each fugitive emissions component, as defined in § 60.5430a, for fugitive emissions.

(f)

- (1) [N/A NO WELL]
- (2) You must conduct an initial monitoring survey within 60 days of the startup of a new compressor station for each new collection of fugitive emissions components at the new compressor station or by June 3, 2017, whichever is later. For a modified collection of fugitive components at a compressor station, the initial monitoring survey must be conducted within 60 days of the modification or by June 3, 2017, whichever is later.
- (g) A monitoring survey of each collection of fugitive emissions components at a well site or at a compressor station must be performed at the frequencies specified in paragraphs (g)(1) and (2) of this section, with the exceptions noted in paragraphs (g)(3) and (4) of this section.
- (1) [N/A NO WELL]
- (2) A monitoring survey of the collection of fugitive emissions components at a compressor station within a company-defined area must be conducted at least quarterly after the initial survey. Consecutive quarterly monitoring surveys must be conducted at least 60 days apart.
- (3) Fugitive emissions components that cannot be monitored without elevating the monitoring personnel more than 2 meters above the surface may be designated as difficult-to-monitor. Fugitive emissions components that are designated difficult-to-monitor must meet the specifications of paragraphs (g)(3)(i) through (iv) of this section.
- (i) A written plan must be developed for all of the fugitive emissions components designated difficult-to-monitor. This written plan must be incorporated into the fugitive emissions monitoring plan required by paragraphs (b), (c), and (d) of this section.
- (ii) The plan must include the identification and location of each fugitive emissions component designated as difficult-to-monitor.
- (iii) The plan must include an explanation of why each fugitive emissions component designated as difficult-to-monitor is





difficult-to-monitor.

- (iv) The plan must include a schedule for monitoring the difficult-to-monitor fugitive emissions components at least once per calendar year.
- (4) Fugitive emissions components that cannot be monitored because monitoring personnel would be exposed to immediate danger while conducting a monitoring survey may be designated as unsafe-to-monitor. Fugitive emissions components that are designated unsafe-to-monitor must meet the specifications of paragraphs (g)(4)(i) through (iv) of this section.
- (i) A written plan must be developed for all of the fugitive emissions components designated unsafe-to-monitor. This written plan must be incorporated into the fugitive emissions monitoring plan required by paragraphs (b), (c), and (d) of this section.
- (ii) The plan must include the identification and location of each fugitive emissions component designated as unsafe-to-monitor.
- (iii) The plan must include an explanation of why each fugitive emissions component designated as unsafe-to-monitor is unsafe-to-monitor.
- (iv) The plan must include a schedule for monitoring the fugitive emissions components designated as unsafe-to-monitor.
- (5) [N/A AVERAGE TEMPERATURE ABOVE 0 DEGREES F]
- (h) Each identified source of fugitive emissions shall be repaired or replaced in accordance with paragraphs (h)(1) and (2) of this section. For fugitive emissions components also subject to the repair provisions of §§ 60.5416a(b)(9) through (12) and (c)(4) through (7), those provisions apply instead to those closed vent system and covers, and the repair provisions of paragraphs (h)(1) and (2) of this section do not apply to those closed vent systems and covers.
- (1) Each identified source of fugitive emissions shall be repaired or replaced as soon as practicable, but no later than 30 calendar days after detection of the fugitive emissions.
- (2) If the repair or replacement is technically infeasible, would require a vent blowdown, a compressor station shutdown, a well shutdown or well shut-in, or would be unsafe to repair during operation of the unit, the repair or replacement must be completed during the next scheduled compressor station shutdown, well shut-in, after a planned vent blowdown or within 2 years, whichever is earlier.
- (3) Each repaired or replaced fugitive emissions component must be resurveyed as soon as practicable, but no later than 30 days after being repaired, to ensure that there are no fugitive emissions.
- (i) For repairs that cannot be made during the monitoring survey when the fugitive emissions are initially found, the operator may resurvey the repaired fugitive emissions components using either Method 21 or optical gas imaging within 30 days of finding such fugitive emissions.
- (ii) For each repair that cannot be made during the monitoring survey when the fugitive emissions are initially found, a digital photograph must be taken of that component or the component must be tagged for identification purposes. The digital photograph must include the date that the photograph was taken, must clearly identify the component by location within the site (e.g., the latitude and longitude of the component or by other descriptive landmarks visible in the picture).
- (iii) Operators that use Method 21 to resurvey the repaired fugitive emissions components are subject to the resurvey provisions specified in paragraphs (h)(3)(iii)(A) and (B) of this section.
- (A) A fugitive emissions component is repaired when the Method 21 instrument indicates a concentration of less than 500 ppm above background or when no soap bubbles are observed when the alternative screening procedures specified in section 8.3.3 of Method 21 are used.
- (B) Operators must use the Method 21 monitoring requirements specified in paragraph (c)(8)(ii) of this section or the



alternative screening procedures specified in section 8.3.3 of Method 21.

- (iv) Operators that use optical gas imaging to resurvey the repaired fugitive emissions components, are subject to the resurvey provisions specified in paragraphs (h)(3)(iv)(A) and (B) of this section.
- (A) A fugitive emissions component is repaired when the optical gas imaging instrument shows no indication of visible emissions.
- (B) Operators must use the optical gas imaging monitoring requirements specified in paragraph (c)(7) of this section.
- (i) Records for each monitoring survey shall be maintained as specified § 60.5420a(c)(15).
- (j) Annual reports shall be submitted for each collection of fugitive emissions components at a well site and each collection of fugitive emissions components at a compressor station that include the information specified in § 60.5420a(b)(7). Multiple collection of fugitive emissions components at a well site or at a compressor station may be included in a single annual report.
- [81 FR 35898, June 3, 2016, as amended at 83 FR 10638, Mar. 12, 2018]
- § 60.5398a What are the alternative means of emission limitations for GHG and VOC from well completions, reciprocating compressors, the collection of fugitive emissions components at a well site and the collection of fugitive emissions components at a compressor station?
- (a) If, in the Administrator's judgment, an alternative means of emission limitation will achieve a reduction in GHG (in the form of a limitation on emission of methane) and VOC emissions at least equivalent to the reduction in GHG and VOC emissions achieved under § 60.5375a, § 60.5385a, and § 60.5397a, the Administrator will publish, in the Federal Register, a notice permitting the use of that alternative means for the purpose of compliance with § 60.5375a, § 60.5385a, and § 60.5397a. The notice may condition permission on requirements related to the operation and maintenance of the alternative means.
- (b) Any notice under paragraph (a) of this section must be published only after notice and an opportunity for a public hearing.
- (c) The Administrator will consider applications under this section from either owners or operators of affected facilities.
- (d) Determination of equivalence to the design, equipment, work practice or operational requirements of this section will be evaluated by the following guidelines:
- (1) The applicant must collect, verify and submit test data, covering a period of at least 12 months to demonstrate the equivalence of the alternative means of emission limitation. The application must include the following information:
- (i) A description of the technology or process.
- (ii) The monitoring instrument and measurement technology or process.
- (iii) A description of performance based procedures (i.e., method) and data quality indicators for precision and bias; the method detection limit of the technology or process.
- (iv) For affected facilities under § 60.5397a, the action criteria and level at which a fugitive emission exists.
- (v) Any initial and ongoing quality assurance/quality control measures.
- (vi) Timeframes for conducting ongoing quality assurance/quality control.
- (vii) Field data verifying viability and detection capabilities of the technology or process.
- (viii) Frequency of measurements.



- (ix) Minimum data availability.
- (x) Any restrictions for using the technology or process.
- (xi) Operation and maintenance procedures and other provisions necessary to ensure reduction in methane and VOC emissions at least equivalent to the reduction in methane and VOC emissions achieved under § 60.5397a.
- (xii) Initial and continuous compliance procedures, including recordkeeping and reporting.
- (2) For each determination of equivalency requested, the emission reduction achieved by the design, equipment, work practice or operational requirements shall be demonstrated.
- (3) For each affected facility for which a determination of equivalency is requested, the emission reduction achieved by the alternative means of emission limitation shall be demonstrated.
- (4) Each owner or operator applying for a determination of equivalence to a work practice standard shall commit in writing to work practice(s) that provide for emission reductions equal to or greater than the emission reductions achieved by the required work practice.
- (e) After notice and opportunity for public hearing, the Administrator will determine the equivalence of a means of emission limitation and will publish the determination in the Federal Register.
- (f) An application submitted under this section will be evaluated as set forth in paragraphs (f)(1) and (2) of this section.
- (1) The Administrator will compare the demonstrated emission reduction for the alternative means of emission limitation to the demonstrated emission reduction for the design, equipment, work practice or operational requirements and, if applicable, will consider the commitment in paragraph (d) of this section.
- (2) The Administrator may condition the approval of the alternative means of emission limitation on requirements that may be necessary to ensure operation and maintenance to achieve the same emissions reduction as the design, equipment, work practice or operational requirements. (g) Any equivalent means of emission limitations approved under this section shall constitute a required work practice, equipment, design or operational standard within the meaning of section 111(h)(1) of the CAA.
- §60.5400a What equipment leak GHG and VOC standards apply to affected facilities at an onshore natural gas processing plant?

[N/A - NOT AN ONSHORE NATURAL GAS PROCESSING PLANT]

§60.5401a What are the exceptions to the equipment leak GHG and VOC standards for affected facilities at onshore natural gas processing plants?

[N/A - NOT AN ONSHORE NATURAL GAS PROCESSING PLANT]

§60.5402a What are the alternative means of emission limitations for GHG and VOC equipment leaks from onshore natural gas processing plants?

[N/A - NOT AN ONSHORE NATURAL GAS PROCESSING PLANT]

§60.5405a What standards apply to sweetening unit affected facilities at onshore natural gas processing plants?

[N/A - NOT AN ONSHORE NATURAL GAS PROCESSING PLANT]

§60.5406a What test methods and procedures must I use for my sweetening unit affected facilities at onshore natural gas processing plants?

[N/A - NOT AN ONSHORE NATURAL GAS PROCESSING PLANT]

DEP Auth ID: 1404295 DEP PF ID: Page 38





§60.5407a What are the requirements for monitoring of emissions and operations from my sweetening unit affected facilities at onshore natural gas processing plants?

[N/A - NOT AN ONSHORE NATURAL GAS PROCESSING PLANT]

§60.5408a What is an optional procedure for measuring hydrogen sulfide in acid gas—Tutwiler Procedure?

[N/A - HYDROGEN SULFIDE MEASUREMENTS NOT REQUIRED]

§ 60.5410a How do I demonstrate initial compliance with the standards for my well, centrifugal compressor, reciprocating compressor, pneumatic controller, pneumatic pump, storage vessel, collection of fugitive emissions components at a well site, collection of fugitive emissions components at a compressor station, and equipment leaks and sweetening unit affected facilities at onshore natural gas processing plants?

You must determine initial compliance with the standards for each affected facility using the requirements in paragraphs (a) through (j) of this section. The initial compliance period begins on August 2, 2016, or upon initial startup, whichever is later, and ends no later than 1 year after the initial startup date for your affected facility or no later than 1 year after August 2, 2016. The initial compliance period may be less than one full year.

- (a) [N/A NO WELL]
- (b) [N/A NO CENTRIFUGAL COMPRESSOR WITH WET SEALS]
- (c) [N/A NO RECIPROCATING COMPRESSORS]
- (d) [N/A PNEUMATIC CONTROLLER NOT USED]
- (e) [N/A NOT A PNEUMATIC PUMP FACILITY]
- (f) & (g) [N/A NOT AN ONSHORE NATURAL GAS PROCESSING PLANT]
- (h) & (i) [N/A EACH STORAGE VESSEL VOC PTE LESS THAN 6 TPY]
- (j) To achieve initial compliance with the fugitive emission standards for each collection of fugitive emissions components at a well site and each collection of fugitive emissions components at a compressor station, you must comply with paragraphs (j)(1) through (5) of this section.
- (1) You must develop a fugitive emissions monitoring plan as required in § 60.5397a(b)(c), and (d).
- (2) You must conduct an initial monitoring survey as required in § 60.5397a(f).
- (3) You must maintain the records specified in § 60.5420a(c)(15).
- (4) You must repair each identified source of fugitive emissions for each affected facility as required in § 60.5397a(h).
- (5) You must submit the initial annual report for each collection of fugitive emissions components at a well site and each collection of fugitive emissions components at a compressor station compressor station as required in § 60.5420a(b)(1) and (7).
- [81 FR 35898, June 3, 2016, as amended at 82 FR 25733, June 5, 2017]

§60.5411a What additional requirements must I meet to determine initial compliance for my covers and closed vent systems routing emissions from centrifugal compressor wet seal fluid degassing systems, reciprocating compressors, pneumatic pumps and storage vessels?

[N/A - NO APPLICABLE COVERS OR CLOSED VENT SYSTEMS]





§60.5412a What additional requirements must I meet for determining initial compliance with control devices used to comply with the emission standards for my centrifugal compressor, and storage vessel affected facilities?

IN/A - NO CENTRIFUGAL COMPRESSOR WITH WET SEALS AND EACH STORAGE VESSEL VOC PTE LESS THAN 6 TPYI

§60.5413a What are the performance testing procedures for control devices used to demonstrate compliance at my centrifugal compressor and storage vessel affected facilities?

[N/A - NO CENTRIFUGAL COMPRESSOR WITH WET SEALS AND EACH STORAGE VESSEL VOC PTE LESS THAN 6 TPY]

§ 60.5415a How do I demonstrate continuous compliance with the standards for my well, centrifugal compressor, reciprocating compressor, pneumatic controller, pneumatic pump, storage vessel, collection of fugitive emissions components at a well site, and collection of fugitive emissions components at a compressor station affected facilities, and affected facilities at onshore natural gas processing plants?

- (a) [N/A NO WELL]
- (b) [N/A NO CENTRIFUGAL COMPRESSOR WITH WET SEALS AND NOT A PNEUMATIC PUMP FACILITY]
- (c) [N/A NO RECIPROCATING COMPRESSORS]
- (d) [N/A PNEUMATIC CONTROLLER NOT USED]
- (e) [N/A EACH STORAGE VESSEL VOC PTE LESS THAN 6 TPY]
- (f) & (g) [N/A NOT AN ONSHORE NATURAL GAS PROCESSING PLANT]
- (h) For each collection of fugitive emissions components at a well site and each collection of fugitive emissions components at a compressor station, you must demonstrate continuous compliance with the fugitive emission standards specified in § 60.5397a according to paragraphs (h)(1) through (4) of this section.
- (1) You must conduct periodic monitoring surveys as required in § 60.5397a(g).
- (2) You must repair or replace each identified source of fugitive emissions as required in § 60.5397a(h).
- (3) You must maintain records as specified in § 60.5420a(c)(15).
- (4) You must submit annual reports for collection of fugitive emissions components at a well site and each collection of fugitive emissions components at a compressor station as required in § 60.5420a(b)(1) and (7).
- [81 FR 35898, June 3, 2016, as amended at 82 FR 25733, June 5, 2017]

§60.5416a What are the initial and continuous cover and closed vent system inspection and monitoring requirements for my centrifugal compressor, reciprocating compressor, pneumatic pump, and storage vessel affected facilities?

[N/A - NO APPLICABLE COVERS OR CLOSED VENT SYSTEMS]

§60.5417a What are the continuous control device monitoring requirements for my centrifugal compressor and storage vessel affected facilities?

IN/A - NO CENTRIFUGAL COMPRESSOR WITH WET SEALS AND EACH STORAGE VESSEL VOC PTE LESS THAN 6 TPYI

- § 60.5420a What are my notification, reporting, and recordkeeping requirements?
- (a) You must submit the notifications according to paragraphs (a)(1) and (2) of this section if you own or operate one or more of the affected facilities specified in § 60.5365a that was constructed, modified or reconstructed during the reporting period.

DEP Auth ID: 1404295 DEP PF ID: Page 40





- (1) If you own or operate an affected facility that is the group of all equipment within a process unit at an onshore natural gas processing plant, or a sweetening unit at an onshore natural gas processing plant, you must submit the notifications required in § 60.7(a)(1), (3), and (4). If you own or operate a well, centrifugal compressor, reciprocating compressor, pneumatic controller, pneumatic pump, storage vessel, or collection of fugitive emissions components at a well site or collection of fugitive emissions components at a compressor station, you are not required to submit the notifications required in § 60.7(a)(1), (3), and (4).
- (2) [N/A NO WELL]
- (b) Reporting requirements. You must submit annual reports containing the information specified in paragraphs (b)(1) through (8) and (12) of this section and performance test reports as specified in paragraph (b)(9) or (10) of this section, if applicable. You must submit annual reports following the procedure specified in paragraph (b)(11) of this section. The initial annual report is due no later than 90 days after the end of the initial compliance period as determined according to § 60.5410a. Subsequent annual reports are due no later than same date each year as the initial annual report. If you own or operate more than one affected facility, you may submit one report for multiple affected facilities provided the report contains all of the information required as specified in paragraphs (b)(1) through (8) of this section. Annual reports may coincide with title V reports as long as all the required elements of the annual report are included. You may arrange with the Administrator a common schedule on which reports required by this part may be submitted as long as the schedule does not extend the reporting period.
- (1) The general information specified in paragraphs (b)(1)(i) through (iv) of this section for all reports.
- (i) The company name, facility site name associated with the affected facility, US Well ID or US Well ID associated with the affected facility, if applicable, and address of the affected facility. If an address is not available for the site, include a description of the site location and provide the latitude and longitude coordinates of the site in decimal degrees to an accuracy and precision of five (5) decimals of a degree using the North American Datum of 1983.
- (ii) An identification of each affected facility being included in the annual report.
- (iii) Beginning and ending dates of the reporting period.
- (iv) A certification by a certifying official of truth, accuracy, and completeness. This certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (2) [N/A NO WELL]
- (3) [N/A NO CENTRIFUGAL COMPRESSOR WITH WET SEALS]
- (4) [N/A NO RECIPROCATING COMPRESSORS]
- (5) [N/A PNEUMATIC CONTROLLER NOT USED]
- (6) [N/A EACH STORAGE VESSEL VOC PTE LESS THAN 6 TPY]
- (7) For the collection of fugitive emissions components at each well site and the collection of fugitive emissions components at each compressor station within the company-defined area, the records of each monitoring survey including the information specified in paragraphs (b)(7)(i) through (xii) of this section. For the collection of fugitive emissions components at a compressor station, if a monitoring survey is waived under § 60.5397a(g)(5), you must include in your annual report the fact that a monitoring survey was waived and the calendar months that make up the quarterly monitoring period for which the monitoring survey was waived.
- (i) Date of the survey.
- (ii) Beginning and end time of the survey.
- (iii) Name of operator(s) performing survey. If the survey is performed by optical gas imaging, you must note the training and



experience of the operator.

- (iv) Ambient temperature, sky conditions, and maximum wind speed at the time of the survey.
- (v) Monitoring instrument used.
- (vi) Any deviations from the monitoring plan or a statement that there were no deviations from the monitoring plan.
- (vii) Number and type of components for which fugitive emissions were detected.
- (viii) Number and type of fugitive emissions components that were not repaired as required in § 60.5397a(h).
- (ix) Number and type of difficult-to-monitor and unsafe-to-monitor fugitive emission components monitored.
- (x) The date of successful repair of the fugitive emissions component.
- (xi) Number and type of fugitive emission components placed on delay of repair and explanation for each delay of repair.
- (xii) Type of instrument used to resurvey a repaired fugitive emissions component that could not be repaired during the initial fugitive emissions finding.
- (8) [N/A NOT A PNEUMATIC PUMP FACILITY]
- (9) & (10) [NO PERFORMANCE TESTING]
- (11) You must submit reports to the EPA via the CEDRI. (CEDRI can be accessed through the EPA's CDX (https://cdx.epa.gov/).) You must use the appropriate electronic report in CEDRI for this subpart or an alternate electronic file format consistent with the extensible markup language (XML) schema listed on the CEDRI Web site (https://www3.epa.gov/ttn/chief/cedri/). If the reporting form specific to this subpart is not available in CEDRI at the time that the report is due, you must submit the report to the Administrator at the appropriate address listed in § 60.4. Once the form has been available in CEDRI for at least 90 calendar days, you must begin submitting all subsequent reports via CEDRI. The reports must be submitted by the deadlines specified in this subpart, regardless of the method in which the reports are submitted.
- (12) [N/A NO APPLICABLE CLOSED VENT SYSTEM]
- (c) Recordkeeping requirements. You must maintain the records identified as specified in § 60.7(f) and in paragraphs (c)(1) through (16) of this section. All records required by this subpart must be maintained either onsite or at the nearest local field office for at least 5 years. Any records required to be maintained by this subpart that are submitted electronically via the EPA's CDX may be maintained in electronic format.

Page 42

- (1) [N/A NO WELL]
- (2) [N/A NO CENTRIFUGAL COMPRESSOR WITH WET SEALS]
- (3) [N/A NO RECIPROCATING COMPRESSORS]
- (4) [N/A PNEUMATIC CONTROLLER NOT USED]
- (5) [N/A EACH STORAGE VESSEL VOC PTE LESS THAN 6 TPY]
- (6) [N/A NO APPLICABLE CLOSED VENT SYSTEM]
- (7) [N/A NO APPLICABLE COVERS]
- (8) [N/A NO BYPASS REQUIREMENTS]

DEP Auth ID: 1404295





- (9) [N/A NO APPLICABLE COVERS OR CLOSED VENT SYSTEMS]
- (10) [N/A NO CENTRIFUGAL COMPRESSOR WITH WET SEALS AND NOT A PNEUMATIC PUMP FACILITY]
- (11) [N/A NO CENTRIFUGAL COMPRESSOR WITH WET SEALS]
- (12) & (13) [N/A EACH STORAGE VESSEL VOC PTE LESS THAN 6 TPY]
- (14) [N/A NO CENTRIFUGAL COMPRESSOR WITH WET SEALS AND EACH STORAGE VESSEL VOC PTE LESS THAN 6 TPY]
- (15) For each collection of fugitive emissions components at a well site and each collection of fugitive emissions components at a compressor station, the records identified in paragraphs (c)(15)(i) through (iii) of this section.
- (i) The fugitive emissions monitoring plan as required in § 60.5397a(b), (c), and (d).
- (ii) The records of each monitoring survey as specified in paragraphs (c)(15)(ii)(A) through (I) of this section.
- (A) Date of the survey.
- (B) Beginning and end time of the survey.
- (C) Name of operator(s) performing survey. You must note the training and experience of the operator.
- (D) Monitoring instrument used.
- (E) When optical gas imaging is used to perform the survey, one or more digital photographs or videos, captured from the optical gas imaging instrument used for conduct of monitoring, of each required monitoring survey being performed. The digital photograph must include the date the photograph was taken and the latitude and longitude of the collection of fugitive emissions components at a well site or collection of fugitive emissions components at a compressor station imbedded within or stored with the digital file. As an alternative to imbedded latitude and longitude within the digital file, the digital photograph or video may consist of an image of the monitoring survey being performed with a separately operating GPS device within the same digital picture or video, provided the latitude and longitude output of the GPS unit can be clearly read in the digital image.
- (F) Fugitive emissions component identification when Method 21 is used to perform the monitoring survey.
- (G) Ambient temperature, sky conditions, and maximum wind speed at the time of the survey.
- (H) Any deviations from the monitoring plan or a statement that there were no deviations from the monitoring plan.
- (I) Documentation of each fugitive emission, including the information specified in paragraphs (c)(15)(ii)(I)(1) through (12) of this section.
- (1) Location.
- (2) Any deviations from the monitoring plan or a statement that there were no deviations from the monitoring plan.
- (3) Number and type of components for which fugitive emissions were detected.
- (4) Number and type of difficult-to-monitor and unsafe-to-monitor fugitive emission components monitored.
- (5) Instrument reading of each fugitive emissions component that requires repair when Method 21 is used for monitoring.
- (6) Number and type of fugitive emissions components that were not repaired as required in § 60.5397a(h).
- (7) Number and type of components that were tagged as a result of not being repaired during the monitoring survey when



the fugitive emissions were initially found as required in § 60.5397a(h)(3)(ii).

- (8) If a fugitive emissions component is not tagged, a digital photograph or video of each fugitive emissions component that could not be repaired during the monitoring survey when the fugitive emissions were initially found as required in § 60.5397a(h)(3)(ii). The digital photograph or video must clearly identify the location of the component that must be repaired. Any digital photograph or video required under this paragraph can also be used to meet the requirements under paragraph (c)(15)(ii)(E) of this section, as long as the photograph or video is taken with the optical gas imaging instrument, includes the date and the latitude and longitude are either imbedded or visible in the picture.
- (9) Repair methods applied in each attempt to repair the fugitive emissions components.
- (10) Number and type of fugitive emission components placed on delay of repair and explanation for each delay of repair.
- (11) The date of successful repair of the fugitive emissions component.
- (12) Instrumentation used to resurvey a repaired fugitive emissions component that could not be repaired during the initial fugitive emissions finding.
- (iii) For the collection of fugitive emissions components at a compressor station, if a monitoring survey is waived under § 60.5397a(g)(5), you must maintain records of the average calendar month temperature, including the source of the information, for each calendar month of the quarterly monitoring period for which the monitoring survey was waived.
- (16) [N/A NOT A PNEUMATIC PUMP FACILITY]
- (17) [N/A NO APPLICABLE CLOSED VENT SYSTEMS]

[81 FR 35898, June 3, 2016, as amended at 82 FR 25733, June 5, 2017]

§60.5421a What are my additional recordkeeping requirements for my affected facility subject to GHG and VOC requirements for onshore natural gas processing plants?

[N/A - NOT AN ONSHORE NATURAL GAS PROCESSING PLANT]

§60.5422a What are my additional reporting requirements for my affected facility subject to GHG and VOC requirements for onshore natural gas processing plants?

[N/A - NOT AN ONSHORE NATURAL GAS PROCESSING PLANT]

§60.5423a What additional recordkeeping and reporting requirements apply to my sweetening unit affected facilities at onshore natural gas processing plants?

[N/A - NOT AN ONSHORE NATURAL GAS PROCESSING PLANT]

 \S 60.5425a What parts of the General Provisions apply to me?

Table 3 to this subpart shows which parts of the General Provisions in §§ 60.1 through 60.19 apply to you.

[TABLE 3 INCLUDED BY REFERENCE]

§60.5430a What definitions apply to this subpart?

[DEFINITIONS INCLUDED BY REFERENCE]

§60.5432a How do I determine whether a well is a low pressure well using the low pressure well equation?

[N/A - NO WELL]



§§ 60.5433a-60.5499a [Reserved]

Regulatory Changes

Individual sources within this source group that are subject to 40 CFR Part 60 Subpart OOOOa shall comply with all applicable requirements of the Subpart. 40 CFR Part 60.4 requires submission of copies of all requests, reports and other communications to both the Department and the EPA copies shall be forwarded to:

Associate Director
United States Environmental Protection Agency
Region III, Enforcement & Compliance Assurance Division
Air, RCRA and Toxics Branch (3ED21)
Four Penn Center
1600 John F. Kennedy Boulevard
Philadelphia, Pennsylvania 19103-2852

The Department copies shall be forwarded to the DEP SCRO Air Quality Program Manager at wiweaver@pa.gov, unless otherwise directed in writing by DEP.

In the event that the Federal Subpart that is the subject of this permit condition is revised, the permittee shall comply with the revised version of the subpart, and shall not be required to comply with any provisions in this permit designated as having the subpart as their authority, to the extent that such permit provisions would be inconsistent with the applicable provisions of the revised subpart.

*** Permit Shield in Effect. ***



36-05025



SECTION E. Source Group Restrictions.

Group Name: SG02

Group Description: Turbine Source ID 043, NSPS Subpart GG

Sources included in this group

ID Name

043 SOLAR MARS 100-T15000S TURB (30507/13,699HP)

I. RESTRICTIONS.

Emission Restriction(s).

001 [40 CFR Part 60 Standards of Performance for New Stationary Sources §40 CFR 60.330]

Subpart GG - Standards of Performance for Stationary Gas Turbines Applicability and designation of affected facility.

60.330(a): The provisions of this subpart are applicable to the following affected facilities: All stationary gas turbines with a heat input at peak load equal to or greater than 10.7 gigajoules (10 million Btu) per hour, based on the lower heating value of the fuel fired.

60.330(b): Any facility under paragraph (a) of this section which commences construction, modification, or reconstruction after October 3, 1977, is subject to the requirements of this part except as provided in paragraphs (e) and (j) of §60.332.

002 [40 CFR Part 60 Standards of Performance for New Stationary Sources §40 CFR 60.332]

Subpart GG - Standards of Performance for Stationary Gas Turbines Standard for nitrogen oxides.

60.332(a): On and after the date on which the performance test required by §60.8 is completed, every owner or operator subject to the provisions of this subpart as specified in paragraphs (b), (c), and (d) of this section shall comply with one of the following, except as provided in paragraphs (e), (f), (g), (h), (i), (j), (k), and (l) of this section.

60.332(a)(1): N/A. HEAT INPUT LESS THAN 100 MMBTU/HR

60.332(a)(2): No owner or operator subject to the provisions of this subpart shall cause to be discharged into the atmosphere from any stationary gas turbine, any gases which contain nitrogen oxides in excess of:

STD = 0.0150 (14.4) / Y + F

where:

STD = allowable ISO corrected (if required as given in §60.335(b)(1)) NOx emission concentration (percent by volume at 15 percent oxygen and on a dry basis),

Y = manufacturer's rated heat rate at manufacturer's rated peak load (kilojoules per watt hour), or actual measured heat rate based on lower heating value of fuel as measured at actual peak load for the facility. The value of Y shall not exceed 14.4 kilojoules per watt hour, and

F = NOx emission allowance for fuel-bound nitrogen as defined in paragraph (a)(4) of this section.

[NOTE: FOR THE CENTAUR AND SATURN TURBINES, THE 'F' FACTOR IS ZERO & 'Y' IS 14.4 THAT DEFAULTS TO NOX LIMIT OF 150 ppmdv. REF: SOLAR TURBINE.]

60.332(a)(3): N/A. 'F' FACTOR IS ZERO. NO NOx ALLOWANCE.

60.332(a)(4): N/A. 'F' FACTOR IS ZERO. NO NOx ALLOWANCE

60.332(b): N/A. NOT ELECTRIC UTILITY GAS TURBINE.

60.332(c): Turbine with heat input greater that 10 mmbtu/hr but less than or equal to 100 mmbtu/hr based on lower heating value of the fuel fired, shall comply with the provisions of paragrapg (a)(2) of this section.

60.332(d): N/A. COVERED BY ABOVE 60.332(c).

60.332(e): N/A. CONSTRUCTED AFTER 1982.



60.332(f): N/A. NO WATER OR STEAM INJECTION.

60.332(g): N/A. TURBINES ARE NOT FOR EMERGENCY OR MILITARY USE.

60.332(h): N/A. TURBINES ARE NOT FOR RESEARCH & DEVELOPMENT.

60.332(i): N/A. NO MANDATORY WATER RESTRICTION AREA.

60.332(j): N/A. TURBINES WERE NOT RECONSTRUCTED BETWEEN 1977 AND 1982.

60.332(k): N/A. TURBINES DO NOT COMBUST ANY EMERGENCY FUEL.

60.332(I): N/A. TURBINES ARE NOT THE REGENERATIVE CYCLE GAS TURBINES.

003 [40 CFR Part 60 Standards of Performance for New Stationary Sources §40 CFR 60.333]

Subpart GG - Standards of Performance for Stationary Gas Turbines Standard for sulfur dioxide.

On and after the date on which the performance test required to be conducted by §60.8 is completed, every owner or operator subject to the provision of this subpart shall comply with one or the other of the following conditions:

60.333(a): No owner or operator subject to the provisions of this subpart shall cause to be discharged into the atmosphere from any stationary gas turbine any gases which contain sulfur dioxide in excess of 0.015 percent by volume at 15 percent oxygen and on a dry basis.

60.333(b): No owner or operator subject to the provisions of this subpart shall burn in any stationary gas turbine any fuel which contains total sulfur in excess of 0.8 percent by weight (8000 ppmw).

II. TESTING REQUIREMENTS.

004 [40 CFR Part 60 Standards of Performance for New Stationary Sources §40 CFR 60.335] Subpart GG - Standards of Performance for Stationary Gas Turbines Test methods and procedures.

§ 60.335 Test methods and procedures.

[COMPLIED. INITIAL PERFORMANCE TEST DEMONSTRATING COMPLIANCE WAS COMPLETED JUNE 9, 1998; IT MEETS SECTION 60.8 (a) & (b)]

III. MONITORING REQUIREMENTS.

005 [40 CFR Part 60 Standards of Performance for New Stationary Sources §40 CFR 60.334] Subpart GG - Standards of Performance for Stationary Gas Turbines Monitoring of operations.

- § 60.334 Monitoring of operations.
- (a) [NA SOURCE DOES NOT USE WATER OR STEAM INJECTION TO CONTROL NOX EMISSIONS]
- (b) [NA SOURCE DOES NOT USE WATER OR STEAM INJECTION TO CONTROL NOX EMISSIONS]
- (c) [NA SOURCE HAS NOT ELECTED TO USE CEMS]
- (d) [NA SOURCE DOES NOT USE WATER OR STEAM INJECTION TO CONTROL NOX EMISSIONS]
- (e) [NA SOURCE WAS INSTALLED BEFORE 2004 [1986]]
- (f) [NA SOURCE WAS INSTALLED BEFORE 2004 [1986]]
- (g) [NA SOURCE HAS NOT ELECTED TO USE CEMS]

DEP Auth ID: 1404295 DEP PF ID: Page 47



- (h) The owner or operator of any stationary gas turbine subject to the provisions of this subpart:
- (1) [NA PERMITTEE HAS ELECTED TO USE (h)(3)]
- (2) [NA FUEL BOUND NITROGEN ALLOWANCE NOT USED]
- (3) Notwithstanding the provisions of paragraph (h)(1) of this section, the owner or operator may elect not to monitor the total sulfur content of the gaseous fuel combusted in the turbine, if the gaseous fuel is demonstrated to meet the definition of natural gas in § 60.331(u), regardless of whether an existing custom schedule approved by the administrator for subpart GG requires such monitoring. The owner or operator shall use one of the following sources of information to make the required demonstration:
- (i) The gas quality characteristics in a current, valid purchase contract, tariff sheet or transportation contract for the gaseous fuel, specifying that the maximum total sulfur content of the fuel is 20.0 grains/100 scf or less; or
- (ii) [NA PERMITTEE RELIES ON TARIFF SHEET PER 3(i)]
- (4) [NA NO CUSTOM FUEL MONITORING SCHEDULE]
- (i) The frequency of determining the sulfur and nitrogen content of the fuel shall be as follows:
- (1) [NA NO OIL USED]
- (2) [NA PERMITTEE HAS ELECTED TO USE THE METHOD IN (h)(3)]
- (3) [NA NO CUSTOM FUEL MONITORIING SCHEDULE]
- (j) [NA NO CONTINUOUS OR PERIODIC MONITORING OF PARAMETERS OR EMISSIONS]

IV. RECORDKEEPING REQUIREMENTS.

No additional record keeping requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

V. REPORTING REQUIREMENTS.

No additional reporting requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

VI. WORK PRACTICE REQUIREMENTS.

No additional work practice requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

VII. ADDITIONAL REQUIREMENTS.

006 [25 Pa. Code §127.512]

Operating permit terms and conditions.

[Additional authority for this permit condition is derived from 40 CFR 60, Subpart GG]

Source ID 043 is subject to 40 CFR Part 60, Subpart GG - Standards of Performance for Stationary Gas Turbines, as well as all applicable portion of General Provisions of Subpart A. The permittee shall comply with 40 CFR §60.4, which requires submission of copies of all requests, reports, applications, submittals, and other communications to both the U.S. Environmental Protection Agency (U.S. EPA) and the Department. The U.S. EPA copies shall be forwarded to:

Page 48

U.S. EPA

Region III, Air and Radiation Division

Permits Branch (3AD10)

Four Penn Center

DEP Auth ID: 1404295 DEP PE ID:



1600 John F. Kennedy Boulevard Philadelphia, PA 19103-2852

The DEP copies shall be forwarded to the DEP SCRO Air Quality Program Manager at wiweaver@pa.gov, unless otherwise directed in writing by DEP.

In the event that the Federal Subpart that is the subject of this Source Group is revised, the permittee shall comply with the revised version of the subpart, and shall not be required to comply with any provisions in this permit designated as having the subpart as their authority, to the extent that such permit provisions would be inconsistent with the applicable provisions of the revised subpart.

*** Permit Shield in Effect. ***

DEP Auth ID: 1404295



36-05025



SECTION E. Source Group Restrictions.

Group Name: SG03

Group Description: Turbine Source IDs: 046 and 047

Sources included in this group

IE	Name	
04	SOLAR TURBINE 2 (7,700 HP)	
04	SOLAR TURBINE 3 (7,700 HP)	

I. RESTRICTIONS.

Emission Restriction(s).

001 [25 Pa. Code §123.13]

Processes

The permittee shall not allow the emissions into the outdoor atmosphere of particulate matter from the sources in a manner that the concentration of particulate matter in the effluent gas exceeds 0.04 grain per dry standard cubic foot.

002 [25 Pa. Code §123.21]

General

The permittee may not permit the emission into the outdoor atmosphere of sulfur dioxide from a source in a manner that the concentration of sulfur oxides, expressed as SO2, in the effluent gas exceeds 500 parts per million, by volume, dry basis.

003 [25 Pa. Code §127.441]

Operating permit terms and conditions.

- (a) Pursuant to the Best Available Technology (BAT) provisions of 25 Pa. Code Section 127.1, the permittee shall limit the emissions from the turbines in this group to the following rates:
- (1) Total PM 0.030 lb/mmBtu
- (2) NOx 9 ppmdv @ 15% oxygen
- (3) CO 10.00 ppmdv @ 15% oxygen
- (4) NMNEHC (as propane) 5.00 ppmdv @ 15% oxygen
- (b) The above emission limitations shall apply at all times except during periods of start-up, shut-down and ambient temperatures less than or equal to 0 degrees F, provided, however, that the duration of start-up and shut-down do not exceed thirty (30) minutes per occurrence. The turbines shall be operated in a manner consistent with good air pollution control practices for minimizing emissions, at all times, including periods of startup, shutdown, and malfunction. The emissions from start-up and shut-down shall be included in the annual emissions report. The owner or operator of a turbine shall comply with all applicable start-up and shut-down requirements in accordance with 40 CFR Part 60, Subpart KKKK.

004 [25 Pa. Code §127.441]

Operating permit terms and conditions.

The permittee shall ensure that each turbine meets the visible emissions standards, as determined by the methods described in 25 Pa. Code §123.43, by not exceeding the following limitations:

(a) Equal to or greater than 10% for a period or periods aggregating more than three minutes in any one hour; and

Page 50

(b) Equal to or greater than 30% at any time.

Fuel Restriction(s).

005 [25 Pa. Code §127.441]

Operating permit terms and conditions.

The permittee shall operate the sources using only pipeline quality natural gas fuel.

36-05025



SECTION E. Source Group Restrictions.

Operation Hours Restriction(s).

006 [25 Pa. Code §127.441]

Operating permit terms and conditions.

The turbines may be operated without oxidation catalyst for up to 100 hours immediately following initial startup (once in the life of each turbine) or a major overhaul in order to prevent catalyst fouling due to oil burnoff.

II. TESTING REQUIREMENTS.

No additional testing requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

III. MONITORING REQUIREMENTS.

007 [25 Pa. Code §127.441]

Operating permit terms and conditions.

The permittee shall install, operate and maintain instrumentation to continuously measure and display the catalyst bed inlet gas temperature for each oxidation catalyst.

008 [25 Pa. Code §127.441]

Operating permit terms and conditions.

Each turbine shall be equipped with a non-resettable hour meter.

009 [25 Pa. Code §127.441]

Operating permit terms and conditions.

- (a) Unless otherwise approved in writing by DEP, the permittee shall conduct periodic monitoring every 2,500 hours of operation.
- (1) Conduct three test runs of at least 20 minutes duration within 25% of the highest achievable load.
- (2) Determine NOx and CO emissions concentrations in the exhaust with an electro-chemical cell portable gas analyzer used and maintained in accordance with the manufacturer's specifications and following the procedures specified in ASTM D6522.
- (3) If the measured NOx or CO emissions concentrations are within the margin of instrument error or in exceedance of the emissions limit, the permittee must perform a stack test within 180 days of the periodic monitoring.
- (b) The 2,500 hours of operation count resets after any performance test performed in accordance with Section C, Condition 007.
- (c) The Department may alter the frequency of periodic monitoring based on the test results. The frequency of periodic monitoring may be altered upon request of the permittee with written Departmental approval.
- (d) If the permittee decides to deviate from the monitoring procedures in (a) above, they must submit a request to use an alternate procedure, in writing, at least 60 days prior to performing the periodic monitoring. In the alternate procedure request, the permittee must demonstrate the alternate procedure's equivalence to the standard procedure to the satisfaction of the Division of Source Testing and Monitoring.

IV. RECORDKEEPING REQUIREMENTS.

010 [25 Pa. Code §127.441]

Operating permit terms and conditions.

The permittee will maintain adequate records to demonstrate that the duration of turbine operation without oxidation catalyst immediately following initial startup or a major overhaul does not exceed 100 hours per event.

011 [25 Pa. Code §127.441]

Operating permit terms and conditions.

The permittee shall maintain comprehensive and accurate records of the following for each turbine in this group on a monthly basis:

(1) The number of operating hours.



(2) The amount of fuel consumed.

All records required by this source group shall be retained by the permittee for 5 years and made available to the Department upon request.

[25 Pa. Code §127.441]

Operating permit terms and conditions.

The permittee shall maintain and make available upon request by the Department, the results of each periodic monitoring.

V. REPORTING REQUIREMENTS.

013 [25 Pa. Code §127.441]

Operating permit terms and conditions.

Within sixty (60) calendar days after the completion of periodic monitoring in Condition 009, the owner or operator shall submit the results to the appropriate DEP Regional Office. The Department reserves the right to require source tests in accordance with EPA reference methods should the data from the portable analyzer warrant such tests.

VI. WORK PRACTICE REQUIREMENTS.

014 [25 Pa. Code §127.441]

Operating permit terms and conditions.

- (a) The permittee shall at all times operate and maintain the combustion turbines and oxidation catalysts, including all associated monitoring equipment, in accordance with the manufacturer's recommendations/specifications (including the manufacturer's preventive maintenance schedule), as well as in a manner consistent with good operating and air pollution control practices that minimize air emissions.
- (b) The permittee shall operate the oxidation catalysts at all times the turbines are in operation once the relevant operating parameters (e.g., catalyst bed inlet gas temperature, air flow) are sufficient for proper control device operation pursuant to the manufacturer's recommendations/specifications, except during periods described under Condition 006.

VII. ADDITIONAL REQUIREMENTS.

No additional requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

*** Permit Shield in Effect. ***



Group Name: SG04
Group Description: RACT 2
Sources included in this group

ID	Name
043	SOLAR MARS 100-T15000S TURB (30507/13,699HP)

I. RESTRICTIONS.

No additional requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

II. TESTING REQUIREMENTS.

No additional testing requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

III. MONITORING REQUIREMENTS.

No additional monitoring requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

IV. RECORDKEEPING REQUIREMENTS.

No additional record keeping requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

V. REPORTING REQUIREMENTS.

No additional reporting requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

VI. WORK PRACTICE REQUIREMENTS.

No additional work practice requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

VII. ADDITIONAL REQUIREMENTS.

001 [25 Pa. Code §129.96]

Applicability

- § 129.96. Applicability.
- (a) The NOx requirements of this section and §§ 129.97—129.100 apply Statewide to the owner and operator of a major NOx emitting facility and the VOC requirements of this section and §§ 129.97—129.100 apply Statewide to the owner and operator of a major VOC emitting facility that were in existence on or before July 20, 2012, for which a requirement or emission limitation, or both, has not been established in §§ 129.51—129.52c, 129.54—129.63, 129.64—129.69, 129.71—129.75, 129.77, 129.101—129.107 and 129.301—129.310.
- (b) [NA FACILITY IS ALREADY MAJOR FOR NOX and VOC]
- (c) This section and §§ 129.97—129.100 do not apply to the owner and operator of a NOx air contamination source located at a major NOx emitting facility that has the potential to emit less than 1 TPY of NOx or a VOC air contamination source located at a major VOC emitting facility that has the potential to emit less than 1 TPY of VOC.
- (d) [NA FACILITY IS ALREADY MAJOR FOR NOX and VOC]
- § 129.97. Presumptive RACT requirements, RACT emission limitations and petition for alternative compliance schedule.
- (a) The owner and operator of a source listed in one or more of subsections (b)—(h) located at a major NOx emitting





facility or major VOC emitting facility subject to § 129.96 (relating to applicability) shall comply with the applicable presumptive RACT requirement or RACT emission limitation, or both, beginning with the specified compliance date as follows, unless an alternative compliance schedule is submitted and approved under subsections (k)—(m) or § 129.99 (relating to alternative RACT proposal and petition for alternative compliance schedule):

- (1) January 1, 2017, for a source subject to § 129.96(a).
- (2) [NA SOURCE IS EXISTING]
- (b) [NA SOURCE IS TURBINE]
- (c) [NA CATEGORIES DO NOT APPLY TO THE TURBINE]
- (d) Except as specified under subsection (c), the owner and operator of a combustion unit or other combustion source located at a major VOC emitting facility subject to § 129.96 shall install, maintain and operate the source in accordance with the manufacturer's specifications and with good operating practices for the control of the VOC emissions from the combustion unit or other combustion source.
- (e) [NA NOT A LANDFILL]
- (f) [NA NOT A MWI]
- (g) Except as specified under subsection (c), the owner and operator of a NOx air contamination source specified in this subsection, which is located at a major NOx emitting facility or a VOC air contamination source specified in this subsection, which is located at a major VOC emitting facility subject to § 129.96 may not cause, allow or permit NOx or VOCs to be emitted from the air contamination source in excess of the applicable presumptive RACT emission limitation:
 - (1) [NA-NO COMBUSTION UNITS OR PROCESS HEATERS]
 - (2) A combustion turbine:
 - (i) (ii) [NA- NO COMBINED CYCLE TURBINES]
 - (iii) [NA SOURCE 043 GREATER THAN 6,000 BHP]
- (iv) For a simple cycle or regenerative cycle combustion turbine with a rated output equal to or greater than 6,000 bhp when firing:
 - (A) Natural gas or a noncommercial gaseous fuel, 42 ppmvd NOx @ 15% oxygen.
 - (B) [NA SOURCE 043 DOES NOT FIRE FUEL OIL]
 - (C) Natural gas or a noncommercial gaseous fuel, 9 ppmvd VOC (as propane) @ 15% oxygen.
 - (D) [NA SOURCE 043 DOES NOT FIRE FUEL OIL]
 - (3) [NA NO NON-EMERGENCY ENGINES]
 - (4) [NA NO UNITS FIRING MULTIPLE FUELS]
- (h) [NA NO CEMENT KILNS]
- (i) The requirements and emission limitations of this section supersede the requirements and emission limitations of a RACT permit issued to the owner or operator of an air contamination source subject to one or more of subsections (b)—(h) prior to April 23, 2016, under § § 129.91—129.95 (relating to stationary sources of NOx and VOCs) to control, reduce or minimize NOx emissions or VOC emissions, or both, from the air contamination source unless the permit contains more stringent requirements or emission limitations, or both.





- (j) The requirements and emission limitations of this section supersede the requirements and emission limitations of § § 129.201—129.205, 145.111—145.113 and 145.141—145.146 (relating to additional NOx requirements; emissions of NOx from stationary internal combustion engines; and emissions of NOx from cement manufacturing) unless the requirements or emission limitations of § § 129.201—129.205, § § 145.111—145.113 or § § 145.141—145.146 are more stringent.
- (k) (m) [NA- SOURCE 043 CAN MEET PRESUMPTIVE RACT]
- § 129.98. [NA NO AVERAGING PLAN]
- § 129.99. [NA NO ALTERNATIVE RACT OR COMPLIANCE SCHEDULE]
- § 129.100. Compliance demonstration and recordkeeping requirements.
- (a) Except as provided in subsection (c), the owner and operator of an air contamination source subject to a NOx RACT requirement or RACT emission limitation or VOC RACT requirement or RACT emission limitation, or both, listed in § 129.97 (relating to presumptive RACT requirements, RACT emission limitations and petition for alternative compliance schedule) shall demonstrate compliance with the applicable RACT requirement or RACT emission limitation by performing the following monitoring or testing procedures:
 - (1) [NA NO CEMS]
 - (2) [NA NO CEMENT KILNS]
 - (3) [NA NO MWI]
- (4) For an air contamination source without a CEMS, monitoring and testing in accordance with a Department-approved emissions source test that meets the requirements of Chapter 139, Subchapter A (relating to sampling and testing methods and procedures). The source test shall be conducted one time in each 5-year calendar period.
- (b) Except as provided in § 129.97(k) and § 129.99(i) (relating to alternative RACT proposal and petition for alternative compliance schedule), the owner and operator of an air contamination source subject to subsection (a) shall demonstrate compliance with the applicable RACT requirement or RACT emission limitation in accordance with the procedures in subsection (a) not later than:
 - (1) January 1, 2017, for a source subject to § 129.96(a) (relating to applicability).
 - (2) [NA SOURCE IS EXISTING]
- (c) [NA NO WAIVER REQUESTED]
- (d) The owner and operator of an air contamination source subject to this section and § § 129.96—129.99 shall keep records to demonstrate compliance with § § 129.96—129.99 in the following manner:
- (1) The records must include sufficient data and calculations to demonstrate that the requirements of § § 129.96—129.99 are met.
- (2) Data or information required to determine compliance shall be recorded and maintained in a time frame consistent with the averaging period of the requirement.
- (e) [NA TURBINE NOT EXEMPT FROM NOX REQUIREMENTS]
- (f) [NA TURBINE NOT EXEMPT FROM VOC REQUIREMENTS]
- (g) [NA-NOT SUBJECT TO § 129.97(b)]
- (h) [NA NO CEMENT KILN]





(i) The records shall be retained by the owner or operator for 5 years and made available to the Department or appropriate approved local air pollution control agency upon receipt of a written request from the Department or appropriate approved local air pollution control agency.

*** Permit Shield in Effect. ***

DEP Auth ID: 1404295 DEP PF ID:





Group Name: SG05

Group Description: NSPS Subpart KKKK - Stationary Combustion Turbines

Sources included in this group

ID	Name
046	SOLAR TURBINE 2 (7,700 HP)
047	SOLAR TURBINE 3 (7,700 HP)

I. RESTRICTIONS.

No additional requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

II. TESTING REQUIREMENTS.

No additional testing requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

III. MONITORING REQUIREMENTS.

No additional monitoring requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

IV. RECORDKEEPING REQUIREMENTS.

No additional record keeping requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

V. REPORTING REQUIREMENTS.

No additional reporting requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

VI. WORK PRACTICE REQUIREMENTS.

No additional work practice requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

VII. ADDITIONAL REQUIREMENTS.

001 [40 CFR Part 60 Standards of Performance for New Stationary Sources §40 CFR 60.4300] Subpart KKKK - Standards of Performance for Stationary Combustion Turbines What is the purpose of this subpart?

60.4300 What is the purpose of this subpart?

This subpart establishes emission standards and compliance schedules for the control of emissions from stationary combustion turbines that commenced construction, modification or reconstruction after February 18, 2005.

Applicability

§60.4305 Does this subpart apply to my stationary combustion turbine?

- (a) If you are the owner or operator of a stationary combustion turbine with a heat input at peak load equal to or greater than 10.7 gigajoules (10 MMBtu) per hour, based on the higher heating value of the fuel, which commenced construction, modification, or reconstruction after February 18, 2005, your turbine is subject to this subpart. Only heat input to the combustion turbine should be included when determining whether or not this subpart is applicable to your turbine. Any additional heat input to associated heat recovery steam generators (HRSG) or duct burners should not be included when determining your peak heat input. However, this subpart does apply to emissions from any associated HRSG and duct burners.
- (b) Stationary combustion turbines regulated under this subpart are exempt from the requirements of subpart GG of this





part. Heat recovery steam generators and duct burners regulated under this subpart are exempted from the requirements of subparts Da, Db, and Dc of this part.

§60.4310 What types of operations are exempt from these standards of performance?

- (a) [N/A NOT EMERGENCY COMBUSTION TURBINE]
- (b) [N/A NOT ENGAGED IN RESEARCH AND DEVELOPMENT]
- (c) [N/A NOT SUBJECT TO SUBPART Da]
- (d) [N/A NO TURBINE TEST CELL/STANDS]

Emission Limits

§60.4315 What pollutants are regulated by this subpart?

The pollutants regulated by this subpart are nitrogen oxide (NOx) and sulfur dioxide (SO2).

§60.4320 What emission limits must I meet for nitrogen oxides (NOx)?

- (a) You must meet the emission limits for NOx specified in Table 1 to this subpart. [FOR A NEW COMBUSTION TURBINE FIRING NATURAL GAS AND HAVING A HEAT INPUT AT PEAK LOAD (HIGHER HEATING VALUE) OF GREATER THAN 50 MMTU/HR AND LESS THAN OR EQUAL TO 850 MMBTU/HR, THE NOX EMISSION STANDARD = 25 ppm @ 15% O2]
- (b) [N/A NO GENERATOR]

§60.4325 What emission limits must I meet for NOx if my turbine burns both natural gas and distillate oil (or some other combination of fuels)?

[N/A - TURBINE BURNS ONLY NATURAL GAS]

§60.4330 What emission limits must I meet for sulfur dioxide (SO2)?

- (a) If your turbine is located in a continental area, you must comply with either paragraph (a)(1), (a)(2), or (a)(3) of this section. If your turbine is located in Alaska, you do not have to comply with the requirements in paragraph (a) of this section until January 1, 2008.
- (1) [N/A FACILITY DOES NOT GENERATE ELECTRICITY]
- (2) You must not burn in the subject stationary combustion turbine any fuel which contains total potential sulfur emissions in excess of 26 ng SO2/J (0.060 lb SO2/MMBtu) heat input. If your turbine simultaneously fires multiple fuels, each fuel must meet this requirement; or
- (3) [N/A THE COMBUSTION TURBINE DOES NOT BURN BIOGAS]
- (b) [N/A THE COMBUSTION TURBINE IS NOT LOCATED IN A NONCONTINENTAL AREA OR A CONTINENTAL AREA THAT THE ADMINISTRATOR DETERMINES DOES NOT HAVE ACCESS TO NATURAL GAS]

[71 FR 38497, July 6, 2006, as amended at 74 FR 11861, Mar. 20, 2009]

General Compliance Requirements

§60.4333 What are my general requirements for complying with this subpart?

(a) You must operate and maintain your stationary combustion turbine, air pollution control equipment, and monitoring equipment in a manner consistent with good air pollution control practices for minimizing emissions at all times including





during startup, shutdown, and malfunction.

(b) [N/A - NO HEAT RECOVERY]

Monitoring

§60.4335 How do I demonstrate compliance for NOx if I use water or steam injection?

[N/A - TURBINES DO NOT USE WATER OR STEAM INJECTION]

§60.4340 How do I demonstrate continuous compliance for NOX if I do not use water or steam injection?

(a) If you are not using water or steam injection to control NOX emissions, you must perform annual performance tests in accordance with §60.4400 to demonstrate continuous compliance. If the NOX emission result from the performance test is less than or equal to 75 percent of the NOX emission limit for the turbine, you may reduce the frequency of subsequent performance tests to once every 2 years (no more than 26 calendar months following the previous performance test). If the results of any subsequent performance test exceed 75 percent of the NOX emission limit for the turbine, you must resume annual performance tests.

(b) [N/A - NO CONTINUOUS MONITORING SYSTEMS]

§60.4345 What are the requirements for the continuous emission monitoring system equipment, if I choose to use this option?

[N/A - NO CEMS]

§60.4350 How do I use data from the continuous emission monitoring equipment to identify excess emissions?

[N/A - NO CEMS]

§60.4355 How do I establish and document a proper parameter monitoring plan?

- (a) [NA NO WATER OR STEAM INJECTION, CONTINUOUS PARAMETER MONITORING NOT REQUIRED]
- (b) [N/A NOT SUBJECT TO PART 75 OF THIS CHAPTER]

§60.4360 How do I determine the total sulfur content of the turbine's combustion fuel?

You must monitor the total sulfur content of the fuel being fired in the turbine, except as provided in §60.4365. The sulfur content of the fuel must be determined using total sulfur methods described in §60.4415. Alternatively, if the total sulfur content of the gaseous fuel during the most recent performance test was less than half the applicable limit, ASTM D4084, D4810, D5504, or D6228, or Gas Processors Association Standard 2377 (all of which are incorporated by reference, see §60.17), which measure the major sulfur compounds, may be used.

§60.4365 How can I be exempted from monitoring the total sulfur content of the fuel?

You may elect not to monitor the total sulfur content of the fuel combusted in the turbine, if the fuel is demonstrated not to exceed potential sulfur emissions of 26 ng SO2/J (0.060 lb SO2/MMBtu) heat input for units located in continental areas and 180 ng SO2/J (0.42 lb SO2/MMBtu) heat input for units located in noncontinental areas or a continental area that the Administrator determines does not have access to natural gas and that the removal of sulfur compounds would cause more environmental harm than benefit. You must use one of the following sources of information to make the required demonstration:

(a) The fuel quality characteristics in a current, valid purchase contract, tariff sheet or transportation contract for the fuel, specifying that the maximum total sulfur content for oil use in continental areas is 0.05 weight percent (500 ppmw) or less and 0.4 weight percent (4,000 ppmw) or less for noncontinental areas, the total sulfur content for natural gas use in continental areas is 20 grains of sulfur or less per 100 standard cubic feet and 140 grains of sulfur or less per 100





standard cubic feet for noncontinental areas, has potential sulfur emissions of less than less than 26 ng SO2/J (0.060 lb SO2/MMBtu) heat input for continental areas and has potential sulfur emissions of less than less than 180 ng SO2/J (0.42 lb SO2/MMBtu) heat input for noncontinental areas; or

(b) [N/A - THE SULFUR CONTENT WILL BE MONITORED BY THE METHOD IN 60.4365(a)]

\$60,4370 How often must I determine the sulfur content of the fuel?

The frequency of determining the sulfur content of the fuel must be as follows:

- (a) [N/A FUEL OIL IS NOT BURNED, ONLY NATURAL GAS]
- (b) Gaseous fuel. [N/A THE SULFUR CONTENT WILL BE MONITORED BY THE METHOD IN 60.4365(a)]
- (c) Custom schedules [N/A CUSTOM SCHEDULE NOT DEVELOPED]

Reporting

§60.4375 What reports must I submit?

- (a) [NA NO CONTINUOUS MONITORING OR PERIODIC FUEL SULFUR CONTENT DETERMINATIONS REQUIRED]
- (b) For each affected unit that performs annual performance tests in accordance with §60.4340(a), you must submit a written report of the results of each performance test before the close of business on the 60th day following the completion of the performance test.

§60.4380 How are excess emissions and monitor downtime defined for NOX?

For the purpose of reports required under §60.7(c), periods of excess emissions and monitor downtime that must be reported are defined as follows:

- (a) [N/A DOES NOT UTILIZE WATER OR STEAM TO FUEL RATIO MONITORING]
- (b) [N/A NO CEMS]
- (c) [NA NO CONTINUOUS PARAMETER MONITORING REQUIRED]

§60.4385 How are excess emissions and monitoring downtime defined for SO2?

[N/A - THE SULFUR CONTENT WILL BE MONITORED BY THE METHOD IN 60.4365(a)]

§60.4390 What are my reporting requirements if I operate an emergency combustion turbine or a research and development turbine?

[N/A - TURBINES NOT USED FOR EMERGENCY OR RESEARCH AND DEVELOPMENT]

§60.4395 When must I submit my reports?

All reports required under §60.7(c) must be postmarked by the 30th day following the end of each 6-month period.

Performance Tests

- §60.4400 How do I conduct the initial and subsequent performance tests, regarding NOX?
- (a) You must conduct an initial performance test, as required in §60.8. Subsequent NOX performance tests shall be conducted on an annual basis (no more than 14 calendar months following the previous performance test).





- (1) There are two general methodologies that you may use to conduct the performance tests. For each test run:
- (i) Measure the NOX concentration (in parts per million (ppm)), using EPA Method 7E or EPA Method 20 in appendix A of this part. For units complying with the output based standard, concurrently measure the stack gas flow rate, using EPA Methods 1 and 2 in appendix A of this part, and measure and record the electrical and thermal output from the unit. Then, use the following equation to calculate the NOX emission rate:

[N/A - EQUATION 5 NOT REQUIRED SINCE Ib/MWh IS NOT UTILIZED]

or

- (ii) Measure the NOX and diluent gas concentrations, using either EPA Methods 7E and 3A, or EPA Method 20 in appendix A of this part. Concurrently measure the heat input to the unit, using a fuel flowmeter (or flowmeters), and measure the electrical and thermal output of the unit. Use EPA Method 19 in appendix A of this part to calculate the NOX emission rate in lb/MMBtu. Then, use Equations 1 and, if necessary, 2 and 3 in §60.4350(f) to calculate the NOX emission rate in lb/MWh.
- (2) Sampling traverse points for NOX and (if applicable) diluent gas are to be selected following EPA Method 20 or EPA Method 1 (non-particulate procedures), and sampled for equal time intervals. The sampling must be performed with a traversing single-hole probe, or, if feasible, with a stationary multi-hole probe that samples each of the points sequentially. Alternatively, a multi-hole probe designed and documented to sample equal volumes from each hole may be used to sample simultaneously at the required points.
- (3) Notwithstanding paragraph (a)(2) of this section, you may test at fewer points than are specified in EPA Method 1 or EPA Method 20 in appendix A of this part if the following conditions are met:
- (i) You may perform a stratification test for NOX and diluent pursuant to
- (A) [Reserved], or
- (B) The procedures specified in section 6.5.6.1(a) through (e) of appendix A of part 75 of this chapter.
- (ii) Once the stratification sampling is completed, you may use the following alternative sample point selection criteria for the performance test:
- (A) If each of the individual traverse point NOX concentrations is within ±10 percent of the mean concentration for all traverse points, or the individual traverse point diluent concentrations differs by no more than ±5ppm or ±0.5 percent CO2 (or O2) from the mean for all traverse points, then you may use three points (located either 16.7, 50.0 and 83.3 percent of the way across the stack or duct, or, for circular stacks or ducts greater than 2.4 meters (7.8 feet) in diameter, at 0.4, 1.2, and 2.0 meters from the wall). The three points must be located along the measurement line that exhibited the highest average NOX concentration during the stratification test; or
- (B) For turbines with a NOX standard greater than 15 ppm @ 15% O2, you may sample at a single point, located at least 1 meter from the stack wall or at the stack centroid if each of the individual traverse point NOX concentrations is within ±5 percent of the mean concentration for all traverse points, or the individual traverse point diluent concentrations differs by no more than ±3ppm or ±0.3 percent CO2 (or O2) from the mean for all traverse points; or
- (C) For turbines with a NOX standard less than or equal to 15 ppm @ 15% O2, you may sample at a single point, located at least 1 meter from the stack wall or at the stack centroid if each of the individual traverse point NOX concentrations is within ±2.5 percent of the mean concentration for all traverse points, or the individual traverse point diluent concentrations differs by no more than ±1ppm or ±0.15 percent CO2 (or O2) from the mean for all traverse points.
- (b) The performance test must be done at any load condition within plus or minus 25 percent of 100 percent of peak load. You may perform testing at the highest achievable load point, if at least 75 percent of peak load cannot be achieved in practice. You must conduct three separate test runs for each performance test. The minimum time per run is 20 minutes.
- (1) [N/A COMBUSTION TURBINE BURNS ONLY NG]

DEP Auth ID: 1404295 DEP PF ID: Page 61



- (2) [N/A TURBINE NOT COMBINED CYCLE]
- (3) [N/A THE COMBUSTION TURBINE DOES NOT EMPLOY WATER OR STEAM INJECTION]
- (4) Compliance with the applicable emission limit in §60.4320 must be demonstrated at each tested load level. Compliance is achieved if the three-run arithmetic average NOX emission rate at each tested level meets the applicable emission limit in §60.4320.
- (5) [N/A NO CEMS]
- (6) The ambient temperature must be greater than 0 °F during the performance test.
- §60.4405 How do I perform the initial performance test if I have chosen to install a NOX-diluent CEMS?

[N/A - NO CEMS]

§60.4410 How do I establish a valid parameter range if I have chosen to continuously monitor parameters?

[NA - NO CONTINUOUS PARAMETER MONITORING REQUIRED]

§60.4415 How do I conduct the initial and subsequent performance tests for sulfur?

- (a) [NA SULFUR CONTENT MONITORED PER 60.4365(a) SO PERFORMANCE TESTS NOT REQUIRED]
- (b) [Reserved]

Regulatory Changes

Individual sources within this source group that are subject to 40 CFR Part 60 Subpart KKKK shall comply with all applicable requirements of the Subpart. 40 CFR Part 60.4 requires submission of copies of all requests, reports and other communications to both the Department and the EPA. The EPA copies shall be forwarded to:

U.S. EPA

Region III, Air and Radiation Division Permits Branch (3AD10) Four Penn Center 1600 John F. Kennedy Boulevard Philadelphia, PA 19103-2852

The DEP copies shall be forwarded to the DEP SCRO Air Quality Program Manager at wiweaver@pa.gov, unless otherwise directed in writing by DEP.

In the event that the Federal Subpart that is the subject of this Source Group is revised, the permittee shall comply with the revised version of the subpart, and shall not be required to comply with any provisions in this permit designated as having the subpart as their authority, to the extent that such permit provisions would be inconsistent with the applicable provisions of the revised subpart.

*** Permit Shield in Effect. ***





Group Name: SG06

Group Description: MACT Subpart ZZZZ

Sources included in this group

ID Name

044 CATERPILLAR EMERGENCY GEN 30536

I. RESTRICTIONS.

No additional requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

II. TESTING REQUIREMENTS.

No additional testing requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

III. MONITORING REQUIREMENTS.

No additional monitoring requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

IV. RECORDKEEPING REQUIREMENTS.

No additional record keeping requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

V. REPORTING REQUIREMENTS.

No additional reporting requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

VI. WORK PRACTICE REQUIREMENTS.

No additional work practice requirements exist except as provided in other sections of this permit including Section B (Title V General Requirements).

VII. ADDITIONAL REQUIREMENTS.

001 [40 CFR Part 63 NESHAPS for Source Categories §40 CFR 63.6585]

Subpart ZZZZ - National Emissions Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines

Am I subject to this subpart?

§ 63.6585 Am I subject to this subpart?

You are subject to this subpart if you own or operate a stationary RICE at a major or area source of HAP emissions, except if the stationary RICE is being tested at a stationary RICE test cell/stand.

- (a) A stationary RICE is any internal combustion engine which uses reciprocating motion to convert heat energy into mechanical work and which is not mobile. Stationary RICE differ from mobile RICE in that a stationary RICE is not a non-road engine as defined at 40 CFR 1068.30, and is not used to propel a motor vehicle or a vehicle used solely for competition.
- (b) A major source of HAP emissions is a plant site that emits or has the potential to emit any single HAP at a rate of 10 tons (9.07 megagrams) or more per year or any combination of HAP at a rate of 25 tons (22.68 megagrams) or more per year, except that for oil and gas production facilities, a major source of HAP emissions is determined for each surface site.
- (c) An area source of HAP emissions is a source that is not a major source.
- (d) If you are an owner or operator of an area source subject to this subpart, your status as an entity subject to a standard or





other requirements under this subpart does not subject you to the obligation to obtain a permit under 40 CFR part 70 or 71, provided you are not required to obtain a permit under 40 CFR 70.3(a) or 40 CFR 71.3(a) for a reason other than your status as an area source under this subpart. Notwithstanding the previous sentence, you must continue to comply with the provisions of this subpart as applicable.

- (e) [NA NOT USED FOR NATIONAL SECURITY PURPOSES]
- (f) [NA RICE NOT RESIDENTIAL, COMMERCIAL OR INSTITUTIONAL]

[69 FR 33506, June 15, 2004, as amended at 73 FR 3603, Jan. 18, 2008; 78 FR 6700, Jan. 30, 2013; 87 FR 48607, Aug. 10, 2022]

§ 63.6590 What parts of my plant does this subpart cover?

This subpart applies to each affected source.

- (a) Affected source. An affected source is any existing, new, or reconstructed stationary RICE located at a major or area source of HAP emissions, excluding stationary RICE being tested at a stationary RICE test cell/stand.
- (1) Existing stationary RICE.
- (i) [NA NOT A MAJOR HAP SOURCE]
- (ii) [NA NOT A MAJOR HAP SOURCE]
- (iii) For stationary RICE located at an area source of HAP emissions, a stationary RICE is existing if you commenced construction or reconstruction of the stationary RICE before June 12, 2006.
- (iv) A change in ownership of an existing stationary RICE does not make that stationary RICE a new or reconstructed stationary RICE.
- (2) New stationary RICE.
- (i) [NA NOT A MAJOR HAP SOURCE]
- (ii) [NA NOT A MAJOR HAP SOURCE]
- (iii) [NA NOT A NEW SOURCE]
- (3) [NA NOT A RECONSTRUCTED SOURCE]
- (b) Stationary RICE subject to limited requirements. (1) An affected source which meets either of the criteria in paragraphs (b)(1)(i) through (ii) of this section does not have to meet the requirements of this subpart and of subpart A of this part except for the initial notification requirements of § 63.6645(f).
- (i) [NA NOT A MAJOR HAP SOURCE]
- (ii) [NA NOT A MAJOR HAP SOURCE]
- (2) [NA NOT A MAJOR HAP SOURCE AND DOES NOT COMBUST LFG]
- (3) The following stationary RICE do not have to meet the requirements of this subpart and of subpart A of this part, including initial notification requirements:
- (i) [NA NOT A MAJOR HAP SOURCE]
- (ii) [NA NOT A MAJOR HAP SOURCE]

DEP Auth ID: 1404295 DEP PF ID:



- (iii) [NA NOT A MAJOR HAP SOURCE]
- (iv) [NA NOT A MAJOR HAP SOURCE]
- (v) [NA NOT A MAJOR HAP SOURCE AND DOES NOT COMBUST LFG]
- (c) [NA NOT SUBJECT TO SUBPARTS IIII OR JJJJ]

[69 FR 33506, June 15, 2004, as amended at 73 FR 3604, Jan. 18, 2008; 75 FR 9674, Mar. 3, 2010; 75 FR 37733, June 30, 2010; 75 FR 51588, Aug. 20, 2010; 78 FR 6700, Jan. 30, 2013; 87 FR 48607, Aug. 10, 2022]

§ 63.6595 When do I have to comply with this subpart?

(a) Affected sources. (1) If you have an existing stationary RICE, excluding existing non-emergency CI stationary RICE, with a site rating of more than 500 brake HP located at a major source of HAP emissions, you must comply with the applicable emission limitations, operating limitations and other requirements no later than June 15, 2007. IF YOU HAVE an existing non-emergency CI stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, an existing stationary CI RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions, or AN EXISTING STATIONARY CI RICE LOCATED AT AN AREA SOURCE OF HAP EMISSIONS, YOU MUST COMPLY WITH THE APPLICABLE EMISSION LIMITATIONS, OPERATING LIMITATIONS, AND OTHER REQUIREMENTS NO LATER THAN MAY 3, 2013.

IF YOU HAVE an existing stationary SI RICE with a site rating of less than or equal to 500 brake HP located at a major source of hap emissions, or AN EXISTING STATIONARY SI RICE LOCATED AT AN AREA SOURCE OF HAP EMISSIONS, YOU MUST COMPLY WITH THE APPLICABLE EMISSION LIMITATIONS, OPERATING LIMITATIONS, AND OTHER REQUIREMENTS NO LATER THAN OCTOBER 19. 2013.

- (2) [NA NOT A MAJOR HAP SOURCE]
- (3) [NA NOT A MAJOR HAP SOURCE]
- (4) [NA NOT A MAJOR HAP SOURCE]
- (5) [NA NOT A MAJOR HAP SOURCE]
- (6) [NA NOT SUBJECT TO EMISSION OR OPERATING LIMITATIONS]
- (7) [NA NOT SUBJECT TO EMISSION OR OPERATING LIMITATIONS]
- (b) Area sources that become major sources. If you have an area source that increases its emissions or its potential to emit such that it becomes a major source of HAP, the compliance dates in paragraphs (b)(1) and (2) of this section apply to you.
- (1) Any stationary RICE for which construction or reconstruction is commenced after the date when your area source becomes a major source of HAP must be in compliance with this subpart upon startup of your affected source.
- (2) Any stationary RICE for which construction or reconstruction is commenced before your area source becomes a major source of HAP must be in compliance with the provisions of this subpart that are applicable to RICE located at major sources within 3 years after your area source becomes a major source of HAP.
- (c) If you own or operate an affected source, you must meet the applicable notification requirements in § 63.6645 and in 40 CFR part 63, subpart A.

[69 FR 33506, June 15, 2004, as amended at 73 FR 3604, Jan. 18, 2008; 75 FR 9675, Mar. 3, 2010; 75 FR 51589, Aug. 20, 2010; 78 FR 6701, Jan. 30, 2013]

Emission and Operating Limitations





§ 63.6600 What emission limitations and operating limitations must I meet if I own or operate a stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions?

[NA - NOT SUBJECT TO EMISSION OR OPERATING LIMITATIONS]

§ 63.6601 What emission limitations must I meet if I own or operate a new or reconstructed 4SLB stationary RICE with a site rating of greater than or equal to 250 brake HP and less than or equal to 500 brake HP located at a major source of HAP emissions?

[NA - NOT SUBJECT TO EMISSION OR OPERATING LIMITATIONS]

§ 63.6602 What emission limitations and other requirements must I meet if I own or operate an existing stationary RICE with a site rating of equal to or less than 500 brake HP located at a major source of HAP emissions?

[NA - NOT SUBJECT TO EMISSION OR OPERATING LIMITATIONS]

§ 63.6603 What emission limitations, operating limitations, and other requirements must I meet if I own or operate an existing stationary RICE located at an area source of HAP emissions?

Compliance with the numerical emission limitations established in this subpart is based on the results of testing the average of three 1-hour runs using the testing requirements and procedures in § 63.6620 and Table 4 to this subpart.

(a) If you own or operate an existing stationary RICE located at an area source of HAP emissions, YOU MUST COMPLY WITH THE REQUIREMENTS IN TABLE 2d to this subpart and the operating limitations in Table 2b to this subpart that apply to you.

TABLE 2d REQUIREMENTS:

- 4. For each EMERGENCY STATIONARY CI RICE and black start stationary CI RICE**, you must meet the following requirement, except during periods of startup:
- a. Change oil and filter every 500 hours of operation or annually, whichever comes first*;
- b. Inspect air cleaner every 1,000 hours of operation or annually, whichever comes first, and replace as necessary; and
- c. Inspect all hoses and belts every 500 hours of operation or annually, whichever comes first, and replace as necessary.
- 5. For each EMERGENCY STATIONARY SI RICE; black start stationary SI RICE; non-emergency, non-black start 4SLB stationary RICE >500 HP that operate 24 hours or less per calendar year; non-emergency, non-black start 4SRB stationary RICE >500 HP that operate 24 hours or less per calendar year**, you must meet the following requirement, except during periods of startup:
- a. Change oil and filter every 500 hours of operation or annually, whichever comes first*;
- b. Inspect spark plugs every 1,000 hours of operation or annually, whichever comes first, and replace as necessary; and
- c. Inspect all hoses and belts every 500 hours of operation or annually, whichever comes first, and replace as necessary.
- *Sources have the option to utilize an oil analysis program as described in § 63.6625(i) or (j) in order to extend the specified oil change requirement in Table 2d of this subpart.
- **If an emergency engine is operating during an emergency and it is not possible to shut down the engine in order to perform the management practice requirements on the schedule required in Table 2d of this subpart, or if performing the management practice on the required schedule would otherwise pose an unacceptable risk under federal, state, or local law, the management practice can be delayed until the emergency is over or the unacceptable risk under federal, state, or local law has abated. The management practice should be performed as soon as practicable after the emergency has





ended or the unacceptable risk under federal, state, or local law has abated. Sources must report any failure to perform the management practice on the schedule required and the federal, state or local law under which the risk was deemed unacceptable.

[END OF TABLE 2d REQUIREMENTS]

- (b) [NA EMERGENCY ENGINE(S)]
- (c) [NA EMERGENCY ENGINE(S)]
- (d) [NA EMERGENCY ENGINE(S)]
- (e) [NA EMERGENCY ENGINE(S)]
- (f) [NA EMERGENCY ENGINE(S)]

[75 FR 9675, Mar. 3, 2010, as amended at 75 FR 51589, Aug. 20, 2010; 76 FR 12866, Mar. 9, 2011; 78 FR 6701, Jan. 30, 2013]

- § 63.6604 What fuel requirements must I meet if I own or operate a stationary CI RICE?
- (a) [NA EMERGENCY ENGINE(S)]
- (b) Beginning January 1, 2015, if you own or operate an existing emergency CI stationary RICE with a site rating of more than 100 brake HP and a displacement of less than 30 liters per cylinder that uses diesel fuel and operates for the purpose specified in § 63.6640(f)(4)(ii), you must use diesel fuel that meets the requirements in 40 CFR 1090.305 for nonroad diesel fuel, except that any existing diesel fuel purchased (or otherwise obtained) prior to January 1, 2015, may be used until depleted.
- (c) [NA NOT A MAJOR SOURCE]
- (d) [NA NOT IN SPECIFIED GEOGRAPHIC LOCATIONS]

[78 FR 6702, Jan. 30, 2013, as amended at 85 FR 78463, Dec. 4, 2020; 87 FR 48607, Aug. 10, 2022]

General Compliance Requirements

- § 63.6605 What are my general requirements for complying with this subpart?
- (a) You must be in compliance with the emission limitations, operating limitations, and other requirements in this subpart that apply to you at all times.
- (b) At all times you must operate and maintain any affected source, including associated air pollution control equipment and monitoring equipment, in a manner consistent with safety and good air pollution control practices for minimizing emissions. The general duty to minimize emissions does not require you to make any further efforts to reduce emissions if levels required by this standard have been achieved. Determination of whether such operation and maintenance procedures are being used will be based on information available to the Administrator which may include, but is not limited to, monitoring results, review of operation and maintenance procedures, review of operation and maintenance records, and inspection of the source.

[75 FR 9675, Mar. 3, 2010, as amended at 78 FR 6702, Jan. 30, 2013]

Testing and Initial Compliance Requirements

§ 63.6610 By what date must I conduct the initial performance tests or other initial compliance demonstrations if I own or operate a stationary RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions?





[NA - NOT A MAJOR HAP SOURCE]

§ 63.6611 By what date must I conduct the initial performance tests or other initial compliance demonstrations if I own or operate a new or reconstructed 4SLB SI stationary RICE with a site rating of greater than or equal to 250 and less than or equal to 500 brake HP located at a major source of HAP emissions?

[NA - NOT A MAJOR HAP SOURCE]

§ 63.6612 By what date must I conduct the initial performance tests or other initial compliance demonstrations if I own or operate an existing stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions or an existing stationary RICE located at an area source of HAP emissions?

[NA - NO PERFORMANCE TESTING REQUIRED]

§ 63.6615 When must I conduct subsequent performance tests?

[NA - NOT SUBJECT TO EMISSION OR OPERATING LIMITATIONS]

§ 63.6620 What performance tests and other procedures must I use?

[NA - NO PERFORMANCE TESTING REQUIRED]

§ 63.6625 What are my monitoring, installation, collection, operation, and maintenance requirements?

- (a) [NA CEMS NOT REQUIRED]
- (b) [NA CPMS NOT REQUIRED]
- (c) [NA LFG NOT USED]
- (d) [NA NOT A MAJOR HAP SOURCE]
- (e) If you own or operate any of the following stationary RICE, you must operate and maintain the stationary RICE and after-treatment control device (if any) according to the manufacturer's emission-related written instructions or develop your own maintenance plan which must provide to the extent practicable for the maintenance and operation of the engine in a manner consistent with good air pollution control practice for minimizing emissions:
- (1) [NA NOT A MAJOR HAP SOURCE]
- (2) [NA NOT A MAJOR HAP SOURCE]
- (3) An existing emergency or black start stationary RICE located at an area source of HAP emissions;
- (4) [NA EMERGENCY ENGINE(S)]
- (5) [NA EMERGENCY ENGINE(S)]
- (6) [NA EMERGENCY ENGINE(S)]
- (7) [NA EMERGENCY ENGINE(S)]
- (8) [NA EMERGENCY ENGINE(S)]
- (9) [NA EMERGENCY ENGINE(S)]
- (10) [NA EMERGENCY ENGINE(S)]





(f) If you own or operate an existing emergency stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions or an existing emergency stationary RICE located at an area source of HAP emissions, you must install a non-resettable hour meter if one is not already installed.

(g) [NA - EMERGENCY ENGINE(S)]

- (h) If you operate a new, reconstructed, or existing stationary engine, you must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes, after which time the emission standards applicable to all times other than startup in Tables 1a, 2a, 2c, and 2d to this subpart apply.
- (i) If you own or operate a stationary CI engine that is subject to the work, operation or management practices in items 1 or 2 of Table 2c to this subpart or in items 1 or 4 of Table 2d to this subpart, you have the option of utilizing an oil analysis program in order to extend the specified oil change requirement in Tables 2c and 2d to this subpart. The oil analysis must be performed at the same frequency specified for changing the oil in Table 2c or 2d to this subpart. The analysis program must at a minimum analyze the following three parameters: Total Base Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Base Number is less than 30 percent of the Total Base Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 business days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 business days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the analysis, and the oil changes for the engine. The analysis program must be part of the maintenance plan for the engine.
- (j) If you own or operate a stationary SI engine that is subject to the work, operation or management practices in items 6, 7, or 8 of Table 2c to this subpart or in items 5, 6, 7, 9, or 11 of Table 2d to this subpart, you have the option of utilizing an oil analysis program in order to extend the specified oil change requirement in Tables 2c and 2d to this subpart. The oil analysis must be performed at the same frequency specified for changing the oil in Table 2c or 2d to this subpart. The analysis program must at a minimum analyze the following three parameters: Total Acid Number, viscosity, and percent water content. The condemning limits for these parameters are as follows: Total Acid Number increases by more than 3.0 milligrams of potassium hydroxide (KOH) per gram from Total Acid Number of the oil when new; viscosity of the oil has changed by more than 20 percent from the viscosity of the oil when new; or percent water content (by volume) is greater than 0.5. If all of these condemning limits are not exceeded, the engine owner or operator is not required to change the oil. If any of the limits are exceeded, the engine owner or operator must change the oil within 2 business days of receiving the results of the analysis; if the engine is not in operation when the results of the analysis are received, the engine owner or operator must change the oil within 2 business days or before commencing operation, whichever is later. The owner or operator must keep records of the parameters that are analyzed as part of the program, the results of the engine.

[69 FR 33506, June 15, 2004, as amended at 73 FR 3606, Jan. 18, 2008; 75 FR 9676, Mar. 3, 2010; 75 FR 51589, Aug. 20, 2010; 76 FR 12866, Mar. 9, 2011; 78 FR 6703, Jan. 30, 2013]

§ 63.6630 How do I demonstrate initial compliance with the emission limitations, operating limitations, and other requirements?

- (a) You must demonstrate initial compliance with each emission limitation, operating limitation, and other requirement that applies to you according to Table 5 of this subpart. [NA NONE OF THE CATEGORIES IN TABLE 5 APPLY TO EMERGENCY ENGINES]
- (b) [NA PERFORMANCE TESTING NOT REQUIRED]
- (c) [NA NOCS NOT REQUIRED FOR EXISTING EMERGENCY RICE]
- (d) [NA EMERGENCY ENGINE(S)]





(e) [NA - EMERGENCY ENGINE(S)]

[69 FR 33506, June 15, 2004, as amended at 78 FR 6704, Jan. 30, 2013]

Continuous Compliance Requirements

§ 63.6635 How do I monitor and collect data to demonstrate continuous compliance?

[NA - NOT SUBJECT TO EMISSION OR OPERATING LIMITATIONS]

§ 63.6640 How do I demonstrate continuous compliance with the emission limitations, operating limitations, and other requirements?

(a) You must demonstrate continuous compliance with each emission limitation, operating limitation, and other requirements in Tables 1a and 1b, Tables 2a and 2b, Table 2c, and Table 2d to this subpart that apply to you according to methods specified in Table 6 to this subpart.

TABLE 6 REQUIREMENTS

- 9. FOR EACH existing emergency and black start stationary RICE <=500 HP located at a major source of HAP, existing non-emergency stationary RICE <100 HP located at a major source of HAP, EXISTING EMERGENCY and black start STATIONARY RICE LOCATED AT AN AREA SOURCE OF HAP, existing non-emergency stationary CI RICE =300 HP located at an area source of HAP, existing non-emergency 2SLB stationary RICE located at an area source of HAP, existing non-emergency stationary SI RICE located at an area source of HAP which combusts landfill or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis, existing non-emergency 4SLB and 4SRB stationary RICE <=500 HP located at an area source of HAP, existing non-emergency 4SLB and 4SRB stationary RICE >500 HP located at an area source of HAP that operate 24 hours or less per calendar year, and existing non-emergency 4SLB and 4SRB stationary RICE >500 HP located at an area source of HAP that are remote stationary RICE, complying with the requirement to "Work or Management practices", you must demonstrate continuous compliance by:
- $i.\ Operating\ and\ maintaining\ the\ stationary\ RICE\ according\ to\ the\ manufacturer's\ emission-related\ operation\ and\ maintenance\ instructions;$
- ii. Develop and follow your own maintenance plan which must provide to the extent practicable for the maintenance and operation of the engine in a manner consistent with good air pollution control practice for minimizing emissions.

[END OF TABLE 6 REQUIREMENTS]

- (b) [NA NOT SUBJECT TO EMISSION OR OPERATING LIMITATIONS]
- (c) [NA ANNUAL COMPLIANCE DEMONSTRATION NOT REQUIRED]
- (d) $[NA-NOT\ SUBJECT\ TO\ EMISSION\ OR\ OPERATING\ LIMITATIONS]$
- (e) You must also report each instance in which you did not meet the requirements in Table 8 to this subpart that apply to you. If you own or operate a new or reconstructed stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions (except new or reconstructed 4SLB engines greater than or equal to 250 and less than or equal to 500 brake HP), a new or reconstructed stationary RICE located at an area source of HAP emissions, or any of the following RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you do not need to comply with the requirements in Table 8 to this subpart: An existing 2SLB stationary RICE, an existing 4SLB stationary RICE, an existing emergency stationary RICE, an existing limited use stationary RICE, or an existing stationary RICE which fires landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis. If you own or operate any of the following RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you do not need to comply with the requirements in Table 8 to this subpart, except for the initial notification requirements: a new or reconstructed stationary RICE that combusts landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis, a new or reconstructed emergency stationary RICE, or a new or





reconstructed limited use stationary RICE. [EXISTING EMERGENCY RICE AT AREA HAP SOURCES ARE NOT AMONG THOSE EXEMPTED FROM THIS SECTION]

- (f) If you own or operate an emergency stationary RICE, you must operate the emergency stationary RICE according to the requirements in paragraphs (f)(1) through (4) of this section. In order for the engine to be considered an emergency stationary RICE under this subpart, any operation other than emergency operation, maintenance and testing, and operation in non-emergency situations for 50 hours per year, as described in paragraphs (f)(1) through (4), is prohibited. If you do not operate the engine according to the requirements in paragraphs (f)(1) through (4), the engine will not be considered an emergency engine under this subpart and must meet all requirements for non-emergency engines.
- (1) There is no time limit on the use of emergency stationary RICE in emergency situations.
- (2) You may operate your emergency stationary RICE for the purpose specified in paragraph (f)(2)(i) of this section for a maximum of 100 hours per calendar year. Any operation for non-emergency situations as allowed by paragraphs (f)(3) and (4) of this section counts as part of the 100 hours per calendar year allowed by this paragraph (f)(2).
- (i) Emergency stationary RICE may be operated for maintenance checks and readiness testing, provided that the tests are recommended by federal, state or local government, the manufacturer, the vendor, the regional transmission organization or equivalent balancing authority and transmission operator, or the insurance company associated with the engine. The owner or operator may petition the Administrator for approval of additional hours to be used for maintenance checks and readiness testing, but a petition is not required if the owner or operator maintains records indicating that federal, state, or local standards require maintenance and testing of emergency RICE beyond 100 hours per calendar year.
- (ii)-(iii) [Reserved]
- (3) [NA NOT A MAJOR HAP SOURCE]
- (4) Emergency stationary RICE located at area sources of HAP may be operated for up to 50 hours per calendar year in non-emergency situations. The 50 hours of operation in non-emergency situations are counted as part of the 100 hours per calendar year for maintenance and testing provided in paragraph (f)(2) of this section. Except as provided in paragraphs (f)(4)(i) and (ii) of this section, the 50 hours per year for non-emergency situations cannot be used for peak shaving or non-emergency demand response, or to generate income for a facility to an electric grid or otherwise supply power as part of a financial arrangement with another entity.
- (i) Prior to May 3, 2014, the 50 hours per year for non-emergency situations can be used for peak shaving or non-emergency demand response to generate income for a facility, or to otherwise supply power as part of a financial arrangement with another entity if the engine is operated as part of a peak shaving (load management program) with the local distribution system operator and the power is provided only to the facility itself or to support the local distribution system.
- (ii) The 50 hours per year for non-emergency situations can be used to supply power as part of a financial arrangement with another entity if all of the following conditions are met:
- (A) The engine is dispatched by the local balancing authority or local transmission and distribution system operator.
- (B) The dispatch is intended to mitigate local transmission and/or distribution limitations so as to avert potential voltage collapse or line overloads that could lead to the interruption of power supply in a local area or region.
- (C) The dispatch follows reliability, emergency operation or similar protocols that follow specific NERC, regional, state, public utility commission or local standards or guidelines.
- (D) The power is provided only to the facility itself or to support the local transmission and distribution system.
- (E) The owner or operator identifies and records the entity that dispatches the engine and the specific NERC, regional, state, public utility commission or local standards or guidelines that are being followed for dispatching the engine. The local balancing authority or local transmission and distribution system operator may keep these records on behalf of the engine owner or operator.





[69 FR 33506, June 15, 2004, as amended at 71 FR 20467, Apr. 20, 2006; 73 FR 3606, Jan. 18, 2008; 75 FR 9676, Mar. 3, 2010; 75 FR 51591, Aug. 20, 2010; 78 FR 6704, Jan. 30, 2013; 87 FR 48607, Aug. 10, 2022]

Notifications, Reports, and Records

- § 63.6645 What notifications must I submit and when?
- (a) You must submit all of the notifications in §§ 63.7(b) and (c), 63.8(e), (f)(4) and (f)(6), 63.9(b) through (e), and (g) and (h) that apply to you by the dates specified if you own or operate any of the following;
- (1) [NA NOT A MAJOR HAP SOURCE]
- (2) [NA PER (5) BELOW]
- (3) [NA NOT A MAJOR HAP SOURCE]
- (4) [NA NOT A MAJOR HAP SOURCE]
- (5) THIS REQUIREMENT DOES NOT APPLY IF YOU OWN OR OPERATE an existing stationary RICE less than 100 HP, AN EXISTING STATIONARY EMERGENCY RICE, OR AN EXISTING STATIONARY RICE THAT IS NOT SUBJECT TO ANY NUMERICAL EMISSION STANDARDS.
- (b) [NA NOT A MAJOR HAP SOURCE]
- (c) [NA NOT A MAJOR HAP SOURCE]
- (d) [NA NOT A MAJOR HAP SOURCE]
- (e) [NA NOT A MAJOR HAP SOURCE]
- (f) [NA 63.6590(b) DOES NOT APPLY]
- (g) [NA PERFORMANCE TEST NOT REQUIRED]
- (h) [NA PERFORMANCE TEST NOT REQUIRED]
- (i) [NA EMERGENCY ENGINE(S)]

[73 FR 3606, Jan. 18, 2008, as amended at 75 FR 9677, Mar. 3, 2010; 75 FR 51591, Aug. 20, 2010; 78 FR 6705, Jan. 30, 2013; 85 FR 73912, Nov. 19, 2020]

- § 63.6650 What reports must I submit and when?
- (a) You must submit each report in Table 7 of this subpart that applies to you.

TABLE 7 REQUIREMENTS

4. For each emergency stationary RICE that operate for the purposes specified in \S 63.6640(f)(4)(ii), you must submit a Report. The report must contain the information in \S 63.6650(h)(1). You must submit the report annually according to the requirements in \S 63.6650(h)(2)-(3).

END OF TABLE 7 REQUIREMENTS

(b) Unless the Administrator has approved a different schedule for submission of reports under § 63.10(a), you must submit each report by the date in Table 7 of this subpart and according to the requirements in paragraphs (b)(1) through (b)(9) of this section.





- (1) [NA ANNUAL REPORT REQUIRED, ONLY UNDER CERTAIN CONDITIONS]
- (2) [NA ANNUAL REPORT REQUIRED, ONLY UNDER CERTAIN CONDITIONS]
- (3) [NA ANNUAL REPORT REQUIRED, ONLY UNDER CERTAIN CONDITIONS]
- (4) [NA ANNUAL REPORT REQUIRED, ONLY UNDER CERTAIN CONDITIONS]
- (5) [NA ANNUAL REPORT REQUIRED, ONLY UNDER CERTAIN CONDITIONS]
- (6) For annual Compliance reports, the first Compliance report must cover the period beginning on the compliance date that is specified for your affected source in § 63.6595 and ending on December 31.
- (7) For annual Compliance reports, the first Compliance report must be postmarked or delivered no later than January 31 following the end of the first calendar year after the compliance date that is specified for your affected source in § 63.6595.
- (8) For annual Compliance reports, each subsequent Compliance report must cover the annual reporting period from January 1 through December 31.
- (9) For annual Compliance reports, each subsequent Compliance report must be postmarked or delivered no later than January 31.
- (c) [NA "COMPLIANCE REPORT" NOT REQUIRED]
- (d) [NA NOT SUBJECT TO EMISSION OR OPERATING LIMITATIONS]
- (e) [NA NOT SUBJECT TO EMISSION OR OPERATING LIMITATIONS]
- (f) [NA NOT SUBJECT TO TITLE V PERMITTING]
- (g) [NA LFG NOT USED]
- (h) If you own or operate an emergency stationary RICE with a site rating of more than 100 brake HP that operates for the purpose specified in § 63.6640(f)(4)(ii), you must submit an annual report according to the requirements in paragraphs (h)(1) through (3) of this section.
- (1) The report must contain the following information:
- (i) Company name and address where the engine is located.
- (ii) Date of the report and beginning and ending dates of the reporting period.
- (iii) Engine site rating and model year.
- (iv) Latitude and longitude of the engine in decimal degrees reported to the fifth decimal place.
- (v)-(vi) {Reserved]
- (vii) Hours spent for operation for the purpose specified in \S 63.6640(f)(4)(ii), including the date, start time, and end time for engine operation for the purposes specified in \S 63.6640(f)(4)(ii). The report must also identify the entity that dispatched the engine and the situation that necessitated the dispatch of the engine.
- (viii) If there were no deviations from the fuel requirements in § 63.6604 that apply to the engine (if any), a statement that there were no deviations from the fuel requirements during the reporting period.
- (ix) If there were deviations from the fuel requirements in § 63.6604 that apply to the engine (if any), information on the number, duration, and cause of deviations, and the corrective action taken.



- (2) The first annual report must cover the calendar year 2015 and must be submitted no later than March 31, 2016. Subsequent annual reports for each calendar year must be submitted no later than March 31 of the following calendar year.
- (3) The annual report must be submitted electronically using the subpart specific reporting form in the Compliance and Emissions Data Reporting Interface (CEDRI) that is accessed through EPA's Central Data Exchange (CDX) (www.epa.gov/cdx). However, if the reporting form specific to this subpart is not available in CEDRI at the time that the report is due, the written report must be submitted to the Administrator at the appropriate address listed in § 63.13.
- [69 FR 33506, June 15, 2004, as amended at 75 FR 9677, Mar. 3, 2010; 78 FR 6705, Jan. 30, 2013; 87 FR 48607, Aug. 10, 2022]
- § 63.6655 What records must I keep?
- (a) [NA NOT SUBJECT TO EMISSION OR OPERATING LIMITATIONS]
- (b) [NA NO CEMS OR CPMS]
- (c) [NA LFG NOT USED]
- (d) [NA NOT SUBJECT TO EMISSION OR OPERATING LIMITATIONS]
- (e) You must keep records of the maintenance conducted on the stationary RICE in order to demonstrate that you operated and maintained the stationary RICE and after-treatment control device (if any) according to your own maintenance plan if you own or operate any of the following stationary RICE;
- (1) [NA NOT A MAJOR HAP SOURCE]
- (2) An existing stationary emergency RICE.
- (3) An existing stationary RICE located at an area source of HAP emissions subject to management practices as shown in Table 2d to this subpart.
- (f) If you own or operate any of the stationary RICE in paragraphs (f)(1) through (2) of this section, you must keep records of the hours of operation of the engine that is recorded through the non-resettable hour meter. The owner or operator must document how many hours are spent for emergency operation, including what classified the operation as emergency and how many hours are spent for non-emergency operation. If the engine is used for the purpose specified in § 63.6640(f)(4)(ii), the owner or operator must keep records of the notification of the emergency situation, and the date, start time, and end time of engine operation for these purposes.
- (1) [NA NOT A MAJOR HAP SOURCE]
- (2) An existing emergency stationary RICE located at an area source of HAP emissions that does not meet the standards applicable to non-emergency engines.
- [69 FR 33506, June 15, 2004, as amended at 75 FR 9678, Mar. 3, 2010; 75 FR 51592, Aug. 20, 2010; 78 FR 6706, Jan. 30, 2013; 87 FR 48607, Aug. 10, 2022]
- § 63.6660 In what form and how long must I keep my records?
- (a) Your records must be in a form suitable and readily available for expeditious review according to § 63.10(b)(1).
- (b) As specified in § 63.10(b)(1), you must keep each record for 5 years following the date of each occurrence, measurement, maintenance, corrective action, report, or record.
- (c) You must keep each record readily accessible in hard copy or electronic form for at least 5 years after the date of each occurrence, measurement, maintenance, corrective action, report, or record, according to § 63.10(b)(1).





[69 FR 33506, June 15, 2004, as amended at 75 FR 9678, Mar. 3, 2010]

Other Requirements and Information

§ 63.6665 What parts of the General Provisions apply to me?

Table 8 to this subpart shows which parts of the General Provisions in §§ 63.1 through 63.15 apply to you. If you own or operate a new or reconstructed stationary RICE with a site rating of less than or equal to 500 brake HP located at a major source of HAP emissions (except new or reconstructed 4SLB engines greater than or equal to 250 and less than or equal to 500 brake HP), a new or reconstructed stationary RICE located at an area source of HAP emissions, or any of the following RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you do not need to comply with any of the requirements of the General Provisions specified in Table 8: An existing 2SLB stationary RICE, an existing 4SLB stationary RICE, an existing stationary RICE that combusts landfill or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis, an existing emergency stationary RICE, or an existing limited use stationary RICE. If you own or operate any of the following RICE with a site rating of more than 500 brake HP located at a major source of HAP emissions, you do not need to comply with the requirements in the General Provisions specified in Table 8 except for the initial notification requirements: A new stationary RICE that combusts landfill gas or digester gas equivalent to 10 percent or more of the gross heat input on an annual basis, a new emergency stationary RICE, or a new limited use stationary RICE. [EXISTING EMERGENCY RICE AT AREA HAP SOURCES ARE NOT AMONG THOSE EXEMPTED FROM THIS SECTION]

[75 FR 9678, Mar. 3, 2010]

§ 63.6675 What definitions apply to this subpart? [INCORPORATED BY REFERENCE]

Regulatory Changes:

Individual sources within this source group that are subject to 40 CFR Part 63 Subpart ZZZZ -National Emissions Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines shall comply with all applicable requirements of the Subpart. 40 CFR 63.13(a) requires submission of copies of all requests, reports and other communications to both the Department and the EPA The EPA copies shall be forwarded to:

U.S. EPA Region III, Air and Radiation Division Permits Branch (3AD10) Four Penn Center 1600 John F. Kennedy Boulevard Philadelphia, PA 19103-2852

The Department copies shall be forwarded to wiweaver@pa.gov, unless otherwise specified in writing by DEP.

In the event that the Federal Subpart that is the subject of this Source Group is revised, the permittee shall comply with the revised version of the subpart, and shall not be required to comply with any provisions in this permit designated as having the subpart as their authority, to the extent that such permit provisions would be inconsistent with the applicable provisions of the revised subpart.

*** Permit Shield in Effect. ***



SECTION F. Alternative Operation Requirements.

No Alternative Operations exist for this Title V facility.

DEP Auth ID: 1404295





SECTION G. Emission Restriction Summary.

No emission restrictions listed in this section of the permit.

DEP Auth ID: 1404295 DEP PF ID:



SECTION H. Miscellaneous.

#001 This permit compiles the conditions and operating requirements of the RACT operating permit No. 36-2025.

#002 Insignificant sources.

The following sources do not require any restrictions, work practice standards or testing, monitoring, recordkeeping and reporting requirements:

- (a) Two (2) gas fired space heaters, capacity each of 100,000 btu/hr.
- (b) Two (2) gas fired space heaters, capacity each of 200,000 btu/hr.
- (c) One (1) gas fired space heater, capacity of 30,000 btu/hr.
- (d) Two (2) water heaters, capacity each of 40,000 Btu/hr and each less than 120 gallons.
- (e) Two (2) above ground oil storage tanks of capacity 5,000 gallons and 2,300 gallons.
- (f) One (1) above ground glycol storage tank of capacity 2,000 gallons.
- (h) One (1) above ground pipeline liquid storage tank of capacity 1,306 gallons.
- (i) Seven (7) small pipeline liquid storage vessels each with a capacity less than or equal to 265 gallons.
- (j) Two (2) natural gas-fired, fuel gas heaters, each ratedd at 0.388 MMbtu/hr.
- (k) Two (2) 28 gallon pressure vessels used to collect pipeline liquids.

#003. This administrative amendment incorporates the operating conditions fo plan approval 36-05025A and supersedes Operating Permit No. 36-05025 issued on May 23, 2019.

Page 78

DEP Auth ID: 1404295 DEP PF ID:





***** End of Report *****