TRIP REPORT NORTH UNION STREET EFRD SITE – INFILTRATION TESTING

1.0 PURPOSE

This Trip Report presents the field data and results of double-ring soil infiltration tests conducted to support the design of a stormwater management system at the North Union Street EFRD site located in Middletown Township, Dauphin County, Pennsylvania, as part of the Pennsylvania Pipeline Project (PPP) for Sunoco Pipeline, LP. Two surface tests (IT-A and IT-B) were performed at the site. The test locations are listed by coordinates (latitude and longitude) in Table 1 and shown on the attached figure.

2.0 FIELD ACTIVITIES

The infiltration tests were conducted by Keith Simpson and Jake Marlow of Tetra Tech, Inc., on October 5, 2016. The test locations were positioned in the field using a handheld, WAAS-enabled GPS unit. Table 1 provides the coordinates of the test locations. Test unit IT-A was located in a grassy area just west of an access road while test unit IT-B was located just inside the tree line due south of a water tower.

The infiltration tests were performed in accordance with the procedure specified in the 2006 Pennsylvania Stormwater Best Management Practices (BMP) Manual. The test locations were prepared with hand tools and a mini-excavator, and care was taken to minimize disturbance of the soil surface to be tested. Double-ring infiltrometers were used for testing and consisted of 10-inch diameter and 6-inch diameter sections of steel casing, each 10 inches in height. After digging to the target depth, the test surface was leveled, and loose soil and debris were removed. The rings were driven a minimum of 2 inches into the soil. The infiltration test depths are presented in Table 1.

Test locations were pre-soaked for 1 hour. The tests were then conducted with measurements at 10-minute or 30-minute intervals, based on the observed water level drops during the last half of the pre-soak period. Pre-soak and test information was recorded on infiltration test data sheets; copies of the test data sheets are attached to this report.

During the testing, the weather was sunny, approximately 70 degrees Fahrenheit, and no precipitation was observed during the time of testing. Additionally, no precipitation was observed 24 hours prior to testing.

A hand auger was utilized to characterize the soil, determine the depth to bedrock, if encountered, and inspect for evidence of the seasonal high water table near the test areas. At each of the Test units, hand augering was completed to a depth of 25 inches below ground surface. Descriptions of the soil were documented on field logs, which were based on the form example in the BMP manual. Copies of the soil logs are attached to this report.

3.0 RESULTS

3.1 <u>Soil Description</u>

Soil encountered generally consisted of a thin topsoil/surface layer composed of a thin (up to approximately 8 inches) dark reddish brown (5YR 3/3) silt loam with trace rock fragments in test unit IT-A, to a dark brown (7.5YR 3/3) sandy clay loam with trace rock fragments in test unit IT-B. This topsoil/surface layer was underlain by a dark reddish brown (2.5YR 3/4) sandy loam with increased clay content in test unit IT-B. Few roots with trace rock fragments where found within this sublayer to approximately 25 inches below ground surface. Bedrock was not encountered.

Seasonal high water was not observed at the testing location, nor was any mottling observed.

According to United States Department of Agriculture Natural Resources Conservation Service Web Soil Survey data, the soil types for the IT-A and IT-B test locations respectively, are mapped as follows:

- Lewisberry Gravelly Sandy Loam (LrB2 soil symbol) with 3-8 percent slopes; with low runoff and is well drained,
- Lewisberry Gravelly Sandy Loam (LrC2 soil symbol) with 8-15 percent slopes; with low runoff and is well drained.


3.2 Infiltration Tests Results


Table 1 summarizes the infiltration rates (inches per hour) calculated from the test data. Infiltration rates presented in Table 1 were calculated from the average water level drop of the last four stabilized readings measured in the inner ring.

The pre-soak test results for IT-A (surface) indicated a low infiltration rate, requiring a 30 minute test cycle; whereas, the pre-soak test results for IT-B (surface) indicated high infiltration rate, requiring 10 minute test cycle.

Table 1 Summary of Infiltration Test Results North Union Street ERFD Middletown Township, Dauphin County, PA Sunoco PPP

Test Location	Location	on Data	Test Depth (inches)	Infiltration Test Result
(IT-)	LATITUDE	LONGITUDE		(inches/hour)
IT-A (surface)	40.2148564°	- 076.7340312°	4	2.00
IT-B (surface)	40.2150201°	- 076.7343377°	4	16.00







-			•	
ľ	14-	TETRA	TECH	
-1				- Q-

Soil Log

Tested By: Jake Marlow	Project:	Suraco - PAP	Project No.: NATCO 595
Test Pit: NUNion St EFRD IT-A Date: 10/8	5/16 Elevation:		Equipment Used Hund Avyer
Geology: (rettyshing Formatic soil Type: Lew	sberry gravelly sondy lo Land Use:		Weather: 70's Sunny
	, 5		

Additional Comments

Hund Augor to 25"

Horizon	Upper Boundary	Lower Boundary	Soil Textural Class	Type, Size, Coarse Fragments, etc.	Soil Color	Color Patterns	Pores, Roots, Rock Structure	Depth to Bedrock	Depth to Water	Comments
O/A	0"	6"	sity hoam	1	l	Solid	Several Rosts veyetation 14" to 12" rocks	- Agents	-	Dry to Maist Gryonic Debris to Tup soil
В	6"	25"	Sondy Loun	Fine sonds w/ silts and trace to minur clay	2.5 YR 3/4		Pores, Few Roots			Muist
							,	ر 		·
									-	
	·								3	·

Horizon:	USDA Definition	Soil Textural Class	Boundary	Notes:
0	Organic debris	Use ternary diagram from	Use depth and classification	-Did Nut Encounter Souscel
Α Α	Dark colored, mixed mineral organic matter	US Department of Agriculture Soil Conservation Service	Classification as Follows: Abrupt	High Groundwater
В	Maximum accumulation of silicate clay minerals]	Clear	- Nu Refusal - < 0.5" of Ruin in Part 21 hours
С	Weathered parent material		Gradual	1- CO'S OLYON IN hors Williams
R	Layer of consolidated rock beneath the soil		Diffuse	

		•
TE	TETRA	TECH

Soil Log


Tested By: Juke Minlow	Project: SUNUCO - PPP	Project No.: 11210595
Test Pit: N Union St EFRD IT-B Date: 10/5/16	Elevation:	Equipment Used Hund Auger
Geology: Cettysburg Formution Soil Type:	Land Use:	Weather: 76's Clear
		•

Additional Comments

Hond Auger to 25"

Horizon	Upper Boundary	Lower Boundary	Soil Textural Class	Type, Size, Coarse Fragments, etc.	Soil Color	Color Patterns	Pores, Roots, Rock Structure	Depth to Bedrock	Depth to Water	Comments
O/A	0"	8"	Cluysordy	Fine solt and Min	7.5 PR 3/3	Selid	Pores, roots, lu" to la" Rock!	- rooments	- .	Orgente Debris to top Soil Dry
B	8"	25"	Smdy Cluy Cluy	Claywolminur Fine truce still Sand F-C Grovel	2.5 Y R 3/4	Solid	Pores, roots !!! to! s' rock			Moist to Dry
	·									

Horizon:	USDA Definition	Soil Textural Class	Boundary	Notes:
0	Organic debris	Use ternary diagram from	Use depth and classification	-DID NOT Encounter Seuschel
Α Α	Dark colored, mixed mineral organic matter	US Department of Agriculture Soil Conservation Service	Classification as Follows: Abrupt	High Groundwater
В	Maximum accumulation of silicate clay minerals		Clear	-No Refuse! -<0.5" of Roin in Post 24 hours
С	Weathered parent material		Gradual	1 20,5 81 Ham 111 1031 824 111012
R	Layer of consolidated rock beneath the soil		Diffuse	·







INFILTRATION TEST DATA SHEET

Tetra Tech, Inc.

N. UNION ST EFRD

PROJECT NAM	BER 112 TC	091STICS 05958 - 17	TEST AREA ID: PERSONNEL:	IT-A	IARIOW
			_	3, 314, J. M	TATE COO
TEST METHOL): Youble Ring Infile Single Ring Infile	trometer Percolation	•		
INNER	RING INSIDE	10 15		Location Coordinates or Des	cription:
	TER/HEIGHT:	6 × 10		40.2148564	
	RING INSIDE TER/HEIGHT:	10"X 10"		-076.7340312	
			L		·
	N HOLE DIAMETE	R: NA	(if performing an	open hole perc test)	
DATE(s):	10/5/16	 .			
Distance from th	ne bottom of the inne	er ring/hole to measur	ing point (minimum v	water column of 6-8 inches):	BGS
MEASURING P	OINT: Ring Righ	Indicator Mark		TI OF TEST	BGS
MEASOIGIVOT	OIIVI. KIIIg KIAI	HIGICATOF MARK	_ DEP	TH OF TEST: 4	
	ELAPSED TIME	WATER LEVEL	VOLUME OF WATER		
TIME	SINCE START OF	DROP, INNER RING OR PERCOLATION	ADDED AT EACH CYCLE, INNER RING	REM	1ARKS
	TEST (minutes)	HOLE (inches)	(liters)		<u>l de 1918.</u> A la central
PRESOAK DAT	ΓA				
1013	0		3,8		
1043	30	12/	0.85		
1113	60	16/16	1.0		
		7.0	· · · · ·		
TEST DATA		20 340			
11/3	0 (60)	30 MII	V TEST	START	
1143	30 (90)	16/1	1.0	3 M/CI	
13 13	60 (129	16/16	1.1		
12 43	90 (150)	16/16	1 1		
13 13	120 (180)	16/16	1.1	END TEST ST	TABILIZED
		7,0		0,00 ,021	
					· · · · · · · · · · · · · · · · · · ·
	· · · · · · · · · · · · · · · · · · ·				
			· · · · · · · · · · · · · · · · · · ·		
	0/0 01	ا ا	CT 34 "	A C	
	NO RA	in over li	15/ 24 H	<u> </u>	
NIACE	1 ~25	NNE - OFF	OF FITTAD	LICE ASIA	
7000	<u> </u>	IAICO OFF	or entage	CIPE KOW	
	CEE ALSO	P HO TO) 21	5011 (119)		



INFILTRATION TEST DATA SHEET

Tetra Tech, Inc.

N. UNION ST. PROJECT NAME: SUNOCO LOGISTICS TEST AREA ID: IT - B
PROJECT NUMBER: 112 ICOS 958 - 17 PERSONNEL: K. SIMPSON, J. PROJECT NAME: SUNOCO LOGISTICS TEST METHOD Double Ring Infiltrometer Percolation Single Ring Infiltrometer Location Coordinates or Description: INNER RING INSIDE 6"×10" 40.2150201 DIAMETER/HEIGHT: OUTER RING INSIDE -076, 7343377 10"× 10" DIAMETER/HEIGHT: NA PERCOLATION HOLE DIAMETER: (If performing an open hole perc test) 10/5/16 DATE(s): Distance from the bottom of the inner ring/hole to measuring point (minimum water column of 6-8 inches): DEPTH OF TEST: 7" BG-S MEASURING POINT: (Ring Rin) Indicator Mark WATER LEVEL VOLUME OF WATER ELAPSED TIME DROP, INNER RING ADDED AT EACH TIME SINCE START OF REMARKS OR PERCOLATION CYCLE, INNER RING TEST (minutes) HOLE (inches) (liters) PRESOAK DATA 10:23 DRUP 2" ADA 1.26 3.9 1018 0 10: 29 1.24 (0 \ 35 i. 26 1048 30 0,65 10:42 ا کے 🕻 1118 60 1.2 4 AUNKING TIME TEST DATA MIN TEST 10 11(8) (60) STANT TEST 1122 64 1131 11 40 22 1154 36 12 00 COL 1208 110 33 40 80 END TEST VERY LITTLE PROP IN outen RING LAST SEE ALSO PHOTO & SOIL WOS