

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision Date: 27/03/2019

Version: 1.24

# **SECTION 1: IDENTIFICATION**

Product Identifier

**Product Form:** Mixture

Product Name: Sanifect D2 (AFCO 5503)

**Product Code:** AFCO 5503 **Intended Use of the Product** 

Use of the Substance/Mixture: RTU sanitizer for use on food contact surfaces. For professional use only.

Name, Address, and Telephone of the Responsible Party

Company

Alex C. Fergusson, LLC. 800 Development Avenue Chambersburg, PA 17201

T: 800-345-1329 www.afcocare.com

**Emergency Telephone Number** 

Emergency number : 1-800-424-9300 (CHEMTREC)

#### **SECTION 2: HAZARDS IDENTIFICATION**

#### Classification of the Substance or Mixture

# Classification (GHS-US)

Flam. Liq. 2 H225 Eye Irrit. 2A H319 STOT SE 3 H336

# **Label Elements**

**GHS-US Labeling** 

Hazard Pictograms (GHS-US)





Signal Word (GHS-US) : Danger.

Hazard Statements (GHS-US) : H225 - Highly flammable liquid and vapor.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

Precautionary Statements (GHS-US): P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical, ventilating, and lighting equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge. P261 - Avoid breathing dust/fumes/gas/mist/vapours/spray.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P271 - Use only outdoors or in a well ventilated area.

P280 - Wear protective gloves, eye protection, face protection.

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower.

P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

27/03/2019 EN (English US) 1/8

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P312 - Call a POISON CENTER or doctor/physician if you feel unwell.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P370+P378 - In case of fire: Use appropriate media for extinction.

P403+P233 - Store in a well ventilated place. Keep container tightly closed

P403+P235 - Store in a well-ventilated place. Keep cool.

P501 - Dispose of contents/container to local, regional, national, territorial, provincial, and

international regulations.

#### **Other Hazards**

**Other Hazards Not Contributing to the Classification**: Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. When heated to decomposition, emits toxic fumes. Flammable gas.

Unknown Acute Toxicity (GHS-US) Not available.

# **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

### **Substances**

#### Mixture

Name	Product identifier	% (w/w)	Classification (GHS-US)
Isopropyl alcohol	(CAS No) 67-63-0	50-60	Flam. Liq. 2, H225
			Eye Irrit. 2A, H319
			STOT SE 3, H336
Water	(CAS No) 7732-18-5	40-50	Not classified
Alkyl dimethyl benzyl ammonium chloride	(CAS No.) 68391-01-5	0.010	Skin Corr. 1A, H314
			Eye Dam. 1, H318
			Aquatic Acute 1, H400
Alkyl dimethyl ethyl benzyl ammonium	CAS No.) 85409-23-0	0.010	Skin Corr. 1A, H314
chloride			Eye Dam. 1, H318
			Aquatic Acute 1, H400

Full text of H-phrases: see section 16.

# **SECTION 4: FIRST AID MEASURES**

#### **Description of First Aid Measures**

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

**Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation persists. Wash contaminated clothing before reuse.

**Eye Contact:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

### Most Important Symptoms and Effects Both Acute and Delayed

**General:** Causes serious eye irritation.

**Inhalation:** Inhalation of large amounts may cause respiratory irritation, drowsiness, or dizziness.

Skin Contact: None known.

Eye Contact: Causes serious eye irritation.

**Ingestion:** Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Not available.

#### Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

### **SECTION 5: FIRE-FIGHTING MEASURES**

# **Extinguishing Media**

**Suitable Extinguishing Media:** Water spray, fog, carbon dioxide, foam, dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

27/03/2019 EN (English US) 2/8

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#### **Special Hazards Arising From the Substance or Mixture**

Fire Hazard: Flammable liquid and vapor.

**Explosion Hazard:** May form flammable/explosive vapor-air mixture.

Reactivity: When heated to decomposition, emits toxic fumes. Flammable gas.

#### **Advice for Firefighters**

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire. **Firefighting Instructions:** Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO<sub>2</sub>).

Other information: Do not allow run-off from fire fighting to enter drains or water courses.

**Reference to Other Sections** 

Refer to section 9 for flammability properties.

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

# Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Avoid breathing (vapors, mist, spray). Avoid all contact with skin, eyes, or clothing. Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

#### **For Non-Emergency Personnel**

Protective Equipment: Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

### **Environmental Precautions**

Prevent entry to sewers and public waters. Avoid release to the environment.

#### Methods and Material for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or inert absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Contact competent authorities after a spill.

#### **Reference to Other Sections**

See heading 8, Exposure Controls and Personal Protection.

# **SECTION 7: HANDLING AND STORAGE**

# **Precautions for Safe Handling**

**Additional Hazards When Processed:** When heated to decomposition, emits toxic fumes. Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Do no eat, drink or smoke when using this product. Wash hands and forearms thoroughly after handling.

# **Conditions for Safe Storage, Including Any Incompatibilities**

**Technical Measures:** Comply with applicable regulations.

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from extremely high temperatures, direct sunlight, heat, ignition sources, incompatible materials.

**Incompatible Materials:** Strong oxidizers.

**Special Rules on Packaging:** Keep only in original container.

### Specific End Use(s):

RTU sanitizer for use on food contact surfaces. For professional use only.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

# **Control Parameters**

Isopropyl alcohol (67-63-0)		
Mexico	OEL TWA (mg/m³)	980 mg/m³
Mexico	OEL TWA (ppm)	400 ppm
Mexico	OEL STEL (mg/m³)	1225 mg/m³
Mexico	OEL STEL (ppm)	500 ppm

27/03/2019 EN (English US) 3/8

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	400 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	980 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m³)	980 mg/m³
USA NIOSH	NIOSH REL (TWA) (ppm)	400 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m³)	1225 mg/m³
USA NIOSH	NIOSH REL (STEL) (ppm)	500 ppm
USA IDLH	US IDLH (ppm)	2000 ppm (10% LEL)
Ontario	OEL STEL (ppm)	400 ppm
Ontario	OEL TWA (ppm)	200 ppm
Québec	VECD (mg/m³)	1230 mg/m³
Québec	VECD (ppm)	500 ppm
Québec	VEMP (mg/m³)	985 mg/m³
Québec	VEMP (ppm)	400 ppm

#### **Exposure Controls**

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed. Ensure adequate ventilation, especially in confined area. If user operations generate fumes, vapors, gas, or spray use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or regulatory limits.

Personal Protective Equipment: Protective goggles. Gloves.





Materials for Protective Clothing: None usually needed. Hand Protection: Wear chemically resistant protective gloves.

**Eye Protection:** Chemical goggles or face shield. **Skin and Body Protection:** None needed.

Respiratory Protection: A respirator is not needed under normal and intended conditions of product use. Whenever worker

exposure may exceed established regulatory exposure limits, use a NIOSH-approved respirator.

Other Information: When using, do not eat, drink or smoke.

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

### **Information on Basic Physical and Chemical Properties**

Physical State : Liquid

**Appearance** : Clear, colorless

Odor Threshold : Alcohol : Not available

**pH** : 8.0

Relative Evaporation Rate (butylacetate=1) Not available **Melting Point** Not available **Freezing Point** Not available **Boiling Point** 82.2°C (179.96°F) Flash Point 21°C (69.8°F) **Auto-ignition Temperature** Not available **Decomposition Temperature** Not available Flammability (solid, gas) Not available **Lower Flammable Limit** Not available **Upper Flammable Limit** Not available Not available **Vapor Pressure** 

27/03/2019 EN (English US) 4/8

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative Vapor Density at 20°C : Not available

Specific Gravity : 0.91
Solubility : Complete.
Partition coefficient: n-octanol/water : Not available
Viscosity : Not available

**Explosion Data – Sensitivity to Mechanical Impact**: Not expected to present an explosion hazard due to mechanical impact.

**Explosion Data – Sensitivity to Static Discharge** : Static discharge may present an explosion hazard.

#### **SECTION 10: STABILITY AND REACTIVITY**

Reactivity: When heated to decomposition, emits toxic fumes. Flammable gas.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight. Extremely high temperatures. Heat. Ignition sources. Combustible materials. Incompatible

materials.

Incompatible Materials: Strong oxidizers.

Hazardous Decomposition Products: Carbon oxides (CO, CO<sub>2</sub>). May release flammable gases.

# **SECTION 11: TOXICOLOGICAL INFORMATION**

### Information on Toxicological Effects - Product

Acute Toxicity: Not classified LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Not classified pH: 8

Serious Eye Damage/Irritation: Causes serious eye irritation. pH: 8

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

**Teratogenicity:** Not available **Carcinogenicity:** Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): May cause drowsiness or dizziness.

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Inhalation of large amounts may cause respiratory irritation, drowsiness, or dizziness.

Symptoms/Injuries After Skin Contact: None known.

Symptoms/Injuries After Eye Contact: Causes serious eye irritation.

**Symptoms/Injuries After Ingestion:** Ingestion is likely to be harmful or have adverse effects.

Information on Toxicological Effects - Ingredient(s)

#### LD50 and LC50 Data:

ED30 and Ee30 Data.		
Water (7732-18-5)		
.D50 Oral Rat >-90000 mg/kg		
Alkyl dimethyl benzyl ammonium chloride (68391-01-5) and	l Alkyl dimethyl ethyl benzyl ammonium chloride (85409-23-0)	
LD50 Oral Rat	507mg/kg	
Isopropyl alcohol (67-63-0)		
LD50 Oral Rat	4396 mg/kg	
LD50 Dermal Rabbit	12800 mg/kg	
LC50 Inhalation Rat (ppm)	16000 ppm (Exposure time: 8 h)	
Isopropyl alcohol (67-63-0)		
IARC Group	3	

#### **SECTION 12: ECOLOGICAL INFORMATION**

# **Toxicity**

Ecology - General: Not classified.

27/03/2019 EN (English US) 5/8

#### Safety Data Sheet

Sanifact D2 (AECO EEO2)

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Sanifect DZ (AFCO 5503)		
LC50 Fish 5133 mg/l (Exposure time: 48 h - Species: Fathead minnow		
EC50 Daphnia	50 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
Iselsopropyl alcohol (67-63-0)		
LC50 Fish 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])	

Isolsopropyl alcohol (67-63-0)	
LC50 Fish 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Other Aquatic Organisms 1	1000 mg/l (Exposure time: 96 h - Species: Desmodesmus subspicatus)
LC 50 Fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Other Aquatic Organisms 2	1000 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)

**Persistence and Degradability** 

Sanifect D2 (AFCO 5503)	
Persistence and Degradability	Not established.

**Bioaccumulative Potential** 

Dioaccamalative i otential	
Sanifect D2 (AFCO 5503)	
Bioaccumulative Potential	Not established.
Isopropyl alcohol (67-63-0)	
Log Pow	0.05 (at 25°C)

Mobility in Soil Not available.

**Other Adverse Effects** 

Other Information: Not classified.

# **SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

**Ecology – Waste Materials:** Keep out of sewers and waterways.

#### SECTION 14: TRANSPORT INFORMATION

# 14.1 In Accordance with DOT

Proper Shipping Name : FLAMMABLE LIQUIDS, n.o.s. (Isopropanol)

Hazard Class : 3

Identification Number : UN1993

 Label Codes
 ⋮
 3

 Packing Group
 ⋮
 !!

 ERG Number
 ⋮
 128

14.2 In Accordance with IMDG

<u>Proper Shipping Name</u> : <u>FLAMMABLE LIQUIDS, n.o.s. (Isopropanol)</u>

Hazard Class <u>:</u> <u>3</u>

Identification Number <u>: UN1993</u>

 Packing Group
 : II

 Label Codes
 : 3

 EmS-No. (Fire)
 : F-E

 EmS-No. (Spillage)
 : S-D



14.3 In Accordance with IATA

<u>Proper Shipping Name</u> : <u>FLAMMABLE LIQUIDS, n.o.s. (Isopropanol)</u>

Packing Group : II

<u>Identification Number</u> <u>: UN1993</u>

 Hazard Class
 : 3

 Label Codes
 : 3

 ERG Code (IATA)
 : 3L



14.4 In Accordance with TDG

27/03/2019 EN (English US) 6/8

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

: FLAMMABLE LIQUIDS, n.o.s. (Isopropanol) **Proper Shipping Name** 

**Packing Group** <u>: II</u> <u>: 3</u> **Hazard Class Identification Number** : UN1993

**Label Codes** 



#### SECTION 15: REGULATORY INFORMATION

# **US Federal Regulations**

Sanifect D2 (AFCO 5503)		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard.	
	Delayed (chronic) health hazard.	
	Fire hazard.	
Water (7732-18-5)		

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

#### Alkyl dimethyl benzyl ammonium chloride (68391-01-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

#### Alkyl dimethyl ethyl benzyl ammonium chloride (85409-23-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

#### Isopropyl alcohol (67-63-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory.

Listed on SARA Section 313 (Specific toxic chemical listings)

Listed on 3/40/1 Section 313 (Specific toxic chemical listings).		
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test	
	rule under TSCA.	
SARA Section 313 - Emission Reporting	1.0% (only if manufactured by the strong acid process, no supplier	
	notification)	

#### **US State Regulations**

#### Isopropyl alcohol (67-63-0)

- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Acute
- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Chronic
- U.S. California Toxic Air Contaminant List (AB 1807, AB 2728)
- U.S. New Jersey Discharge Prevention List of Hazardous Substances
- U.S. New Jersey Environmental Hazardous Substances List
- RTK U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- U.S. New York Occupational Exposure Limits TWAs
- RTK U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- RTK U.S. Pennsylvania RTK (Right to Know) List
- U.S. Texas City of Austin Aerosol Paint and Glue Restrictions
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

#### **Canadian Regulations**

### Water (7732-18-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

# Alkyl dimethyl benzyl ammonium chloride (68391-01-5 and Alkyl dimethyl ethyl benzyl ammonium chloride (85409-23-0)

Listed on the Canadian DSL (Domestic Substances List) inventory.

# Isopropyl alcohol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List) inventory.

# SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

: 5/19/20<del>27/03/2019</del> **Revision date** 

27/03/2019 EN (English US)

#### Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	_	_
Other	Infor	matiar
Omer	ппоп	malioi

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

# **GHS Full Text Phrases:**

Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Eye Dam 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Skin Corr. 1A	Skin corrosion/irritation Category 1A
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H400	Very toxic to aquatic life

NFPA Health Hazard : 2 - Intense or continued exposure could cause temporary

incapacitation or possible residual injury unless prompt

medical attention is given.

NFPA Fire Hazard : 3 - Liquids and solids that can be ignited under almost all

ambient conditions.

NFPA Reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.

**HMIS III Rating** 

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard Physical : 0 Minimal Hazard


# Party Responsible for the Preparation of This Document

Alex C. Fergusson, LLC. 800 Development Avenue Chambersburg, PA 17201

T: 800-345-1329

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (U.S., Can., Mex.)



27/03/2019 EN (English US) 8/8