



Material Safety Data Sheet

Issue Date: 10-MAR-2010 Supercedes: 30-SEP-2008

POLYFLOC AE1703

1 Identification

Identification of substance or preparation POLYFLOC AE1703

Product Application Area Flocculant.

Company/Undertaking Identification GE Betz, Inc. 4636 Somerton Road Trevose, PA 19053 T 215 355-3300, F 215 953 5524

Emergency Telephone (800) 877-1940

Prepared by Product Stewardship Group: T 215-355-3300 Prepared on: 10-MAR-2010

2 Hazard(s) identification

EMERGENCY OVERVIEW

CAUTION

May cause moderate irritation to the skin. May cause dermatitis. May cause moderate irritation to the eyes. Vapors, gases, mists or aerosols may cause irritation to the upper respiratory tract. Prolonged exposure may cause dizziness and headache.

DOT hazard: ORS (when container > RQ) Odor: Ammonia; Appearance: White To Off-White, Emulsion

Fire fighters should wear positive pressure self-contained breathing apparatus(full face-piece type). Proper fire-extinguishing media: dry chemical, carbon dioxide or foam--Avoid water if possible.

POTENTIAL HEALTH EFFECTS

ACUTE SKIN EFFECTS:

Primary route of exposure; May cause moderate irritation to the skin. May cause dermatitis.

ACUTE EYE EFFECTS:

May cause moderate irritation to the eyes.

ACUTE RESPIRATORY EFFECTS:

Primary route of exposure; Vapors, gases, mists or aerosols may cause irritation to the upper respiratory tract. Prolonged exposure may cause dizziness and headache.

INGESTION EFFECTS:

May cause gastrointestinal irritation. Small amounts aspirated during ingestion or vomiting may cause lung injury, possibly leading to death.

TARGET ORGANS:

Prolonged or repeated exposures may cause CNS depression and/or defatting-type dermatitis.

MEDICAL CONDITIONS AGGRAVATED:

Not known.

SYMPTOMS OF EXPOSURE:

Excessive dermal exposure causes defatting and drying of skin. Excessive inhalation of vapors causes dizziness, headache and nausea.

3 Composition / information on ingredients

Information for specific product ingredients as required by the U.S. OSHA HAZARD COMMUNICATION STANDARD is listed. Refer to additional sections of this MSDS for our assessment of the potential hazards of this formulation. This product is subject to the Pennsylvania and New Jersey Worker and Community Right to Know Law.

HAZARDOUS INGREDIENTS:

Cas#	Chemical Name Ra	ange(w/w%)	
64742-47-8	ISOPARAFFINIC PETROLEUM DISTILLATE Combustible liquid; irritant; CNS depressant; IARC= (carcinogen status not classifiable)	30-60 =3	
68002-97-1	ALCOHOLS,C10-C16,ETHOXYLATED Slight Irritant (eyes and skin)	3-7	
68551-12-2	ALCOHOLS,C12-16,ETHOXYLATED Severe irritant (eyes); moderate irritant (skin)	3-7	
68439-50-9	ALCOHOLS,C12-14,ETHOXYLATED Irritant (eyes and skin)	3-7	
26635-93-8	POLYOXYETHYLENATED OLEYLAMINE	1-5	
NON-HAZARDOUS INGREDIENTS:			

CAS#	CHEMICAL NAME
7732-18-5	WATER
PROPRIETARY	ANIONIC POLYACRYLAMIDE

4 First-aid measures

SKIN CONTACT:

Wash thoroughly with soap and water. Remove contaminated clothing. Thoroughly wash clothing before reuse. Get medical attention if irritation develops or persists.

EYE CONTACT:

Remove contact lenses. Hold eyelids apart. Immediately flush eyes with plenty of low-pressure water for at least 15 minutes. Get immediate medical attention.

INHALATION:

Remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, give artificial respiration. Get immediate medical attention.

INGESTION:

Do not feed anything by mouth to an unconscious or convulsive victim. Do not induce vomiting. Immediately contact physician. Dilute contents of stomach using 2-8 fluid ounces (60-240 mL) of milk or water.

NOTES TO PHYSICIANS:

This product contains a hydrocarbon solvent. Aspiration into the lungs will result in chemical pneumonia and may be fatal.

5 Fire-fighting measures

FIRE FIGHTING INSTRUCTIONS:

Fire fighters should wear positive pressure self-contained breathing
apparatus (full face-piece type).
EXTINGUISHING MEDIA:

dry chemical, carbon dioxide or foam--Avoid water if possible. HAZARDOUS DECOMPOSITION PRODUCTS:

oxides of carbon and nitrogen, ammonia and volatile amines

FLASH POINT:

> 200F > 93C P-M(CC)

MISCELLANEOUS:

ORS (when container > RQ) UN 3082;Emergency Response Guide #171

6 Accidental release measures

PROTECTION AND SPILL CONTAINMENT:

Ventilate area. Use specified protective equipment. Contain and absorb on absorbent material. Place in waste disposal container. Flush area with water. Wet area may be slippery. Spread sand/grit.

DISPOSAL INSTRUCTIONS:

Water contaminated with this product may be sent to a sanitary sewer treatment facility, in accordance with any local agreement, a permitted waste treatment facility or discharged under a permit. Product as is - Incinerate or land dispose in an approved landfill.

7 Handling and storage

HANDLING:

Clean spill immediately. Wash contaminated skin promptly. **STORAGE:** Keep containers closed when not in use. Store in cool ventilated location. Store away from oxidizers. Shelf life 240 days.

8 Exposure controls / personal protection

EXPOSURE LIMITS

CHEMICAL NAME

ISOPARAFFINIC PETROLEUM DISTILLATE PEL (OSHA): NOT DETERMINED TLV (ACGIH): 200 MG/M3-A3

ALCOHOLS, C10-C16, ETHOXYLATED PEL (OSHA): NOT DETERMINED TLV (ACGIH): NOT DETERMINED

ALCOHOLS, C12-16, ETHOXYLATED PEL (OSHA): NOT DETERMINED TLV (ACGIH): NOT DETERMINED

ALCOHOLS, C12-14, ETHOXYLATED PEL (OSHA): NOT DETERMINED TLV (ACGIH): NOT DETERMINED

POLYOXYETHYLENATED OLEYLAMINE PEL (OSHA): Not determined TLV (ACGIH): Not determined

ENGINEERING CONTROLS:

Adequate ventilation to maintain air contaminants below exposure limits.

PERSONAL PROTECTIVE EQUIPMENT:

Use protective equipment in accordance with 29CFR 1910 Subpart I **RESPIRATORY PROTECTION:**

A RESPIRATORY PROTECTION PROGRAM THAT MEETS OSHA'S 29 CFR 1910.134 AND ANSI Z88.2 REQUIREMENTS MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT A RESPIRATOR'S USE. USE AIR PURIFYING RESPIRATORS WITHIN USE LIMITATIONS ASSOCIATED WITH THE EQUIPMENT OR ELSE USE SUPPLIED AIR-RESPIRATORS. If air-purifying respirator use is appropriate, use organic vapor cartridges and any of the following particulate respirators: R95, R99, R100, P95, P99 or P100. SKIN PROTECTION: viton gloves-- Wash off after each use. Replace as necessary. EYE PROTECTION:

splash proof chemical goggles

9 Physical and chemical properties

Spec. Grav.(70F,21C) 1.082	Vapor Pressure (mmHG) ~ 18.0
Freeze Point (F) ~ 23	Vapor Density (air=1) > 1.00
Freeze Point (C) ~ -5	
Viscosity(cps 70F,21C) 2800	% Solubility (water) ND
Odor	Ammonia
Appearance	White To Off-White
Physical State	Emulsion
Flash Point P-M(CC)	> 200F > 93C
pH 0.5% Sol. (approx.)	8.7
Evaporation Rate (Ether=1)	< 1.00

NA = not applicable ND = not determined

10 Stability and reactivity

CHEMICAL STABILITY: Stable under normal storage conditions. POSSIBILITY OF HAZARDOUS REACTIONS: Contact with oxidizers may cause fire. INCOMPATIBILITIES: May react with strong oxidizers. DECOMPOSITION PRODUCTS: oxides of carbon and nitrogen, ammonia and volatile amines

11 Toxicological information

Oral LD50 RAT:	>5,000 mg/kg
Dermal LD50 RABBIT:	>2,000 mg/kg
Inhalation LC50 RAT:	>20 mg/L/4hr
Skin Irritation Score RABBIT:	MODERATE
Eye Irritation Score RABBIT:	MODERATE

12 Ecological information

AQUATIC TOXICOLOGY

Daphnia magna 48 Hour Static Acute Bioassay LC50= 6.2; No Effect Level= .81 mg/L Fathead Minnow 96 Hour Static Acute Bioassay LC50= 17.3; No Effect Level= 7.8 mg/L Rainbow Trout 96 Hour Static Acute Bioassay LC50= 30.8; No Effect Level= 20 mg/L

BIODEGRADATION

No Data Available.

13 Disposal considerations

If this undiluted product is discarded as a waste, the US RCRA hazardous waste identification number is : Not applicable.

Please be advised; however, that state and local requirements for waste disposal may be more restrictive or otherwise different from federal regulations. Consult state and local regulations regarding the proper disposal of this material.

14 Transport information

Transportation Hazard: ORS (when container > RQ)
DOT: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, N.O.S.(AMMONIUM ACETATE)
 9, UN3082, PG III RQ
DOT EMERGENCY RESPONSE GUIDE #: 171
Note: Some containers may be DOT exempt, please check BOL for
exact container classification
IATA: Not Regulated
IMDG: Not Regulated

15 Regulatory information

```
TSCA:
          All components of this product are included on or are in
          compliance with the U.S. TSCA regulations.
    CERCLA AND/OR SARA REPORTABLE QUANTITY (RQ):
          Treat as oil spill
   FOOD AND DRUG ADMINISTRATION:
          21 CFR 176.170 (components of paper and paperboard in contact
          with aqueous and fatty foods)
   NSF Registered and/or meets USDA (according to 1998 Guidelines):
          Registration number: Not Registered
    SARA SECTION 312 HAZARD CLASS:
          Immediate(acute);Delayed(Chronic)
    SARA SECTION 302 CHEMICALS:
          No regulated constituent present at OSHA thresholds
    SARA SECTION 313 CHEMICALS:
          No regulated constituent present at OSHA thresholds
CALIFORNIA REGULATORY INFORMATION
    CALIFORNIA SAFE DRINKING WATER AND TOXIC
```

ENFORCEMENT ACT (PROPOSITION 65):
 This product contains one or more ingredients at trace levels known
 to the state of California to cause cancer.
MICHIGAN REGULATORY INFORMATION

No regulated constituent present at OSHA thresholds

16 Other information

HMIS VII

CODE TRANSLATION

Health	2	Moderate Hazard
Fire	1	Slight Hazard
Reactivity	0	Minimal Hazard
Special	NONE	No special Hazard
(1) Protective Equipment	В	Goggles,Gloves

(1) refer to section 8 of MSDS for additional protective equipment recommendations.

CHANGE LOG

EFFECTIVE			
DATE	REVISIONS 7	TO SECTION:	SUPERCEDES

MSDS status:	07-DEC-1999		** NEW **
	03-FEB-2000	15	07-DEC-1999
	11-FEB-2000	12	03-FEB-2000
	22-MAY-2000	4,16	11-FEB-2000
	06-JUN-2001	2,3,4,5,14,15	22-MAY-2000
	08-JUN-2006	8	06-JUN-2001
	30-SEP-2008	2,4,5,7,8,10	08-JUN-2006
	10-MAR-2010	3,8,10,14,15	30-SEP-2008