



Material Safety Data Sheet

Issue Date: 29-SEP-2011
Supersedes: 08-JUN-2007

SPECTRUS DT1400

1 Identification

Identification of substance or preparation
SPECTRUS DT1400

Product Application Area
A detoxifying agent

Company/Undertaking Identification
GE Betz, Inc.
4636 Somerton Road
Trevose, PA 19053
T 215 355-3300, F 215 953 5524

Emergency Telephone
(800) 877-1940

Prepared by Product Stewardship Group: T 215-355-3300 Prepared on: 29-SEP-2011

2 Hazard(s) identification

EMERGENCY OVERVIEW

CAUTION

May cause slight irritation to the skin. May cause moderate irritation to the eyes. Mists/aerosols may cause irritation to upper respiratory tract.

DOT hazard is not applicable
Odor: Slight; Appearance: Green-Brown, Dispersion

Fire fighters should wear positive pressure self-contained breathing apparatus(full face-piece type). Proper fire-extinguishing media: dry chemical, carbon dioxide, foam or water

POTENTIAL HEALTH EFFECTS

ACUTE SKIN EFFECTS:

Primary route of exposure; May cause slight irritation to the skin.

ACUTE EYE EFFECTS:

May cause moderate irritation to the eyes.

ACUTE RESPIRATORY EFFECTS:

Mists/aerosols may cause irritation to upper respiratory tract.

INGESTION EFFECTS:

May cause gastrointestinal irritation with possible nausea, vomiting, headache, dizziness, unconsciousness and injury to the kidneys and liver.

TARGET ORGANS:

Prolonged or repeated exposures may cause silicosis, toxicity to the liver and/or kidneys, and may increase risk of cancer.

MEDICAL CONDITIONS AGGRAVATED:

Respiratory ailments.

SYMPTOMS OF EXPOSURE:

May cause redness or itching of skin.

3 Composition / information on ingredients

Information for specific product ingredients as required by the U.S. OSHA HAZARD COMMUNICATION STANDARD is listed. Refer to additional sections of this MSDS for our assessment of the potential hazards of this formulation.

HAZARDOUS INGREDIENTS:

Cas#	Chemical Name	Range (w/w%)
14464-46-1	RESPIRABLE CRISTOBALITE (CRYSTALLINE SILICA) Irritant (respiratory); human carcinogen (IARC=1; NTP=known); may cause long term lung disease (silicosis)	0.1-1.0
14808-60-7	SILICA, CRYSTALLINE Irritant (respiratory); human carcinogen (IARC=1; NTP=known); may cause long term lung disease (silicosis) with prolonged or excessive exposure	0.1-1.0
15468-32-3	RESPIRABLE TRIDYMITE (CRYSTALLINE SILICA) Irritant (respiratory); probable human carcinogen (IARC=2A; NTP=anticipated); may cause long term lung disease (silicosis)	0.1-1.0

4 First-aid measures

SKIN CONTACT:

Wash thoroughly with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

EYE CONTACT:

Remove contact lenses. Hold eyelids apart. Immediately flush eyes with plenty of low-pressure water for at least 15 minutes. Get immediate medical attention.

INHALATION:

If nasal, throat or lung irritation develops - remove to fresh air and get medical attention.

INGESTION:

Do not feed anything by mouth to an unconscious or convulsive

victim. Do not induce vomiting. Immediately contact physician.
Dilute contents of stomach using 3-4 glasses milk or water.

NOTES TO PHYSICIANS:

No special instructions

5 Fire-fighting measures

FIRE FIGHTING INSTRUCTIONS:

Fire fighters should wear positive pressure self-contained breathing apparatus (full face-piece type).

EXTINGUISHING MEDIA:

dry chemical, carbon dioxide, foam or water

HAZARDOUS DECOMPOSITION PRODUCTS:

oxides of carbon, nitrogen and silicon; ammonia and volatile amines

FLASH POINT:

> 200F > 93C P-M(CC)

6 Accidental release measures

PROTECTION AND SPILL CONTAINMENT:

Ventilate area. Use specified protective equipment. Contain and absorb on absorbent material. Place in waste disposal container. Flush area with water. Wet area may be slippery. Spread sand/grit.

DISPOSAL INSTRUCTIONS:

Water contaminated with this product may be sent to a sanitary sewer treatment facility, in accordance with any local agreement, a permitted waste treatment facility or discharged under a permit. Product as is - Incinerate or land dispose in an approved landfill.

7 Handling and storage

HANDLING:

Normal chemical handling.

STORAGE:

Keep containers closed when not in use. Protect from freezing. If frozen, thaw and mix completely prior to use. Shelf life 135 days.

8 Exposure controls / personal protection

EXPOSURE LIMITS

CHEMICAL NAME

RESPIRABLE CRISTOBALITE (CRYSTALLINE SILICA)

PEL (OSHA): TWA = 0.05 MG/M3 (Respirable); TWA = 0.15 MG/M3 (Total dust)

TLV (ACGIH): TWA = 0.025 MG/M3; A2 (SILICA, CRYSTALLINE - CRISTOBALITE, RESPIRABLE FRACTION)

SILICA, CRYSTALLINE

PEL (OSHA): TWA = 0.1 MG/M3 (RESPIRABLE); TWA = 0.3 MG/M3 (TOTAL DUST)

TLV (ACGIH): TWA = 0.025 MG/M3; A2 (QUARTZ, RESPIRABLE FRACTION)

MISC: NIOSH REL = 0.05 MG/M3; NIOSH IDLH = 25 MG/M3

RESPIRABLE TRIDYMITE (CRYSTALLINE SILICA)

PEL (OSHA): 0.05 MG/M3
TLV (ACGIH): 0.05 MG/M3

ENGINEERING CONTROLS:

Adequate ventilation to maintain air contaminants below exposure limits.

PERSONAL PROTECTIVE EQUIPMENT:

Use protective equipment in accordance with 29CFR 1910 Subpart I

RESPIRATORY PROTECTION:

A RESPIRATORY PROTECTION PROGRAM THAT MEETS OSHA'S 29 CFR 1910.134 AND ANSI Z88.2 REQUIREMENTS MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT A RESPIRATOR'S USE.

USE AIR PURIFYING RESPIRATORS WITHIN USE LIMITATIONS ASSOCIATED WITH THE EQUIPMENT OR ELSE USE SUPPLIED AIR-RESPIRATORS.

If air-purifying respirator use is appropriate, use organic vapor cartridges and any of the following particulate respirators: N95, N99, N100, R95, R99, R100, P95, P99 or P100.

SKIN PROTECTION:

butyl gloves-- Wash off after each use. Replace as necessary.

EYE PROTECTION:

splash proof chemical goggles

9 Physical and chemical properties

Spec. Grav. (70F,21C)	1.186	Vapor Pressure (mmHG)	~ 18.0
Freeze Point (F)	32	Vapor Density (air=1)	< 1.00
Freeze Point (C)	0		
Viscosity(cps 70F,21C)	2900	% Solubility (water)	0.0
Odor		Slight	
Appearance		Green-Brown	
Physical State		Dispersion	
Flash Point	P-M(CC)	> 200F > 93C	
pH As Is (approx.)		7.0	
Evaporation Rate (Ether=1)		< 1.00	
Percent VOC:		1.0	

NA = not applicable ND = not determined

10 Stability and reactivity

CHEMICAL STABILITY:

Stable under normal storage conditions.

POSSIBILITY OF HAZARDOUS REACTIONS:

INCOMPATIBILITIES:

May react with strong oxidizers.

DECOMPOSITION PRODUCTS:

oxides of carbon, nitrogen and silicon; ammonia and volatile amines

11 Toxicological information

Oral LD50 RAT: >5000 mg/kg
NOTE - Calculated value according to GHS additivity formula
Dermal LD50 RABBIT: >5000 mg/kg
NOTE - Calculated value according to GHS additivity formula
Inhalation LC50 RAT: >5 mg/L/4hr
NOTE - Calculated value according to GHS additivity formula

12 Ecological information

AQUATIC TOXICOLOGY

Daphnia magna 48 Hour Static Screen
0% Mortality= 435 mg/L
Fathead Minnow 96 Hour Static Screen
0% Mortality= 435 mg/L

BIODEGRADATION

BOD-28 (mg/g): 2
BOD-5 (mg/g): 0
COD (mg/g): 64
TOC (mg/g): 26

13 Disposal considerations

If this undiluted product is discarded as a waste, the US RCRA hazardous waste identification number is :
Not applicable.

Please be advised; however, that state and local requirements for waste disposal may be more restrictive or otherwise different from federal regulations. Consult state and local regulations regarding the proper disposal of this material.

14 Transport information

Transportation Hazard: Not Applicable
DOT: Not Regulated

DOT EMERGENCY RESPONSE GUIDE #: Not applicable
Note: Some containers may be DOT exempt, please check BOL for exact container classification
IATA: Not Regulated

IMDG: Not Regulated

15 Regulatory information

TSCA:

All components of this product are included on or are in compliance with the U.S. TSCA regulations.

CERCLA AND/OR SARA REPORTABLE QUANTITY (RQ):

Treat as oil spill

NSF Registered and/or meets USDA (according to 1998 Guidelines):

Registration number: Not Registered

SARA SECTION 312 HAZARD CLASS:

Delayed(Chronic)

SARA SECTION 302 CHEMICALS:

No regulated constituent present at OSHA thresholds

SARA SECTION 313 CHEMICALS:

No regulated constituent present at OSHA thresholds

CALIFORNIA REGULATORY INFORMATION

CALIFORNIA SAFE DRINKING WATER AND TOXIC

ENFORCEMENT ACT (PROPOSITION 65):

This product contains one or more ingredients known to the state of California to cause cancer.

MICHIGAN REGULATORY INFORMATION

No regulated constituent present at OSHA thresholds

16 Other information

HMIS vII		CODE TRANSLATION
Health	1	Slight Hazard
Fire	1	Slight Hazard
Reactivity	0	Minimal Hazard
Special	NONE	No special Hazard
(1) Protective Equipment	B	Goggles,Gloves

(1) refer to section 8 of MSDS for additional protective equipment recommendations.

CHANGE LOG

	EFFECTIVE DATE	REVISIONS TO SECTION:	SUPERCEDES
	-----	-----	-----
MSDS status:	28-JUL-1997		** NEW **
	18-MAY-1998		28-JUL-1997
	17-MAY-2001	8	18-MAY-1998
	01-APR-2004	15	17-MAY-2001
	08-JUN-2007	3, 4, 5, 7, 8, 10	01-APR-2004
	29-SEP-2011	11	08-JUN-2007