

GE Water & Process Technologies

Material Safety Data Sheet

STEAMATE NA1324

Issue Date: 30-NOV-2011 Supercedes: 22-SEP-2010

1 Identification

Identification of substance or preparation STEAMATE NA1324

Product Application Area

Steam condensate treatment.

Company/Undertaking Identification

GE Betz, Inc. 4636 Somerton Road Trevose, PA 19053 T 215 355-3300, F 215 953 5524

Emergency Telephone

(800) 877-1940

Prepared by Product Stewardship Group: T 215-355-3300 Prepared on: 30-NOV-2011

2 Hazard(s) identification

EMERGENCY OVERVIEW

DANGER

Corrosive. Absorbed by skin. Corrosive to the eyes. Vapors, gases, mists and/or aerosols cause irritation to the upper respiratory tract.

DOT hazard: Corrosive to skin Odor: Strong Ammonia; Appearance: Colorless, Liquid

Fire fighters should wear positive pressure self-contained breathing apparatus(full face-piece type). Proper fire-extinguishing media: dry chemical, carbon dioxide, foam or water

POTENTIAL HEALTH EFFECTS

ACUTE SKIN EFFECTS:

Primary route of exposure; Corrosive. Absorbed by skin.

ACUTE EYE EFFECTS:

Corrosive to the eyes.

ACUTE RESPIRATORY EFFECTS:

Primary route of exposure; Vapors, gases, mists and/or aerosols cause irritation to the upper respiratory tract.

INGESTION EFFECTS:

May cause severe irritation or burning of mouth, throat, and gastrointestinal tract with severe chest and abdominal pain, nausea, vomiting, diarrhea, lethargy and collapse. Possible death when ingested in very large doses.

TARGET ORGANS:

Prolonged or exposures may cause primary irritant dermatitis, tissue necrosis, and/or toxicity to the liver and kidney.

MEDICAL CONDITIONS AGGRAVATED:

Pre-existing skin disorders and chronic respiratory disease.

SYMPTOMS OF EXPOSURE:

Symptoms range from headache, eye irritation, chest pain, nausea and vomiting to severe coughing, difficulty in breathing, pulmonary edema and production of pink frothy sputum.

3 Composition / information on ingredients

Information for specific product ingredients as required by the U.S. OSHA HAZARD COMMUNICATION STANDARD is listed. Refer to additional sections of this MSDS for our assessment of the potential hazards of this formulation. This product is subject to the Pennsylvania and New Jersey Worker and Community Right to Know Law.

HAZARDOUS INGREDIENTS:

Cas#	Chemical Name	Range(w/w%)
1336-21-6	AMMONIUM HYDROXIDE Corrosive; toxic (by ingestion)	30-60
141-43-5	MONOETHANOLAMINE Combustible; corrosive; irritant; CNS depressant; may cause liver and kidney toxicity; fetotoxic an developmental toxin in laboratory animals	
37037 TT3 FT3 FD00TT	G THEODER TENER	

NON-HAZARDOUS INGREDIENTS:

CAS# CHEMICAL NAME

7732-18-5 WATER

4 First-aid measures

SKIN CONTACT:

URGENT! Wash thoroughly with soap and water. Remove contaminated clothing. Get immediate medical attention. Thoroughly wash clothing before reuse.

EYE CONTACT:

URGENT! Immediately flush eyes with plenty of low-pressure water for at least 20 minutes while removing contact lenses. Hold eyelids apart. Get immediate medical attention.

INHALATION:

If nasal, throat or lung irritation develops - remove to fresh air and get medical attention.

INGESTION:

Do not feed anything by mouth to an unconscious or convulsive victim. Do not induce vomiting. Immediately contact physician. Rinse mouth with plenty of water. Dilute contents of stomach using 4-10 fluid ounces (120-300 mL) of milk or water.

NOTES TO PHYSICIANS:

Material is corrosive. It may not be advisable to induce vomiting. Possible mucosal damage may contraindicate the use of gastric lavage.

5 Fire-fighting measures

FIRE FIGHTING INSTRUCTIONS:

Fire fighters should wear positive pressure self-contained breathing apparatus (full face-piece type).

EXTINGUISHING MEDIA:

dry chemical, carbon dioxide, foam or water

HAZARDOUS DECOMPOSITION PRODUCTS:

oxides of carbon and nitrogen, ammonia and volatile amines

FLASH POINT:

> 213F > 101C P-M(CC)

MISCELLANEOUS:

Corrosive to skin
UN 2672; Emergency Response Guide #154

6 Accidental release measures

PROTECTION AND SPILL CONTAINMENT:

Ventilate area. Use specified protective equipment. Contain and absorb on absorbent material. Place in waste disposal container. Flush area with water. Wet area may be slippery. Spread sand/grit.

DISPOSAL INSTRUCTIONS:

Water contaminated with this product may be sent to a sanitary sewer treatment facility, in accordance with any local agreement, a permitted waste treatment facility or discharged under a permit. Product as is - Incinerate or land dispose in an approved landfill.

7 Handling and storage

HANDLING:

Alkaline. Corrosive(Skin/eyes). Do not mix with acidic material.

STORAGE:

Keep containers closed when not in use. Store in cool, well ventilated area. Protect from freezing. If frozen, thaw completely and mix thoroughly prior to use. Store away from acids.

8 Exposure controls / personal protection

EXPOSURE LIMITS

CHEMICAL NAME

AMMONIUM HYDROXIDE

PEL (OSHA): 50 PPM(35PPM-STEL)
TLV (ACGIH): 25 PPM(35PPM-STEL)

```
MONOETHANOLAMINE
```

```
PEL (OSHA): 3 PPM (6 MG/M3)
TLV (ACGIH): TWA = 3 PPM; STEL = 6 PPM
MISC: NIOSH REL = 3 PPM (8 MG/M3); NIOSH STEL = 6 PPM (15 MG/M3);
NIOSH IDLH = 30 PPM
```

ENGINEERING CONTROLS:

Adequate ventilation to maintain air contaminants below exposure limits.

PERSONAL PROTECTIVE EQUIPMENT:

Use protective equipment in accordance with 29CFR 1910 Subpart I

RESPIRATORY PROTECTION:

A RESPIRATORY PROTECTION PROGRAM THAT MEETS OSHA'S 29 CFR 1910.134 AND ANSI Z88.2 REQUIREMENTS MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT A RESPIRATOR'S USE.

USE AIR PURIFYING RESPIRATORS WITHIN USE LIMITATIONS ASSOCIATED WITH THE EQUIPMENT OR ELSE USE SUPPLIED AIR-RESPIRATORS.

If air-purifying respirator use is appropriate, use a respirator with ammonia/methylamine cartridges.

SKIN PROTECTION:

gauntlet-type butyl or neoprene gloves, chemical resistant apron -- Wash off after each use. Replace as necessary.

EYE PROTECTION:

splash proof chemical goggles, face shield

9 Physical and chemical properties

```
Spec. Grav. (70F, 21C) 0.936
                                      Vapor Pressure (mmHG) ~ 240.0
Freeze Point (F) -24
Freeze Point (C) -31
                                      Vapor Density (air=1) < 1.00
Viscosity(cps 70F,21C) 6
                                      % Solubility (water)
                                                             100.0
Odor
                                 Strong Ammonia
Appearance
                                 Colorless
Physical State
                                 Liquid
Flash Point
                   P-M(CC)
                                > 213F > 101C
                                 13.0
pH As Is (approx.)
                                  < 1.00
Evaporation Rate (Ether=1)
Percent VOC:
```

NA = not applicable ND = not determined

10 Stability and reactivity

CHEMICAL STABILITY:

Stable under normal storage conditions.

POSSIBILITY OF HAZARDOUS REACTIONS:

Contact with strong acids may cause a violent reaction releasing heat.

INCOMPATIBILITIES:

May react with acids.

DECOMPOSITION PRODUCTS:

oxides of carbon and nitrogen, ammonia and volatile amines

11 Toxicological information

```
Oral LD50 RAT: 960 mg/kg

NOTE - Calculated value according to GHS additivity formula

Dermal LD50 RABBIT: >5000 mg/kg

NOTE - Calculated value according to GHS additivity formula
```

12 Ecological information

AQUATIC TOXICOLOGY

Daphnia magna 48 Hour Static Acute Bioassay (Estimated) LC50= 277; 100% Mortality= 165~mg/L Fathead Minnow 96 Hour Static Acute Bioassay (Estimated) LC50= 120; No Effect Level= 86~mg/L

BIODEGRADATION

BOD-28 (mg/g): 27 BOD-5 (mg/g): 28 COD (mg/g): 62 TOC (mg/g): 17

13 Disposal considerations

If this undiluted product is discarded as a waste, the US RCRA hazardous waste identification number is: D002=Corrosive(pH).

Please be advised; however, that state and local requirements for waste disposal may be more restrictive or otherwise different from federal regulations. Consult state and local regulations regarding the proper disposal of this material.

14 Transport information

```
Transportation Hazard: Corrosive to skin

DOT: AMMONIA SOLUTION
8, UN2672, PG III, RQ

DOT EMERGENCY RESPONSE GUIDE #: 154

Note: Some containers may be DOT exempt, please check BOL for exact container classification

IATA: AMMONIA SOLUTION
8, UN2672, PG III

IMDG: AMMONIA SOLUTION
8, UN2672, PG III
```

15 Regulatory information

TSCA:

All components of this product are included on or are in compliance with the U.S. TSCA regulations.

CERCLA AND/OR SARA REPORTABLE QUANTITY (RQ):

363 gallons due to AMMONIUM HYDROXIDE;

NSF Registered and/or meets USDA (according to 1998 Guidelines):

Registration number: Not Registered

SARA SECTION 312 HAZARD CLASS:

Immediate(acute); Delayed(Chronic)

SARA SECTION 302 CHEMICALS:

No regulated constituent present at OSHA thresholds

SARA SECTION 313 CHEMICALS:

CAS# CHEMICAL NAME RANGE 1336-21-6 AMMONIUM HYDROXIDE 31.0-40.0%

CALIFORNIA REGULATORY INFORMATION

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65):

This product contains one or more ingredients at trace levels known to the state of California to cause cancer and reproductive toxicity.

MICHIGAN REGULATORY INFORMATION

No regulated constituent present at OSHA thresholds

16 Other information

HMIS VII	CODE T	RANSLATION

Health	3	Serious Hazard
Fire	0	Minimal Hazard
Reactivity	0	Minimal Hazard
Special	CORR	DOT corrosive

(1) Protective Equipment D Goggles, Face Shield, Gloves, Apron

CHANGE LOG

	DATE	REVISIONS TO SECTION:	SUPERCEDES
MSDS status:	15-MAY-2009		** NEW **
	12-FEB-2010	14	15-MAY-2009
	22-SEP-2010	7,12,15	12-FEB-2010
	30-NOV-2011	14	22-SEP-2010

⁽¹⁾ refer to section 8 of MSDS for additional protective equipment recommendations.