

GE Water & Process Technologies

Material Safety Data Sheet

Issue Date: 31-JAN-2012

Supercedes:

DEPOSITROL SF5109

1 Identification

Identification of substance or preparation DEPOSITROL SF5109

Product Application Area

Deposit control agent

Company/Undertaking Identification

GE Betz, Inc. 4636 Somerton Road Trevose, PA 19053 T 215 355-3300, F 215 953 5524

Emergency Telephone

(800) 877-1940

Prepared by Product Stewardship Group: T 215-355-3300 Prepared on: 31-JAN-2012

2 Hazard(s) identification

EMERGENCY OVERVIEW

WARNING

May cause moderate irritation to the skin. Severe irritant to the eyes. Vapors, gases, mists and/or aerosols may cause irritation to upper respiratory tract.

DOT hazard is not applicable Odor: Slight; Appearance: Colorless, Liquid

Fire fighters should wear positive pressure self-contained breathing apparatus(full face-piece type). Proper fire-extinguishing media: dry chemical, carbon dioxide, foam or water

POTENTIAL HEALTH EFFECTS

ACUTE SKIN EFFECTS:

Primary route of exposure; May cause moderate irritation to the skin.

ACUTE EYE EFFECTS:

Severe irritant to the eyes.

ACUTE RESPIRATORY EFFECTS:

Vapors, gases, mists and/or aerosols may cause irritation to upper

respiratory tract.

INGESTION EFFECTS:

May cause severe gastrointestinal irritation with possible nausea, vomiting, diarrhea, incoordination, mental confusion and lethargy.

TARGET ORGANS:

No evidence of potential chronic effects.

MEDICAL CONDITIONS AGGRAVATED:

Not known.

SYMPTOMS OF EXPOSURE:

May cause redness or itching of skin.

3 Composition / information on ingredients

Information for specific product ingredients as required by the U.S. OSHA HAZARD COMMUNICATION STANDARD is listed. Refer to additional sections of this MSDS for our assessment of the potential hazards of this formulation. This product is subject to the Pennsylvania and New Jersey Worker and Community Right to Know Law.

HAZARDOUS INGREDIENTS:

Cas# Chemical Name Range(w/w%)

68551-13-3 ALCOHOLS, C12-15, ETHOXYLATED PROPOXYLATED 10-20

Irritant (eyes and skin)

NON-HAZARDOUS INGREDIENTS:

CAS# CHEMICAL NAME

7732-18-5 WATER

9003-11-6 ETHYLENE/PROPYLENE OXIDES COPOLYMER

4 First-aid measures

SKIN CONTACT:

Wash thoroughly with soap and water. Remove contaminated clothing. Thoroughly wash clothing before reuse. Get medical attention if irritation develops or persists.

EYE CONTACT:

Remove contact lenses. Hold eyelids apart. Immediately flush eyes with plenty of low-pressure water for at least 15 minutes. Get immediate medical attention.

INHALATION:

If nasal, throat or lung irritation develops – remove to fresh air and get medical attention.

INGESTION:

Do not feed anything by mouth to an unconscious or convulsive victim. Do not induce vomiting. Immediately contact physician. Dilute contents of stomach using 2-8 fluid ounces (60-240 mL) of milk or water.

NOTES TO PHYSICIANS:

No special instructions

5 Fire-fighting measures

FIRE FIGHTING INSTRUCTIONS:

Fire fighters should wear positive pressure self-contained breathing apparatus (full face-piece type).

EXTINGUISHING MEDIA:

dry chemical, carbon dioxide, foam or water

HAZARDOUS DECOMPOSITION PRODUCTS:

oxides of carbon

FLASH POINT:

> 213F > 101C P-M(CC)

MISCELLANEOUS:

Not Applicable

NON-HAZ; Emergency Response Guide #

6 Accidental release measures

PROTECTION AND SPILL CONTAINMENT:

Ventilate area. Use specified protective equipment. Contain and absorb on absorbent material. Place in waste disposal container. Flush area with water. Wet area may be slippery. Spread sand/grit.

DISPOSAL INSTRUCTIONS:

Water contaminated with this product may be sent to a sanitary sewer treatment facility, in accordance with any local agreement, a permitted waste treatment facility or discharged under a permit. Product as is - Incinerate or land dispose in an approved landfill.

7 Handling and storage

HANDLING:

Normal chemical handling.

STORAGE:

Keep containers closed when not in use. Reasonable and safe chemical storage. Protect from freezing. Atmospheric exposure should be minimized.

8 Exposure controls / personal protection

EXPOSURE LIMITS

CHEMICAL NAME

ALCOHOLS, C12-15, ETHOXYLATED PROPOXYLATED
PEL (OSHA): LIMITS HAVE NOT BEEN ESTABLISHED BY US OSHA.
TLV (ACGIH): LIMITS HAVE NOT BEEN ESTABLISHED BY ACGIH.

ENGINEERING CONTROLS:

adequate ventilation

PERSONAL PROTECTIVE EQUIPMENT:

Use protective equipment in accordance with 29CFR 1910 Subpart I RESPIRATORY PROTECTION:

A RESPIRATORY PROTECTION PROGRAM THAT MEETS OSHA'S 29 CFR 1910.134 AND ANSI Z88.2 REQUIREMENTS MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT A RESPIRATOR'S USE.
USE AIR PURIFYING RESPIRATORS WITHIN USE LIMITATIONS ASSOCIATED WITH THE EQUIPMENT OR ELSE USE SUPPLIED AIR-RESPIRATORS.

```
If air-purifying respirator use is appropriate, use organic vapor cartridges and any of the following particulate respirators: R95, R99, R100, P95, P99 or P100.
```

SKIN PROTECTION:

rubber, butyl or viton gloves -- Wash off after each use. Replace as necessary.

EYE PROTECTION:

splash proof chemical goggles

9 Physical and chemical properties

Spec. Grav.(70F,21C)	1.014	Vapor Pressure (mmHG)	~ 18.0
Freeze Point (F)	33	Vapor Density (air=1)	< 1.00
Freeze Point (C)	1		
Viscosity(cps 70F,21C)	21	% Solubility (water)	100.0
Odor		Slight	
Appearance		Colorless	
Physical State		Liquid	
Flash Point P	-M(CC)	> 213F > 101C	
pH As Is (approx.)		12.8	
Evaporation Rate (Ether=1)		< 1.00	
Percent VOC:		0.0	

NA = not applicable ND = not determined

10 Stability and reactivity

CHEMICAL STABILITY:

Stable under normal storage conditions.

POSSIBILITY OF HAZARDOUS REACTIONS:

Contact with water reactive compounds may cause fire or explosion.

INCOMPATIBILITIES:

May react with strong oxidizers.

DECOMPOSITION PRODUCTS:

oxides of carbon

11 Toxicological information

No Data Available.

12 Ecological information

AQUATIC TOXICOLOGY

```
Daphnia magna 48 Hour Acute Toxicity (Estimated) LC50= 13 \, mg/L Fathead Minnow 96 Hour Acute Toxicity (Estimated) LC50= 4 \, mg/L
```

BIODEGRADATION

No Data Available.

13 Disposal considerations

If this undiluted product is discarded as a waste, the US RCRA hazardous waste identification number is : D002=Corrosive(pH).

Please be advised; however, that state and local requirements for waste disposal may be more restrictive or otherwise different from federal regulations. Consult state and local regulations regarding the proper disposal of this material.

14 Transport information

Transportation Hazard: Not Applicable
DOT: Not Regulated

DOT EMERGENCY RESPONSE GUIDE #: Not applicable
Note: Some containers may be DOT exempt, please check BOL for exact container classification
IATA: Not Regulated

IMDG: Not Regulated

15 Regulatory information

```
TSCA:
          All components of this product are included on or are in
          compliance with the U.S. TSCA regulations.
    CERCLA AND/OR SARA REPORTABLE QUANTITY (RQ):
          Treat as oil spill
    NSF Registered and/or meets USDA (according to 1998 Guidelines):
          Registration number: 144577
          Category Code(s):
       G5
            Cooling and retort water treatment products - all
             food processing areas
             Boiler treatment products - all food processing
             areas/nonfood contact
    SARA SECTION 312 HAZARD CLASS:
          Immediate (acute)
    SARA SECTION 302 CHEMICALS:
          No regulated constituent present at OSHA thresholds
    SARA SECTION 313 CHEMICALS:
          No regulated constituent present at OSHA thresholds
CALIFORNIA REGULATORY INFORMATION
```

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65):

This product contains one or more ingredients at trace levels known to the state of California to cause cancer and reproductive toxicity.

MICHIGAN REGULATORY INFORMATION

No regulated constituent present at OSHA thresholds

16 Other information

HMIS vII CODE TRANSLATION

Health	2	Moderate Hazard
Fire	1	Slight Hazard
Reactivity	0	Minimal Hazard
Special	ALK	pH above 12.0
(1) Protective Equipment	В	Goggles, Gloves

(1) refer to section 8 of MSDS for additional protective equipment recommendations.

CHANGE LOG

EFFECTIVE