BUCKMAN LABORATORIES, INC.

Material Safety Data Sheet

Buckman

BUSAN 30WB

Revision date: 2/5/2013

Buckman Laboratories, Inc. 1256 North McLean Boulevard Memphis, TN 38108

Phone 1-800-282-5626

24 Hour Emergency Phone

(901) 767-2722

SECTION 1

OSHA HAZARD CLASSIFICATIONS

Highly toxic by inhalation of mist. Corrosive to eyes and skin. Sensitizer.

SECTION 2	HAZARDOUS COMPONENTS

Chemical Name CAS Number % by Weight TLV2-(Thiocyanomethylthio)benzothiazole 21564-17-0 **30** Not available. **ACGIH (United States).** 107-21-1 Ethylene glycol <5 CEIL: 100 mg/m³

While some substances are claimed as trade secret in accordance with the provision of OSHA 29 CFR 1910.1200(i), all known hazards are clearly communicated within this document.

SECTION 3

FIRST AID INFORMATION

Eve Exposure: Flush immediately with copious amounts of tap water or normal saline (minimum of 15 minutes). Take exposed individual to a health care professional, preferably an ophthalmologist,

for further evaluation.

Skin Exposure:

Wash exposed area with plenty of water. Repeat washing. Remove contaminated clothing and wash thoroughly before reuse. If irritation persists consult a health care professional.

Inhalation:

If exposure by inhalation is suspected, immediately move exposed individual to fresh air. If individual experiences nausea, headache, dizziness, has difficulty in breathing or is cyanotic, seek a health care professional immediately.

Ingestion:

DO NOT INDUCE VOMITING. Rinse with copious amounts of water or milk, first. Irrigate the esophagus and dilute stomach contents by slowly giving one (1) to two (2) glasses of water or milk. Avoid giving alcohol or alcohol related products. In cases where the individual is semicomatose, comatose or convulsing, DO NOT GIVE FLUIDS BY MOUTH. In case of intentional ingestion of the product seek medical assistance immediately; take individual to nearest medical facility.

USA **BUSAN 30WB**

~-~	
SECTION	1
SECTION	4

PRIMARY ROUTES OF EXPOSURE

1. Effects from Acute Exposure:

 $\underline{\underline{Eye}}$ Very hazardous in case of eye contact (irritant, corrosive). Inflammation of the eye is

Exposure: characterized by redness, watering and itching.

Skin Very hazardous in case of skin contact (sensitizer). Hazardous in case of skin contact

Exposure: (corrosive, irritant). Skin contact may produce burns. Skin inflammation is characterized by

itching, scaling, reddening or, occasionally, blistering.

<u>Inhalation:</u> May be harmful if inhaled. Do not breathe spray mists of the undiluted product. Effects will

depend upon solution strength and length of time of exposure.

Ingestion: Ingestion is not expected to be a primary route of exposure.

2. Effects from Chronic Exposure:

Chronic toxicity testing performed on the active ingredient indicates no significant chronic effects. Chronic feeding studies on the active ingredient did not reveal any significant adverse effects. Repeated dermal exposures may cause allergic contact dermatitis type reactions in susceptible individuals. In vitro mutagenicity tests on the active ingredients were negative. Birth defects are unlikely, as animal tests on the active ingredients were negative.

SECTION 5

Toxicological Information

Acute Effects:

Acute Oral (LD50) = 1200 mg/kg Rat
Acute Dermal (LD50) = >2000 mg/kg Rabbit
Acute Inhalation (LC50) = 0.4 mg/l (4 hours) Rat

Irritant / Sensitization Effects:

Very hazardous in case of eye contact (irritant, corrosive). Inflammation of the eye is characterized by redness, watering and itching.

Very hazardous in case of skin contact (sensitizer). Hazardous in case of skin contact (corrosive, irritant). Skin contact may produce burns. Skin inflammation is characterized by itching, scaling, reddening or, occasionally, blistering.

May be harmful if inhaled. Do not breathe spray mists of the undiluted product. Effects will depend upon solution strength and length of time of exposure.

Target Organs Effects:

Contains material which causes damage to the following organs: the nervous system. May cause damage to the following organs: upper respiratory tract, skin, eyes.

Other Health Effects:

Inhalation toxicity was conducted with a 4 hour exposure under misting conditions. Normal use of this product under non-misting conditions should not present an occupational hazard. Trace amounts of ethylene oxide could accumulate in the headspace of drums, storage/transport vessels or in enclosed areas where the product is being handled or used. If the product is handled according to the recommendations set forth in this Material Safety Data Sheet, the presence of trace amounts is not expected to result in any short- and/or long-term hazard. Ethylene oxide is considered by OSHA to be a possible human carcinogen and reproductive hazard.

USA BUSAN 30WB

SECTION 6

Environmental Toxicological Information

LC50 = 0.06 mg/l 48 hours Daphnia magna

LC50 = 0.07 mg/l 96 hours Fathead minnow

LC50 = 0.176 mg/l 96 hours Rainbow trout

SECTION 7

Physical and Chemical Properties

Appearance Opaque, tan, viscous liquid

Odor Mild.

Density 1.11 g/cm³ $(25^{\circ}C / 77^{\circ}F)$

Flash Point Closed cup: >100°C (212°F). (Pensky-Martens.)

Melting/Freezing Point Not available. Boiling Point >100 $^{\circ}$ C (212 $^{\circ}$ F)

Solubility Dispersible in cold water. Dispersible in hot water.

pH (Neat) 3 [Acidic.]

pH (100 ppm in water) 5-6

o/w Partition Coefficient Not available.

Oxidizing/Reducing Properties. Neither a strong oxidizer nor a strong reducing agent.

NOTE: The physical data presented above are typical values and should not be construed as specifications.

SECTION 8

Fire and Explosion Information

Flammable Limits Not available.

Extinguishing Media Water fog, carbon dioxide, foam, dry chemical.

Special Firefighting
Procedures

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 9

Reactivity Information

Stability Stable under normal conditions of use and storage. Do not heat and/or store above

50°C as decomposition may increase packaging pressure.

Incompatibility Strong acids; strong bases; strong oxidizers; extended heating at high

temperatures.

Hazardous Decomposition

decomposition of product can produce toxic vapors of hydrogen cyanide and sulfur dioxide. Exposure to fire or flames may generate oxides of sulfur, nitrogen and/or

carbon.

USA BUSAN 30WB

SECTION 10

Handling Precautions

Rubber gloves, safety glasses or goggles, body protective clothing and shoes are required.

Eye-wash fountains in the work place are strongly recommended.

When splashing can occur, a neoprene apron or neoprene rain suit and a face shield are advisable.

Respiratory protection is required for work areas where misting may occur. A comprehensive respiratory protection program is needed when respirators must be used. The handling precautions for this product are based on the characteristics of the neat product unless otherwise specified.

SECTION 11

Satisfactory Materials of Construction

304 Stainless steel

316 Stainless steel

Aluminum 5052 H34

Polyethylene - crosslink

Polyethylene - high density

Polyethylene - low density

Polypropylene

Rehau Tubing

Silicone rubber

6/6 Nylon

Teflon

Tygon 2275

Pharmed Tubing

Norprene

Dow Sillastic Tube

C-Flex (Cole Parmer)

NOTE: With respect to all other materials not listed above, user should be aware that use of such materials with this product may be hazardous and result in damages to such materials and other property and personal injuries. No data concerning such materials not listed above should be implied by the user.

SECTION 12

Spill, Leak, and Disposal Procedures

SPILL AND LEAK RESPONSE GUIDELINES:

Important: Before responding to a spill or leak of this product, review each section of this MSDS. Follow the recommendations given in the Handling Precautions sections. Check the Fire and Explosion Data section to determine if the use of non-sparking tools is merited. Insure that spilled or leaked product does not come into contact with materials listed as incompatible. If irritating fumes are present, consider evacuation of enclosed areas.

Emergency Response Assistance: Emergency technical assistance is available at any time from Buckman Laboratories, Inc., by calling (901) 767-2722.

Initially minimize area affected by the spill or leak. Block any potential routes to water systems (e.g., sewers, streams, lakes, etc.). Based on the product's toxicological and chemical properties, and on the size and location of the spill or leak, assess the impact on contaminated environments (e.g. water systems, ground, air equipment, etc.). There are no methods available to completely eliminate any toxicity this product may have on aquatic environments. Minimize adverse effects on these environments. Buckman Laboratories, Inc. can be contacted for technical assistance. Determine if federal, state, and/or local release notification is required (see Regulatory Classifications section of this MSDS). Recover as much of the pure product as possible into appropriate containers. Later, determine if this recovered product can be used for its intended purpose. Address clean-up of contaminated environments. Spill or leak residuals may have to be collected and disposed of. Clay, soil, or commercially available absorbents may be used to recover any material that can not readily be recovered as pure product. Flushing residual material to an industrial sewer, if present at the site of a spill or leak incident, may be acceptable if authorized approval is obtained. If product and/or spill/leak residuals are flushed to an industrial sewer, insure that they do not come into contact with incompatible materials. Contact the person(s) responsible for the operation of your facility's industrial sewer system prior to intentionally flushing or pumping spills or leaks of this product to the industrial sewer.

DISPOSAL GUIDELINES

Note: Follow federal, state, and local regulations governing the disposal of waste materials.

Neat Product: Contact your Buckman representative or Buckman Laboratories, Inc., at (901) 278-0330.

Contaminated Materials: Determine if waste containing this product can be handled by available industrial effluent system or other on-site waste management unit. If off-site management is required, contact a company experienced in industrial waste management. This product is not specifically listed in 40 CFR 261 as a Resource Conservation and Recovery Act (RCRA) hazardous waste. However, spill or leak residuals may meet the criteria of a characteristic hazardous waste under this Act. Check the characteristics of the material to be disposed of and/or the physical and reactivity data given in this MSDS for the neat product.

Container Disposal: Empty containers, as defined by appropriate sections of the RCRA, are not RCRA hazardous wastes. However, insure proper management of any residuals remaining in container.

SECTION 13

Transportation and Shipping Information

DOT Shipping Information:

UN3265, CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S., (2-(Thiocyanomethylthio)benzothiazole), Class 8, P.G. III, (ERG Guide 153)

IMO/IMDG Shipping Information:

UN3265, CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S., (2-(Thiocyanomethylthio)benzothiazole), Class 8, P.G. III, MARINE POLLUTANT, (EmS No. F-A, S-B, ERG Guide 153, HazMat Code 4931466)

IATA Shipping Information:

UN3265, CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S., (2-(Thiocyanomethylthio)benzothiazole), Class 8, P.G. III, (ERG Guide 153, ERG Code 8L)

DOT "RQ": NONE (Material does not meet concentration requirements for hazardous substances as defined in 49 CFR 171.8)

Unless otherwise stated, the shipping information provided above applies only to non-bulk containers of this product. Proper shipping name and general shipping information may vary depending on packaging and mode of shipment. All products shipped from Buckman locations have been properly packaged and labeled according to appropriate hazardous materials shipping regulations. If any alteration of packaging, product, or mode of transportation is further intended, different shipping information, including but not limited to proper shipping name, RQ designation, and labeling may apply. For further information pertaining to the shipping requirements for this product, contact Buckman's Transportation Department or DOT Coordinator.

SECTION 14

Regulatory Information

The following Regulations are known to apply to the use and disposal of this product. Additional Federal, State and Local regulations may also be applicable.

SARA (Superfund Amendments and Reauthorization Act)

SARA 302 Extremely Hazardous Substances List ...

No components of this product are listed.

SARA 312 Hazard Category ...

Immediate (Acute) Health Hazard

SARA 313 Toxic Chemicals List ...

This product contains the following toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372:

Ethylene glycol

CERCLA (Comprehensive Environmental Response, Compensation and Liability Act)

Ethylene glycol RQ = 5000 lbs.

RCRA (Resource Conservation and Recovery Act) Listed Hazardous Waste

No components of this product are listed.

CWA (Clean Water Act) Listed Substances

No components of this product are listed.

FDA (Food and Drug Administration)

This product is allowed under the following FDA (21 CFR) sections :176.300.

Bundesinstitut für Risikobewertung (BfR) (The Federal Institute for Risk Assessment)

XXXVI

TSCA (Toxic Substances Control Act) Applicability

All components may not be listed on the TSCA Inventory. Registered pesticides are exempt from the requirements of TSCA.

FIFRA (Federal Insecticide, Fungicide, and Rodenticide Act)

This product is a registered pesticide. EPA Reg. No. 1448-55

HMIS/NPCA Rating ... Health 3 Flammability 1 Reactivity 1

NFPA Ratings Health 3 Flammability 1 Reactivity 1

State Regulations

Various State Right To Know Acts ...

Non-proprietary hazardous chemicals are listed in Section 2 of this MSDS. Should you require further information on specific proprietary or inert ingredients please contact Buckman Laboratories' Regulatory Affairs Department.

The information on this Material Safety Data Sheet reflects the latest information and data that we have on hazards, properties, and handling of this product under the recommended conditions of use. Any use of this product or method of application which is not described in the Data Sheet is the responsibility of the user. This Material Data Safety Sheet was prepared to comply with the OSHA Hazard Communication regulations. While some components are claimed Trade Secret under OSHA Hazard Communication regulations, all known OSHA hazards associated with the Trade Secret component(s), if contained in this product, are fully disclosed.

Buckman Laboratories, Inc. warrants that this product conforms to its chemical description and is reasonably fit for the purpose referred to in the directions for use when used in accordance with the directions under normal conditions. Buyer assumes the risk of any use contrary to such directions.

Seller makes no other warranty or representation of any kind, express or implied, concerning the product, including NO IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS OF THE GOODS FOR ANY OTHER PARTICULAR PURPOSE. No such warranties shall be implied by law and no agent of seller is authorized to alter this warranty in any way except in writing with a specific reference to this warranty.

The exclusive remedy against seller shall be in a claim for damages not to exceed the purchase price of the product, without regard to whether such a claim is based upon breach of warranty or tort.

Any controversy or claim arising out or relating to this contract, or breach thereof, shall be settle by arbitration in accordance with the commercial arbitration rules of the American Arbitration Association, and judgement upon the rendered by the Arbitrator(s) may be entered in any court having jurisdiction thereof.