

*Atlantic Sunrise Project – PA DEP Chapter 105 Permit Application
Transcontinental Gas Pipe Line Company, LLC
Luzerne County*

**ATTACHMENT P -1
ALTERNATIVES ANALYSIS**

Revised November 18, 2016

1.0 Introduction..... 3

2.0 No Action Alternative 3

3.0 Transco Existing System Alternatives 4

4.0 Development of the Proposed Route 8

4.1 Route Start and End Points 8

4.2 Selecting the North Endpoint of CPL North 8

4.3 Selecting the Tie-In Location between CPL North, CPL South, and Existing Leidy Line System 8

4.4 Selecting the Tie-In Location between CPL South and the Existing Transco Mainline... 9

4.5 Routing Alternatives & Proposed Route Selection..... 10

5.0 Routing Process/Impact Avoidance and Minimization Measures 13

6.0 Atlantic Sunrise Major Route Alternatives..... 16

6.1 Diamond CPL North Alternative..... 16

6.2 Williams Midstream CPL North Alternative..... 19

6.3 Western CPL South Alternative 22

7.0 Luzerne County Specific Minor Route Alternatives..... 27

8.0 Luzerne County Deviations Considered..... 32

9.0 Construction Method Alternatives 33

Appendix P-1 Stream and Wetland Avoidance and Minimization Measures Identified for the Project in Luzerne County

Appendix P-2 Trenchless Crossing Analysis, Central Penn Line Luzerne County, Pennsylvania

1.0 INTRODUCTION

This Alternatives Analysis report describes the alternatives considered or currently under consideration for the proposed Atlantic Sunrise Project. This report discusses the following categories of alternatives: the no-action alternative, system alternatives, route alternatives, and construction alternatives. Additionally, ~~there s~~Sections 7 and 8 herein consider ~~Lancaster~~ Luzerne County minor route alternatives and deviations.

The objective of Transcontinental Gas Pipe Line Company's (Transco's) alternatives analysis is to develop proposed pipeline routes that will be constructible, accomplish the Project's purpose, and will avoid or minimize potential adverse environmental impacts. This alternatives analysis was also developed to be consistent with the Federal Energy Regulatory Commission's regulatory requirements as set forth in 18 Code of Federal Regulations 380.15 and 25 PA. Code § 105.13(e)(viii). Thus, it contains a detailed analysis of alternatives to the proposed action, including alternative locations, ~~r~~outings or designs to avoid or minimize environmental impacts.

The information contained in this report is based upon field surveys, desktop review of available literature, stakeholder input, and publicly available information regarding existing pipeline infrastructure. Comparison analysis of the alternatives discussed in this report is based on rights-of-way (ROW) width assumptions and available data sets for desktop analysis. ~~Because this is a linear pipeline project access to private property will need to be obtained by negotiation in condemnation following the issuance of a Certificate of Public Necessity from FERC. Therefore, this report does not rely upon actual field survey data.~~

2.0 NO-ACTION ALTERNATIVE

This section describes the benefits and consequences of not constructing the Project. For example, if Transco does not construct the Project, temporary and permanent environmental impacts associated with construction and operation would be avoided. However, by not constructing the Project, Transco would not be able to provide the natural gas transportation service requested by the customers that have executed binding agreements for Transco to provide 1.7 million dekatherms per day (MMDth/d) of incremental firm transportation of natural

gas from the Marcellus Shale production areas in northern Pennsylvania to its existing market areas, extending to as far south as the Station 85 Pooling Point¹ in Choctaw County, Alabama. The no-action alternative would not result in increased access to reliable, domestic natural gas supplies from the Marcellus Shale production areas. Transco's review of existing and available energy sources indicates that natural gas is the best fuel source to provide clean, reliable energy necessary to meet existing and future demand while minimizing environmental impacts.

The existing Transco facilities in or near the Project area are not currently designed to transport natural gas from north to south and do not provide adequate pipeline takeaway capacity for transportation of natural gas to meet current transportation demand. If the no-action alternative is selected, Transco's customers will need to:

- Seek other transportation services;
- Forgo meeting their natural gas demand until energy conservation measures stabilize or decrease demand, possibly limiting their growth and the growth of the local economies they serve; and
- Depend on other future development projects with unpredictable schedules and undetermined environmental impacts.

For the reasons described above, the no-action alternative does not meet the Project objectives of providing the additional transportation capacity of natural gas requested by its customers within the time frame required.

3.0 TRANSCO EXISTING SYSTEM ALTERNATIVE

The Transco Existing System Alternative (Figure P-1) would utilize the existing ROWs of Transco's Leidy Line and Mainline systems to the extent practicable by installing noncontiguous pipeline looping and other facilities along these systems. This alternative incorporates a segment of the current proposed CPL North route, from the Zick Meter Station at about milepost (MP) 57.33, to the proposed North Diamond Regulator Station near MP L92.7 in Luzerne County, Pennsylvania. From this point, the alternative route runs east along the Leidy Line system to existing Compressor Station 515 in Luzerne County, Pennsylvania. An additional Leidy Line loop would be required between existing Compressor Stations 517 and 515 to accommodate volumes moving eastward. East of Compressor Station 515, several sections of

looping would be required to transport the incremental volumes along the Leidy Line and Transco Mainline systems.

The proposed Unity Loop, Chapman Loop, and horsepower additions at Compressor Stations 517, 520 and 190 would still be required. Similarly, facilities located south of Compressor Station 195 (i.e., pipeline replacements in Virginia and aboveground facility modifications in Maryland, Virginia, North Carolina, and South Carolina) would also be required for the Transco Existing System Alternative to meet the purpose and need for the Project. Facilities that are common between the Project and the Transco Existing System Alternative are presented below in underlined text to distinguish them from the facilities unique to the Transco Existing System Alternative. This alternative is depicted as Figure P-1.

The following facilities would be necessary for the Transco Existing System Alternative:

- Greenfield Pipeline
 - 36.2 miles of new 30-inch-diameter greenfield pipeline in Pennsylvania from the Zick Meter Station to the North Diamond Regulator Station.
- Looping Pipeline
 - 8.6 miles of new 42-inch-diameter looping in Lycoming County, Pennsylvania (Unity Loop).
 - 2.9 miles of new 36-inch-diameter looping in Clinton County, Pennsylvania (Chapman Loop).
 - 23.7 miles of new 42-inch-diameter loop from MP L92.7 to Station 515 in Luzerne County, Pennsylvania.
 - 8.6 miles of new 42-inch-diameter loop from MP LL7.7 4 to MP LL9.0 in Luzerne County, Pennsylvania.
 - 8.3 miles of new 42-inch-diameter loop from Station 515 to L60.7 in Luzerne County and Monroe County, Pennsylvania.
 - 14.8 miles of new 42-inch-diameter loop from L57.5 to L42.7 in Monroe County, Pennsylvania.
 - 30.3 miles of new 42-inch-diameter loop from Transco Delaware Regulator Station to Centerville Regulator Station (includes Delaware River Crossing) in

Northampton County, Somerset County, and Warren County, New Jersey, and Northampton County, Pennsylvania.

- 16.6 miles of new 42-inch-diameter loop from Transco Centerville Regulator Station to Transco Station 205 in Somerset County and Mercer County, New Jersey.
- 7.7 miles of new 42-inch-diameter loop from MP 1765.7 to Station 205 in Mercer County, New Jersey.
- 43.0 miles of new 42-inch-diameter loop from Station 200 to MP 1765.3 in Mercer County, New Jersey, and Bucks County, Pennsylvania.
- 39.6 miles of new 42-inch diameter loop from MP 1682.7 to Station 200 in Chester County and Lancaster County, Pennsylvania.
- 4.8 miles of new 42-inch-diameter loop from Station 195 to MP 1679.3 in York County, Pennsylvania.
- Pipeline Replacement
 - 2.5 miles of 30-inch-diameter pipeline replacements between Transco Mainline MP 1578.7 and 1581.0 in Prince William County, Virginia.
- Greenfield Compressor Station
 - One new 30,000-horsepower (hp) compressor station in Wyoming County, Pennsylvania (Station 605).
- Horsepower Additions at Existing Transco Compressor Stations
 - One new 16,000-hp compressor unit at Station 520 in Lycoming County, Pennsylvania.
 - One new 16,000-hp compressor unit at Station 517 in Columbia County, Pennsylvania.
 - One new 16,000-hp compressor unit and one new 30,000-hp compressor unit at Station 515 in Luzerne County, Pennsylvania.
 - One new 30,000-hp compressor unit at Station 200 in Chester County, Pennsylvania.
 - One new 15,000-hp compressor unit at Station 195 in York County, Pennsylvania.
 - One new 30,000-hp compressor unit at Station 190 in Howard County,

Maryland.

- Additional ancillary facilities, such as MLVs, cathodic protection, communication facilities, and internal inspection device (i.e., pig) launchers and receivers in Pennsylvania.
- Two new meter stations and three new regulator stations with interconnecting piping in Pennsylvania.
- Modifications to six existing compressor stations that enable compression for bidirectional flow in Maryland, Virginia, and North Carolina;
- Installation of deodorization/odor masking equipment at four existing compressor stations in North Carolina
- Supplemental odorization, odor detection, and/or odor masking/deodorization equipment at 42 meter/regulator stations in North Carolina and South Carolina; and
- Odor masking/deodorization equipment at 14 MLV locations in North Carolina and South Carolina.

Transco did not select this system alternative due to the following constraints:

- The alternative would require construction of about 51.1 miles of additional pipeline along the Transco Mainline and Leidy Line systems. The longer distance of this route would require more total land than the Project for construction and would increase impacts on land uses, especially on forest lands, wetlands, waterbodies, and major waterbodies. As indicated above, the Chapman Loop would still be needed for this alternative.
- Pipeline looping along Transco's existing Mainline System would locate pipeline in proximity to areas of high population density, including: Wilkes-Barre, Pennsylvania; Trenton, New Jersey; and Princeton, New Jersey. Therefore, colocation with the existing Mainline System would not be possible for all pipeline looping.
- Looping along these areas would result in greater impacts on residential and other developed areas with a 15 times greater occurrence of residential structures located within 50 feet of construction workspace.
- High densities of residential developments in proximity to the existing pipeline facilities would likely require acquisition of residential properties to allow the addition of a pipeline loop within Transco's existing Mainline System ROWs.

- The alternative would require 183,000 hp of compression, which is 51,000 hp more than the Project.

Due to the increased horsepower and looping required and the associated increase in residential impacts, this alternative was removed from further consideration.

4.0 DEVELOPMENT OF THE PROPOSED ROUTE

Based on the commercial aspects of the Project, Transco evaluated start and endpoints for the Project and identified potential route alternatives between the start and endpoints of the Central Penn Line. This section provides the framework used to define the route start and endpoints of the Central Penn Line, as well as selection of the proposed route.

4.1 Route Start and Endpoints

The locations that Transco evaluated for start and endpoints were based on the need to meet the stated purpose of the Project while maximizing the use of existing Transco infrastructure for efficiency and reliability and to minimize the amount of incremental facilities required. Using these parameters, Transco designed the Project to have the capacity to receive up to 1.7 MMDth/d of natural gas from both new receipt points on CPL North and from existing receipt points along the Leidy Line system.

4.2 Selecting the North Endpoint of CPL North

New receipt points on CPL North include the Zick and Springville Meter Station in Susquehanna County, Pennsylvania, which can provide approximately 850,000 dekatherms per day (Dth/d) from interconnecting midstream pipelines. As it is the northernmost receipt point, Transco determined that the Zick Meter Station will serve as the northern endpoint of the pipeline route.

4.3 Selecting the Tie-In Location between CPL North, CPL South, and Existing Leidy Line System

In addition to the 850,000 Dth/d received on CPL North, the remaining 850,000 Dth/d will be received through various receipt points along Transco's existing Leidy Line system, and the full 1.7 MMDth/d will be aggregated into CPL South. CPL North and existing Leidy Line A share a corridor that rejoins Leidy Line system pipelines B, C, and D at MP L113.7. This is

the easternmost location of the preferred aggregation point. Compressor Station 517 is located at MP L115.2 and defines the westernmost location of the aggregation point. Aggregating volumes on the discharge (east) side of Compressor Station 517 optimizes the horsepower at the station, providing higher pressure into CPL South. Therefore, an aggregation point between MP L113.7 and L115.2 is preferred. Transco determined MP L114.0 to be the ideal point within this range, as it would shorten the length of the CPL North pipeline. Furthermore, if the aggregation point were located west of Compressor Station 517 at approximately MP L123.0, an additional 25,000 hp would be required at proposed Compressor Station 610 as lower suction pressure gas would be entering the station piping. Consequently, this reinforces Transco's proposed tie-in location between MP L113.7 and MP L115.2.

4.4 Selecting the Tie-In Location between CPL South and the Existing Transco Mainline

The southern endpoint of CPL South must tie into Transco's existing Mainline system in order to serve its existing market areas. To minimize the amount of additional facilities needed to meet the Project's purpose, Transco determined that the optimal hydraulic endpoint of the pipeline route is between MP 1674.6 (existing Compressor Station 195) and MP 1683.7 of the Transco Mainline system. However, extending south of MP 1679.8 would necessitate an additional crossing of the Susquehanna River, for which Transco was not able to find a suitable crossing location. Therefore, Transco determined the optimal range to be between MP 1679.8 and 1683.7. The proposed route for CPL South ties into the existing Transco Mainline system at MP 1683.3.

Any system tie-ins north of MP 1683.7 would require additional mainline facilities (mainline looping and/or compression) between existing Compressor Station 195 and the tie-in location. For example, Transco evaluated a tie-in point near MP 1686.4, located 3.10 miles northeast of the current proposed tie-in. Transco's hydraulic study determined that a tie-in at this location would require an additional 4,000 hp at existing Compressor Station 195, as well as compressor re-wheeling and modifications to two existing reciprocating compressors to operate the higher differential pressure. Alternatively, an approximately 4-mile-long loop would be required between MP 1682.4 and MP 1686.4. Any tie-in point further northeast

than MP 1686.4 would necessitate additional incremental facilities, such as additional compression, looping, or some combination of the two.

4.5 Routing Alternatives & Proposed Route Selection

Transco identified certain routing constraints and sensitive areas requiring detailed analysis to ensure avoidance or minimization of impacts when evaluating alternatives and selecting the proposed pipeline routes.

When identifying routing options, Transco attempted to co-locate the pipeline with existing utility corridors and ROWs while considering impacts on other environmental factors. The use of co-location as a principal design element is consistent with the FERC guidelines, which stress the corridor concept, and complements the existing land use characteristics in the Project area. Siting pipeline facilities along existing corridors reduces the need to establish new corridors in previously undisturbed areas, which reduces the amount of fragmentation of interior forest and minimizes the number of affected landowners. Transco defines co-location as siting a pipeline right-of-way (ROW) that:

- Lies within an existing ROW or easement; or
- Abuts an existing ROW or easement.

The following routing considerations also influenced the development of the proposed routes:

- Identifying crossing locations of the Susquehanna River where, based on terrain, horizontal directional drilling (HDD) appeared to be technically feasible;
- Minimizing visual impacts on the Appalachian Trail;
- Crossing areas of significant topographic relief where technically feasible;
- Avoiding state lands, including state parks, state forests, and state game lands to the maximum extent practicable; and
- Avoiding densely populated areas to the extent practicable.

Transco's pipeline route selection process considered three types of route alternatives:

- Major route alternative – a route that differs substantially in both length and distance from the proposed route, which are described in Section 6.0 and are presented on an entire Project basis for the overall Atlantic Sunrise Project;

- Minor route alternative – a route that deviates from short segments of the proposed route which are described in Section 7.0 and are presented on a County basis related to the specific permit application for which this Attachment P is prepared for; and
- Route deviation – minor adjustments to the proposed route, typically to avoid specific features (e.g., topography, sensitive habitat, structures), summarized in Table P-1 for CPL North and CPL South.

After taking the above into consideration, Transco narrowed its analysis to 600-foot-wide study corridors for the CPL North and CPL South pipeline routes, which were determined based on desktop data and aerial reconnaissance (helicopter overflights). Once this initial routing process was complete, Transco began field routing efforts within these study corridors. These field efforts began in May 2014 and continued up to the submittal of this **revised** application. A detailed discussion on the field routing process and impact avoidance and minimization measures undertaken as part of the Project are described in Section 5.0 of this Alternatives Analysis.

In addition to route adjustments based on field routing, biological and cultural resource surveys, Transco considered alternatives requested by landowners and other stakeholders through stakeholder outreach, commencing with Transco's open houses held in May and June of 2014. Transco reviewed each requested route adjustment for feasibility as a viable alternative based on the Project route, constructability, and the minimization of impacts on sensitive resources.

Transco used various data sources to identify and evaluate pipeline route alternatives, including: observations made during routing surveys and field reconnaissance; Google Earth™; geographic information system databases from county, state, and federal sources; recently produced aerial photography; U.S. Geological Survey (USGS) topographic maps; National Wetland Inventory maps; and remote-sensing data. The factors used to select the proposed routes over the alternative routes focused on FERC scoping information, landowner concerns, minimizing the number of affected landowners, minimizing adverse environmental impacts, ensuring constructability, and promoting safety.

FIGURE 1

5.0 IMPACT AVOIDANCE AND MINIMIZATION MEASURES

Due to the linear nature of the Project, it is not possible to completely avoid impacts to wetlands, waterbodies, or other sensitive resources. Therefore, Transco used a comprehensive field routing process to identify a constructible alignment for CPL North and CPL South that would minimize impacts to wetlands, waterbodies, or other sensitive resources to the extent practicable. A similar approach was taken on the Chapman and Unity Loops; however, in these cases routing options were limited to the north or south side of the existing right-of-way to maximize opportunities for co-location. Impact minimization and avoidance has been accomplished with field routing teams comprised of engineering, construction, and environmental specialists. These teams are assessing the routes with regard to the following considerations:

Engineering

- Avoiding general engineering and constructability constraints;
- Minimizing route distance along steep slopes and side slopes;
- Reducing the number of severe pipeline bends and turning angles;
- Identifying and avoiding, where practicable, areas of karst topography;
- Identifying and evaluating opportunities for utilizing trenchless technology such as HDD and boring; and
- Identifying and avoiding, where practicable, locations with a potential need for blasting.

Environmental

- Minimizing impacts at any single wetland crossing to 1 acre or less wherever practicable;
- Avoiding or minimizing impacts on forested wetlands and other wetlands;
- Avoiding or minimizing impacts on known threatened and endangered species habitat, such as:
 - Rocky talus slopes potentially used as habitat by the timber rattlesnake (*Crotalus horridus*), Allegheny woodrat (*Neotoma magister*), and small-footed bat (*Myotis leibii*);
 - Wetland complexes with features suggesting potential suitability as bog turtle habitat; and

- Palustrine emergent wetlands surrounded by woodlands, which may be suitable habitat for the northeastern bulrush (*Scirpus ancistrochaetus*)
- Forest stands containing trees greater than 5 inches diameter at breast height with exfoliating bark, cracks, crevices, and/or hollows. Prime examples would include live shagbark hickory trees (*Carya ovata*) and shellbark hickory trees (*C. laciniosa*), dead elms (*Ulmus* spp.), dead poplars (*Populus* spp.), or any tree with a rotted-out cavity, which may be potential roosting trees or suitable habitat for the Indiana bat (*Myotis sodalis*) and northern long-eared bat (*Myotis septentrionalis*).
- Crossing waterbodies at 90 degree angles to minimize in-stream disturbance wherever practicable;
- Avoiding or minimizing crossings of major waterbodies;
- Minimizing impacts on contiguous upland forest by routing the centerline along tree lines or through existing cleared areas to the greatest extent practicable; and
- Identifying and avoiding, where practicable, groundwater springs/seeps.

Land

- Minimizing impacts on private property and structures;
- Minimizing conflicts with land use; and
- Minimizing impacts on residential water wells and septic systems.

Cultural

- Avoiding or minimizing impacts on sites listed on or potentially eligible for listing on the National Register of Historic Places; and
- Identifying and avoiding, where practicable, aboveground structures that appeared to be over 50 years old.

Transco initiated routing surveys within the 600-foot-wide study corridors in May [2014](#) and ~~will~~ [has](#) continued the routing process [through 2016](#) as survey permission [has been is](#) granted. ~~This process will continue until all parcels are surveyed.~~

The routing survey crews started with a preliminary pipeline route centered within the 600-foot-wide study corridors. The preliminary pipeline route was either confirmed as adequate or adjusted to avoid and/or minimize, to the extent practicable, any issues encountered during the routing surveys according to the considerations noted above. The routing survey teams documented the reasons for the adjustments and classified them according to the engineering, environmental, land, and cultural considerations evaluated. **Appendix P-1 provides the results of stream and wetland avoidance and minimization measures identified for the Project in Luzerne County by the routing survey crews.**

~~Since routing surveys began in May 2014, the survey teams have completed 352 adjustments to the CPL North and CPL South routes. These adjustments avoided, reduced, or minimized impacts on sensitive features identified during the routing surveys. Approximately 25 percent of the adjustments were along CPL North, with the remaining 75 percent located along CPL South. Most of the adjustments resulted in the avoidance or minimization of impacts on more than one feature. Table P-1 depicts the summary of route adjustments made during field survey for CPL North and CPL South by feature type.~~

Table P-1
 Summary of Routing Adjustments

County	Features Avoided or Minimized Based on Route Adjustments						
	Wetland	Waterbody	T&E Habitat	Engineering	Land	Cultural	Upland Forest
Columbia	1	0	0	0	1	0	1
Luzerne	6	3	1	2	7	0	6
Wyoming	9	8	0	9	16	1	9
Susquehanna	2	3	0	5	2	0	2
CPL North Total	18	14	1	16	26	1	18
Lancaster	6	19	1	21	33	0	6
Lebanon	17	21	3	18	25	2	17
Schuylkill	2	4	0	2	6	0	2
Northumberland	0	0	0	3	5	0	0
Columbia	6	11	1	8	12	1	6
CPL South Total	31	55	5	52	84	3	34

County	Features Avoided or Minimized Based on Route Adjustments						
	Wetland	Waterbody	T&E Habitat	Engineering	Land	Cultural	Upland Forest
Key: CPL — Central Penn Line T&E — Threatened and Endangered							

6.0 ATLANTIC SUNRISE MAJOR ROUTE ALTERNATIVES – CENTRAL PENN LINES

Major route alternatives differ substantially in both length and distance from the proposed route. During the Project development process, Transco considered three major route alternatives before selecting its 600-foot-wide study corridors and proposed routes: the Diamond CPL North Alternative, Williams Midstream CPL North Alternative, and Western CPL South Alternative.

Each of the major route alternatives is described below. Transco did not complete full hydraulic modeling, nor did it evaluate costs for any of the major alternatives, because those alternatives have significantly greater environmental impacts than proposed routes for CPL North and CPL South. Figure P-2 shows the major alternatives in relation to the proposed routes.

6.1 Diamond CPL North Alternative

The Diamond CPL North Alternative⁶ starts at the Zick Meter Station in Susquehanna County, Pennsylvania. The route continues south for approximately 80 miles, bisecting Transco’s existing Leidy Line A to the north and Leidy Lines B and C to the south and terminates near MP 93.2 of the CPL South route in Columbia County, Pennsylvania.

Approximately 48 miles of the route is co-located with other ROW, with the remaining approximately 32 miles being primarily greenfield. The Diamond CPL North Alternative is an alternative route for CPL North, as the entire length of CPL South would still be required for this alternative, including the segment of the proposed route between MP 125.1 and MP 93.2. CPL South MP 93.2 would become the new aggregation point for Leidy Line system volumes and CPL North volumes.

The Diamond CPL North Alternative is approximately 23 miles longer than the corresponding sections of the proposed CPL North route and would likely require an additional compressor station along CPL North because it would bypass Compressor Station 517 along Transco’s Leidy Line system. Table P-2 provides a summary comparison of the Diamond CPL North Alternative to the CPL North route.

**Table P-2
 Diamond CPL North Alternative Route Comparison**

Factor	Diamond CPL North Alternative	Corresponding Section of CPL North	Difference from CPL North
Length of Corresponding Segment (miles)	79.9	57.4	+22.5
Co-location			
Length Adjacent to Interstate Pipeline ROW (miles)	0.0	21.2	-21.2
Length Adjacent to Midstream Pipeline ROW	0.0	4.8	-4.8
Length Adjacent to Electric Transmission Line ROW (miles)	47.3	0.0	+47.3
Length Adjacent to Roadway (miles)	1.4	0.1	+1.3
Total Length Co-located (miles)	48.7	26.1	+22.6
ROW Requirements			
Pipeline Construction Requirements (acres) ^a	968.4	696.0	+272.4
Pipeline Operation Requirements (acres) ^b	484.3	283.8	+200.5
Federal and State Land			
Federal Lands Crossed (number/miles)	0 / 0.0	0 / 0.0	0 / 0.0
State Lands Crossed (number/miles)	1 / 1.4	2 / 1.6	-1 / -0.2
Land Use			
Forested Land Crossed (miles) ^c	47.7	37.5	+10.2
Forested Land Impacts (construction/operation) (acres) ^d	577.4 / 288.8	456.6 / 174.7	+120.8 / +114.1
Agricultural Land Crossed (miles) ^c	23.1	15.0	+8.1
Agricultural Land Impacted (construction/operation) (acres) ^d	281.0 / 140.3	180.6 / 84.8	+100.4 / +55.5
Other Land Crossed (miles) ^{c,e}	9.1	4.9	+4.2
Other Land Impacted (construction/operation)	110.0 / 55.2	58.8 / 24.3	+51.2 / +30.9
Waterbodies			

**Table P-2
 Diamond CPL North Alternative Route Comparison**

Factor	Diamond CPL North Alternative	Corresponding Section of CPL North	Difference from CPL North
Waterbodies Crossed (number) ^f	72	51	+21
Major Waterbody Crossings (number >100 feet) ^g	8	2	+6
Wetlands			
Total Wetland Complexes Crossed (number) ^h	32	15	+17
Total Wetland Crossed (miles) ^h	1.7	0.7	+1.0
Palustrine Forested Wetland Complex Impacts (construction/operation) (acres) ^h	10.2 / 5.1	7.0 / 2.7	+3.2 / +2.4
Other Physical Features			
Road Crossings (number)	122	86	+36
Railroad Crossings (number)	7	2	+5
<p>a Pipeline construction requirements based on a 100-foot-wide construction corridor and includes a 100-foot long buffer at begin and end points.</p> <p>b Pipeline operation requirements based on a 50-foot-wide corridor in greenfield segments, and a 25-foot-wide corridor for segments co-located with Transco pipelines. Calculation includes a 50-foot long buffer at begin and end points.</p> <p>c Forested land, agricultural land and other land crossed are based on geographic information system (GIS) centerline analysis using United States Geological Survey (USGS) National Land Cover Dataset (NLCD).</p> <p>d Forest land, agricultural land, and other land impacted are based on GIS corridor analysis using USGS NLCD. Since multiple land use types may be present within the corridor, impact acreage for individual land uses will not be representative of distance crossed, which is based on centerline analysis.</p> <p>e Other land based on USGS NLCD and includes land cover types: Barren Land, Developed High Intensity, Developed Low Intensity, Developed Medium Intensity, Developed Open Space, Emergent Herbaceous Wetlands, Herbaceous, Open Water, Shrub Scrub, Woody Wetlands.</p> <p>f Waterbodies identified based on National Hydrography Dataset (NHD).</p> <p>g Major waterbodies identified based on review of aerial photography.</p> <p>h Wetlands identified using the National Wetland Inventory (NWI).</p> <p>Key: CPL = Central Penn Line ROW = right-of-way</p>			

Transco did not select this alternative due, in part, to the following constraints:

- It would likely require a second new compressor station along the CPL North pipeline;

- The route crosses in proximity to Scranton, Wilkes-Barre, and Nanticoke, Pennsylvania, resulting in greater impacts on residential and other developed areas; and
- Total mileage of CPL North would increase by about 23 miles, and the length of CPL South would not be reduced.

Any configuration of the Diamond CPL North Alternative would still require construction of the portion of the alternative north of the intersection with the Leidy Line System. Due to the high density of populated areas north of the Leidy Line System, Transco did not evaluate additional configurations of the Diamond CPL North Alternative.

6.2 Williams Midstream CPL North Alternative

The Williams Midstream CPL North Alternative starts at the Zick Meter Station in Susquehanna County, Pennsylvania. The route continues west along the Williams Field Services (midstream) Appalachian Basin Area, generally co-locating with 10-inch- and 12-inch- diameter pipelines for approximately 11 miles. The majority of the route then runs adjacent to the existing Williams Field Services Springville 24-inch-diameter midstream pipeline until the route intersects with the Transco’s Leidy System, where the route is co-located four (4) miles before terminating at its connection point, near MP 21.3 on the proposed CPL North route in Luzerne County, Pennsylvania. The Williams Midstream CPL North Alternative is approximately 10.9 miles longer than the CPL North proposed route. Table P-3 provides a summary comparison of the Williams Midstream CPL North Alternative and the CPL North proposed route.

**Table P-3
 Williams Midstream CPL North Alternative Route Comparison**

Factor	Williams Midstream CPL North Alternative	Corresponding Section of CPL North	Difference from CPL North
Length of Corresponding Segment (miles)	46.2	36.0	10.2
Co-location			
Length Adjacent to Interstate Pipeline ROW	4.0	0.0	+4.0
Length Adjacent to Midstream Pipeline ROW	40.2	4.8	+35.4
Length Adjacent to Electric Transmission Line ROW (miles)	0.0	0.0	0.0

*Atlantic Sunrise Project – PA DEP Chapter 105 Permit Application
Transcontinental Gas Pipe Line Company, LLC
Luzerne County
Attachment P – Alternatives Analysis*

Factor	Williams Midstream CPL North Alternative	Corresponding Section of CPL North	Difference from CPL North
Length Adjacent to Roadway (miles)	0.0	0.1	-0.1
Total Length Co-located (miles)	44.2	4.9	+39.3
ROW Requirements			
Pipeline Construction Requirements (acres) ^a	560.0	436.6	+123.6
Pipeline Operation Requirements (acres) ^b	267.9	218.3	+49.7
Federal and State Land			
Federal Lands Crossed (number/miles)	0 / 0.0	0 / 0.0	0 / 0.0
State Lands Crossed (number/miles)	0 / 0.0	0 / 0.0	0 / 0.0
Land Use			
Forested Land Crossed (miles) ^c	25.6	20	+5.6
Forested Land Impacts (construction/operation) (acres) ^d	310.0 / 151.7	244.4 / 121.7	+65.6 / +30.0
Agricultural Land Crossed (miles) ^c	15.9	13.0	+2.9
Agricultural Land Impacted (construction/operation) (acres) ^d	192.4 / 92.5	156.7 / 78.7	+35.7 / +13.8
Other Land Crossed (miles) ^{c,e}	4.7	3.0	+1.7
Other Land Impacted (construction/operation)	57.6 / 22.8	35.5 / 17.9	+22.1 / +4.9
Waterbodies			
Waterbodies Crossed (number) ^f	37	24	+13
Major Waterbody Crossings (number >100 feet) ^g	6	2	+4
Wetlands			
Total Wetland Complexes Crossed (number) ^h	20	10	+10
Total Wetland Crossed (miles) ^h	0.7	0.4	+0.3
Palustrine Forested Wetland Complex Impacts (construction/operation) (acres) ^h	4.2 / 1.5	3.8 / 1.9	+0.4 / -0.4
Other Physical Features			
Road Crossings (number)	65	50	+15
Railroad Crossings (number)	3	2	+1

Factor	Williams Midstream CPL North Alternative	Corresponding Section of CPL North	Difference from CPL North
<p>a Pipeline construction requirements based on a 100-foot-wide construction corridor and includes a 100-foot long buffer at begin and end points.</p> <p>b Pipeline operation requirements based on a 50-foot-wide corridor in greenfield segments, and a 25-foot-wide corridor for segments co-located with Transco pipelines. Calculation includes a 50-foot long buffer at begin and end points.</p> <p>c Forested land, agricultural land and other land crossed are based on geographic information system (GIS) centerline analysis using United States Geological Survey (USGS) National Land Cover Dataset (NLCD).</p> <p>d Forest land, agricultural land, and other land impacted are based on GIS corridor analysis using USGS NLCD. Since multiple land use types may be present within the corridor, impact acreage for individual land uses will not be representative of distance crossed, which is based on centerline analysis.</p> <p>e Other land based on USGS NLCD and includes land cover types: Barren Land, Developed High Intensity, Developed Low Intensity, Developed Medium Intensity, Developed Open Space, Emergent Herbaceous Wetlands, Herbaceous, Open Water, Shrub Scrub, Woody Wetlands.</p> <p>f Waterbodies identified based on National Hydrography Dataset (NHD).</p> <p>g Major waterbodies identified based on review of aerial photography.</p> <p>h Wetlands identified using the National Wetland Inventory (NWI).</p> <p>Key: CPL = Central Penn Line ROW = right-of-way</p>			

Transco did not select this route due to the following constraints:

- The midstream pipeline routes have several tight turns that would be impractical for the route of the 30-inch-diameter CPL North pipeline, making co-location through certain areas of the alternative infeasible; and
- The alternative crosses through more densely populated areas than the CPL North route, particularly on the south end where the alternative route is not co-located with the Springville pipeline. This would result in significant impacts on residential and other developed areas.

6.3 Western CPL South Alternative

The Western CPL South Alternative starts in Lycoming County, Pennsylvania, near MP L123.0 of the Leidy Line system. The route runs south for approximately 123 miles and terminates at the existing Transco Compressor Station 195 in York County, Pennsylvania.

Approximately 50 miles of the route is co-located with other utility ROWs, with the remaining approximately 73 miles being primarily greenfield. The Western CPL South Alternative is approximately 2 miles shorter than the CPL South proposed route.

The Western CPL South Alternative would require an extension of CPL North westward, to the west side of Compressor Station 517. This modification is required to ensure that CPL North gas volumes could enter the Leidy Line system at the prevailing system pressure. Moving the aggregation point of CPL North and Leidy Line system volumes to the west side of Compressor Station 517 would increase the horsepower required at Compressor Station 610 by 25,000 hp. Table P-4 provides a summary comparison of the Western CPL South Alternative and the CPL South proposed route.

**Table P-4
 Western CPL South Alternative Route Comparison**

Factor	Western CPL South Alternative	Corresponding Section of CPL South	Difference from CPL South
Length of Corresponding Segment (miles)	122.9	126.3	-3.4
Co-location			
Length Adjacent to Interstate Pipeline ROW (miles)	0.9	2.6	-1.7
Length Adjacent to Midstream Pipeline ROW (miles)	0.4	0.0	+0.4
Length Adjacent to Electric Transmission Line ROW (miles)	40.2	4.0	+36.2
Length Adjacent to Roadway (miles)	7.8	0.1	+7.7
Total Length Co-located (miles)	49.3	6.6	+42.7
ROW Requirements			
Pipeline Construction Requirements (acres) ^a	1,490.0	1,531.1	-41.1
Pipeline Operation Requirements (acres) ^b	742.1	765.6	-23.5
Federal and State Land			
Federal Lands Crossed (number/miles)	1 / 2.7	1 / 0.6	0 / +2.1

**Table P-4
 Western CPL South Alternative Route Comparison**

Factor	Western CPL South Alternative	Corresponding Section of CPL South	Difference from CPL South
State Lands Crossed (number/miles)	15 / 12.9	3 / 1.9	+13 / +11.0
Land Use			
Forested Land Crossed (miles) ^c	50.7	38.9	+11.8
Forested Land Impacts (construction/operation) (acres) ^d	613.6 / 306.0	469.4 / 235.1	+144.2 / +70.9
Agricultural Land Crossed (miles) ^c	52.1	76.4	-24.3
Agricultural Land Impacted (construction/operation) (acres) ^d	629.2 / 314.9	925.9 / 463.3	-296.7 / -148.4
Other Land Crossed (miles) ^{c,e}	20.1	11.0	+9.1
Other Land Impacted (construction/operation) (acres) ^{d,e}	247.2 / 121.2	135.8 / 67.2	+111.4 / +54.0
Waterbodies			
Waterbodies Crossed (number) ^f	148	99	+49
Major Waterbody Crossings (number >100 feet) ^g	11	3	+8
Wetlands			
Total Wetland Complexes Crossed (number) ^h	31	8	+23
Total Wetland Crossed (miles) ^h	1.6	0.4	+1.2
Palustrine Forested Wetland Complex Impacts (construction/operation) (acres) ^h	5.7 / 2.9	1.3 / 0.7	+4.4 / +2.2
Other Physical Features			
Road Crossings (number)	251	232	+19
Railroad Crossings (number)	13	12	+1

**Table P-4
 Western CPL South Alternative Route Comparison**

Factor	Western CPL South Alternative	Corresponding Section of CPL South	Difference from CPL South
a	Pipeline construction requirements based on a 100-foot-wide construction corridor and includes a 100-foot long buffer at begin and end points.		
b	Pipeline operation requirements based on a 50-foot-wide corridor in greenfield segments, and a 25-foot-wide corridor for segments co-located with Transco pipelines. Calculation includes a 50-foot long buffer at begin and end points.		
c	Forested land, agricultural land and other land crossed are based on geographic information system (GIS) centerline analysis using United States Geological Survey (USGS) National Land Cover Dataset (NLCD).		
d	Forest land, agricultural land, and other land impacted are based on GIS corridor analysis using USGS NLCD. Since multiple land use types may be present within the corridor, impact acreage for individual land uses will not be representative of distance crossed, which is based on centerline analysis.		
e	Other land based on USGS NLCD and includes land cover types: Barren Land, Developed High Intensity, Developed Low Intensity, Developed Medium Intensity, Developed Open Space, Emergent Herbaceous Wetlands, Herbaceous, Open Water, Shrub Scrub, Woody Wetlands.		
f	Waterbodies identified based on National Hydrography Dataset (NHD).		
g	Major waterbodies identified based on review of aerial photography.		
h	Wetlands identified using the National Wetland Inventory (NWI).		
Key:	CPL = Central Penn Line ROW = right-of-way		

Transco did not select this route due to the following constraints:

- This route crosses 15 state lands, compared to three crossings of state lands for the proposed route;
- Transco engineers flew the length of the Susquehanna River as it borders Lancaster County, Pennsylvania and were unable to find a suitable location to install the pipeline across the river using HDD. A crossing of the Susquehanna River in Lancaster County would be necessary for this alternative to interconnect with the southern endpoint for the Project on the Transco Mainline system;
- The route is in proximity to Harrisburg and Hershey, Pennsylvania, resulting in increased impacts on residential and other developed areas;
- The route is in proximity to the Three Mile Island Nuclear Generating Station in Dauphin County, Pennsylvania; and

*Atlantic Sunrise Project – PA DEP Chapter 105 Permit Application
Transcontinental Gas Pipe Line Company, LLC
Luzerne County
Attachment P – Alternatives Analysis*

- The alternative would require an additional 25,000 hp at proposed Compressor Station 610.

FIGURE 2

7.0 LUZERNE COUNTY SPECIFIC ROUTE ALTERNATIVES

As part of developing the proposed pipeline route for the Project, Transco considered **one-four** minor alternative for the pipeline alignment in Luzerne County. Minor route alternatives have been developed in response to comments received from landowners, stakeholders, or to attempt to avoid or minimize impacts to sensitive resources. Identification and evaluation of minor route alternatives has been on-going since the inception of the Project. Alternatives were developed as they arose during the development phase of the Project; therefore, alternative numbering is not sequential per county. Furthermore, mileposts may have changed and should only be considered reference points as they may not be reflective of the current Project alignment.

7.1 CPL North Alternative 4

CPL North Alternative 4 (proposed route) was developed and adopted to avoid multiple wetland crossings and improve waterbody crossing angles. CPL North Alternative 4 (proposed route) and the corresponding segment of the October 2014 route are shown in Figure P-3. Table P-5 provides a comparison of CPL North Alternative 4 with the corresponding segment of the October 2014 route.

CPL North Alternative 4 (proposed route) is approximately the same length as the October 2014 route but eliminates 150 feet of parallel workspace adjacent to a waterbody and reduces impacts on a PFO wetland complex. Due to the reduction of impacts on wetlands and parallel waterbodies, CPL North Alternative 4 (proposed route) was accepted into the proposed route as discussed in this application.

**Table P-5
 CPL North Alternative 4
 Minor Route Alternatives Comparison**

Factor	CPL North Alternative 4 (proposed route)	Corresponding Section of October 2014 Route	Difference from October 2014 Route
Length of corresponding segment (miles)	2.2	2.2	0.0
Co-location			
Length adjacent to Interstate Pipeline ROW (miles)	0.0	0.0	0.0

Table P-5
CPL North Alternative 4
Minor Route Alternatives Comparison

Factor	CPL North Alternative 4 (proposed route)	Corresponding Section of October 2014 Route	Difference from October 2014 Route
Length adjacent to Midstream Pipeline ROW (miles)	0.0	0.0	0.0
Length adjacent to electric transmission line ROW (miles)	0.0	0.0	0.0
Length adjacent to roadway (miles)	0.0	0.0	0.0
Total length co-located (miles)	0.0	0.0	0.0
ROW Requirements			
Pipeline construction requirements (acres) ^a	26.8	26.7	+0.1
Pipeline operation requirements (acres) ^b	13.4	13.3	+0.1
Federal and State Land			
Federal lands crossed (number / miles)	0 / 0.0	0 / 0.0	0 / 0.0
State lands crossed (number / miles)	0 / 0.0	0 / 0.0	0 / 0.0
Land Use			
Forested land crossed (miles) ^c	1.8	1.3	+0.5
Forested land impacts (construction / operation) (acres) ^d	21.7 / 10.8	15.6 / 7.7	+6.1 / +3.1
Forest interior crossed (miles) ^{c,e}	0.5	0.4	+0.1
Forest interior impacts (construction / operation) (acres) ^{d,e}	6.2 / 3.1	5.0 / 2.5	+1.2 / +0.6
Agricultural land crossed (miles) ^c	0.0	0.2	-0.2
Agricultural land impacted (construction / operation) (acres) ^d	0.0 / 0.0	1.9 / 0.9	-1.9 / -0.9
Other Land Crossed (miles) ^{c,f}	0.4	0.7	-0.3
Other Land Impacted (construction/operation) (acres) ^{d,f}	5.1 / 2.6	9.2 / 4.7	-4.1 / -2.1
Residences within 50 feet of the construction workspace (number) ^g	0	0	0
Landfills, quarries, and other mining operations within 0.25 mile (number)	0	0	0
Waterbodies			
Waterbodies crossed (number) ^h	3	3	0
Major waterbody crossings (number >100 feet) ⁱ	0	0	0
Wetlands			
Total wetland complexes crossed (number) ^j	0	1	-1

Table P-5
CPL North Alternative 4
Minor Route Alternatives Comparison

Factor	CPL North Alternative 4 (proposed route)	Corresponding Section of October 2014 Route	Difference from October 2014 Route
Total wetland crossed (miles) ^l	0.0	0.1	-0.1
Palustrine forested wetland complex impacts (construction / operation) (acres) ^l	0.0 / 0.0	1.4 / 0.7	-1.4 / -0.7
Cultural Resources			
Sites crossed that are eligible or potentially eligible for listing on the National Register of Historic Places (number) ^k	0	0	0
Other Physical Features			
Road crossings (number)	5	3	+2
Railroad crossings (number)	0	0	0
Other Environmental Features			
Steep slopes crossed (30 degrees or greater) (miles) ^l	0.0	0.0	0.0
Side slope construction (miles) ^m	0.0	0.0	0.0

Table P-5
CPL North Alternative 4
Minor Route Alternatives Comparison

Factor	CPL North Alternative 4 (proposed route)	Corresponding Section of October 2014 Route	Difference from October 2014 Route
a	Pipeline construction requirements based on a 100-foot-wide construction corridor and includes a 100-foot long buffer at begin and end points.		
b	Pipeline operation requirements based on a 50-foot-wide corridor in greenfield segments, and a 25-foot-wide corridor for segments co-located with Transco pipelines. Calculation includes a 50-foot long buffer at begin and end points.		
c	Forested land, forest interior, agricultural land and other land crossed are based on geographic information system (GIS) centerline analysis using United States Geological Survey (USGS) National Land Cover Dataset (NLCD).		
d	Forest land, forest interior, agricultural land, and other land impacted are based on GIS corridor analysis using USGS NLCD. Since multiple land use types may be present within the corridor, impact acreage for individual land uses will not be representative of distance crossed, which is based on centerline analysis.		
e	Forest interior determined by assessment of forest cover from USGS NLCD, where forest interior was considered 300 feet from forest breaks and outer forest edge. Interior forest is a sub-type of Forested Land.		
f	Other land based on USGS NLCD and includes land cover types: Barren Land, Developed High Intensity, Developed Low Intensity, Developed Medium Intensity, Developed Open Space, Emergent Herbaceous Wetlands, Herbaceous, Open Water, Shrub Scrub, Woody Wetlands.		
g	Residences identified based on review of aerial photography; in cases where it was not clear whether a structure was a residence or other built feature (e.g., barn, storage facility), the structure was assumed to be a residence.		
h	Waterbodies identified based on National Hydrography Dataset.		
i	Major waterbodies identified based on review of aerial photography.		
j	Wetlands identified using the National Wetland Inventory.		
k	National Register of Historic Places sites were identified using desktop data.		
l	Length determined perpendicular to slope contour.		
m	Length determined parallel with slope contour. Developed using USGS 10-foot contours.		
Key:	CPL = Central Penn Line ROW = right-of-		

*Atlantic Sunrise Project – PA DEP Chapter 105 Permit Application
Transcontinental Gas Pipe Line Company, LLC
Luzerne County
Attachment P – Alternatives Analysis*

FIGURE 3

Revised November 18, 2016

7.2 CPL North Alternative 5

CPL North Alternative 5 was developed in response to landowner comments. CPL North Alternative 5 begins at about MP 24.2, follows the landowner’s western and northern property lines, and ends at about MP 24.6. CPL North Alternative 5 is approximately 0.6 miles in length, slightly longer than the June 2015 proposed route, and intersects a barn along the western property line. This alternative slightly reduces impacts on forested land and agricultural land when compared to the corresponding segment of the June 2015 proposed route. This alternative results in additional impacts on streams and wetlands, based on the desktop evaluation. As a result of FERC’s recommendation in the DEIS, Transco incorporated this alternative into the proposed route.

**Table P-6
 CPL North Alternative 5
 Minor Route Alternatives Comparison**

Factor	CPL North Alternative 5	Corresponding Section of CPL North	Difference from Proposed Route
Length of corresponding segment (miles)	0.6	0.5	+0.1
Co-location			
Length adjacent to Interstate Pipeline ROW (miles)	0.0	0.0	0.0
Length adjacent to Midstream Pipeline ROW (miles)	0.0	0.0	0.0
Length adjacent to electric transmission line ROW (miles)	0.0	0.0	0.0
Length adjacent to roadway (miles)	0.0	0.0	0.0
Total length co-located (miles)	0.0	0.0	0.0
ROW Requirements			
Pipeline construction requirements (acres)^a	7.5	6.3	+1.2
Pipeline operation requirements (acres)^b	3.8	3.1	+0.7
Federal and State Land			
Federal lands crossed (number / miles)	0 / 0.0	0 / 0.0	0 / 0.0
State lands crossed (number / miles)	0 / 0.0	0 / 0.0	0 / 0.0
Land Use			
Forested land crossed (miles)^c	0.3	0.3	0.0
Forested land impacts (construction / operation) (acres)^d	3.9 / 1.9	4.2 / 2.1	-0.3 / -0.2

Table P-6
CPL North Alternative 5
Minor Route Alternatives Comparison

Factor	CPL North Alternative 5	Corresponding Section of CPL North	Difference from Proposed Route
Forest interior crossed (miles)^{c,d}	0.0	0.0	0.0
Forest interior impacts (construction / operation) (acres)^{d,e}	0.0 / 0.0	0.4 / 0.2	-0.4 / -0.2
Agricultural land crossed (miles)^c	0.1	0.2	-0.1
Agricultural land impacted (construction / operation) (acres)^d	0.9 / 0.3	1.8 / 0.9	-0.9 / -0.6
Other Land Crossed (miles)^{c,f}	0.2	0.0	+0.2
Other Land Impacted (construction/operation) (acres)^{d,f}	2.7 / 1.6	0.3 / 0.1	+2.4 / +1.5
Residences within 50 feet of the construction workspace (number)^g	0	0	0
Landfills, quarries, and other mining operations within 0.25 mile (number)	0	0	0
Waterbodies			
Waterbodies crossed (number)^h	1	1	0
Major waterbody crossings (number >100 feet)	0	0	0
Wetlands			
Total wetland complexes crossed (number)	0	0	0
Total wetland crossed (miles)	0.0	0.0	0.0
Palustrine forested wetland complex impacts (construction / operation) (acres)	0.0 / 0.0	0.0 / 0.0	0.0 / 0.0
Cultural Resources			
Sites crossed that are eligible or potentially eligible for listing on the National Register of Historic Places (number)^h	0	0	0

Table P-6
CPL North Alternative 5
Minor Route Alternatives Comparison

Factor	CPL North Alternative 5	Corresponding Section of CPL North	Difference from Proposed Route
Other Physical Features			
Road crossings (number)	1	1	0
Railroad crossings (number)	0	0	0
Other Environmental Features			
Steep slopes crossed (30 degrees or greater) (miles)	0.0	0.0	0.0
Side slope construction (miles)^m	0.0	0.0	0.0
<p>^a Pipeline construction requirements based on a 100-foot-wide construction corridor and includes a 100-foot long buffer at begin and end points.</p> <p>^b Pipeline operation requirements based on a 50-foot-wide corridor in greenfield segments, and a 25-foot-wide corridor for segments co-located with Transco pipelines. Calculation includes a 50-foot long buffer at begin and end points.</p> <p>^c Forested land, forest interior, agricultural land and other land crossed are based on geographic information system (GIS) centerline analysis using United States Geological Survey (USGS) National Land Cover Dataset (NLCD).</p> <p>^d Forest land, forest interior, agricultural land, and other land impacted are based on GIS corridor analysis using USGS NLCD. Since multiple land use types may be present within the corridor, impact acreage for individual land uses will not be representative of distance crossed, which is based on centerline analysis.</p> <p>^e Forest interior determined by assessment of forest cover from USGS NLCD, where forest interior was considered 300 feet from forest breaks and outer forest edge. Interior forest is a sub-type of Forested Land.</p> <p>^f Other land based on USGS NLCD and includes land cover types: Barren Land, Developed High Intensity, Developed Low Intensity, Developed Medium Intensity, Developed Open Space, Emergent Herbaceous Wetlands, Herbaceous, Open Water, Shrub Scrub, Woody Wetlands.</p> <p>^g Residences identified based on review of aerial photography; in cases where it was not clear whether a structure was a residence or other built feature (e.g., barn, storage facility), the structure was assumed to be a residence.</p> <p>^h Waterbodies identified based on National Hydrography Dataset.</p> <p>ⁱ Major waterbodies identified based on review of aerial photography.</p> <p>^j Wetlands identified using the National Wetland Inventory.</p> <p>^k National Register of Historic Places sites were identified using desktop data.</p> <p>^l Length determined perpendicular to slope contour.</p> <p>^m Length determined parallel with slope contour. Developed using USGS 10-foot contours.</p>			
Key:			
CPL = Central Penn Line			
ROW = right-of-way			

*Atlantic Sunrise Project – PA DEP Chapter 105 Permit Application
Transcontinental Gas Pipe Line Company, LLC
Luzerne County
Attachment P – Alternatives Analysis*

FIGURE 4

Revised November 18, 2016

7.3 CPL North Alternative 10A

CPL North Alternative 10A was developed in response to landowner comments.

Table P-7 provides a comparison of CPL North Alternative 10A to the corresponding section of the June 2015 route. CPL North Alternative 10A is approximately 0.6 miles in length, approximately the same length as the corresponding section of the June 2015 proposed route. Both routes cross the same amount of forested land; however, CPL North Alternative 10A crosses more forest interior than the corresponding section of the proposed route. No waterbodies or wetland complexes are crossed by this alternative or the corresponding section of the proposed route based on review of available data. In addition, no residences are within 50 feet of the construction workspace for this alternative or the corresponding section of the proposed route. As a result of FERC’s recommendation in the DEIS, Transco incorporated this alternative into the proposed route.

**Table P-7
 CPL North Alternative 10A
 Minor Route Alternatives Comparison**

Factor	CPL North Alternative 10	Corresponding Section of CPL North	Difference from Proposed Route
Length of corresponding segment (miles)	0.6	0.6	0.0
Co-location			
Length adjacent to Interstate Pipeline ROW (miles)	0.0	0.0	0.0
Length adjacent to Midstream Pipeline ROW (miles)	0.0	0.0	0.0
Length adjacent to electric transmission line ROW (miles)	0.0	0.0	0.0
Length adjacent to roadway (miles)	0.0	0.0	0.0
Total length co-located (miles)	0.0	0.0	0.0
ROW Requirements			
Pipeline construction requirements (acres)^a	6.9	7.0	-0.1
Pipeline operation requirements (acres)^a	3.4	3.4	0.0
Federal and State Land			
Federal lands crossed (number / miles)	0 / 0.0	0 / 0.0	0 / 0.0
State lands crossed (number / miles)	0 / 0.0	0 / 0.0	0 / 0.0

Atlantic Sunrise Project – PA DEP Chapter 105 Permit Application
 Transcontinental Gas Pipe Line Company, LLC
 Luzerne County
 Attachment P – Alternatives Analysis

Table P-7
CPL North Alternative 10A
Minor Route Alternatives Comparison

Factor	CPL North Alternative 10	Corresponding Section of CPL North	Difference from Proposed Route
Land Use			
Forested land crossed (miles) ^c	0.5	0.5	0.0
Forested land impacts (construction / operation) (acres) ^d	6.7 / 3.3	5.8 / 2.9	0.9 / 0.4
Forest interior crossed (miles) ^{c,e}	0.4	0.2	0.2
Forest interior impacts (construction / operation) (acres) ^{d,e}	5.1 / 2.6	2.8 / 1.4	2.3 / 1.2
Agricultural land crossed (miles) ^c	<0.1	0.1	0.1
Agricultural land impacted (construction / operation) (acres) ^f	0.1 / 0.1	0.8 / 0.4	-0.7 / -0.3
Other Land Crossed (miles) ^{c,f}	0.0	0.0	0.0
Other Land Impacted (construction/operation) (acres) ^{d,f}	0.0 / 0.0	0.4 / 0.2	-0.4 / -0.2
Residences within 50 feet of the construction workspace (number) ^g	0	0	0
Landfills, quarries, and other mining operations within 0.25 mile (number)	0	0	0
Waterbodies			
Waterbodies crossed (number) ^h	0	0	0
Major waterbody crossings (number >100 feet) ⁱ	0	0	0
Wetlands			
Total wetland complexes crossed (number) ^j	0	0	0
Total wetland crossed (miles) ^j	0	0	0
Palustrine forested wetland complex impacts (construction / operation) (acres) ^j	0.0 / 0.0	0.0 / 0.0	0.0 / 0.0
Cultural Resources			
Sites crossed that are eligible or potentially eligible for listing on the National Register of Historic Places (number) ^k	0	0	0

Table P-7
CPL North Alternative 10A
Minor Route Alternatives Comparison

Factor	CPL North Alternative 10	Corresponding Section of CPL North	Difference from Proposed Route
Other Physical Features			
Road crossings (number)	0	1	-1
Railroad crossings (number)	0	0	0
Other Environmental Features			
Steep slopes crossed (30 degrees or greater) (miles)	0.0	0.0	0.0
Side slope construction (miles)^m	0.0	0.0	0.0
<p>^a Pipeline construction requirements based on a 100-foot-wide construction corridor and includes a 100-foot-long buffer at begin and end points.</p> <p>^b Pipeline operation requirements based on a 50-foot-wide corridor in greenfield segments, and a 25-foot-wide corridor for segments co-located with Transco pipelines. Calculation includes a 50-foot-long buffer at begin and end points.</p> <p>^c Forested land, forest interior, agricultural land, and other land crossed are based on geographic information system (GIS) centerline analysis using United States Geological Survey (USGS) National Land Cover Dataset (NLCD).</p> <p>^d Forest land, forest interior, agricultural land, and other land impacted are based on GIS corridor analysis using USGS NLCD. Since multiple land use types may be present within the corridor, impact acreage for individual land uses will not be representative of distance crossed, which is based on centerline analysis.</p> <p>^e Forest interior determined by assessment of forest cover from USGS NLCD, where forest interior was considered 300 feet from forest breaks and outer forest edge. Interior forest is a sub-type of Forested Land.</p> <p>^f Other land based on USGS NLCD and includes land cover types: Barren Land, Developed High Intensity, Developed Low Intensity, Developed Medium Intensity, Developed Open Space, Emergent Herbaceous Wetlands, Herbaceous, Open Water, Shrub Scrub, Woody Wetlands.</p> <p>^g Residences identified based on review of aerial photography; in cases where it was not clear whether a structure was a residence or other built feature (e.g., barn, storage facility), the structure was assumed to be a residence.</p> <p>^h Waterbodies identified based on National Hydrography Dataset.</p> <p>ⁱ Major waterbodies identified based on review of aerial photography.</p> <p>^j Wetlands identified using the National Wetland Inventory.</p> <p>^k National Register of Historic Places sites were identified using desktop data.</p> <p>^l Length determined perpendicular to slope contour.</p> <p>^m Length determined parallel with slope contour. Developed using USGS 10-foot contours.</p>			
Key:			
CPL = Central Penn Line			
ROW = right-of-way			

*Atlantic Sunrise Project – PA DEP Chapter 105 Permit Application
Transcontinental Gas Pipe Line Company, LLC
Luzerne County
Attachment P – Alternatives Analysis*

FIGURE 5

Revised November 18, 2016

7.4 CPL North Alternative 12

Transco identified an alternative route on CPL North, CPL North Alternative 12, in Luzerne County based on the results of landowner requests and concerns, cultural resource surveys, and Native American tribal coordination on the previously proposed route between milepost (MP) 26.3 and MP 30.0.

Archaeological Survey

The June 2015 Proposed Route crosses contiguous properties owned by Ms. Geraldine Nesbitt between MP 26.3 and MP 30.0. Transco gained survey permission for the Nesbitt properties in August 2015. Prior to conducting archaeological surveys, Mr. Steve McDougal of the Pennsylvania Historical and Museum Commission (PHMC) informed Transco that the landowner and caretakers of the properties were concerned about the June 2015 Proposed Route. It was expressed to Mr. McDougal and subsequently to Transco representatives that there were numerous stone walls and stone features, including actual or potential stone piles (also referred to as cairns), along the route and throughout the properties.

Archaeological surveys were initiated by Transco on August 5, 2015. Mr. McDougal participated in a site visit on August 5, 2015, and spent the day with the property caretakers (Mr. Frank Taylor and Ms. Heather Taylor) and Transco's survey personnel. In addition to the stone features, Ms. Nesbitt and the Taylors expressed further concerns with the June 2015 Proposed Route, including proximity to the main house, crossing a meadow, and bisecting the properties. PHMC's initial concerns regarding the stone features warranted further field investigation and route discussions with Ms. Nesbitt and the Taylors, which resulted in the proposed CPL North Alternative 12 Route along the eastern property boundary.

Transco completed archeological and aboveground historical structures surveys within a 300-foot-wide corridor along the June 2015 Proposed Route and CPL North Alternative 12 in August 2015. Both routes run generally in a northeastern direction from MP 0.0 of M-0088, terminating at Levitt Hill Road. The Nesbitt properties associated with both routes are primarily covered in mixed forest with moderately

sloped terrain throughout, and the two survey corridors encompass portions of Luzerne and Wyoming counties.

The Phase I archaeological field reconnaissance investigated a total of 2,696 sample loci data collection points on both the June 2015 Proposed and CPL North Alternative 12 routes. The entire 300-foot-wide survey corridor for both routes was visually inspected for archaeological features, both buried and aboveground, while 1,518 shovel tests were excavated. Selection of the CPL North Alternative 12 Route was initially coordinated during the August 2015 surface reconnaissance with the property caretakers to specifically address landowner concerns and minimize impacts to cultural resources, including stone landscape features.

Transco continued coordination with PHMC from August 2015 through April 2016, as well as provided additional information to Native American Indian Tribes that were interested in further details gathered about the Nesbitt properties. Transco specifically coordinated in detail with Mr. Jesse Bergevin of the Oneida Indian Nation and Ms. Susan Bachor of the Delaware Tribe of Indians, as further discussed below under “Native American Coordination.”

Based on survey results, discussions with the landowner and caretakers, and coordination with the PHMC and Native American Indian Tribes, Transco adopted the CPL North Alternative 12 Route. The June 2015 Proposed Route bisected the property and is within the viewshed of the main house, which is currently being recommended as Potentially Eligible to the National Register of Historic Places (NRHP) and a contributing element of the proposed Nesbitt Estate Rural Historic District (see Addendum 2, Volume I: Aboveground Report). There were no archeological resources found during site reconnaissance along the June 2015 Proposed Route. However, approximately 38 landscape features, including rock walls and stone piles, were identified by Transco during the archaeological surveys. In addition, the June 2015 Proposed Route is in proximity and adjacent to a large cairn field, which is of concern to the Oneida Indian Nation and Delaware Tribe of Indians.

The CPL North Alternative 12 Route survey identified four archaeological resources, including three resources recommended as Not Eligible and one Potentially Eligible historic farmstead, which is being avoided by the limits of disturbance (LOD). All four of these resources are detailed in full in Addendum 2, Volume I: Phase I Archaeological Report provided in Attachment 1-1 of this filing. This route crosses approximately 50 stone landscape features, including rock walls and stone piles, of which many are dilapidated/compromised from current and past logging activities. However, in coordination with PHMC, Oneida Indian Nation, and Delaware Tribe of Indians, CPL North Alternative 12 was acceptable and preferred over the June 2015 Proposed Route.

In summary, Transco identified no archaeological resources during the August 2015 surveys along the June 2015 Proposed Route. However, approximately 38 stone landscape features, including rock walls and stone piles, or cairns were identified. Additionally, both Oneida Indian Nation and Delaware Tribe of Indian representatives were of the opinion that the June 2015 Proposed Route would be in proximity and in the viewshed of a large cairn field. Moreover, PHMC's coordination revealed this route to be in the viewshed of the main house, which is Potentially Eligible to the NRHP and a contributing element to the proposed Nesbitt Estate Rural Historic District. Transco subsequently developed and adopted a route alternative (CPL North Alternative 12) to avoid these resources and concerns. Transco completed survey of the alternative route, which revealed approximately 50 stone landscape features, as well as three archaeological resources recommended as Not Eligible, and one Potentially Eligible historic farmstead, avoided by the LOD. The alternative avoids the larger cairn field and its viewshed along the June 2015 Proposed Route, as well as minimizes adverse effects to other aboveground resources.

Native American Coordination

On June 23, 2014 and September 26, 2014, Transco sent 35 initial coordination letters to 25 Native American tribal entities and copies of the letters were provided in Appendix 4N of the March 2015 Certificate Application (Certificate Application).

Subsequent to the transmittal of the coordination letters, Transco contacted each of the tribes to ensure that receipt of the letter, and to address any questions resulting therein. Of the original 25 tribes contacted, the Catawba Indian Tribe, Delaware Tribe of Indians, Oneida Indian Nation, and the Stockbridge Munsee Band of Mohicans requested copies of the Project cultural resources documentation, and each have provided written comments regarding the Project, which included the June 2015 Proposed Route only.

On September 17, 2015, approximately two weeks after completion of the survey on the June 2015 Proposed and CPL North Alternative 12 routes, Transco sent informational coordination letters to the Catawba Indian Tribe, Delaware Tribe of Indians, Oneida Indian Nation, and the Stockbridge Munsee Band of Mohicans. Copies of these letters are provided in the agency correspondence in the Addendum 2 report (see Attachment 1-1). The focus of the letters was to provide further information about the Project's cultural resources survey, specifically as related to rock walls and stone piles. Both the Delaware Tribe of Indians and the Oneida Indian Nation expressed an interest in these resources and requested additional information in a series of e-mails and letters dated October 9 through November 12, 2015 (Delaware Tribe of Indians), and November 3, 2015 (Oneida Indian Nation). Information provided included survey results for both the June 2015 Proposed and CPL North Alternative 12 routes. Both tribal representatives responded that the CPL North Alternative 12 Route would satisfy landowner concerns regarding the June 2015 Route, as well as avoid tribal concerns. However, a site visit was recommended to review the alternative route only.

On November 20, 2015, a site visit was conducted along CPL North Alternative 12 involving the landowner's representative, Transco and its cultural resources consultants, Mr. Steve McDougal (PHMC), and Ms. Susan Bachor, Delaware Tribe Historic Preservation Representative. Mr. Jesse Bergevin, Historic Resources Specialist of the Oneida Nation, was unable to attend, but did remain in close contact with Ms. Bachor. The purpose of the on-site meeting was to examine the alternative route and address concerns of both the Delaware Tribe of Indians and the Oneida

Indian Nation. During the site visit, Ms. Bachor reviewed one area of the proposed Alternative 12 Route, and verbally concluded that there would be no effect to properties of concern to the Delaware Tribe of Indians. Examination of a second area of the route indicated that there would be no viewshed effects to cairn fields located outside the LOD. Although the site visit did not include walking the June 2015 Proposed Route, Ms. Bachor discussed that the June 2015 Proposed Route would be a potential concern due to the route being within the viewshed and immediately adjacent to a large cairn field which may have significance to the Delaware Tribe of Indians. Previous conversations with Mr. Bergevin revealed similar concerns related to the June 15 Proposed Route.

On January 11, 2016, Mr. Bergevin discussed the survey of the Alternative 12 Route in a letter to Transco. He indicated that after a review of materials supplied by Transco (as discussed above), discussions with the Delaware Tribe of Indians and the PHMC, “it is my opinion that the features identified within the LOD... are not related to past Oneida land use.” On January 22, 2016, Ms. Bachor requested supplemental photographic and mapping information to complete her review of the Alternative 12 Route. On “February 1, 2015” (sic 2016), she concluded that, “Our review [of the Alternative 12 Route, as well as Wyoming County as a whole – inserted for clarity] indicates that there are no religious or culturally significant sites within the Area of Potential Effect. We have no objection to the proposed project as planned.”

Other Environmental Resources

In addition to the cultural resource considerations, Transco conducted a comparative analysis of other environmental resource impacts between CPL North Alternative 12 and the June 2015 Propose Route. CPL North Alternative 12 is approximately 0.6 mile longer than the corresponding section of the June 2015 Proposed Route. This alternative route increases impacts on forested land and interior forests. Transco conducted stream and wetland surveys along both routes. CPL North Alternative 12 crosses 0.1 mile of wetlands, and would impact 1.8 acre of wetlands including 1.5 acre of forested wetlands. The June 2015 Proposed Route

crosses 0.3 miles of wetlands, and would impact 3.6 acres of wetlands including 3.1 acres of forested wetlands. CPL North Alternative 12 crosses five streams while the June 2015 Proposed Route crosses eight streams. No residences are located within 50 feet of the construction workspace for either route. Table P-8 provides a comparison of this alternative and the corresponding section of the June 2015 proposed route.

Transco has incorporated this alternative into the proposed route to minimize impacts to archaeological resources identified on the Nesbitt properties. The comparative analysis between the two routes did not identify any significantly greater impacts on other resources along CPL North Alternative 12.

Table P-8
 CPL North Alternative 12
 Minor Route Alternative Comparison

Factor	CPL North Alternative 12	Corresponding Section of June 2015 Proposed Route	Difference from Proposed Route
Length of corresponding segment (miles)	4.2	3.7	+0.6
Co-location			
Length adjacent to Interstate Pipeline ROW (miles)	0.0	0.0	0.0
Length adjacent to Midstream Pipeline ROW (miles)	0.0	0.0	0.0
Length adjacent to electric transmission line ROW (miles)	0.0	0.0	0.0
Length adjacent to roadway (miles)	0.0	0.0	0.0
Total length co-located (miles)	0.0	0.0	0.0
ROW Requirements			
Pipeline construction requirements (acres) ^a	48.7	42.4	+6.3
Pipeline operation requirements (acres) ^a	25.5	22.2	+3.3
Federal and State Land			
Federal lands crossed (number / miles)	0 / 0.0	0 / 0.0	0 / 0.0
State lands crossed (number / miles)	0 / 0.0	0 / 0.0	0 / 0.0
Land Use			
Forested land crossed (miles) ^c	3.7	2.8	+0.9

Table P-8
CPL North Alternative 12
Minor Route Alternative Comparison

Factor	CPL North Alternative 12	Corresponding Section of June 2015 Proposed Route	Difference from Proposed Route
Forested land impacts (construction / operation) (acres) ^d	42.8 / 22.5	32.3 / 17.2	+10.5 / +5.3
Forest interior crossed (miles) ^{c,e}	1.9	1.0	+0.9
Forest interior impacts (construction / operation) (acres) ^{d,e}	22.4 / 11.4	11.4 / 5.9	+11.0 / +5.5
Agricultural land crossed (miles) ^c	0.0	0.0	0.0
Agricultural land impacted (construction / operation) (acres) ^d	0.0 / 0.0	0.0 / 0.0	0.0 / 0.0
Other Land Crossed (miles) ^{c,f}	0.5	0.9	+0.4
Other Land Impacted (construction/operation) (acres) ^{d,f}	5.9 / 3.0	10.1 / 5.0	-4.2 / -2.0
Residences within 50 feet of the construction workspace (number) ^g	0	0	0
Landfills, quarries, and other mining operations within 0.25 mile (number)	0	0	0
Waterbodies			
Waterbodies crossed (number) ^h	5	8	-3
Major waterbody crossings (number >100 feet)	0	0	0
Wetlands			
Total wetland complexes crossed (number)	7	12	-5
Total wetland crossed (miles)	0.1	0.3	-0.2
Palustrine forested wetland complex impacts (construction / operation) (acres)	1.5 / 0.8	3.1 / 1.6	-1.6 / -0.8
Cultural Resources			
Sites crossed that are eligible or potentially eligible for listing on the National Register of Historic Places (number) ^h	0	0	0
Other Physical Features			
Road crossings (number)	5	7	-2
Railroad crossings (number)	0	0	0
Other Environmental Features			
Steep slopes crossed (30 degrees or greater) (miles)	0.0	<0.1	< -0.1
Side slope construction (miles) ^m	0.0	<0.1	< -0.1

Table P-8
CPL North Alternative 12
Minor Route Alternative Comparison

Factor	CPL North Alternative 12	Corresponding Section of June 2015 Proposed Route	Difference from Proposed Route
<p>^a Pipeline construction requirements based on a 100-foot-wide construction corridor and includes a 100-foot-long buffer at begin and end points.</p> <p>^b Pipeline operation requirements based on a 50-foot-wide corridor in greenfield segments, and a 25-foot-wide corridor for segments co-located with Transco pipelines. Calculation includes a 50-foot-long buffer at begin and end points.</p> <p>^c Forested land, forest interior, agricultural land, and other land crossed are based on geographic information system (GIS) centerline analysis using United States Geological Survey (USGS) National Land Cover Dataset (NLCD).</p> <p>^d Forest land, forest interior, agricultural land, and other land impacted are based on GIS corridor analysis using USGS NLCD. Since multiple land use types may be present within the corridor, impact acreage for individual land uses will not be representative of distance crossed, which is based on centerline analysis.</p> <p>^e Forest interior determined by assessment of forest cover from USGS NLCD, where forest interior was considered 300 feet from forest breaks and outer forest edge. Interior forest is a sub-type of Forested Land.</p> <p>^f Other land based on USGS NLCD and includes land cover types: Barren Land, Developed High Intensity, Developed Low Intensity, Developed Medium Intensity, Developed Open Space, Emergent Herbaceous Wetlands, Herbaceous, Open Water, Shrub Scrub, Woody Wetlands.</p> <p>^g Residences identified based on review of aerial photography; in cases where it was not clear whether a structure was a residence or other built feature (e.g., barn, storage facility), the structure was assumed to be a residence.</p> <p>^h Waterbodies identified based on field surveys.</p> <p>ⁱ Major waterbodies identified based on field surveys.</p> <p>^j Wetlands identified using the field surveys.</p> <p>^k National Register of Historic Places sites were identified using desktop data.</p> <p>^l Length determined perpendicular to slope contour.</p> <p>^m Length determined parallel with slope contour. Developed using USGS 10-foot contours.</p>			
<p>Key: CPL = Central Penn Line ROW = right-of-way</p>			

*Atlantic Sunrise Project – PA DEP Chapter 105 Permit Application
Transcontinental Gas Pipe Line Company, LLC
Luzerne County
Attachment P – Alternatives Analysis*

FIGURE 6

Revised November 18, 2016

8.0 ROUTE DEVIATIONS CONSIDERED

A route deviation is a minor adjustment to the proposed route, typically to avoid a specific feature (e.g., topography, sensitive habitat, structures) and/or to accommodate requests by affected landowners. A route deviation differs from a minor route alternative in that a route deviation diverges from the proposed alignment for a short distance in the same general area as the proposed route. Transco developed route deviations in response to landowner and other stakeholder comments and site-specific conditions identified during field surveys and desktop analyses.

~~Transco adopted, as part of the proposed route, 25599 deviations, including 64 deviations to the October 2014 route during the early development of the Project and, 35 deviations to the March 2015 route, and 156 deviations to the June 2015 Route.~~

~~A summary of deviations considered for the Atlantic Sunrise Project is as follows:~~

- ~~• CPLN – 30 42 total = 12 from June 2015 Route, 7 from March 2015 Route; 23 from October 2014 Route~~
- ~~• CPLS – 11468 total = 46 from June 2015 Route, 27 from March 2015 Route; 41 from October 2014 Route~~
- ~~• Unity – 1 from March 2015 Route~~
- ~~• Chapman – 0 from March 2015 Route~~

Table P-6 summarizes the route deviations considered within Luzerne County and the reason for the deviation.

Table P-6
Summary of Route Deviations Accepted into the Proposed Routes for the Atlantic Sunrise Project In Luzerne County

Reference ID	County	Milepost	Length (miles)	Distance from Proposed Centerline (feet)	Reason for Deviation
#M-0026	Luzerne	5.1 - 5.5	0.4	305	Avoid impact on a beaver pond and inundated wetland
#M-0027	Luzerne	6.2 - 6.6	0.4	300	Avoid impact on a beaver pond and inundated wetland
#M-0036	Luzerne	8.5 - 9.0	0.5	401	Avoid impact on suitable northeastern bulrush habitat and a wetland
M#-028/037	Luzerne	19.6 - 21.3	1.7	75	Reduces impact on open water pond and parallel stream
M#-0044	Luzerne	21.8 - 22.0	0.2	480	Avoid two stream crossings and future pond remediation/expansion
#D-0001	Luzerne	25.0 - 25.2	0.2	75	Maintain co-location and minimize tree clearing
#D-0002	Luzerne	25.6 - 25.7	0.1	30	Landowner request
#M-0056	Luzerne	8.4 - 9.0	0.6	591	Landowner request to parallel property line
#M-0060	Luzerne	22.2 – 23.2	1.0	300	Landowner request to parallel property line
#M-0088/ CPL North Alternative 12	Luzerne/ Wyoming	26.3 – 30.0	4.21	5132	Landowner request to be near property boundaries and cultural resource considerations
#M-0141 / CPL North Alternative 10A	Luzerne	24.1 – 24.7	0.70	850	Minor alternative recommended by FERC in the draft EIS
#M-0142/ CPL North Alternative 5	Luzerne	25.6 – 25.9	0.35	590	Minor alternative recommended by FERC in the draft EIS
#M-0150	Luzerne	M-0141 0.3 – M-0141 0.4	0.09	240	Reduce impacts to stream

9.0 WETLAND AND WATERBODY CONSTRUCTION ALTERNATIVES

During design of the Project, Transco attempted to avoid and minimize wetland and waterbody impacts that would result from construction and installation of the Project by reducing the construction right-of-way to 75 feet in most wetlands and by proposing to maintain the right-of-way in accordance with the FERC Wetland and Waterbody Construction and Mitigation Procedures. Transco is also addressing feasibility of trenchless installation measures at major waterbody crossings and in locations where wetlands or waterbodies are located in close proximity to a road crossing. Some of the critical factors taken into consideration to determine if trenchless construction methods would be successful include surface conditions, workspace requirements, subsurface conditions, ground surface elevation, water allocations, inadvertent returns, drilling fluid disposal, risks, constructability, schedule and post-construction accessibility. The following details generally discusses the factors considered when determining the crossing method for certain resources.

Horizontal Directional Drill

The Horizontal Directional Drill (HDD) method allows for trenchless construction across an area by drilling a hole below the conventional pipeline depth and pulling the pipeline through a pre-drilled hole. A number of factors need to be evaluated when considering use of the HDD method including: minimum drill length, typical area of disturbance for set-up of an HDD, and feasibility/risk factors.

Minimum Drill Length

The pipeline radius of curvature for the drill path is proportional to the diameter of the pipeline, which affects how tight the bend in the drill hole can be and, thus, the minimum length of the crossing. The exit and entry angles are relatively flat (8 to 12 degrees from horizontal) to avoid excessive lifting heights to install the pipe and to avoid buckling the pipe at the inflection point in the entry hole. A number of factors determine the minimum drill hole length, with the key factors being:

- Required clearance depth below the obstacle(s) to be crossed;
- Pipeline radius of curvature;
- Adjacent terrain and/or topography;

- Desired entry/exit angles; and
- Required layout for the drilling equipment and pullback string.

Deeper drill holes require longer drill hole lengths to achieve minimum necessary clearance. Similarly, the minimum drill hole length is longer for larger pipe, which has a greater radius of curvature. The depths can also be dictated by the site geology. Transco typically designs the radius of curvature to be 1,200 times the pipe diameter (i.e., a 42-inch-diameter pipeline will have a design radius of curvature of 4,200 feet). The exit and entry points are chosen to be installed in a relatively flat, open area at similar elevations. The HDD will produce a minimum drill hole length of approximately 1,600 feet and profile depth of 75 feet below the entry point (at entry angle of 10 degrees). At entry angles greater than 10 degrees, the minimum depth from the entry point increases, (i.e., 92 feet for a 12 degree entry angle), and hence increases the minimum length (i.e., 1,800 feet for a 12 degree entry angle). The drill hole lengths can vary due to actual site conditions, such as subsurface conditions and topography. The topography of the Project area requires a minimum drill hole length of 1,900 to 2,300 feet. The duration of drilling and construction will vary due to subsurface geologic and hydrologic conditions, layout, and drill hole length. For example, the rate of penetration of the drill bit through hard rock such as granite will be slower than through a softer material such as shale.

Typical HDD Disturbance Areas

HDDs may still require portions of the ROW to be cleared to allow the pipeline pullback section to be assembled (strung) and pulled through the drill hole. Similarly, clearing vegetation may be necessary to provide a line-of-sight to the pipeline ROW for both construction and long-term operation. For example, a 2,100-foot-long drill hole would require a minimum of approximately 5 acres to be cleared and graded to provide adequate and safe workspace at the entry and exit points to accommodate the HDD equipment, drilling mud pits, ancillary support equipment, and a 2,200-foot by 40- or 60-foot work strip for pipe stringing/pullback operations. Temporary workspace areas at the entry and exit workspaces typically measure 200 feet by 250 feet for pipelines with a 24-inch diameter or greater. The pipe stringing workspace must be aligned with the drill hole so that lateral forces are minimized during the pipeline pullback. If a pipeline ROW curves on the approach to an HDD crossing, the pullback section will have an additional impact on areas outside of the ROW where the pullback workspace deviates at an angle to the

construction ROW. Additional heavy equipment would be required to handle the pipe around any curves. There would also be an added risk of damaging the pipe coating if the pipe were to slide off the roller assemblies.

HDD Feasibility & Risk Factors

Site-specific geotechnical factors have a substantial effect on HDD feasibility. Subsurface characteristics must be fully evaluated with on-site borings and sample testing to determine whether the HDD would be deemed technically infeasible. Furthermore, geotechnical factors, including but not limited to rock hardness, rock quality, and borehole stability, have a substantial effect on the duration of construction for an HDD.

HDD risks increase as pipe diameter increases. The risks increase disproportionately for larger diameter pipelines, such as the 42-inch-diameter pipeline proposed for portions of the Project. Drill hole failure (collapse of the drill hole) during pipeline pullback operations is one of the greatest risks to the successful completion of an HDD. A drill hole failure can cause an accidental release of drilling mud. The loss of tooling downhole also poses a substantial risk of failure for large-diameter HDD installations. The risk of lost tooling downhole increases disproportionately with increased hole diameter because of the higher rotary torque required to ream a larger-diameter hole. HDDs are often used to avoid direct impacts on a sensitive environmental resource, such as a wetland, waterbody, or special status species habitat. If the impact of a release is greater than the risk of an open-cut crossing, and the risk of release cannot be reduced to an appropriate level, then an open-cut crossing may be preferable to an HDD crossing.

Methods to reduce HDD failure risks include the following:

- Ensuring that the geologic formation through which the drill is planned is stable and suitable for HDD. For example, a formation containing flowing sand or cobbles and boulders will often result in a borehole collapse or a stuck pipe, and thus is unsuitable for drilling.
- Minimizing the number of pipeline strings required to be welded during the pullback process (where the pipeline is pulled back through the drilled borehole). A single-string pullback is preferred for HDDs because it avoids the need to stop the pullback activity in

order to weld up two or more separate pipe strings. A single string pullback allows for a continuous force to be applied to the pipe during the pullback, and reduces the risk of the pipeline becoming stuck in the borehole (due to the potential for a localized collapse of the borehole around the pipeline).

- Designing the entry and exit point at or near the same elevation. When a significant elevation difference exists between the entry and exit points, a portion of the drilled hole will not be filled with drilling fluid. In rock formations, the risk of drill tool failure increases because the tools may not be adequately cooled and lubricated through the dry section of the hole despite drilling fluid being pumped during operations. In soil formations, the risk of hole collapse is highly elevated, which may lead to ground surface settlement along the HDD alignment, damage to structures, drilling fluid release, or a stuck pipe during pullback operations.

Other Construction Limitations

HDDs for large-diameter pipelines (e.g., 30- to 42-inch) typically require 20,000 to 30,000 gallons of water per day for use in the creation of drilling mud. If surface water is not available at the site, it must be identified and trucked in daily from a municipal water source. Duration from site preparation to pipe tie-in following the HDD can be at least 6 months. Furthermore, the number of HDDs on a project can be limited due to the number of available drilling rigs in the United States. For these and other reasons, Transco limits its use of HDDs to crossings of highly sensitive resources.

Operations Implications

Due to the radius of curvature required to install a large diameter pipeline using the HDD technique, the pipe is usually installed at depths greater than 70 feet below the ground surface, which poses substantial operational implications. If in-line inspection activities indicate that maintenance or repairs are needed for a section of pipe that has been installed using the HDD technique, the pipeline's installation depth would render it inaccessible for repairs. In these cases, the section of pipe would have to be replaced. Replacement would result in additional environmental impacts, usually from having to install a second HDD parallel and adjacent to the original HDD section, assuming adequate clearance (space) is available for a replacement HDD section to be installed. As an industry practice, for long-term operations and maintenance

purposes, an HDD is only utilized where no other construction method is deemed feasible and where adequate space exists for a replacement pipeline in the event the HDD section must be replaced (e.g., at very large river crossings).

Conventional Bore

The conventional bore method for cased or uncased pipeline crossings is typically employed under roads or railroad crossings, but may also be employed at shallow wetland or waterbody crossings. Soil conditions, the length of the flight auger string, and equipment torque generally limit this method to a maximum length of approximately 400 feet. This installation method involves digging a bore pit on each side of the feature to be crossed and typically requires a minimum setback from the feature for worker safety and slope stability purposes. The bore pit and receiving pit vary in size but are usually about 20 feet wide by 60 feet long. This provides the necessary space for the boring machine to insert a pipe joint or pipe string (two or more joints welded together) into the borehole. The bore pit depth generally ranges from 10 to 12 feet but may be greater, depending on topography, to accommodate the minimum of 5 feet of cover over the bored pipeline segment. The depth would be greater for wetlands or waterbodies with an adjacent slope.

Auger boring equipment is usually track-mounted. The track is set to the required line and grade for the proposed bore path and requires a stable bore pit bottom. The bore pit bottom is often stabilized with crushed stone or other material. Minor adjustments can be made by setting the track and keeping it stable, which is critical for a successful bore. As such, keeping groundwater out of the bore pit is important. Once the bore pit is excavated, the boring machine is placed in the bore pit and conventional horizontal auger drilling commences to ream the borehole before the pipe can be installed. The boring machine rides along the track as the bore pipe is advanced (or pushed) into the borehole. The boring machine generates thrust by pushing from either the back wall of the bore pit lined with sheet piles or piles driven behind the track.

A rotating auger cutting bit attached to the lead bore pipe section cuts the soil ahead of the bore pipe as it advances. The rotating auger inside the bore pipe discharges the soil out the rear of the pipe. After the lead bore pipe section has reached its maximum distance, a second auger section is coupled (or pinned) to the first auger section. The second bore pipe section is then

placed over the second auger section and welded to the first bore pipe section. The bore pipe is then advanced again by applying thrust and simultaneously rotating the auger bit inside the bore pipe. This process is repeated until the desired bore length is achieved and the bore pipe extends into the receiving pit. The auger cutting head is then removed, and the remaining soil is removed from within the bore pipe section.

A conventional bore method may be “dry” (no water or drilling fluid used) or “wet” (requiring the use of water or a bentonite-based drilling fluid), depending on soil conditions. No wet conventional bores are proposed for the Project. After the bored pipeline section is installed, additional excavation is necessary to tie the bored pipeline section to the pipeline section conventionally installed by open trench.

While the pipeline industry considers this a dependable method for crossing under elevated road beds, highways, and railroad beds, it is not generally preferred for use in areas with shallow or near-surface groundwater. These crossings require large bore pits adjacent to saturated areas with potentially low soil shear strength, particularly near wetlands. Large bore pits in these areas would require shoring of pit walls and implementation of significant dewatering measures. Crossings of these features also would result in an increased risk of the bore-pit walls slumping and/or borehole misalignment due to track settlement. The duration of construction for bored crossings of wetlands and waterbodies typically ranges from 3 to more than 4 weeks, depending on the crossing length, topography, soil conditions, and the need for blasting in areas of shallow bedrock. A conventional open-cut crossing of wetlands and waterbodies is generally much quicker, taking days rather than weeks, which minimizes the duration of disturbance of the feature. For these reasons, Transco rejected the conventional auger bore method as a preferred construction method for crossing wetlands, forested areas, and waterbodies where conventional trenching construction is feasible.

Summary of Trenchless Installation Methods

As described in Appendix P-2, While a successful HDD or bore **may have** certain environmental benefits, **but** the overall environmental impact can be greater, particularly if the stream is small and can be crossed using dry crossing methods in a short period of time (i.e., 24 to 48 hours). Also, trenchless crossings may not be feasible at all locations because of

suboptimal substrate or geologic conditions. For these reasons, Transco plans to use conventional construction methods to cross the majority of waterbodies along the Atlantic Sunrise Project.

In the absence of environmental or construction concerns requiring the use of other crossing methods, conventional open cut methods are the most efficient construction method for crossing wetlands and waterbodies. Dry-crossing construction techniques will be implemented on the majority of streams crossed by the Project. Dry-crossing techniques minimize impacts to fisheries by reducing the potential for sediment to mix with the existing flow of stream water and by allowing unobstructed stream flow during construction.

Wet Open-Cut

In the absence of environmental or construction concerns requiring the use of other crossing methods, conventional open cut methods are the most efficient construction method for crossing waterbodies. Dry-crossing construction techniques will be implemented on the majority of waterbodies crossed by the Project. Dry-crossing techniques minimize impacts to fisheries by reducing the potential for increases in turbidity and by allowing unobstructed stream flow during construction.

The dry open-cut crossing method is an approved installation method in the DEP Erosion and Sediment Control Best Management Practice (BMP) Manual and has been proposed at locations where engineering has determined the method is appropriate, feasible and safe to construct. However, a dry crossing method is not viable for number of stream crossings due to technical restrictions, site-specific environmental factors, or safety concerns. **Table P-6 provides a list of the streams where a wet open-cut is the preferred installation method.**

Table P-7

Waterbodies Proposed to be Crossed Using Wet Open-Cut Method

Waterbody Name	Milepost	County	Stream Type
UNT to Hess Hollow	2.88	Columbia	Perennial
Hess Hollow	2.9	Columbia	Perennial
Kitchen Creek	7.3	Luzerne	Perennial
UNT to Leonard Creek	25.6	Luzerne	Perennial
UNT to Susquehanna	37.70	Wyoming	Perennial

Waterbody Name	Milepost	County	Stream Type
River			
UNT to Qureg Run	54.3	Lebanon	Perennial
UNT to Frozen Run	104.25	Columbia	Intermittent
UNT to Beaver Run	124.4	Lycoming	Perennial

The Wet Open-Cut method would involve the use of conventional pipeline construction techniques to install the pipeline which will be weighted to ensure negative buoyancy. The stream crossings would be completed in the “wet”; i.e., excavation, backfilling and equipment operation would occur in the flowing stream without any diversion of flow. This is a common installation method in the pipeline industry that is reliable and offers the key benefit of a significantly shorter construction duration in-stream relative to the other installation options. Although, in-stream construction activities result in temporarily higher concentrations of suspended sediment as compared to isolated or dry installations, these peak suspended sediment concentrations and turbidity values decline rapidly following in-stream activities without any residual effects (as in Moyer and Hyer, 2009).

The Wet Open-Cut installation method proposed for the limited number of stream crossings relies on standard construction techniques with minimal safety or installation risks while decreasing the duration of in-stream construction relative to other installation options. The Wet Open-Cut installation would have an estimated duration of 48 hours with an anticipated 12 to 24 hours of direct in-stream work prior to restoration.

These installations would be scheduled around storm events, since the construction duration is limited and can be completed where water flows and depths are slightly greater, where other conventional methods may not be feasible. In addition, ROW impacts are reduced since there is less need for additional temporary workspace.

The Wet Open-Cut installation method provides for the optimal pipeline configuration with respect to operation and maintenance. The proposed pipe would be installed a minimum of five feet below the streambed and is therefore easily accessible for routine maintenance or emergency access during operation. Trenchless methods, such as HDD and conventional bore

installations, do not offer this operational benefit due to the installation depth and would require replacement of the entire pipe segment should an integrity issue arise during operation.

The disturbance of streambed materials during in-stream pipeline construction has the potential to affect water quality and aquatic life through the re-suspension and subsequent deposition of sediment (Reid and Anderson, 1999). Wet Open-Cut pipeline installations (i.e., those which occur without any isolation or diversion of flow away from the work area -- excavation, pipeline installation and backfilling occur within the active, flowing channel) have been shown to have relatively minor, short-term impacts on aquatic communities.

Suspended sediment concentrations and turbidity levels can increase rapidly at the onset of in-stream activities but are not uniformly elevated throughout the construction process. Pipeline construction causes discrete pulses of suspended sediment concentrations associated with specific in-stream activities. These peak suspended sediment concentrations and turbidity values decline rapidly following in-stream activities without any residual effects (as in Moyer and Hyer, 2009). Thus the potential Project-induced water quality effects would be short-lived, lasting only for the duration of in-stream construction activities. This work is timed to coincide with low-flow conditions in the stream, further reducing the potential for increased suspended sediment concentrations. The magnitude and duration of suspended sediment concentration and turbidity level increases depending on a number of site and project-specific factors, including construction activity, sediment settling rates, and stream size, flow, and bed composition. However, construction-related impacts are expected to be minimal compared to those caused by natural runoff events.

In-stream pipeline construction activities and the associated water quality issues can temporarily reduce the abundance and diversity of downstream benthic invertebrate and fish communities due to emigration from affected areas (e.g. high invertebrate drift rates) and reductions in habitat suitability due to sediment deposition. These effects are temporary with full recovery to pre-disturbance conditions generally occurring within 1 to 2 years (Reid and Anderson 1999). These short-term impacts are minor and transitory when compared to the more chronic degradation of stream and river ecosystems caused by sediment loading from urban development and various agricultural, forestry, and mining practices (Waters, 1995). In some

cases, the recovery of benthic invertebrate communities has been enhanced through streambed improvements at the crossing site (Reid and Anderson, 1999).

In some specific cases the Wet Open-Cut installation is the most practical and environmentally preferable option. Transco carefully evaluated all of the streams crossed by the Project; the wet open-cut installation method is only proposed for crossings where it represents the safest, most reliable and environmentally-sound method for pipeline installation. Each crossing will be completed in accordance with the ECP, including the installation of BMPs and immediate bank stabilization to reduce turbidity. Each proposed wet open-cut crossing and its site specific justification is detailed below.

CPL North

- Unnamed Tributary to Hess Hollow WW-T92-15001 at MP 2.88

This unnamed tributary to Hess Hollow is located at Mile Post 2.88 in Columbia County. The wet open-cut method is the preferred crossing method for this location due to the stream being confined within a saturated/flooded wetland. These conditions make it impractical to use a dam and pump or flume for this tributary. The saturated and unconsolidated soils will allow a high infiltration rate of water into the trench which makes pumping or fluming water infeasible or impractical.

- Hess Hollow (WW-T02-15010) at Mile Post 2.9

Hess Hollow is located at Mile Post 2.9 in Columbia County. This waterbody is part of a larger saturated/flooded wetland complex. The saturated wetlands surrounding Hess Hollow Creek present safety concerns and limit the effectiveness of a dry open cut installation. Soils within the wetland and waterbody complex are saturated and unconsolidated allowing a high infiltration rate of water into the ditch. These conditions make the diversion of stream flow using pumps or flumes impractical and dewatering of the workspace infeasible. Moreover, if the dry open cut were used at this location, additional workspace would be required within wetlands located adjacent to the stream to set up and store equipment to perform dam and pump or flume crossing method. The dry open cut will require more time for set up prior to excavating the pipeline trench. The

duration of wetland and stream impacts for a dry open cut would extend over a significantly greater duration (approximately 8-10 days).

Wet open cut has been identified as the preferred method because dry open cut is infeasible due to saturated and unconsolidated soils. And the wet open cut will reduce the construction duration within the resource (approximately 24-48 hours) and will require a reduced limit of disturbance for the construction activity compared to the trenchless and dry open-cut methods, thereby reducing overall impacts to regulated features.

- Kitchen Creek (WW-T02-15018) at Mile Post 7.3

Kitchen Creek is located at CPLN Milepost 7.3 in Luzerne County, Pennsylvania. This waterbody occurs within a “V-bottom” valley with steep banks (approximately 50% slope). High amounts of solid rock are present in the bottom of this creek.

Transco determined that a dry open cut installation was not practical at this location due to topographic conditions and the associated safety concerns. The steep banks at the crossing location do not allow for additional workspace necessary to accommodate the equipment and staging areas required for a dry open cut installation. The banks of the creek are too steep to safely mobilize and place the pre-fabricated pipe section required for a dry open cut. In addition, the installation of cofferdams necessary for a dry open cut crossing are not feasible due to high flow conditions in this section of Kitchen Creek.

The HDD method was also considered but was deemed infeasible due to the topography, poor access to the site and rocky conditions at the crossing. Additional impact to riparian buffers and a greater number of trees would need to be cleared in the adjacent Ricketts Glen State Park to facilitate an HDD crossing setup, which will cause a greater impact than wet open cut method.

- Unnamed tributary to Leonard Creek (WW-T17-18001) at Mile Post 25.6

This unnamed tributary to Leonard Creek is located at Mile Post 25.6 in Luzerne County, Pennsylvania. This tributary crossing is located within an area characterized by a large

amount of rock and boulders on the stream bed, which make the dry open cut methods unfeasible because an effective seal for the cofferdam on the stream bottom cannot be achieved. Moreover, the banks of the tributary are steep and rocky which makes method dry crossing impractical as it will be difficult to seal the bottom of the coffer dam in this condition to prevent water from entering the workspace. The availability of additional work space for storage and equipment for dry open cut method is minimal as this tributary is confined between a major roadway (State Highway 309) on west side and a very steep bank on east side. The HDD method was determined to be unfeasible at this crossing due to the presence of large rocks and boulders.

A wet open cut is proposed as the preferred method due reduction in the construction duration (approximately 24-48 hours) and required activities compared to the trenchless and dry open-cut methods (approximately 8-10 days), thereby reducing impacts to regulated features.

- Unnamed Tributary to the Susquehanna River (WW-T24-19001) at Mile Post 37.70
This unnamed tributary to the Susquehanna River is located at Mile Post 37.70 in Wyoming County. The wet open-cut method is the preferred crossing method for this location due to the stream being confined within a saturated/flooded wetland. These conditions make it impractical to use a dam and pump or flume for this tributary. The saturated and unconsolidated soils will allow a high infiltration rate of water into the trench which makes pumping or fluming water infeasible or impractical.

CPL South

- Unnamed Tributary to Qureg Run (WW-T40-6004) at Mile Post 54.3
This unnamed tributary to Qureg Run is located at Mile Post 54.3 in Lebanon County. The wet open-cut preferred method is the preferred crossing method due to the stream being confined within a saturated/flooded wetland. These conditions make it impractical to use a dam and pump or flume for this tributary. The saturated and unconsolidated soils will allow a high infiltration rate of water into the trench which makes pumping or fluming water infeasible or impractical. Additionally, due to another pipeline at close proximity to the stream, a wet open-cut will expedite construction and minimize impact.

- Unnamed Tributary to Frozen Run (WW-T90-13002) at Mile Post 104.25

This unnamed tributary to Frozen Run is located at Mile Post 104.25 in Columbia County. The wet open-cut preferred method is the preferred crossing method due to the stream being confined within a saturated/flooded wetland. These conditions make it impractical to use a dam and pump or flume for this tributary. The saturated and unconsolidated soils will allow a high infiltration rate of water into the trench which makes pumping or fluming water infeasible or impractical

Unity Loop

- Unnamed tributary to Beaver Run (WW-T01-22008B) at Mile Post 124.4

Unnamed tributary to Beaver Run is located at Unity Loop Milepost 124.4 in Lycoming County, Pennsylvania. This tributary is confined within a large saturated/flooded wetland complex with no defined banks. Therefore, it is impractical to dam and pump or flume this tributary. Difficulty is associated with saturated and unconsolidated soils that will allow a high infiltration rate of water into the trench which makes pumping or fluming water infeasible or impractical. Moreover, additional workspaces will be required within wetlands to set up and store equipment to perform dam and pump or flume crossing methods. Additionally, the dry open cut will require a longer time for construction to set up the dam and pump or flume prior to excavating pipeline ditch and therefore wetland and stream will have impact to longer period of time (approximately 8-10 days) during construction.

Wet open cut is determined to be the preferred method due to reduction of impacts and the construction duration (approximately 24-48 hours) and required activities compared to the trenchless and dry open-cut methods, thereby reducing impacts to regulated features.