3800-PM-BCW0405b Rev. 3/2019
Application

pennsylvania
DEPARTMENT OF ENVIRONMENTAL
PROTECTION

COMMONWEALTH OF PENNSYLVANIA DEPARTMENT OF ENVIRONMENTAL PROTECTION BUREAU OF CLEAN WATER

OFFICIAL USE ONLY
NPDES Permit ID #
Date Received
NOI Complete Date
Issue Date
Effective Date
Expiration Date

NOTICE OF INTENT FOR COVERAGE UNDER THE GENERAL (PAG-02) NPDES PERMIT OR

APPLICATION FOR AN INDIVIDUAL NPDES PERMIT FOR STORMWATER DISCHARGES ASSOCIATED WITH CONSTRUCTION ACTIVITIES

PLEASE READ THE PERMIT SUMMARY SHEET AND INSTRUCTIONS PROVIDED IN THIS PERMIT APPLICATION PACKAGE BEFORE COMPLETING THIS FORM. COMPLETE THE ATTACHED CHECKLIST AND APPROPRIATE WORKSHEETS.

PLEASE PRINT OR TYPE INFORMATION IN BLACK OR BLUE INK.

PERMIT TYPE		GENERAL		⊠ INDIVIDUAI	L	1.171-1.1-1.1-1.1-1.1-1.1-1.1-1.1-1.1-1.	
APPLICATION TYPE	NEW 🛛 R	ENEWAL	\boxtimes	MAJOR AMENDMENT	☐ MINOR AI	MENDMENT	☐ PHASED
		SECTION	A.	APPLICANT INFORMAT	ION		
professional associations at	nd business or	statutory trus	sts th	ability companies, partnershi at were not created or forme sylvania Department of State	ed under the la		
Applicant/Organization	Name				Phone	610-332-	3300
New Demi Road, LLC					FAX		
Mailing Address		Cit	y		State	ZIP + 4	
559 Main Street, Suite	300	Be	thlel	nem	PA	-1801858	62
Supplemental Mailing A	address (if need	led)					
Employer ID (EIN) 8	4-3872726						
Email Address L	Pektor@ashley	/developmen	t.coi	n			
Contact Name Louis P	. Pektor, III			Contact Title Presid	lent		
Contact Phone 610-33	2-3300			Contact Email Addre	ess LPektor@	ashleydevelop	ment.com
Co-Applicant/Organizat	ion Name				Phone		
					FAX		
Mailing Address		Cit	у		State	ZIP + 4	
Supplemental Mailing A	ddress (if need	led)					
Employer ID (EIN)							
Email Address							
Contact Name				Contact Title			
Contact Phone				Contact Email Addre	ess		

	SECTION B. PROJECT INFORMATION							
1.	Project Name: 303 Demi Road Planned Industrial Park							
2.	Total Project Site (Acres): 86.0	3. Total Disturbed Area	(Acres): <u>50</u>).9				
4.	Project Description: Construction of a 420,000 sf planned in 97 spaces, rear truck court for 42 loading dock spaces, 72 detention basins discharging via level spreaders over a 250 volume. The site is being served with public water and on-lo	2 trailer spaces and direct '-300' wide riparian buffer	access to	Demi Road.	Three dry extended			
5.	Project Location or Physical Address:		0.1	710 . 4				
	Address City		State	ZIP + 4				
	303 Demi Road Mount Bethe	el	PA	18343				
	Supplemental Address (If needed)							
6.	Project County Project Municipality		City	Boro	Twp			
	Northampton Upper Mount Bethel							
	Northampton Portland			\boxtimes				
7.	Type of Ownership:							
	☐ County Government ☐ Municipa	ality (local)		School [District			
	Federal Facility (U.S. Government) Non-Gov	vernment		State G	overnment			
	☐ Mixed Ownership (e.g. Public/Private)							
8.	Project Latitude: 40 °/ 54 '/ 46.6 "	Project Longitude:	-75	°/ 6	<u>'/ 4.7 "</u>			
	8a. Collection Method: 🛛 EMAP 🔲 HGIS	GISDR ITPMP	☐ GPS	☐ WAA	S 🗌 LORAN			
	8b. Horizontal reference datum (or projection datum) emplorand HGIS (PNDI) has a known datum of NAD83)	oyed in the collection meth	nod. (EMAF AD83	has a knov	vn datum of WGS84 /GS84 (GEO84)			
Ent	er the date of collection if the latitude and longitude coordinate	es were derived from GPS,	, WAAS or L	ORAN.				
	mm dd yyyy	<u></u>						
9.	U.S.G.S. Quad Map Name(s) Portland, PA							
10.	Primary NAICS Code (check one):							
	☐ 236115 New Single-Family Housing Construction (except							
	236116 New Multifamily Housing Construction (except Fo	or-Sale Builders)						
	236117 New Housing For-Sale Builders							
	□ 236210 Industrial Building Construction							
	☐ 236220 Commercial and Institutional Building Construction☐ 237110 Water and Sewer Line and Related Construction	on						
	☐ 237120 Oil and Gas Pipeline and Related Structures Con	etruction						
	237130 Power and Communication Line and Related Structures							
	☐ 237310 Highway, Street, and Bridge Construction							
	237990 Other Heavy and Civil Engineering Construction							
	☐ Other Primary NAICS Code (specify)							
11.	Additional NAICS Code(s) (list all additional codes that apply	from the list above):						
	SECTION C	. SITE ANALYSIS		ar ve				
1.	Existing and Previous Uses of the Project Site:							
	-	orest/Woodland <u>84</u> %	□в	arren	%			
Uses:								

3800-PM-BCW0405b Rev. 3/2019 Application

1b. Historical Land	☑ Agriculture 16 %	⊠ Forest/Wo	odland <u>84</u> 9	% [Barren	_%
Uses:	☐ Urban %	Brownfield	i %		Other	%
2. Potential Toxic or Hazard	ous Pollutants: 🗵 N/A					
Pollutant	Concentration w/Units	Source		Sample Type		of Samples
3. Fill Material		0 0	<u> </u>			L - C
Will the applicant need to imp fill will be imported or exporte	d, Form FP-001 (Document	# 258-2182-773) must be u	sed to certify o	rigin of the fill n	naterial.
Check the appropriate box						
fill imported to the si	cant will, in most situations te meets the department's d s) responsibility and provide	efinition of clean	fill. The pl	an designer mi	ust include a no	ote on the drawings to
☐ Export fill – the Appl determine that any f	cant is responsible for perfo Il exported from the site will	rming environme be certified as cl	ental due di lean fill.	ligence at the t	ime this applica	ation was submitted to
☑ Balance all cuts and	fills with the amount of rock	and soil availab	le on the sit	е.		
4. Estimated Timetable for	Phased Projects (Complete	for phased proje	cts only)			
Phase No. or Name	Proposed Type of Activity		otal Area	Disturbed Area	Start Date	End Date
	,					
	<u> </u>					
-	Discharges (Check all that a		b th	o matantial to a	liachargo to (in	aluding EV watlands)
	Commonwealth to which the ls, CSOs, private storm sew		es or nas tr	ie potentiai to c	ilscriarge to (iii	cluding EV Wellands)
Name of W		signated Use of	Water		Existing Use	e of Water
UNT to the Delawa UNT to Del. River,		, MF			√/A √/A	
			·			
Overflow System	wer Municipal Separ to Sewer (MS4) to ject project discharge	which the	Private which discharge		oject (ir di	on Surface Water: ncluding off-site scharges): ee below *
5b. Does the site disch	arge to waters classified as eport? ☐ Yes ☒ No	impaired accordi	ing to Categ	ory 4 of PA Int	egrated Water	Quality Monitoring
	nd cause of impairment:					
5c. Does the site disci Assessment Repor	narge to waters with a TMI ??	OL according to	Category 5	of the PA Int	egrated Water	Quality Monitoring &
If yes, list source a	nd cause of impairment TMD	DL addresses: _				

* DEMI ROAD STORM SEWER TO UNT TO DELAWAGE RIVER OWNED AND MAINTAINED BY UPPER MOUNTBETHER TOWNSHIP THROUGH INTER-MUNICIPAL AGREEMENT WITH PORTLAND BOROUGH.

				& SEDIMENTATION (E&S) AND TORMWATER MANAGEMENT (
					plete, separate Section D for each additional
1.	E&9	S Pla	n - The E&S Plan must satisfy at leas	st one of subparagraph A or B below.	
	A.	\boxtimes	E&S plan is designed using BMF (Technical Guidance #363-2134-00		Sedimentation Pollution Control Manual (ESPC)
	OR				
	B.		E&S plan is designed using an alter	rnative BMP or design standard	
			seep collars, baffles, skimmers, an	d dewatering facilities. Filter bag and	on entrance, two sedimentation basins with anti- stone & concrete block inlet protection, compost ence, silt soxx diversion berms, and E&S control
2.	PC:	SM P	an		
Th	e PC	SM P	lan must satisfy either subparagraph	A, or B <u>or</u> C below.	
	A.				CSM Plan, in its entirety, is consistent with all ed Act 167 Stormwater Management Plan.
		nplet essa	•	able approved Act 167 Stormwater	Management Plans. (use additional sheets if
		ACT	167 Plan Name	Date Adopted	Consistency Letter Included
		Mar	ins-Jacoby Creek	4/9/07	_ Consistency Letter Pending ⊠
		cons the	sistent with the standard design criter	ria from the 25 Pa. Code Chapter 102	or later and the Act 167 plan is without variance .8(g)(2) and (3) then utilizing worksheets 1-5 and recommended, otherwise check the applicable
	OR				
	B.		The PCSM Plan meets the standard	design criteria from the 25 Pa. Code	Chapter 102.8(g)(2) and (3).
	OR				
	C.	\boxtimes	Chapter 102.8(g)(2) and (3). Demoi Code Chapter 102.8(g)(2) and (3). a allowed in 102.8(g)(2)(iv) and 102.	nstrate how this standard will be eithe nd will maintain and protect existing v .8(g)(3)(iii). Alternative design stand	sing approaches other than those in 25 Pa. Code or more protective than what is required in 25 Pa. water quality and existing and designated uses as dard selected due to use of voluntary forested element with PADEP (see PCSM narraive for

3. Summary Table for Supporting Calculation and Measurement Data								
□ Not Applicable in accordance with 102.8(g)(2)(iv)- provide supporting calculations and documentation in the Narrative. If checked, proceed to Peak Rate Analysis (provide supporting details to include a summary, calculations, and a statement and demonstration of attainment in the Narrative- Reference the Instructions for a General (PAG-02) OR Individual NPDES Permit for stormwater discharges associated with construction activities Section D)								
calculations and documentation in the Narrative summary, calculations and a statement and d	Not Applicable PCSM Plan satisfies an Act 167 Plan approved on or after January 2005, in its entirety- provide supporting calculations and documentation in the Narrative. If checked proceed to Section D.4 (provide supporting details to include a summary, calculations and a statement and demonstration of attainment in the Narrative- Reference the Instructions for a General (PAG-02) OR Individual NPDES Permit for stormwater discharges associated with construction activities Section D)							
Please reference the stormwater methodology used 3,4, and 5 and be accompanied by supporting calcuses.	d (Numbers generated lations in the Narrative	in the table below should telephone	pe consistent with Worksheets					
	Pre-construction	Post Construction	Net Change					
Design storm frequency <u>2-year/24-hour</u> Rainfall amount <u>3.31</u> inches								
Impervious area (acres)	1 0.60	2 15.72	3 15.12					
Volume of stormwater runoff ☐ acre-feet or ☒ cubic feet (check appropriate box)	4 186,768	5 305,835	6 119,067					
Volume of stormwater runoff ☐ acre-feet or ☒ cubic feet (check appropriate box)		7 228,651	8 -109,584					
Peak Rate Analysis: Complete Boxes 9-20 (Numbers narrative)	s generated in table s	hould be accompanied by	supporting calculations in the					
☐ Exempt in accordance 102.8(g)(3)(ii), Complete Boxe	es 9-20							
☑ Not Applicable in accordance with 102.8(g)(3)(iii)								
{If any of the above is checked, provide supporting calculations	ulations and document	ation in the Narrative}						
Stormwater peak discharge rate for the 2-year/24-hour storm (cubic feet per second (cfs))	9 5.47	10 1.47	11 -4.00					
Stormwater peak discharge rate for 10-year/24-hour storm (cfs)	12 28.61	13 18.59	14 -10.02					
Stormwater peak discharge rate for 50-year/24-hour storm (cfs)	15 79.74	16 77.38	17 -2.36					
Stormwater peak discharge rate for the 100-year/24-hour storm	18 111.86	19 109.27	20 -2.59					
Pre-construction impervious area: The total acres of impervious area on the project site before construction activities begin, based on land use for five years preceding the planned project.								

- Box 2. Post construction impervious area: The total acres of impervious area on the project site after construction activities have been completed.
- Box 3. Net change of impervious area: The change in the impervious area (acres) listed in Box 1 and Box 2. Zero or negative values are acceptable. (Box 2- Box 1)
- **Box 4. Pre-construction stormwater runoff volume**: The amount of stormwater runoff volume from the project site that would result from the design storm occurrence before construction activities begin based on land use for five years preceding the project.
- Box 5. Post construction stormwater runoff volume: The amount of stormwater runoff volume from the project site that would result from the design storm occurrence after construction activities have finished assuming that no non-structural/structural BMP(s) have been installed.
- Box 6. Net change in stormwater volume: The change in stormwater runoff volumes listed in Box 4 and Box 5. (Box 5 Box 4)
- Box 7. Post construction stormwater runoff volume reduction: The amount of stormwater runoff volume reduction that would result from the planned non-structural/structural BMP(s) installation. (Total non-structural volume credit (from worksheet 3) + Total Structural volume (from worksheet 5)))

Box 8. Net change in stormwater runoff volume with planned BMPs: The change in stormwater runoff volume and volume reduction listed in Box 6 and Box 7. (Box 6 – Box 7)

Figures contained in the "Summary table for supporting calculation and measurement data" should be consistent with those on Worksheets 3, 4, and 5, when applicants have utilized the Stormwater Best Management Practices (BMP) Manual to meet design standards. Below is a depiction of which worksheet(s) corresponds (i.e. WKST 4) to each Box and where on the worksheet to find the information (i.e. 2-Year Volume Increase).

	Pre-construction	Post Construction	Net Change
Design storm frequency 2-year/24-hour storm Rainfall amount WKST 4 "2-Year Rainfall" inches			
Impervious area (acres)	1 WKST 4 Existing Condition: Impervious cover type	2 WKST 4 Developed Condition: Impervious cover type	3 Box 2 - Box 1
Volume of stormwater runoff ⊠ acre-feet or □ cubic feet (check appropriate box)	4 WKST 4 Existing Condition: Total Runoff Volume	5 WKST 4 Developed Condition: Total Runoff Volume	6 WKST 4 2-Year Volume Increase
Volume of stormwater runoff ⊠ acre-feet or ☐ cubic feet (check appropriate box)		7 WKST 3 Total non-structural volume credit + WKST 5 Total structural volume	8 WKST 5 Difference

- **Box 9. Pre-construction stormwater discharge rate**: The stormwater runoff discharge rate for the 2-year/24-hour storm as determined by the land use for the past five years.
- **Box 10.** Post construction stormwater discharge rate: The stormwater runoff discharge rate for the 2-year/24-hour storm after all planned stormwater BMPs are installed.
- **Box 11. Net change stormwater discharge rate**: The change in stormwater runoff discharge rates listed in Box 9 and Box 10. (Box 10 Box 9)
- **Box 12. Pre-construction stormwater discharge rate**: The stormwater runoff discharge rate for the 10-year/24-hour storm as determined by the land use for the past five years.
- Box 13. Post construction stormwater discharge rate: The stormwater runoff discharge rate for the 10-year/24-hour storm after all planned stormwater BMPs are installed.
- Box 14. Net change stormwater discharge rate: The change in stormwater runoff discharge rates listed in Box 12 and Box 13. (Box 13 Box 12)
- **Box 15. Pre-construction stormwater discharge rate**: The stormwater runoff discharge rate for the 50-year/24-hour storm as determined by the land use for the past five years.
- **Box 16.** Post construction stormwater discharge rate: The stormwater runoff discharge rate for the 50-year/24-hour storm after all planned stormwater BMPs are installed.
- Box 17. Net change stormwater discharge rate: The change in stormwater runoff discharge rates listed in Box 15 and Box 16. (Box 16 Box 15)
- **Box 18. Pre-construction stormwater discharge rate:** The stormwater runoff discharge rate for the 100-year/24-hour storm as determined by the land use for the past five years.
- **Box 19.** Post construction stormwater discharge rate: The stormwater runoff discharge rate for the 100-year/24-hour storm after all planned stormwater BMPs are installed.
- Box 20. Net change stormwater discharge rate: The change in stormwater runoff discharge rates listed in Box 18 and Box 19. (Box 19 Box 18)

4.	Summary Description of Post Construction Stormw	water BMPs (consistent with the	e design or applicable works	heets)
	Key: RC = Rate Control	VC = Volume Control	WQ = Water	Quality
•	In the lists below, check the BMPs identified in the may be checked for a BMP. A BMP may have more than one volume/acres listed. For example, a Ravolume control and water quality, that differs from Plan is not listed below, it must be described in the	ore than one function (rate, vo ain garden/Bio-retention BMP n the volume treated and acres	lume, water quality), therefol may have a volume treated treated for rate control. If a	re, there may be more and acres treated for any BMP in the PCSM
	For Rate Control provide the volume of stormwater	r treated and acres treated for	the 100-year/24-hour storm	event
	For Volume Control and Water Quality provide th event		ed and acres treated for the	
	ВМР	Function(s)	Volume of stormwater treated	Acres treated
	Wet ponds	□ VC □ RC □ WQ		
	Constructed wetlands	□ VC □ RC □ WQ		
	Retention basins	□ VC □ RC □ WQ		
	Detention basin	□ VC □ RC □ WQ		
	Underground detention	□ VC □ RC □ WQ		
\boxtimes	Dry Extended detention basin	□ VC ☒ RC ☒ WQ	474,325 cf (RC) 153,941 cf (WQ)	20.69
	Sediment fore bay	□ VC □ RC □ WQ		
	Infiltration trench	□ VC □ RC □ WQ		
	Infiltration Berm/Retentive Grading	□ VC □ RC □ WQ		
	Subsurface Infiltration bed	□ VC □ RC □ WQ		
	Infiltration basin	□ VC □ RC □ WQ		
	Pervious pavement	□ VC □ RC □ WQ		
	Dry well/Seepage pit	UVC RC WQ		
	Bio-infiltration areas	□ VC □ RC □ WQ		
	Rain gardens/Bio-retention	□ VC □ RC □ WQ		
	Vegetated swales	□ VC □ RC □ WQ		
	Constructed filters	☐ VC ☐ RC ☐ WQ		
	Protect Sensitive & Special Value Features	□ VC □ RC □ WQ		
	Protect/Convert/Establish Riparian buffers	□ VC □ RC □ WQ		
\boxtimes	Restoration: Buffers/ Landscape/Floodplain	☑ VC	16,453 cf	9.93
	Disconnection from storm sewers	□ VC □ RC □ WQ		
	Rooftop disconnection	UVC RC WQ		
	Vegetated roofs	□ VC □ RC □ WQ		
	Runoff capture/Reuse	□ VC □ RC □ WQ		
	Oil/grit separators	☐ WQ		
Ø	Water quality inserts/inlets	⊠ WQ	96,126 cf	16.19
	Street sweeping	wq		
Ø	Other <u>Level Spreaders</u>	□ VC □ RC ☑ WQ	n/a	28.35
	Other voluntary forested riparian buffer	☑ VC ☐ RC ☑ WQ	207,936 cf	28.35
<u>X</u>	Other Protect Ex. Trees		2,726 cf 1,536 cf	1.50 31 dec. & 135 ev.
<u>X</u>	Other Revegetate/Reforest		1,000 01	trees
	The second secon			

5.	Of	f Site Discharge Analysis
	Do	bes the project propose any off-site discharges to areas other than surface waters?
	ap nu	yes, the applicant must have appropriate easement that provides the legal authority for this off-site discharge. In addition, plicant must provide a demonstration in both the E&S and PCSM plans that the discharge will not cause erosion, damage, or isance to off-site properties.
	where properties and term per the by aggregation may be the properties and properties are the properties and properties are the properties and properties are the pro	nunnamed tributary to the Delaware River is located partially within and along the project's westerly property boundary. In areas here the tributary is not located on the subject property, wetland areas connected directly to the tributary extend onto the subject operty. A minimum 150' wide existing undisturbed wooded buffer (250'-300' for bog turtle) is being provided for this project for entire length of the westerly property boundary. Discharges from the three dry extended detention basins onsite utilize three yet property and discharge runoff for the project over a 760LF width to mimick existing pre-development runoff flow itterns. The project rate and volume discharges as a whole are controlled to less than pre-development levels for all storms up to discluding the 2-year runoff event. In addition, the project utilizes a portion of the adjacent Ultra-Poly property to the East as a mporary haul road/construction access and possible future sanitary sewer easement. Ultra-Poly also has a current NPDES remit (#PAC480057). Runoff generated the proposed haul road extension drains primarily to existing storm sewer located along are same UNT that flows thru the subject property. Demi Road and the existing storm sewer contained therein is being maintained upper Mount Bethel Township from the structures located in Demi Road to their terminus at the UNT through a maintenance prement with Portland Road. Regarding the future sanitary sewer easement, the associated runoff drains to another section of form sewer in the Demi Road cul-de-sac which outlets into the same UNT previously mentioned. Once construction is complete to both the offsite temporary access road road and sanitary easement areas, the disturbed areas will be reseeded and restored as eadow. Therefore, there will be no future/post-development increase in stormwater rate of runoff or volume as a result of this opect. The runoff that is generated from the subject site and discharged into this same UNT as the Ultra-Poly runoff considers to Ultra-Poly POI #1 as t
6.		ential Pollution Causing Materials ntify naturally occurring geologic formations or soil conditions that may have the potential to cause pollution during earth
	dist	surbance activities and include BMPs to avoid or minimize potential pollution and its impacts from the formation.
		ere are no naturally occurring geologic formations or soil conditions that have the potential to cause pollution during earth curbance activities.
7.	Rip	arian Buffers
	A.	Does the project discharge to a river, stream, creek, lake, pond or reservoir with a designated use of high quality or exceptional value? If so, is earth disturbance occurring within 150 feet of the river, stream, creek, lake, pond or reservoir? X Yes No
		If yes, go to B. If no, continue to Section 8.
	B.	Will you be protecting, converting, or establishing a 150 foot riparian buffer throughout the project area?
*		Protect ⊠ Yes ☐ No Convert ☐ Yes ☒ No Establish ☐ Yes ☒ No
		If No to all above, the application must contain a demonstration of riparian buffer or riparian forest buffer equivalency. (Continue to C) ** **VOLUNTBRY RIPARIAN FOREST BUFFER BEING UTILIZE WHICH WILL PREVENT THERMALINE PER 103.14 (C) What BMPs will you be using that will be functionally equivalent to that of either a riparian buffer or a riparian forest buffer
	C.	whatever is applicable to the project? Please attach an equivalency demonstration.
		An equivalency demonstration must be completed, including worksheets 12-15 and a narrative that shows that the alternative BMPs implemented will be functionally equivalent to that of either a riparian buffer or a riparian forest buffer, whichever is applicable to the project according to 102.14(a)(1) and (2).
	D.	Will the project propose any earth disturbance within 100 feet of a surface water? XYes ☐ No
		If yes, the applicant shall provide an offset riparian forest buffer at a ratio of one to one for the disturbed area.
3	*	PROPOSED STORM OUTFALL LOCATED AT NW CORNER OF SITE WAS PREVIOUSLY APPROVED AS PART OF ORIGINAL UPDER PERMIT AND QUALIFIES AS AN ALLOWABLE ACTIVITY PER 102.14 (f)(2) (I.E., CONSTRUCTION OR RACEMENT OF ROADS, STORM DRAINAGE, UTILITIES, ETC.).

8. Thermal Impacts Analysis

Explain how thermal impacts associated with this project were avoided, minimized, or mitigated.

1. Storm Sewerage Geo-Thermal Transfer

Surface runoff from street impervious surfaces and unshaded vegetated areas, having elevated water temperatures, will be provided with some thermal mitigation via the underground storm sewerage conveyance system. The underground storm sewerage system will naturally maintain the cooler geothermal subsurface temperature of surrounding sub-soils. As water enters and travels through the storm sewerage system, natural geo-thermal heat transfer from the water through the walls of the storm sewerage piping to the cooler surround subsurface soils will occur. The storm sewer conveyance has significant length from the far corners of the site to the basin facilities which should provide significant geo-thermal mitigating factors.

2. PCSM BMP 5.6.3 (Revegetate And Reforest Disturbed Areas, Using Native Species)

Street and buffer trees are being provided throughout the proposed site while portions of the existing wooded areas will remain undisturbed and protected. Trees will help to mitigate temperature with partial shading of impervious surfaces and supplemental shading of vegetated surfaces. Shading generated by these new plantings will provide reduced ground temperatures where currently there is no shading, which will thus aid in reducing temperature of runoff crossing shaded area. Refer to plans for details.

3. PCSM BMP 6.6.3 - Dry Extended Detention Basin

The project proposes three (1 vegetated & two underground) dry extended detention basins. Basin 1-B includes an Ernst detention basin seed mix to promote the uptake of water/runoff as well as a small water quality orifice at the basin bottom (with larger orifice above the 2-year storm elevation) to manage or control the 2-year frequency storm volume increase over a 72-hour period. In order to mitigate the potential for warm water discharge and to provide water quality/pollutant removal, the runoff will naturally experience some thermal mitigation from the cooler geothermal subsurface temperature of surrounding sub-soils due to the small water quality orifice at the bottom of the basin. Additional thermal mitigation will occur through natural geo-thermal heat transfer from the water through the walls of the storm sewerage outlet piping to the cooler surrounding subsurface soils as its being discharged to the associated level spreaders.

4. PCSM BMP 6.8.1 - Level Spreader

Level spreaders are designed in conjunction with MRC BMP discharges and storm sewerage inlet & piping facilities and are located downslope of the proposed development. The level spreaders will convey runoff in a sheet flow condition similar to predevelopment runoff flow conditions. Thermal mitigation will occur through natural geo-thermal heat transfer from the water through the walls of the perforated storm sewerage level spreader piping to the cooler surrounding subsurface soils prior to being discharged overland in a sheet flow condition similar pre-development conditions.

5. PCSM BMP Voluntary Riparian Forest Buffer

Upon being discharged from the dry extended detention basins and outletted via level spreaders, runoff will naturally experience thermal mitigation as it travels overland for a minimum 250'-300' across the wooded and shaded forest floor prior to infiltrating entirely into the cooler Hydrologic Soil Group A soils contained therein prior to ever reaching the downstream wetlands and UNT to the Delaware River.

Critical Stages

Identify the critical stages of implementation of the PCSM plan for which a licensed professional or designee shall be present on the project site.

- 1. Surface facilities that can be visually inspected, such as landscape restoration (BMP 6.7.2), water quality filters & hydrodynamic devices (snouts & water quality inlet filter inserts, BMP 6.6.4), and revegetate & reforest (BMP 5.6.3), will be visually inspected and certified upon completion.
- 2. PCSM BMP 6.8.1 level spreaders will be observed during the installation of the geo-textile, stone base, level lip (i.e., conc. slab over gabion basket), and perforated pipe stubs at the time of the sediment basin installation. The remainder of the perforated pipe and stone backfill material (i.e., river rock) will be inspected and certified upon completion.
- 3. PCSM BMP 6.6.3 Dry Extended Detention Basins, when used as a sediment basin (Basin 1-B) during construction, will be observed during the excavation, preparation, and stabilization of the sediment basin. Upon completion of site construction and removal of sediment from basin floor, the dry extended detention basin will be observed again during basin conversion. Underground Basins 1A & 1C will be observed during the excavation, installation, and backfill.
- 4. Voluntary Riparian Forest Buffer Will be visually inspected during construction for invasive species and any invasive species will be removed and certified upon completion.

SECTION E. ANTIDEGRADATION ANALYSIS MODULE

This Section is to be completed for Special Protection Waters Only (Projects that drain to HQ/EV Waters and EV Wetlands).

PART 1 NO	NDISCHARGE ALTERNATIVES EVALU	JATION		
		Official		Official
		Use		Use
	E & S Plan	Only	PCSM Plan	Only

3800-PM-BCW0405b Rev. 3/2019 Application

Check off the environmentally sound nondischarge Best Management Practices (BMPs) listed below to be used prior to, during, and after earth disturbance activities that have been incorporated into the E & S Plan based on the site analysis. For BMPs not checked, provide an explanation of why they were not utilized, attach additional sheets if necessary. SEE ATTACHED	Check off the environmentally sound nondischarge Best Management Practices (BMPs) listed below to be used after construction that have been incorporated into the PCSM Plan based on the site analysis. For BMPs not checked, provide an explanation of why they were not utilized, attach additional sheets if necessary. SEE ATTACHED
Nondischarge BMPs Alternative Siting Alternative location Alternative configuration Alternative location of discharge Limited Disturbed Area Limiting Extent & Duration of Disturbance (Phasing, Sequencing) Riparian Buffers (150 ft min) Riparian Forest Buffer (150 ft min) Other* level spreaders	Nondischarge BMPs Alternative Siting Alternative location Alternative configuration Alternative location of discharge Low Impact Development (LID / BSD) Riparian Buffers (150 ft min) Riparian Forest Buffer (150 ft min) Infiltration Water Reuse Other* level spreaders
riparian buffer or riparian forest buffer in effectiveness, to minim protect, maintain, reclaim and restore water quality and for existin creek or lake, pond or reservoir of this Commonwealth to ensure standards).	irds and alternatives that collectively are substantially equivalent to a ize the potential for accelerated erosion and sedimentation and to g and designated uses of a perennial or intermittent river, stream or compliance with 25 Pa. Code Chapter 93 (relating to water quality
Will the nondischarge alternative BMPs eliminate the change in rate, volume, or quality during construction? ☐ Yes ☒ No If yes, the antidegradation analysis is complete. If no, proceed to Part 2.	Will the nondischarge alternative BMPs eliminate the change in rate, volume, or quality after construction? ☐ Yes ☒ No If yes, the antidegradation analysis is complete. If no, proceed to Part 2.

Treatment BMPs: Sediment basin with skimmer Sediment basin with skimmer Sediment basin with skimmer Sediment basin with 47 day detention Floculants Land disposal: Riparian Duffers 150ft. Riparian Derest Buffer ≤150ft. POLIUtion prevention: PROP Plans Immediate stabilization Street sweeping Channels, collectors and diversions lined with permanent vegetation, rock, geotextile or other non-erosive malerials Scimment basin water for discission Stefiment basin water for irrigation Other* **All dentify any and all best management practices, design standards and alternatives that collectively are substantially equivalent to a rock or lake, pond or reservoir of this Commonwealth to ensure compliance with 25 Pa. Code Chapter 93 (relating to water quality standards). Are the ABACT BMPs selected sufficient to minimize the St Gisharges to the extent that existing or designated surface water uses are protected? Not fino, and the project discharges to a HQ waters only) If the project discharges to HQ waters only, is there an important economic or social justification for the project? If reatment BMPs: Infilitration Practices Wet ponds Wet ponds Created wetlend treatment systems Vegetated wetlend treatment systems Vegetated swales Bio-retention/filitration Strene Roofs Riparian Forest Buffer <150ft. Ripa				
utilize ABACT BMPs to manage the change. The applicant must specify whether the discharge will occur during construction, post-construction or both, and identify the technologies that will be used to ensure that the discharge will be a non-degrading discharge will be a non-degrading discharge will be a non-degrading discharges to the Quite post-conservation discharges to the Quite post-conservation or or speatrum tregional office. Vegatated BMPs:	Part 2 Antidegradation Best Available Combination	of Technol	ogies (ABACT)	
Treatment BMPs: Sediment basin with skimmer Sediment basin with skimmer Sediment basin with skimmer Sediment basin with 47 day detention Floculants Land disposal: Riparian Duffers 150ft. Riparian Derest Buffer ≤150ft. POLIUtion prevention: PROP Plans Immediate stabilization Street sweeping Channels, collectors and diversions lined with permanent vegetation, rock, geotextile or other non-erosive malerials Scimment basin water for discission Stefiment basin water for irrigation Other* **All dentify any and all best management practices, design standards and alternatives that collectively are substantially equivalent to a rock or lake, pond or reservoir of this Commonwealth to ensure compliance with 25 Pa. Code Chapter 93 (relating to water quality standards). Are the ABACT BMPs selected sufficient to minimize the St Gisharges to the extent that existing or designated surface water uses are protected? Not fino, and the project discharges to a HQ waters only) If the project discharges to HQ waters only, is there an important economic or social justification for the project? If reatment BMPs: Infilitration Practices Wet ponds Wet ponds Created wetlend treatment systems Vegetated wetlend treatment systems Vegetated swales Bio-retention/filitration Strene Roofs Riparian Forest Buffer <150ft. Ripa	utilize ABACT BMPs to manage the change. The app	olicant mus	it specify whether the discharge will occur during con-	struction,
Treatment BMPs: Sediment basin with skimmer Sediment basin ratio of 4:1 or greater (flow length to basin with) Sediment basin with 4-7 day detention Flocoulants Greated welfand treatment systems Vegetated swales Wet ponds Greated welfand treatment systems Vegetated swales Wet ponds Greated welfand treatment systems Vegetated swales Bio-retention/infiltration Green Roofs Riparian buffers <150ft. Riparian Everse Stuffer <150ft. Riparian Forest Buffer <150ft. Riparian Forest Buf	F & S Plan	Use	PCSM Plan	
Sediment basin with skimmer Sediment basin with 5 day detention Flocculants Sediment basin with 4-7 day detention Flocculants Created wetland treatment systems Vegetated swates Wegetated swates Bio-retention/infilitation Green Roofs Land disposal: Pollution prevention: Pollution prevention: Pollution prevention: Flocculants Stormwater rouse technologies: Stormwater rous		Omy		
riparian buffer or riparian forest buffer in effectiveness, to minimize the potential for accelerated erosion and sedimentation and to protect, maintain, reclaim and restore water quality and for existing and designated uses of a perennial or intermittent river, stream or creek or lake, pond or reservoir of this Commonwealth to ensure compliance with 25 Pa. Code Chapter 93 (relating to water quality standards). Are the ABACT BMPs selected sufficient to minimize E & S discharges to the extent that existing or designated surface water uses are protected? Yes If yes, antidegradation analysis is complete. No If no, and the project discharges to an EV Water, contact the local conservation district or Department regional office. Part 3 Social or Economic Justification (SEJ) (for projects in high quality waters only) If the project discharges to HQ waters only, is there an important economic or social justification for the project?	 Sediment basin with skimmer Sediment basin ratio of 4:1 or greater (flow length to basin width) Sediment basin with 4-7 day detention Flocculants Land disposal: Vegetated filters Riparian buffers <150ft. Riparian Forest Buffer <150ft. Pollution prevention: PPC Plans Immediate stabilization Street sweeping Channels, collectors and diversions lined with permanent vegetation, rock, geotextile or other non-erosive materials Stormwater reuse technologies: Sediment basin water for dust control Sediment basin water for irrigation 		Infiltration Practices Wet ponds Created wetland treatment systems Vegetated swales Manufactured devices Bio-retention/infiltration Green Roofs Land disposal: Vegetated filters Riparian Buffers <150ft. Riparian Forest Buffer <150ft. Pollution prevention: Disconnection of roof drainage Bio-retention/bio-infiltration Street sweeping Nutrient, pesticide, herbicide or other chemical application plan alternatives PPC Plans Non-structural Practices Land Preservation Restoration BMPs Stormwater reuse technologies: Cisterns Rain barrels Dry hydrant with underground storage Spray/Drip Irrigation	
protect, maintain, reclaim and restore water quality and for existing and designated uses of a perennial or intermittent river, stream or creek or lake, pond or reservoir of this Commonwealth to ensure compliance with 25 Pa. Code Chapter 93 (relating to water quality standards). Are the ABACT BMPs selected sufficient to minimize E & S discharges to the extent that existing or designated surface water uses are protected? Yes If yes, antidegradation analysis is complete. No If no, and the project discharges to an EV Water, contact the local conservation district or Department regional office. Part 3 Social or Economic Justification (SEJ) (for projects in high quality waters only) If the project discharges to HQ waters only, is there an important economic or social justification for the project?				
E & S discharges to the extent that existing or designated surface water uses are protected? ☐ Yes If yes, antidegradation analysis is complete. ☐ No If no, and the project discharges to a HQ water, proceed to Part 3. If no and the project discharges to an EV Water, contact the local conservation district or Department regional office. ☐ Part 3 Social or Economic Justification (SEJ) (for projects in high quality waters only) If the project discharges to the extent that existing or designated surface water uses are protected? ☐ Yes If yes, antidegradation analysis is complete. ☐ No If no, and the project is located in a HQ water, proceed to Part 3. If no and the project discharges to an EV Water, contact the local conservation district or Department regional office.	protect, maintain, reclaim and restore water quality and for creek or lake, pond or reservoir of this Commonwealth to	or existing a	and designated uses of a perennial or intermittent river, s	stream or
Part 3 Social or Economic Justification (SEJ) (for projects in high quality waters only) If the project discharges to HQ waters only, is there an important economic or social justification for the project?	E & S discharges to the extent that existing or designated surface water uses are protected? ☐ Yes If yes, antidegradation analysis is complete. ☐ No If no, and the project discharges to a HQ water, proceed to Part 3. If no and the project discharges to an EV Water, contact the local conservation district or		no net change and assure that existing or designated surface water uses are protected? ☑ Yes If yes, antidegradation analysis is complete. ☐ No If no, and the project is located in a HQ water, proceed to Part 3. If no and the project discharges to an EV Water, contact the local	
□ Voc. □ M No. If you placed contact the Department regional office for the county in which the project is legated	Part 3 Social or Economic Justification (SEJ) (for pro	-	gh quality waters only)	<u> </u>
☐ Yes ☐ No If yes, please contact the Department regional office for the county in which the project is located.	☐ Yes ☑ No If yes, please contact the Department	regional offi	ce for the county in which the project is located.	

3800-PM-BCW0405b Rev. 3/2019 Application

SECTION F. CONSULTANT FOR THIS PROJECT						
Plan Preparer's Name			eFACTS Consu	ıltant ID		
Michael A. Sodl, P.E.				المرادع	TITTE	
Title	Consulting Firm		Seal (if applicable)			
Senior Project Manager/Engineer	Vertek Constr. Mgmt.,		PROFESSION L PROFESSION L PROFE		DEESSION NGINEER E-044862-E	
Mailing Address					20000000	
7171 Airport Road, Suite 200						
City	State	ZIP+4				
Bath	PA	18014				
Email		Phone 6	6108371856	Ext	357	
msodl@vertekcm.net		FAX				
SECTION G. C	OMPLIA	NCE HISTORY I	REVIEW			
Is/was the applicant(s) in violation of any Department regulation, order, schedule of compliance or permit or in violation of any Department regulated activities within the past five years? Yes No If yes, list each permit order, schedule of compliance or project that is/was in violation and provide compliance status of the activity (use additional sheets to provide information on all permits). Permit Program or Activity: Permit Number (if applicable): Brief description of non-compliance:						
Steps taken to achieve compliance		Date(s) com	pliance achieved			
Current Compliance Status: 🛛 In-Compliance 🔲 In Non-Compliance						
If in non-compliance, please attach schedule for achieving compliance.						

10,46		SECTION H.	PERMIT COORDINAT	ION	<u>ilikaatikkees.</u>		
1.	1. Are there pending permits or any other permits, approvals or planning requirements for this project?						
	☐ Yes No	If yes, list each permit or appro	val, permit number, and o	description.			
2.	Does the project invalong, across, or pr	volve any of the following: placer ojecting into a water course, flood	nent of fill and/or excava lway or body of water (in	tion within or a cluding wetland	placement ds)?	of a struct	ure located in,
	☐ Yes	If yes, identify which authorizat	on under Chapter 105 is	applicable.			
	☐ Joint Permit	☐ Gener	al Permit] Waiver		
3.	activity.	's 537 Plan status? Please note	e that 537 Plan approva	l is required pr	ior to initiati	on of eart	h disturbance
	Pending						
4.	Is the project assoc	iated with a brownfield remediation	on and/or requires an Act	: 2 approval? [] Yes	⊠ No	If yes, please
	indicate any coordin	nation to date with the Departmer	ıt's Environmental Cleanı	up Program.			
	-						

Application	
SECTION I. CERTIFI	CATION
Applicant Certification I certify under penalty of law that this application and all related attachments a accordance with a system designed to assure that qualified personnel properly own knowledge and on inquiry of the person or persons directly responsible for best of my knowledge and belief, true, accurate and complete. The responsible participate in the NPDES permit, and that BMP's, E&S Plan, PPC Plan, PCSM ensure that water quality standards and effluent limits are attained. I am an information, including the possibility of fine and imprisonment or both for knowin Act and, 18 Pa. C.S. §§4903-4904.	gather and evaluate the information submitted. Based on my gathering the information, the information submitted is, to the e official's signature also verifies that the activity is eligible to Plan, and other controls are being or will be, implemented to ware that there are significant penalties for submitting falso.
I grant permission to the agencies responsible for the permitting of this work, or tinspection purposes. I will abide by the conditions of the permit if issued and will	heir duly authorized representative to enter the project site for not begin work prior to permit issuance.
(For individuals no indication of title is necessary, choose the box below. All other	rs proceed to the next paragraph)
☐ Individual; proceed to signature portion.	
I hereby certify that I am the signatory pursuant to 25 Pa, Code § 92a.22 and 40 decision-making regarding environmental compliance functions for New Dem production, or operating facilities of the applicant and am authorized to make ma facility including having explicit or implicit duty of making major capital invecomprehensive measures to assure the applicant's long term environmental coresponsible for ensuring that the necessary systems are established or actions application requirements.	i Road, LLC, the manager of one or more manufacturing, anagement decisions which govern the operation of regulated stment recommendations, and initiating and directing other appliance with environmental laws and regulations; and Law
(choose one of the following; not applicable for individuals):	
☐ The responsible corporate officer ☐ president ☐ vice president ☐ secretary	treasure of New Demi Road,LLC Corporation/Company
☐ The ☐ member or ☐ manager ofLLC	a.m.y name
Entity name	
☐ The general partner of partnership/LP/LLP	
Entity name	
☐ The principal executive officer or ranking elected official of	Municipality/State/Federal/other public agency
Entity name	
Power of Attorney/delegation of contractual authority (documentation support	rting delegation of contracting authority must be provided) for
Entity name	
SIGNATURES	
Applicant	Co-Applicant (if applicable)
New Dami Road, LLC	
Print Name and Title of Person Signing	Print Name and Title of Person Signing
Signature of Applicant	Signature of Co-Applicant
Date Signed	Date Signed
Please note below the name, address and telephone number of the individual tha required.	t should be contacted in the event additional information is
Name Michael A. Sodl, P.E.	Phone <u>610-837-1856</u>
	FAX