

COMMONWEALTH OF PENNSYLVANIA DEPARTMENT OF ENVIRONMENTAL PROTECTION OFFICE OF WATER PROGRAMS OFFICE OF OIL AND GAS MANAGEMENT

OFFICIAL USE ONLY
ID#
Date Received
AUTH
SITE
CLNT
APS
Fee
Check No.
Check Date

NOTICE OF INTENT (NOI) FOR COVERAGE UNDER THE EROSION AND SEDIMENT CONTROL GENERAL PERMIT (ESCGP-3) FOR EARTH DISTURBANCE ASSOCIATED WITH OIL AND GAS EXPLORATION, PRODUCTION, PROCESSING, OR TREATMENT OPERATIONS OR TRANSMISSION FACILITIES

READ THE INSTRUCTIONS PROVIDED IN THIS PERMIT APPLICATION PACKAGE BEFORE COMPLETING THIS FORM. PLEASE PRINT OR TYPE INFORMATION IN BLACK OR BLUE INK.					
SEC	TION A. APPLICATION TY	PE			
Check one:					
NEW ⊠ RENEWAL □ MAJOR MO	DIFICATIONS (Provide ES	CGP r	number) 🗌		
$\textbf{PHASED} \boxtimes \text{(check only if applicable; } \textit{note: Most}$	projects are not submitted a	s phas	sed projects)		
Check one: E	XPEDITED STA	NDAR	D 🖂		
If an Expedited Review Process being requested Refer to Section D - Expedited Review Process of					
SECT	ION B. CLIENT INFORMAT	ION			
Applicant's Last Name (If applicable)	First Name	MI	Telephone No	o. 732-938-1169	
Valori	Mark				
Organization Name or Registered Fictitious Name Adelphia Gateway, LLC	:	Telephone No.			
DEP Client ID No.					
Headquarters Mailing Address	City		State	ZIP Code	
1415 Wyckoff Road	Wall		NJ	07719	
Email Address mvalori@njresources.com					
Co-Applicant's Last Name (If applicable)	First Name		Telephone No.		
Organization Name or Registered Fictitious Name		Telephone No.		o.	
Address	City		State	ZIP Code	
Email Address	•				

	SECTION C. SITE INFORMATION						
Is there	Is there an existing ESCGP associated with this site? Yes No If yes, Permit No.						
Has a v	Has a well permit application been submitted for this site? Yes No If yes, Permit No.						
Does th	nis site have a	a 911 address? 🗌 Ye	es 🛛 No If yes, <u>pro</u>	vide site location addr	ess.		
Site Na	ame						
see At	see Attachment on next Page						
Site Lo	cation			Site No. (if another p	ermit has bee	n issued for the	site)
	ttachment on ne	xt Page			1		
	cation – City				State	ZIP Code	
	Attachment on ne				see Att	achment on next Pag	ge ————
Detaile	d Written Dire	ections to Site					
see Att	achment on next	: Page					
		-					
Primary	y Location	County	Municipality		City	Boro Twp.	
see Attachment on next Page see Attachment on next Page							
			SECTION D. EX	PEDITED REVIEW			
I. Ex	pedited Revi	ew Eligibility					
1.				ace water with an exis		⊠ Yes □ I	No
				lity pursuant to Cha _l l I value wetland in acco			
	with 25 Pa. 0	Code § 105.17, or in t	the watershed of an	impaired surface wate			
	the cause of	the impairment is ide	entified as siltation?				
2.	Will the proje	ect in which the well p	ad will be constructe	ed be in or on a floodp	lain?	☐ Yes ⊠ l	No
3.	· · · · · · · · · · · · · · · · · · ·						No
	contaminated by the release of regulated substances as defined in Section 103 of Act 2, 35 P.S. § 6026.103?						
4.							 No
	the project of	or surrounding enviror		otential to cause or co			
	to pollution v	when disturbed?					
5.	Do any unre	solved non-compliand	ce issues exist with t	he applicant or the fac	cility?	☐ Yes ⊠ l	No
6.	6. Is the project a transmission project? ☐ Yes ☒ No						

Site #	Site Name	Site Address	Latitude	Longitude	City	State	Zip Code	County	Municipality	Directions To Site
1	Quakertown Compressor Station	Unknown	40°24'15.39"N	75°20'53.13"W	Quakertown	Pennsylvania	18951	Bucks	Richland Township & West Rockhill Township (split)	From Allentown Road & Camp Rock Hill Road Head east on Camp Rock Hill Rd toward Schukraft Rd 1.2 mi Continue onto Scholls School Rd approximately 1,125' Turn right onto Rich Hill Rd approximately 525' Turn left and travel approximately 1,250' Destination will be on the right
2	East Perkiomen Blowdown	Unknown	40°15'2.51"N	75°26'30.06"W	Schwenksville	Pennsylvania	19473	Montgomery	Skippack Township	From West Skippack Pike & Cross Road Head north onto Cross Rd Travel approximately 1,100' Turn left onto Grages Rd Travel approximately 2,500' Destination will be on the right
3	Skippack Pike Meter Station	Unknown	40°14'32.70"N	75°26'48.26"W	Schwenksville	Pennsylvania	19473	Montgomery	Skippack Township	From West Skippack Pike & Cross Road Head northwest on PA-73 W/W Skippack Pike toward Cressman Rd 2.5 mi Destination will be on the right
4	Perkiomen Creek Blowdown	Unknown	40°12'58.57"N	75°27'14.12"W	Collegeville	Pennsylvania	19426	Montgomery	Perkiomen Township	From Bridge Road & Gravel Pike Head north on PA-29 N toward Ellis Rd approximately 2,500' Destination will be on the left
5	Schuylkill River Blowdown	Unknown	40° 9'38.76"N	75°31'42.05"W	Spring City	Pennsylvania	19475	Chester	East Pikeland Township	From Cromby Road & Township Line Road Head north approximately 400' on Cromby Rd Turn left into private drive at Cromby Station Travel approximately 875' along private drive Turn left and travel approximately 600' to west gravel parking lot of Cromby Station Turn right onto schuylkill River Trail Continue approximately 3,625' Destination will be on the right
6	Cromby Blowdown	Unknown	40° 9'7.01"N	75°31'58.89"W	Phoenixville	Pennsylvania	19460	Chester	East Pikeland Township	From Cromby Road & Township Line Road Head north approximately 400' on Cromby Rd Turn left into private drive at Cromby Station Travel approximately 875' along private drive Turn left and travel approximately 600' to west gravel parking lot of Cromby Station Destination will be on the right
7	French Creek Blowdown	Unknown	40° 8'0.21"N	75°32'56.35"W	Phoenixville	Pennsylvania	19460	Chester	East Pikeland Township	From Kimberton Rd & Powder Mill Dr Head east approximately 125' Turn left and travel approximately 1,500' through private property Destination will be directly ahead
8	Mainline Valve 2	Unknown	40° 1'49.95"N	75°35'1.78"W	Malvern	Pennsylvania	19355	Chester	East Whiteland Township	From Lincoln Highway & Phoenixville Pike Head south on Phoenixville Pike toward Mystic Ln approximately 2,900' Turn left into private drive Travel approximately 515' Destination will be on the left

Site #	Site Name	Site Address	Latitude	Longitude	City	State	Zip Code	County	Municipality	Directions To Site
9	Paoli Pike Blowdown	Unknown	39°59'27.05"N	75°32'58.69"W	West Chester	Pennsylvania	19380	Chester	East Goshen Township	From Boot Road & Paoli Pike Head northeast on Paoli Pike toward Boot Rd approximately 750' Destination will be on the left
10	Chester Creek Blowdown	Unknown	39°55'54.06"N	75°30'40.35"W	Glen Mills	Pennsylvania	19342	Delaware	Thornbury Township	From Creek Road & Locksley Road Head south on Locksley Rd approximately 415' Turn right onto private drive Travel approximately 1,600' Destination will be on the right
11	Mainline Valve 1	Unknown	39°53'52.18"N	75°29'18.63"W	Glen Mills	Pennsylvania	19342	Delaware	Concord Township	From Stoney Bank Road & Baltimore Pike Head west on Baltimore Pike approximately 500' Turn right into private parking lot Travel approximately 225' Destination will be directly ahead
12	Transco Meter Station	Unknown	39°49'7.46"N	75°26'5.59"W	Marcus Hook	Pennsylvania	19061	Delaware	Lower Chichester Township	From Naamans Road and Ridge Road Head northeast on Ridge Rd toward Virginia Ave approximately 3,700' Turn left onto private drive (Fed Ex Drive) Travel approximately 200' Destination will be on the left
13	Marcus Hook Compressor Station	Unknown	39°48'53.17"N	75°26'19.12"W	Marcus Hook	Pennsylvania	19061	Delaware	Lower Chichester Township	From Naamans Road and Ridge Road Head northeast on Ridge Rd toward Virginia Ave approximately 1,900' Destination will be on the Right

	If yes to any of the above questions the project is not eligible for Expedited Review; If the project is eligible for Expedited Review, all the following items must be completed.						
II.	Ex	pedited Review Process					
	1.	Is the technically and administratively complete and accurate NOI package prepared and certified by a licensed professional?	☐ Yes ☐ No				
	2.	Are E&S and PCSM/Site Restoration Plan drawings and narrative prepared and sealed by a licensed professional? (Include interim restoration details when needed)	☐ Yes ☐ No				
	3. Include a Resource Delineation Report and answer the following questions: (If the answer to question a. is "Yes" then skip to #4. If the answer to a. is "No" the applicant must answer "Yes" to at least one of the questions, b. through d. to be eligible for expedited review.)						
		Were all wetland resources delineated during the growing season?	☐ Yes ☐ No				
		b. If not during the growing season, was a follow-up visit conducted during the growing season to verify/adjust boundaries and look for potentially missed resources?	☐ Yes ☐ No				
		c. Was a quality assurance field review conducted at a later date by an independent qualified wetland professional to verify boundaries and look for potentially missed resources? (If yes, attach Quality Assurance Field Review Report)	☐ Yes ☐ No				
		d. Was a Jurisdictional Determination (JD) or Preliminary JD conducted by the US Army Corps of Engineers on the whole project? (If yes, attach Preliminary or Jurisdictional Determination Report)	☐ Yes ☐ No				
	4.	If applicable, have you included PNDI clearance letters or other documentation from applicable resource agencies?	☐ Yes ☐ No				
	5.	If the project site contains, is along, or within 100 feet of a river, stream, creek, lake, pond or reservoir, will you establish new or preserve existing riparian forest buffer at least 100 feet in width between the top of streambank or normal pool elevation of a lake, pond or reservoir and areas of earth disturbances.	☐ Yes ☐ No				
		If no, will a waiver be obtained? ☐ Yes ☐ No					
	6.	Name of Licensed Professional					
		Company					
		Address					
		Phone					

SECTION E. PROJECT INFORMATION								
1. Total Project	otal Project Area/Project Site (Ac): 23.44 Total Disturbed Area (Ac): 13.44							
Increased distu	ncreased disturbed acreage (for permit modification only) 10.00							
Fee: (For addi Fees.)	tional information regarding fees, refer	to NOI Instru	ctions #3 Pe	rmit NOI Filin	g \$ 2,900			
2. Project Nan	ne: Adelphia Gateway Project							
3. Project Typ	e (Check all that apply)							
Oil/Gas	Well ¹	☐ Tra	ansmission Fa	cility				
☐ Gatherin	ng Facility	☐ Pro	cessing Facil	ity				
☐ Treatme	nt Facility	□We	ell Developme	nt Impoundme	nt			
	ssor Station	☐ No	n-FERC regul	ated Transmis	sion Facility			
□ Pipeline		☐ Gro	ound/Surface	Water Withdra	wal Site			
Storage	Field Facility							
☐ Other								
¹ If Oil/Gas Wel	l; is the well conventional or unconventiona	al? 🔲 Co	nventional		Unconventional			
Project Descript	<u>tion</u>							
Meter Station, F Mainline Valve & Hook Compress The subsequen approximately 4 installation method main, new meter This application information und	The Adelphia Gateway Pipeline is an 84-mile pipeline that runs from Martins Creek to Marcus Hook. Facility upgrades will occur to thirteen (13) sites along the pipeline: Quakertown Compressor Station, East Perkiomen Blowdown, Skippack Pike Meter Station, Perkiomen Creek Blowdown, Schuylkill River Blowdown, Cromby Blowdown, French Creek Blowdown, Mainline Valve 2, Paoli Pike Blowdown, Chester Creek Blowdown, Mainline Valve 1, Transco Meter Station, and Marcus Hook Compressor Station. The subsequent phase is the Tilghman and Parkway lateral pipeline installations. The Tilghman lateral pipeline consists of approximately 4.5 miles of a 16-inch O.D. pipeline through traditional pipeline installation and horizontal direction drill (HDD) installation methods. The project scope for the Parkway Lateral includes the installation of 500 linear feet of natural gas main, new meter pads, gravel paths, and a small compressor building. This application is for Phase 1 only. The subsequent phase (Phase 2) will be submitted to DEP with more detailed information under a separate cover. Provide the date of pre-application meeting (if conducted with the Department) 2/21/2019							
degrees an	4. Provide the latitude and longitude coordinates for the center of the project. The coordinates should be in Decimal degrees and North American Datum 1983. The coordinates must meet the current DEP policy regarding locational accuracy. For linear projects provide the project's termini.							
Latitude (DI	D) 39.8147	Longitude (DD) - 75.4383	3				
Latitude (DI	D) 40.7933	Longitude (DD) - 75.1313	3				
Horizontal (Collection Method: 🛛 GPS 🔲 Inter	polated from U	.S.G.S. Topog	graphic Map	☐ DEP's eMAP			
Phoenixville, Co	5. U.S.G.S. 7.5 min. topographic quadrangle Name Perkiomenville, Media, Malvern, West Chester, Quakertown, Phoenixville, Collegeville, Marcus Hook (Include a copy of the project area on the 7.5 min quad map)							
6. Will the project be conducted as a phased permit project? ⊠ Yes □ No								
If Yes, Inclu	de Master Site Plan Estimated Timetable f	or Phased Pro	jects. 🔲 /	Additional shee	et(s) attached.			
Phase No.	December 1999	Tatal Assa	Disturbed	011 D-1-	Ford Date			
or Name	Description Adelphia Gateway	Total Area 13.44	Area 13.44	Start Date 1/2/20	End Date 6/2/20			
2	Tilghman & Parkway Laterals	10.00	10.00	1/2/20	6/2/20			
	, <u> </u>							
		1	1					

7.	List existing	g and previo	us land use for a	a minimum of th	ne previous 5 y	ears.		
The	e existing us	e for the Qu	akertown Compi	ressor Station i	is a partially de	eveloped mete	er site with grav	vel and brush.
Eas	East Perkiomen Blowdown, Skippack Pike Meter Station, Perkiomen Creek Blowdown, Schuylkill River Blowdown, Cromby Blowdown, French Creek Blowdown, Mainline Valve 2, Paoli Pike Blowdown, Chester Creek Blowdown, Mainline Valve 1 are existing valve sites with gravel and grass.							
The	The existing use for the Quakertown Compressor Station is a partially developed site with an adjacent meter site. The area to be distributed is primarily meadow.							
Ма	rcus Hook C	Compressor	Station is a fully	developed con	npressor site th	nat is primarily	gravel in exis	ting conditions.
8.	Other Pollu	ıtants: Will t	he stormwater d	ischarge conta	in pollutional s	ubstances oth	ner than sedim	ent? ☐ Yes ⊠ No
	If yes, expla	ain and prov	ide any available	e quantitative o	lata.			
9.			olvents, other har Ital Directional D				tored on site d	uring earth disturbance
			s, Preparednes nce. See NOI In					e maintained on site ation.)
10.	Is the proje	ct in the wat	ershed of an imp	paired surface	water where th	e cause of th	e impairment is	s identified as siltation?
			s, show how the 10 of NOI instru		ot result in a	net change i	n volume, rate	or water quality. See
11.		potentially f g area? Yes		rally occurring	geological or	soil condition	ons in any po	rtion of the project or
			/ hazardous geo earth disturbance		onditions have	the potential t	o cause or cor	ntribute to pollution as a
	If no, provid	de an explan	ation.					
	If yes, Geologic Hazard Mitigation Plan must be attached and explain where in this application details are provided.							
12.	Has the Act	t 14 Municip	al Notification ar	nd proof of rece	eipt of notificati	on been attac	hed to the NO	l?
	2. Has the Act 14 Municipal Notification and proof of receipt of notification been attached to the NOI? Yes \infty No \infty (If not, the NOI is not complete, see E.12 and #4 Municipal Notification in the NOI Instructions for additional guidance.)							
13.	Has the PN	IDI receipt b	een attached to	the NOI?				
	Yes ⊠ N guidance.)		ot, the NOI is r	not complete,	see E.13 and	#5 PNHP in	the NOI Inst	ructions for additional
14.	Have the E	&S Plan and	PCSM/SR Plar	n been planned	and designed	to be consist	ent?	
	Yes ⊠ N	1o 🗌						
15.	Have existing	ing and/or pr	oposed Ripariar	Forest Buffers	s been identifie	ed?		
	Yes 🗌 N	NA⊠ (If ye	s, they must be	shown on the	E&S Plan as w	rell as the PC	SM/SR Plans.)	
16.	Have antide	egradation ir	mplementation re	•				
	Yes ⊠ N	lo 🗌 N/A	(If yes, ant	tidegradation	requirements	must be incl	uded in the p	lan.)
17.	for pits for o		operations and					all excavation locations erations?

18. Receiving Waters	Chapter 93, Designated Use Stream Classification	Chapter 93, Existing Use Stream Classification
Tohickon Creek	☐ HQ ☐ EV Other <u>WWF, MF</u>	☐ HQ ☐ EV ☑ Other <u>WWF, MF</u>
		⊠ Siltation-impaired
Perkiomen Creek	☐ HQ ☐ EV ☐ Other <u>WWF, MF</u>	☐ HQ ☐ EV ☒ Other <u>WWF, MF</u>
	⊠ Siltation-impaired	⊠ Siltation-impaired
Schuylkill River	☐ HQ ☐ EV ☒ Other <u>WWF, MF</u>	☐ HQ ☐ EV ☒ Other <u>WWF, MF</u>
	⊠ Siltation-impaired	⊠ Siltation-impaired
Stony Run	☐ HQ ☐ EV ☐ Other TSF, MF	☐ HQ ☐ EV ☐ Other TSF, MF
	⊠ Siltation-impaired	
Casandary Dagaining Water	Consider Charter 02 Decimented Lie	Secondary Existing Use
Secondary Receiving Water	Secondary Chapter 93, Designated Use	Secondary Existing Ose
Name of Municipal or Private Se	parate Storm Sewer Operator, if applicable.	
Non-Surface Receiving Water: (i	nclude off-site discharges)	

18. Receiving Waters	Chapter 93, Designated Use Stream Classification	Chapter 93, Existing Use Stream Classification
French Creek	☐ HQ ☐ EV ☒ Other <u>TSF, MF</u>	☐ HQ ☐ EV ☑ Other <u>TSF, MF</u>
	☐ Siltation-impaired	☐ Siltation-impaired
Valley Creek	☐ HQ ☐ EV ☒ Other CWF, MF	☐ HQ ☐ EV ☒ Other CWF, MF
valley Greek	⊠ Siltation-impaired	⊠ Siltation-impaired
Ridley Creek	☐ HQ☐ EV☐ OtherHQ-TSF, MF	☐ HQ ☐ EV ☐ Other <u>HQ-TSF, MF</u>
	⊠ Siltation-impaired	⊠ Siltation-impaired
Chester Creek	☐ HQ ☐ EV ☒ Other <u>TSF, MF</u>	☐ HQ ☐ EV ☒ Other <u>TSF, MF</u>
	⊠ Siltation-impaired	⊠ Siltation-impaired
Secondary Receiving Water	Secondary Chapter 93, Designated Use	Secondary Existing Use
Name of Municipal or Private Se	parate Storm Sewer Operator, if applicable.	
Non-Surface Receiving Water: (i	nclude off-site discharges)	

18. Receiving Waters	Chapter 93, Designated Use Stream Classification	Chapter 93, Existing Use Stream Classification
Naamans Creek	☐ HQ ☐ EV ☒ Other <u>WWF, MF</u>	☐ HQ ☐ EV ☒ Other <u>WWF, MF</u>
	☐ Siltation-impaired	☐ Siltation-impaired
	☐ HQ ☐ EV ☐ Other	☐ HQ ☐ EV ☐ Other
	☐ Siltation-impaired	☐ Siltation-impaired
	☐ HQ ☐ EV ☐ Other	☐ HQ ☐ EV ☐ Other
	☐ Siltation-impaired	☐ Siltation-impaired
	☐ HQ ☐ EV ☐ Other	☐ HQ ☐ EV ☐ Other
	☐ Siltation-impaired	☐ Siltation-impaired
Secondary Receiving Water	Secondary Chapter 93, Designated Use	Secondary Existing Use
Name of Municipal or Private Se	parate Storm Sewer Operator, if applicable.	
Non Confess Descioles Water (i	in all the affinite disabourses)	
Non-Surface Receiving Water: (i	nclude off-site discharges)	

SECTION F. EROSION AND SEDIMENT CONTROL (E&S) PLAN See the attached Instructions for additional guidance with E&S Plans

Erosion and Sediment Control Plan BMPs should be designed to minimize accelerated erosion and sedimentation through limiting the extent and duration of earth disturbance, protection of existing drainage and vegetation, limiting soil compaction and controlling the generation of increased runoff. The Department recommends the use of the *Pennsylvania Erosion & Sedimentation Pollution Control Program Manual (E&S Manual)* (363-2134-008) to achieve this goal. The E&S Plan must meet the requirements of Pa. Code § 102.4(b) and submitted with the NOI. Also, see section 2. of the NOI instruction for detailed information on completing the E&S plan and additional requirements.

a. E&S Plan Summary

Provide a summary of proposed E&S BMPs and their performance to manage E&S for the project.

The following measures are aimed at controlling accelerated erosion and sedimentation during construction. Temporary erosion and sediment control will be accomplished by utilizing Best Management Practices, such as Rock Construction Entrance, Compost Filter Sock, Inlet Protection, Compost Sock Washout Facility, Pumped Water Filter Bags, Erosion Control Blanket, Temporary Wetland Crossings and Rock Filters. The extent and duration of earth disturbance is to be minimized to limit impacts of erosion and sedimentation to neighboring and downstream properties.

For project site in HQ watersheds, the E&S Desgin includes ABACT measures to ensure limited erosion and sedimentation.

b.	E&S Plan BMP Design
	Check those that apply:
	☐ E&S Plan is designed using an alternative BMP or design standard approved by DEP.

Note: NOI packages submitted with alternate BMPs not approved by the Department will be returned to the Applicant.

c.	Do you have any information regarding riparian buffer which differs from Section G, Riparian Buffer?
	Yes ☐ No ⊠
	Explain:
_	
a.	Thermal Impacts Analysis
	Explain how thermal impacts associated with this project were avoided, minimized, or mitigated.
	Thermal impacts associated with the project will be minimized and/or mitigated through the incorporation of various
	BMPs, which include a subsurface and subsurface MRC basins, stormwater swale with check dams and a subsurface infiltration bed. Runoff from the impervious areas will be directed to the BMPs where the travel time is increased to
	infiltrate and/or store runoff, reducing the quantity and temperature of the runoff.
	The surface basin at Marcus Hook Compressor Station will be vegetated. Landscaping and vegetative cover will mimic
	natural ecosystems, resulting in a system that is resistant to climatic stresses. Additionally, the basin's outlet structure
	is designed to promote the slow release of outflow to the surface waters.
	The subsurface basin at Transco Meter Station will temporarily store stormwater runoff beneath the surface, away
	from direct sunlight and will promote infiltration which will release water into the groundwater instead of discharging to the surface waters.
	The subsurface basin at Quakertown Compressor Station will temporarily store stormwater runoff beneath the surface, away from direct sunlight and will promote the slow release of outflow to the surface waters.
	away from direct sumight and will promote the slow release of outflow to the surface waters.
e.	Off-Site Discharge Analysis
	Does the activity propose any off-site discharges to areas other than surface waters? 🖂 Yes 🔲 No
	If yes, it is the applicant's responsibility to ensure that they have legal authority for any off-site discharge to neighboring properties.
	The applicant must provide a demonstration in both E&S and PCSM/SR plans that the discharge will not cause erosion, damage, or a nuisance to off-site properties.

	SECTION G. RIPARIAN BUFFER							
1.	Will you be protecting, converting or establishing a voluntary riparian forest buffer as part of this project? \square Yes \square No If yes, as part of the PCSM/SR Plan, provide a Buffer Management Plan.							
2.	Will proposed earth disturbance activities be conducted in an EV or HQ watershed AND within 150 feet of a perennial or intermittent river, stream, or creek, or lake, pond, or reservoir? \square Yes \square No							
	If no, proceed to the next section/module.							
3.	Does this project qualify for an exception (see § 102.14(d)(1))? ⊠ Yes ☐ No							
	If yes, indicate below the type of project for which the exception applies by marking the appropriate box.							
	Oil and gas activities for which site reclamation or restoration is part of the permit authorization in Chapter 78 and 78a.							
	☐ Road maintenance activities.							
	☐ The repair or maintenance of existing pipelines and utilities.							
	☐ Other (see §102.14(d)(1))							
	If exceptions are checked, explain how existing riparian buffer will be undisturbed to the extent practicable. Provide a demonstration that the requirements of §102.14(b) are met, or provide the necessary information to request a riparian buffer waiver.							
4.	Are you requesting a riparian buffer waiver for this project (see § 102.14(d)(2))? ☐ Yes ☐ No							
	If yes, indicate below the type of project for which you are requesting a waiver by marking the appropriate box.							
	☐ Linear project that may include pipelines, public roadways, rail lines, or utility lines.							
	Project is of a temporary nature where the site will be fully restored to its preexisting conditions during the ESCGP permit term.							
	Project where compliance with mandatory riparian buffers is not appropriate or feasible due to site characteristics or existing structures at the project site.							
	☐ Other (see §102.14(d)(2)):							
	If waivers are checked, explain how existing riparian buffers will be undisturbed to the extent practicable.							
	Note: If "Yes" to #2 AND "No" to #3 and #4, provide an attachment to demonstrate how the requirements of §102.14 are met.							
	See PCSM Narrative, Section XII							

SECTION H. POST CONSTRUCTION STORMWATER MANAGEMENT (PCSM) AND/OR SITE RESTORATION(SR) PLAN See NOI Instructions for additional guidance with PCSM Plans

See NOT Instructions for additional guidance with PCSM Plans						
PCSM/SR BMPs should be designed to use natural measures to eliminate pollution, infiltrate runoff, not require extensive construction/maintenance, promote pollutant reduction, and preserve the integrity of stream channels. All PCSM/SR BMPs proposed in the PCSM/SR Plan must be designed in accordance with Ch. 102, Ch. 78a for unconventional operations, Ch. 78 for conventional operations and the <i>Pennsylvania Stormwater Best Management Practices Manual (Stormwater BMP Manual)</i> (363-0300-002). If alternate design criteria are utilized for the proposed project, they must have prior approval by the Department, or the NOI Application will be returned to the Applicant.						
	ruction is con conditions?	npleted, how much of the entire di ⊠ All Partial None	isturbed area will be rest	tored to meadow in good condit	ion or better,	
	SM narrative toration plan.	and drawings for remaining impe	ervious area. Also includ	de a map showing the proposed	I contours of	
required by	subsection '	ages of the project prior to permit a' to section 'g' for each stage (e. s areas). Upload a narrative for ea	g. partial restoration or o	changes to the amount of comp		
	EXAMPLE					
	Stage No	Stage Name	PCSM Plan	SR Plan	7	
	Stage 1	Adelphia Gateway	\boxtimes			
	Stage 2	Tilghman & Parkway Laterals				
	Stage 3					
	Stage 4					
Is there a	ın Act 167 Pla	. Check those that apply. Ch	es: ester Creek Blowdown inline Valve 1 applicable approved Act			
-		g for all approved Act 167 Stormw	ater Management Plans	. (Use additional sheets if nece	ssary)	
	Plan Name Crook Water	Date Adopted		Consistency Letter Included		
Cnester	Creek Water	shed June 2002		Verification Report Included		
		letter is not required if a verifica ither sub paragraph 1, 2, or 3 belo			SM/SR Plan	
1. Act 167 Plan approvals on or after January 2005 – The attached PCSM/SR Plan, in its entirety, is consistent with all requirements pertaining to rate, volume, and water quality from an Act 167 Stormwater Management Plan approved by DEP on or after January 2005. Box 1 must be checked if a current, DEP approved Act 167 plan exists.						
2. A The PCSM/SR Plan meets the standard design criteria from sections 102.8(g)(2) and (3) and the Stormwater BMP Manual. For projects involving oil and gas activities authorized by a permit issued under Chapter 78 or Chapter 78a (well pads) or pipelines and other similar utility infrastructure, post construction stormwater management requirements are met for all areas that are restored to preconstruction conditions or to a condition of meadow in good condition or better. [Note: PCSM plans must meet both the volume and rate requirements in the regulations, which are provided in the 2 sections mentioned in this paragraph].						
3.						

PC	SM/SR BMP Alternative Standards: SITE RESTORATION ONLY - MEET SECTION 102.8(g)(2) and (3)
На	s the alternative BMP or design standard been approved by the Department?
	Yes
	No – Do not submit the ESCGP-3 application and see Section (H) of the NOI Instructions concerning the alternative BMP approval process.
Wa	ater Quality Compliance:
Do	es the PCSM/SR plan comply with requirements for volume control? 🛛 Yes 🔲 No
lf y	res, is at least 90% of the disturbed area controlled by a PCSM BMP? ☐ Yes ☐ No
	res, do you have the Standard PCSM Worksheet # 10 attached to show water quality compliance has achieved? Yes □ No
lf r	no, attach Standard PCSM Worksheets # 12 and #13 to show water quality compliance has achieved.
	PCSM/SR plan is not complying with the requirements for volume control, attach Standard PCSM Worksheets # 11, # 12 d #13 to show water quality compliance has achieved.
a.	PCSM/SR Plan Summary
	Provide a summary of proposed BMPs and their performance to manage PCSM/SR for the project.
	All sites will be restored to pre-existing conditions. By limiting the disturbed areas, limiting extent and duration of disturbance and performing site restoration, these practices will eliminate the net change in rate, volume and water quality after construction.
	Check all that apply ☐ PCSM BMPs ☐ SR BMPs
b.	Do you have any information regarding riparian buffer which differs from what was submitted in the Section G, Riparian Buffer?
	☐ Yes ⊠ No
	Explain:
C.	Thermal Impacts Analysis
	Explain how thermal impacts associated with this project were avoided, minimized, or mitigated. Thermal impacts have been minimized by limiting the disturbed area to the maximum extent practicable. By minimizing
	the extent of the disturbed area, vegetative clearing has been minimized. Thermal impacts will also be minimizing the duration of disturbance and reseeding and restoring vegetative growth as soon as possible.
d.	Off-Site Discharge Analysis.
	Does the activity propose any off-site discharges to areas other than surface waters? Yes No If yes, it is the applicant's responsibility to ensure that they have legal authority for any off-site discharge to neighboring properties.
	The Applicant must provide a demonstration in both the E&S and PCSM/SR Plans that the discharge will not cause erosion, damage, or a nuisance to off-site properties.
	See PCSM Narrative, Section XI, Page 15

The remainder of this section (Summary Table for Calculation and Measurement Data) does not need to be completed for areas of projects involving oil and gas activities authorized by Chapter 78 or Chapter 78a (well pads) or pipelines and other similar utility infrastructure which will be restored to meadow in good condition or better or existing conditions.

Watershed Name: Chester Creek						
Volume Control design storm frequency N/A Rainfall amount N/A inches	Pre-construction	Post Construction	Net Change			
Impervious area (acres)	N/A	N/A	N/A			
Volume of stormwater runoff (acrefeet) without planned stormwater BMPs	N/A	N/A	N/A			
Volume of stormwater runoff (acrefeet) with planned stormwater BMPs		N/A	N/A			
Stormwater discharge rate for the design frequency storm	Pre-construction	Post Construction	Net Change			
1) 2-Year/24-Hour	N/A	N/A	N/A			
2) 10-Year/24-Hour	N/A	N/A	N/A			
3) 50-year/24-Hour	N/A	N/A	N/A			
4) 100-year/24-Hour	N/A	N/A	N/A			

f. Summary Description of PCSM/SR BMPs SITE RESTORATION ONLY

In the lists below, check the BMPs identified in the PCSM Plan. The primary function(s) of the BMP listed in the functions column (infiltration/recharge; detention/retention; water quality). Additional functions may be added if applicable to that BMP. List the stormwater volume and area of runoff to be treated by each BMP type when calculations are required. If any BMP in the PCSM/SR Plan is not listed below, describe it in the space provided after "Other". A summary table with infiltration testing information (Attachment E, included in the NOI Instructions) must be submitted for all Bio-infiltration BMPs included in PCSM/SR plan.

For Rate control provide the volume of stormwater treated and acres treated for the 100-year/24-hour storm event.

For volume control and water quality provide the volume of stormwater treated and acres treated for the 2-year/24-hour storm event.

,			•	
ВМР	Function(s)	Purpose(s)	Volume of stormwater treated	Acres treated
Site Restoration ONLY				
Restore Site to Meadow in Good Condition or Better, or Existing Conditions	Infiltration/Recharge Detention/WQ Treatment	⊠ VC ⊠ RC ⊠ WQ		
Bio-infiltration areas	Infiltration/Recharge			
☐ Infiltration Trench		□ VC □ RC □ WQ		
☐ Infiltration Bed		☐ VC ☐ RC ☐ WQ		
☐ Infiltration Basin		□ VC □ RC □ WQ		
Rain Garden/ Bioretention		□ VC □ RC □ WQ		
☐ Infiltration Berm		UVC □RC □WQ		

			T	
Natural Area Conservation	Infiltration/Recharge			
☐ Streamside Buffer Zone		☐ VC ☐ RC ☐ WQ		
		☐ VC ☐ RC ☐ WQ		
Sensitive Area Buffer Zone		☐ VC ☐ RC ☐ WQ		
☐ Pre-Construction Drainage		□ VC □ RC □ WQ		
Pattern Intact				
Stormwater Retention	Detention/Retention			
☐ Constructed Wetlands		□ VC □ RC □ WQ		
☐ Wet Ponds		☐ VC ☐ RC ☐ WQ		
Retention Basin		☐ VC ☐ RC ☐ WQ		
Sediment and Pollutant	Water Quality			
Removal	Treatment			
□ Vegetated Filter Strips		☐ VC ☐ RC ☐ WQ		
☐ Compost Filter Sock		□ VC □ RC □ WQ		
☐ Detention Basins		☐ VC ☐ RC ☐ WQ		
Access Road Design	Infiltration/Recharge			
☐ Road Crowning		□ VC □ RC □ WQ		
Ditches		□ VC □ RC □ WQ		<u> </u>
☐ Turnouts		□ VC □ RC □ WQ		
☐ Culverts		□ VC □ RC □ WQ		<u> </u>
☐ Roadside Vegetated Filter		□ VC □ RC □ WQ		
Strips		∐ VC ∐ RC ∐ WQ		
Stormwater Energy Dissipaters	Infiltration/Recharge			
☐ Level Spreaders		☐ VC ☐ RC ☐ WQ		
☐ Riprap Aprons		☐ VC ☐ RC ☐ WQ		
☐ Upslope Diversions		☐ VC ☐ RC ☐ WQ		
Other		☐ VC ☐ RC ☐ WQ		
g. Critical PCSM Plan stage	S			
Identify and list critical stages	s of implementation of t	he PCSM Plan for which	a licensed professional	or designee shall
be present on site.				
License professional to be pre	esent during the site res	toration activities as noted	d the in Site Restoration	Schedule.

SECTION H. POST CONSTRUCTION STORMWATER MANAGEMENT (PCSM) AND/OR SITE RESTORATION(SR) PLAN See NOI Instructions for additional guidance with PCSM Plans

See NOI instructions for additional guidance with PCSM Plans						
PCSM/SR BMPs should be designed to use natural measures to eliminate pollution, infiltrate runoff, not require extensive construction/maintenance, promote pollutant reduction, and preserve the integrity of stream channels. All PCSM/SR BMPs proposed in the PCSM/SR Plan must be designed in accordance with Ch. 102, Ch. 78a for unconventional operations, Ch. 78 for conventional operations and the <i>Pennsylvania Stormwater Best Management Practices Manual (Stormwater BMP Manual)</i> (363-0300-002). If alternate design criteria are utilized for the proposed project, they must have prior approval by the Department, or the NOI Application will be returned to the Applicant.						
After const or existing				ped area will be restored	to meadow in good condition	on or better,
Include PC the site res			remaining impervio	us area. Also include a	map showing the proposed	contours of
required by	subsectio	n 'a' to section 'g' for	each stage (e.g. pa		t the stages and provide the ges to the amount of compa on to the drawings.	
	EXAMPL	E				
	Stage No			PCSM Plan	SR Plan	
	Stage 1	Adelphia Gatew	ay			
	Stage 2	Tilghman & Park	kway Laterals			
	Stage 3					
	Stage 4					
Is there a	Act 167 Consistency. Check those that apply. Is there an Act 167 Plan? ☑ Yes ☐ No ☑ The attached PCSM/SR Plan is consistent with an applicable approved Act 167 Plan. Sites: French Creek Blowdown Cromby Blowdown Schuylkill River Blowdown Paoli Pike Blowdown Paoli Pike Blowdown					
•	the follow Plan Name	ng for all approved A	Act 167 Stormwater Date Adopted	,	se additional sheets if neces onsistency Letter Included	sary)
	County-wi	de	March 27,2013		erification Report Included	
				report is provided. See Check those that apply.	NOI Instructions. The PCS	SM/SR Plan
1.	1. Act 167 Plan approvals on or after January 2005 – The attached PCSM/SR Plan, in its entirety, is consistent with all requirements pertaining to rate, volume, and water quality from an Act 167 Stormwater Management Plan approved by DEP on or after January 2005. Box 1 must be checked if a current, DEP approved Act 167 plan exists.					
2. A The PCSM/SR Plan meets the standard design criteria from sections 102.8(g)(2) and (3) and the Stormwater BMP Manual. For projects involving oil and gas activities authorized by a permit issued under Chapter 78 or Chapter 78a (well pads) or pipelines and other similar utility infrastructure, post construction stormwater management requirements are met for all areas that are restored to preconstruction conditions or to a condition of meadow in good condition or better. [Note: PCSM plans must meet both the volume and rate requirements in the regulations, which are provided in the 2 sections mentioned in this paragraph].						
3.	in 10 will b	2.8(g)(2)(iv) and 102	2.8(g)(3)(iii). Demoi tive than what is red	nstrate/explain in the sp quired in 102.8(g)(2) and	eveloped using approaches bace provided below how the strain of 102.8(g)(3) or will maintain	nis standard

SITE RESTORATION ONLY - MEET SECTION 102.8(g)(2) and (3)

PCS	SM/SR BMP Alternative Standards:
Has	the alternative BMP or design standard been approved by the Department?
	Yes
<u> </u>	No – Do not submit the ESCGP-3 application and see Section (H) of the NOI Instructions concerning the alternative BMP approval process.
Wat	ter Quality Compliance:
Doe	s the PCSM/SR plan comply with requirements for volume control? 🛛 Yes 🔲 No
If ye	es, is at least 90% of the disturbed area controlled by a PCSM BMP? Yes No
	es, do you have the Standard PCSM Worksheet # 10 attached to show water quality compliance has achieved? Yes
If no	o, attach Standard PCSM Worksheets # 12 and #13 to show water quality compliance has achieved.
	CSM/SR plan is not complying with the requirements for volume control, attach Standard PCSM Worksheets # 11, # 12 #13 to show water quality compliance has achieved.
a.	PCSM/SR Plan Summary
	Provide a summary of proposed BMPs and their performance to manage PCSM/SR for the project.
	All sites will be restored to pre-existing conditions. By limiting the disturbed areas, limiting extent and duration of disturbance and performing site restoration, these practices will eliminate the net change in rate, volume and water quality after construction.
	Check all that apply ☐ PCSM BMPs ☐ SR BMPs
	Do you have any information regarding riparian buffer which differs from what was submitted in the Section G, Riparian Buffer?
	☐ Yes ☐ No
	Explain:
	Thermal Impacts Applysis
	Thermal Impacts Analysis
	Explain how thermal impacts associated with this project were avoided, minimized, or mitigated. Thermal impacts have been minimized by limiting the disturbed area to the maximum extent practicable. By minimizing the extent of the disturbed area, vegetative clearing has been minimized. Thermal impacts will also be minimizing the duration of disturbance and reseeding and restoring vegetative growth as soon as possible.
d.	Off-Site Discharge Analysis.
	Does the activity propose any off-site discharges to areas other than surface waters? Yes No If yes, it is the applicant's responsibility to ensure that they have legal authority for any off-site discharge to neighboring properties.
	The Applicant must provide a demonstration in both the E&S and PCSM/SR Plans that the discharge will not cause erosion, damage, or a nuisance to off-site properties.
	See PCSM Narrative, Section XI, Page 15

The remainder of this section (Summary Table for Calculation and Measurement Data) does not need to be completed for areas of projects involving oil and gas activities authorized by Chapter 78 or Chapter 78a (well pads) or pipelines and other similar utility infrastructure which will be restored to meadow in good condition or better or existing conditions.

Watershed Name: French Creek					
Volume Control design storm frequency N/A Rainfall amount N/A inches	Pre-construction	Post Construction	Net Change		
Impervious area (acres)	N/A	N/A	N/A		
Volume of stormwater runoff (acrefeet) without planned stormwater BMPs	N/A	N/A	N/A		
Volume of stormwater runoff (acrefeet) with planned stormwater BMPs		N/A	N/A		
Stormwater discharge rate for the design frequency storm	Pre-construction	Post Construction	Net Change		
1) 2-Year/24-Hour	N/A	N/A	N/A		
2) 10-Year/24-Hour	N/A	N/A	N/A		
3) 50-year/24-Hour	N/A	N/A	N/A		
4) 100-year/24-Hour	N/A	N/A	N/A		
f Common Description of DCCM/CD DMDs OUT DECTOD ATION ONLY					

f. Summary Description of PCSM/SR BMPs SITE RESTORATION ONLY

In the lists below, check the BMPs identified in the PCSM Plan. The primary function(s) of the BMP listed in the functions column (infiltration/recharge; detention/retention; water quality). Additional functions may be added if applicable to that BMP. List the stormwater volume and area of runoff to be treated by each BMP type when calculations are required. If any BMP in the PCSM/SR Plan is not listed below, describe it in the space provided after "Other". A summary table with infiltration testing information (Attachment E, included in the NOI Instructions) must be submitted for all Bio-infiltration BMPs included in PCSM/SR plan.

For Rate control provide the volume of stormwater treated and acres treated for the 100-year/24-hour storm event.

For volume control and water quality provide the volume of stormwater treated and acres treated for the 2-year/24-hour storm event.

	,	•		
ВМР	Function(s)	Purpose(s)	Volume of stormwater treated	Acres treated
Site Restoration ONLY				
Restore Site to Meadow in Good Condition or Better, or Existing Conditions	Infiltration/Recharge Detention/WQ Treatment	⊠ VC ⊠ RC ⊠ WQ		
Bio-infiltration areas	Infiltration/Recharge			
☐ Infiltration Trench		□ VC □ RC □ WQ		
☐ Infiltration Bed		☐ VC ☐ RC ☐ WQ		
☐ Infiltration Basin		□ VC □ RC □ WQ		
Rain Garden/ Bioretention		□ VC □ RC □ WQ		
☐ Infiltration Berm		UVC □RC □WQ		

Natural Area Conservation	Infiltration/Recharge			
☐ Streamside Buffer Zone		☐ VC ☐ RC ☐ WQ		
		☐ VC ☐ RC ☐ WQ		
Sensitive Area Buffer Zone		☐ VC ☐ RC ☐ WQ		
☐ Pre-Construction Drainage		□ VC □ RC □ WQ		
Pattern Intact				
Stormwater Retention	Detention/Retention			
☐ Constructed Wetlands		□ VC □ RC □ WQ		
☐ Wet Ponds		☐ VC ☐ RC ☐ WQ		
Retention Basin		☐ VC ☐ RC ☐ WQ		
Sediment and Pollutant	Water Quality			
Removal	Treatment			
□ Vegetated Filter Strips		☐ VC ☐ RC ☐ WQ		
☐ Compost Filter Sock		□ VC □ RC □ WQ		
☐ Detention Basins		☐ VC ☐ RC ☐ WQ		
Access Road Design	Infiltration/Recharge			
☐ Road Crowning		□ VC □ RC □ WQ		
Ditches		□ VC □ RC □ WQ		<u> </u>
☐ Turnouts		□ VC □ RC □ WQ		
☐ Culverts		□ VC □ RC □ WQ		<u> </u>
☐ Roadside Vegetated Filter		□ VC □ RC □ WQ		
Strips		∐ VC ∐ RC ∐ WQ		
Stormwater Energy Dissipaters	Infiltration/Recharge			
☐ Level Spreaders		☐ VC ☐ RC ☐ WQ		
☐ Riprap Aprons		☐ VC ☐ RC ☐ WQ		
☐ Upslope Diversions		☐ VC ☐ RC ☐ WQ		
Other		☐ VC ☐ RC ☐ WQ		
g. Critical PCSM Plan stage	S			
Identify and list critical stages	of implementation of t	he PCSM Plan for which	a licensed professional	or designee shall
be present on site.	·		·	Ğ
License professional to be pre-	sent during the site rest	oration activities as noted	the in Site Restoration	Schedule.

The remainder of this section (Summary Table for Calculation and Measurement Data) does not need to be completed for areas of projects involving oil and gas activities authorized by Chapter 78 or Chapter 78a (well pads) or pipelines and other similar utility infrastructure which will be restored to meadow in good condition or better or existing conditions.

Watershed Name: Schuylkill River					
Volume Control design storm frequency N/A Rainfall amount N/A inches	Pre-construction	Post Construction	Net Change		
Impervious area (acres)	N/A	N/A	N/A		
Volume of stormwater runoff (acrefeet) without planned stormwater BMPs	N/A	N/A	N/A		
Volume of stormwater runoff (acrefeet) with planned stormwater BMPs		N/A	N/A		
Stormwater discharge rate for the design frequency storm	Pre-construction	Post Construction	Net Change		
1) 2-Year/24-Hour	N/A	N/A	N/A		
2) 10-Year/24-Hour	N/A	N/A	N/A		
3) 50-year/24-Hour	N/A	N/A	N/A		
4) 100-year/24-Hour	N/A	N/A	N/A		

f. Summary Description of PCSM/SR BMPs SITE RESTORATION ONLY

In the lists below, check the BMPs identified in the PCSM Plan. The primary function(s) of the BMP listed in the functions column (infiltration/recharge; detention/retention; water quality). Additional functions may be added if applicable to that BMP. List the stormwater volume and area of runoff to be treated by each BMP type when calculations are required. If any BMP in the PCSM/SR Plan is not listed below, describe it in the space provided after "Other". A summary table with infiltration testing information (Attachment E, included in the NOI Instructions) must be submitted for all Bio-infiltration BMPs included in PCSM/SR plan.

For Rate control provide the volume of stormwater treated and acres treated for the 100-year/24-hour storm event.

For volume control and water quality provide the volume of stormwater treated and acres treated for the 2-year/24-hour storm event.

,			•	
ВМР	Function(s)	Purpose(s)	Volume of stormwater treated	Acres treated
Site Restoration ONLY				
Restore Site to Meadow in Good Condition or Better, or Existing Conditions	Infiltration/Recharge Detention/WQ Treatment	⊠ VC ⊠ RC ⊠ WQ		
Bio-infiltration areas	Infiltration/Recharge			
☐ Infiltration Trench		□ VC □ RC □ WQ		
☐ Infiltration Bed		☐ VC ☐ RC ☐ WQ		
☐ Infiltration Basin		□ VC □ RC □ WQ		
Rain Garden/ Bioretention		□ VC □ RC □ WQ		
☐ Infiltration Berm		UVC □RC □WQ		

			T	
Natural Area Conservation	Infiltration/Recharge			
☐ Streamside Buffer Zone		☐ VC ☐ RC ☐ WQ		
		☐ VC ☐ RC ☐ WQ		
Sensitive Area Buffer Zone		☐ VC ☐ RC ☐ WQ		
☐ Pre-Construction Drainage		□ VC □ RC □ WQ		
Pattern Intact				
Stormwater Retention	Detention/Retention			
☐ Constructed Wetlands		□ VC □ RC □ WQ		
☐ Wet Ponds		□ VC □ RC □ WQ		
Retention Basin		☐ VC ☐ RC ☐ WQ		
Sediment and Pollutant	Water Quality			
Removal	Treatment			
□ Vegetated Filter Strips		☐ VC ☐ RC ☐ WQ		
☐ Compost Filter Sock		☐ VC ☐ RC ☐ WQ		
☐ Detention Basins		☐ VC ☐ RC ☐ WQ		
Access Road Design	Infiltration/Recharge			
☐ Road Crowning		□ VC □ RC □ WQ		
Ditches		□ VC □ RC □ WQ		<u> </u>
☐ Turnouts		□ VC □ RC □ WQ		
☐ Culverts		□ VC □ RC □ WQ		<u> </u>
☐ Roadside Vegetated Filter		□ VC □ RC □ WQ		
Strips				
Stormwater Energy Dissipaters	Infiltration/Recharge			
☐ Level Spreaders		☐ VC ☐ RC ☐ WQ		
☐ Riprap Aprons		☐ VC ☐ RC ☐ WQ		
☐ Upslope Diversions		☐ VC ☐ RC ☐ WQ		
Other		☐ VC ☐ RC ☐ WQ		
g. Critical PCSM Plan stage	S			
Identify and list critical stages	of implementation of t	he PCSM Plan for which	a licensed professional	or designee shall
be present on site.	·		·	
License professional to be pre-	sent during the site rest	oration activities as noted	the in Site Restoration	Schedule.

The remainder of this section (Summary Table for Calculation and Measurement Data) does not need to be completed for areas of projects involving oil and gas activities authorized by Chapter 78 or Chapter 78a (well pads) or pipelines and other similar utility infrastructure which will be restored to meadow in good condition or better or existing conditions.

Watershed Name: Stony Run					
Volume Control design storm frequency N/A Rainfall amount N/A inches	Pre-construction	Post Construction	Net Change		
Impervious area (acres)	N/A	N/A	N/A		
Volume of stormwater runoff (acrefeet) without planned stormwater BMPs	N/A	N/A	N/A		
Volume of stormwater runoff (acrefeet) with planned stormwater BMPs		N/A	N/A		
Stormwater discharge rate for the design frequency storm	Pre-construction	Post Construction	Net Change		
1) 2-Year/24-Hour	N/A	N/A	N/A		
2) 10-Year/24-Hour	N/A	N/A	N/A		
3) 50-year/24-Hour	N/A	N/A	N/A		
4) 100-year/24-Hour	N/A	N/A	N/A		

f. Summary Description of PCSM/SR BMPs SITE RESTORATION ONLY

In the lists below, check the BMPs identified in the PCSM Plan. The primary function(s) of the BMP listed in the functions column (infiltration/recharge; detention/retention; water quality). Additional functions may be added if applicable to that BMP. List the stormwater volume and area of runoff to be treated by each BMP type when calculations are required. If any BMP in the PCSM/SR Plan is not listed below, describe it in the space provided after "Other". A summary table with infiltration testing information (Attachment E, included in the NOI Instructions) must be submitted for all Bio-infiltration BMPs included in PCSM/SR plan.

For Rate control provide the volume of stormwater treated and acres treated for the 100-year/24-hour storm event.

For volume control and water quality provide the volume of stormwater treated and acres treated for the 2-year/24-hour storm event.

,			•	
ВМР	Function(s)	Purpose(s)	Volume of stormwater treated	Acres treated
Site Restoration ONLY				
Restore Site to Meadow in Good Condition or Better, or Existing Conditions	Infiltration/Recharge Detention/WQ Treatment	⊠ VC ⊠ RC ⊠ WQ		
Bio-infiltration areas	Infiltration/Recharge			
☐ Infiltration Trench		□ VC □ RC □ WQ		
☐ Infiltration Bed		☐ VC ☐ RC ☐ WQ		
☐ Infiltration Basin		□ VC □ RC □ WQ		
Rain Garden/ Bioretention		□ VC □ RC □ WQ		
☐ Infiltration Berm		UVC □RC □WQ		

			T	
Natural Area Conservation	Infiltration/Recharge			
☐ Streamside Buffer Zone		☐ VC ☐ RC ☐ WQ		
		☐ VC ☐ RC ☐ WQ		
Sensitive Area Buffer Zone		☐ VC ☐ RC ☐ WQ		
☐ Pre-Construction Drainage		□ VC □ RC □ WQ		
Pattern Intact				
Stormwater Retention	Detention/Retention			
☐ Constructed Wetlands		□ VC □ RC □ WQ		
☐ Wet Ponds		□ VC □ RC □ WQ		
Retention Basin		☐ VC ☐ RC ☐ WQ		
Sediment and Pollutant	Water Quality			
Removal	Treatment			
□ Vegetated Filter Strips		☐ VC ☐ RC ☐ WQ		
☐ Compost Filter Sock		□ VC □ RC □ WQ		
☐ Detention Basins		☐ VC ☐ RC ☐ WQ		
Access Road Design	Infiltration/Recharge			
☐ Road Crowning		□ VC □ RC □ WQ		
Ditches		□ VC □ RC □ WQ		<u> </u>
☐ Turnouts		□ VC □ RC □ WQ		
☐ Culverts		□ VC □ RC □ WQ		<u> </u>
☐ Roadside Vegetated Filter		□ VC □ RC □ WQ		
Strips				
Stormwater Energy Dissipaters	Infiltration/Recharge			
☐ Level Spreaders		☐ VC ☐ RC ☐ WQ		
☐ Riprap Aprons		☐ VC ☐ RC ☐ WQ		
☐ Upslope Diversions		☐ VC ☐ RC ☐ WQ		
Other		☐ VC ☐ RC ☐ WQ		
g. Critical PCSM Plan stage	S			
Identify and list critical stages	of implementation of t	he PCSM Plan for which	a licensed professional	or designee shall
be present on site.	·		·	
License professional to be pre-	sent during the site rest	oration activities as noted	the in Site Restoration	Schedule.

The remainder of this section (Summary Table for Calculation and Measurement Data) does not need to be completed for areas of projects involving oil and gas activities authorized by Chapter 78 or Chapter 78a (well pads) or pipelines and other similar utility infrastructure which will be restored to meadow in good condition or better or existing conditions.

Watershed Name: Ridley Creek					
Volume Control design storm frequency N/A Rainfall amount N/A inches	Pre-construction	Post Construction	Net Change		
Impervious area (acres)	N/A	N/A	N/A		
Volume of stormwater runoff (acrefeet) without planned stormwater BMPs	N/A	N/A	N/A		
Volume of stormwater runoff (acrefeet) with planned stormwater BMPs		N/A	N/A		
Stormwater discharge rate for the design frequency storm	Pre-construction	Post Construction	Net Change		
1) 2-Year/24-Hour	N/A	N/A	N/A		
2) 10-Year/24-Hour	N/A	N/A	N/A		
3) 50-year/24-Hour	N/A	N/A	N/A		
4) 100-year/24-Hour	N/A	N/A	N/A		

f. Summary Description of PCSM/SR BMPs SITE RESTORATION ONLY

In the lists below, check the BMPs identified in the PCSM Plan. The primary function(s) of the BMP listed in the functions column (infiltration/recharge; detention/retention; water quality). Additional functions may be added if applicable to that BMP. List the stormwater volume and area of runoff to be treated by each BMP type when calculations are required. If any BMP in the PCSM/SR Plan is not listed below, describe it in the space provided after "Other". A summary table with infiltration testing information (Attachment E, included in the NOI Instructions) must be submitted for all Bio-infiltration BMPs included in PCSM/SR plan.

For Rate control provide the volume of stormwater treated and acres treated for the 100-year/24-hour storm event.

For volume control and water quality provide the volume of stormwater treated and acres treated for the 2-year/24-hour storm event.

	,	•		
ВМР	Function(s)	Purpose(s)	Volume of stormwater treated	Acres treated
Site Restoration ONLY				
Restore Site to Meadow in Good Condition or Better, or Existing Conditions	Infiltration/Recharge Detention/WQ Treatment	⊠ VC ⊠ RC ⊠ WQ		
Bio-infiltration areas	Infiltration/Recharge			
☐ Infiltration Trench		□ VC □ RC □ WQ		
☐ Infiltration Bed		☐ VC ☐ RC ☐ WQ		
☐ Infiltration Basin		□ VC □ RC □ WQ		
Rain Garden/ Bioretention		□ VC □ RC □ WQ		
☐ Infiltration Berm		UVC □RC □WQ		

Natural Area Conservation	Infiltration/Recharge			
☐ Streamside Buffer Zone☐ Wetland Buffer Zone		□ VC □ RC □ WQ		
Sensitive Area Buffer Zone		UVC □RC □WQ		
☐ Pre-Construction Drainage				
Pattern Intact		□ VC □ RC □ WQ		
Stormwater Retention	Detention/Retention			
Constructed Wetlands		□ VC □ RC □ WQ		
☐ Wet Ponds		□ VC □ RC □ WQ		
Retention Basin		☐ VC ☐ RC ☐ WQ		
Sediment and Pollutant Removal	Water Quality Treatment			
□ Vegetated Filter Strips		□ VC □ RC □ WQ		
☐ Compost Filter Sock		☐ VC ☐ RC ☐ WQ		
☐ Detention Basins		□ VC □ RC □ WQ		
Access Road Design	Infiltration/Recharge			
Road Crowning		□ VC □ RC □ WQ		
Ditches		□ VC □ RC □ WQ		
Turnouts		□ VC □ RC □ WQ		
Culverts		□ VC □ RC □ WQ		
Roadside Vegetated Filter Strips		□ VC □ RC □ WQ		
Stormwater Energy Dissipaters	Infiltration/Recharge			
☐ Level Spreaders		☐ VC ☐ RC ☐ WQ		
Riprap Aprons		□ VC □ RC □ WQ		
Upslope Diversions		□ VC □ RC □ WQ		
Other		☐ VC ☐ RC ☐ WQ		
g. Critical PCSM Plan stage				
Identify and list critical stages be present on site.	s of implementation of t	he PCSM Plan for which	a licensed professional	or designee shall
License professional to be pre	sent during the site rest	oration activities as noted	I the in Site Restoration	Schedule.

SECTION H. POST CONSTRUCTION STORMWATER MANAGEMENT (PCSM) AND/OR SITE RESTORATION(SR) PLAN See NOI Instructions for additional guidance with PCSM Plans

See NOI Instructions for additional guidance with PCSM Plans					
PCSM/SR BMPs should be designed to use natural measures to eliminate pollution, infiltrate runoff, not require extensive construction/maintenance, promote pollutant reduction, and preserve the integrity of stream channels. All PCSM/SR BMPs proposed in the PCSM/SR Plan must be designed in accordance with Ch. 102, Ch. 78a for unconventional operations, Ch. 78 for conventional operations and the <i>Pennsylvania Stormwater Best Management Practices Manual (Stormwater BMP Manual)</i> (363-0300-002). If alternate design criteria are utilized for the proposed project, they must have prior approval by the Department, or the NOI Application will be returned to the Applicant.					
	ruction is co conditions?	mpleted, how much of the entire distur ☐ All ☑ Partial ☐ None	rbed area will be restored	d to meadow in good condition of	or better,
	SM narrativ toration plar	e and drawings for remaining impervion.	ous area. Also include a	map showing the proposed co	ntours of
required by	subsection	tages of the project prior to permit terr 'a' to section 'g' for each stage (e.g. p us areas). Upload a narrative for each	partial restoration or char	nges to the amount of compacte	
	EXAMPLE	≣			
	Stage No	Stage Name	PCSM Plan	SR Plan	
	Stage 1	Adelphia Gateway			
	Stage 2	Tilghman & Parkway Laterals			
	Stage 3				
	Stage 4				
	•		es: nsco Meter Station rcus Hook Compressor	Station	
☐ The a	attached PC	SM/SR Plan is consistent with an appli	icable approved Act 167	Plan.	
•		ng for all approved Act 167 Stormwater	•		<u>-</u> y)
	Plan Name	Date Adopted	C	onsistency Letter Included]
Naaman'	s Creek	<u>N/A</u>	V	erification Report Included]
		y letter is not required if a verification either sub paragraph 1, 2, or 3 below.		e NOI Instructions. The PCSM/	'SR Plan
1. Act 167 Plan approvals on or after January 2005 – The attached PCSM/SR Plan, in its entirety, is consistent with all requirements pertaining to rate, volume, and water quality from an Act 167 Stormwater Management Plan approved by DEP on or after January 2005. Box 1 must be checked if a current, DEP approved Act 167 plan exists.					
2. A The PCSM/SR Plan meets the standard design criteria from sections 102.8(g)(2) and (3) and the Stormwater BMP Manual. For projects involving oil and gas activities authorized by a permit issued under Chapter 78 or Chapter 78a (well pads) or pipelines and other similar utility infrastructure, post construction stormwater management requirements are met for all areas that are restored to preconstruction conditions or to a condition of meadow in good condition or better. [Note: PCSM plans must meet both the volume and rate requirements in the regulations, which are provided in the 2 sections mentioned in this paragraph].					
3.	in 102 will be	ative Design Standard – The attached 2.8(g)(2)(iv) and 102.8(g)(3)(iii). Demo e either more protective than what is re ng water quality and existing and desig	onstrate/explain in the spequired in 102.8(g)(2) and	pace provided below how this	standard

PCS	SM/SR BMP Alternative Standards:
Has	the alternative BMP or design standard been approved by the Department?
	Yes
	No – Do not submit the ESCGP-3 application and see Section (H) of the NOI Instructions concerning the alternative BMP approval process.
Wat	ter Quality Compliance:
Doe	es the PCSM/SR plan comply with requirements for volume control? 🛛 Yes 🔲 No
If ye	es, is at least 90% of the disturbed area controlled by a PCSM BMP? Yes No
	es, do you have the Standard PCSM Worksheet # 10 attached to show water quality compliance has achieved? Yes
If no	o, attach Standard PCSM Worksheets # 12 and #13 to show water quality compliance has achieved.
If P	CSM/SR plan is not complying with the requirements for volume control, attach Standard PCSM Worksheets # 11, # 12
and	#13 to show water quality compliance has achieved. See PCSM Narrative, Section VII & App. D.1
a.	PCSM/SR Plan Summary
The integ	Provide a summary of proposed BMPs and their performance to manage PCSM/SR for the project. following Best Management Practices (BMP), in accordance with Pennsylvania Stormwater BMP Manual, dated December 2006, have been grated into the design to reduce runoff volume, reduce peak rates and improve water quality. These structural BMPs will result in the rention or minimization of increased stormwater runoff rate, volume and/or changes in stormwater runoff. Implementing these controls will serve the integrity of stream channels and maintain and protect the physical, biological and chemical qualities of the receiving stream.
runo	egetated MRC BMP will be constructed at Marcus Hook Compressor Station. This structural BMP serves the functions of volume reduction, off quality and peak rate reduction. A subsurface infiltration bed (BMP 6.4.3, StormTank) will be constructed at Transco Meter Station. This ctural BMP serves the functions of volume reduction, runoff quality and peak rate reduction.
	Check all that apply ☐ PCSM BMPs ☐ SR BMPs
	Do you have any information regarding riparian buffer which differs from what was submitted in the Section G, Riparian Buffer?
	☐ Yes ☐ No
	Explain:
C.	Thermal Impacts Analysis
	Explain how thermal impacts associated with this project were avoided, minimized, or mitigated.
	Thermal impacts associated with the project will be minimized and/or mitigated through the incorporation of a vegetated MRC BMP. Runoff from the impervious areas will be directed to the BMPs where the travel time is increased to infiltrate and/or store runoff, reducing the quantity and temperature of the runoff.
	The subsurface basin at Transco Meter Station will temporarily store stormwater runoff beneath the surface, away from direct sunlight and will promote infiltration which will release water into the groundwater instead of discharging to the surface waters. The surface basin at Marcus Hook Compressor Station will be vegetated. Landscaping and vegetative cover will mimic natural ecosystems, resulting in a system that is resistant to climatic stresses. Additionally, the basin's outlet structure is designed to promote the slow release of outflow to the surface waters.
	Off-Site Discharge Analysis.
	Does the activity propose any off-site discharges to areas other than surface waters? ☐ Yes ☐ No
	If yes, it is the applicant's responsibility to ensure that they have legal authority for any off-site discharge to neighboring properties.
	The Applicant must provide a demonstration in both the E&S and PCSM/SR Plans that the discharge will not cause erosion, damage, or a nuisance to off-site properties. See PCSM Narrative, Section XI, Page 15
	coci com narativo, oconori xi, i age 10

The remainder of this section (Summary Table for Calculation and Measurement Data) does not need to be completed for areas of projects involving oil and gas activities authorized by Chapter 78 or Chapter 78a (well pads) or pipelines and other similar utility infrastructure which will be restored to meadow in good condition or better or existing conditions.

Watershed Name: Naamans Creek (Site - Marcus Hook Compressor Site)					
Volume Control design storm frequency 2-yr Rainfall amount 3.4 inches	Pre-construction	Post Construction	Net Change		
Impervious area (acres)	0.56	1.39	+0.83		
Volume of stormwater runoff (acrefeet) without planned stormwater BMPs	1.418	1.416	-0.002		
Volume of stormwater runoff (acrefeet) with planned stormwater BMPs		0.377	+0.375		
Stormwater discharge rate for the design frequency storm	Pre-construction	Post Construction	Net Change		
1) 2-Year/24-Hour	28.74	18.94	-9.80		
2) 10-Year/24-Hour	44.85	29.23	-15.62		
3) 50-year/24-Hour	67.52	43.18	-19.54		
4) 100-year/24-Hour	80.43	25.70	-23.15		

f. Summary Description of PCSM/SR BMPs

In the lists below, check the BMPs identified in the PCSM Plan. The primary function(s) of the BMP listed in the functions column (infiltration/recharge; detention/retention; water quality). Additional functions may be added if applicable to that BMP. List the stormwater volume and area of runoff to be treated by each BMP type when calculations are required. If any BMP in the PCSM/SR Plan is not listed below, describe it in the space provided after "Other". A summary table with infiltration testing information (Attachment E, included in the NOI Instructions) must be submitted for all Bio-infiltration BMPs included in PCSM/SR plan.

For Rate control provide the volume of stormwater treated and acres treated for the 100-year/24-hour storm event.

For volume control and water quality provide the volume of stormwater treated and acres treated for the 2-year/24-hour storm event.

, , , , ,					
ВМР	Function(s)	Purpose(s)	Volume of stormwater treated	Acres treated	
Site Restoration ONLY					
Restore Site to Meadow in Good Condition or Better, or Existing Conditions	Infiltration/Recharge Detention/WQ Treatment	□VC □RC □WQ			
Bio-infiltration areas	Infiltration/Recharge				
☐ Infiltration Trench		□ VC □ RC □ WQ			
☐ Infiltration Bed		☐ VC ☐ RC ☐ WQ			
☐ Infiltration Basin		☐ VC ☐ RC ☐ WQ			
Rain Garden/ Bioretention(MRC)		\boxtimes VC \boxtimes RC \boxtimes WQ	<u>0.377</u>	<u>2.20</u>	
☐ Infiltration Berm		□ VC □ RC □ WQ			

Natural Area Conservation Streamside Buffer Zone Wetland Buffer Zone Sensitive Area Buffer Zone Pre-Construction Drainage Pattern Intact	Infiltration/Recharge	VC RC WQ			
Stormwater Retention	Detention/Retention				
☐ Constructed Wetlands☐ Wet Ponds☐ Retention Basin		<pre></pre>	<u> </u>		
Sediment and Pollutant Removal	Water Quality Treatment				
☐ Vegetated Filter Strips☐ Compost Filter Sock☐ Detention Basins		<pre></pre>	<u>—</u>	<u>—</u>	
Access Road Design	Infiltration/Recharge				
 ☐ Road Crowning ☐ Ditches ☐ Turnouts ☐ Culverts ☐ Roadside Vegetated Filter Strips 		□ VC □ RC □ WQ □ VC □ RC □ WQ □ VC □ RC □ WQ □ VC □ RC □ WQ			
Stormwater Energy Dissipaters	Infiltration/Recharge				
Level Spreaders Riprap Aprons Upslope Diversions Other	3				
g. Critical PCSM Plan stages Identify and list critical stages of implementation of the PCSM Plan for which a licensed professional or designee shall be present on site.					
A licensed professional should	A licensed professional should be present and witness the following stages in construction:				
Excavation and final grading	Excavation and final grading of the BMP.				
Placement of geotextile and a	Placement of geotextile and aggregate within the BMP.				
Construction of the outlet structure and discharging of piping from the BMP.					

The remainder of this section (Summary Table for Calculation and Measurement Data) does not need to be completed for areas of projects involving oil and gas activities authorized by Chapter 78 or Chapter 78a (well pads) or pipelines and other similar utility infrastructure which will be restored to meadow in good condition or better or existing conditions.

Watershed Name: Naamans Creek (Site - Transco Meter Station Site)						
Volume Control design storm frequency 2-yr Rainfall amount 3.4 inches	Pre-construction	Post Construction	Net Change			
Impervious area (acres)	0.00	0.10	+0.10			
Volume of stormwater runoff (acrefeet) without planned stormwater BMPs	0.073	0.172	+0.099			
Volume of stormwater runoff (acrefeet) with planned stormwater BMPs		0.105	+0.006			
Stormwater discharge rate for the design frequency storm	Pre-construction	Post Construction	Net Change			
1) 2-Year/24-Hour	1.29	1.19	-0.10			
2) 10-Year/24-Hour	2.79	1.89	-0.90			
3) 50-year/24-Hour	5.20	3.93	-1.27			
4) 100-year/24-Hour	6.65	5.78	-0.87			

f. Summary Description of PCSM/SR BMPs

In the lists below, check the BMPs identified in the PCSM Plan. The primary function(s) of the BMP listed in the functions column (infiltration/recharge; detention/retention; water quality). Additional functions may be added if applicable to that BMP. List the stormwater volume and area of runoff to be treated by each BMP type when calculations are required. If any BMP in the PCSM/SR Plan is not listed below, describe it in the space provided after "Other". A summary table with infiltration testing information (Attachment E, included in the NOI Instructions) must be submitted for all Bio-infiltration BMPs included in PCSM/SR plan.

For Rate control provide the volume of stormwater treated and acres treated for the 100-year/24-hour storm event.

For volume control and water quality provide the volume of stormwater treated and acres treated for the 2-year/24-hour storm event.

ВМР	Function(s)	Purpose(s)	Volume of stormwater treated	Acres treated
Site Restoration ONLY				
Restore Site to Meadow in Good Condition or Better, or Existing Conditions	Infiltration/Recharge Detention/WQ Treatment	□VC □RC □WQ		
Bio-infiltration areas	Infiltration/Recharge			
☐ Infiltration Trench		□ VC □ RC □ WQ		
		⊠ VC ⊠ RC ⊠ WQ	<u>0.105</u>	<u>0.64</u>
☐ Infiltration Basin		□ VC □ RC □ WQ		
☐ Rain Garden/ Bioretention		☐ VC ☐ RC ☐ WQ		
☐ Infiltration Berm		□VC □RC □WQ		

Natural Area Conservation Streamside Buffer Zone Wetland Buffer Zone Sensitive Area Buffer Zone Pre-Construction Drainage Pattern Intact	Infiltration/Recharge	VC RC WQ			
Stormwater Retention	Detention/Retention				
☐ Constructed Wetlands☐ Wet Ponds☐ Retention Basin		<pre></pre>	<u> </u>		
Sediment and Pollutant Removal	Water Quality Treatment				
☐ Vegetated Filter Strips☐ Compost Filter Sock☐ Detention Basins		<pre></pre>	<u>—</u>	<u>—</u>	
Access Road Design	Infiltration/Recharge				
 ☐ Road Crowning ☐ Ditches ☐ Turnouts ☐ Culverts ☐ Roadside Vegetated Filter Strips 		□ VC □ RC □ WQ □ VC □ RC □ WQ □ VC □ RC □ WQ □ VC □ RC □ WQ			
Stormwater Energy Dissipaters	Infiltration/Recharge				
Level Spreaders Riprap Aprons Upslope Diversions Other	3				
g. Critical PCSM Plan stages Identify and list critical stages of implementation of the PCSM Plan for which a licensed professional or designee shall be present on site.					
A licensed professional should	A licensed professional should be present and witness the following stages in construction:				
Excavation and final grading	Excavation and final grading of the BMP.				
Placement of geotextile and a	Placement of geotextile and aggregate within the BMP.				
Construction of the outlet structure and discharging of piping from the BMP.					

SECTION H. POST CONSTRUCTION STORMWATER MANAGEMENT (PCSM) AND/OR SITE RESTORATION(SR) PLAN See NOI Instructions for additional guidance with PCSM Plans

		See NOI Instructions	tor additional gi	lidance with PC	SIVI Plans	
constructio proposed i for conver <i>Manual)</i> (3	n/maintenanc n the PCSM/S ntional operat 63-0300-002)	be designed to use nature, promote pollutant reduces Plan must be designed in the pennsylvania. If alternate design criteria Application will be returned	tion, and preserven accordance with accordance with a Stormwater Beare utilized for the	e the integrity of n Ch. 102, Ch. 78 est <i>Management</i>	stream channels. All PCS a for unconventional opera Practices Manual (Storn	M/SR BMPs tions, Ch. 78 nwater BMP
	ruction is com conditions?	pleted, how much of the er ☑ All Partial	tire disturbed are Ione	a will be restored	to meadow in good condit	ion or better,
	SM narrative toration plan.	and drawings for remaining	g impervious area	ı. Also include a ı	map showing the proposed	I contours of
required by	subsection 'a	ages of the project prior to particular in the particular is to section 'g' for each states areas). Upload a narrative	ge (e.g. partial re	storation or chan	ges to the amount of comp	
	EXAMPLE					
	Stage No	Stage Name	PCSN	l Plan	SR Plan	
	Stage 1	Adelphia Gateway			\boxtimes	1
	Stage 2	Tilghman & Parkway Late	erals		\boxtimes	
	Stage 3					1
	Stage 4					1
Is there a The a Complete Act 167 F	an Act 167 Pla attached PCS	M/SR Plan is consistent wit for all approved Act 167 St Date Ad	ormwater Manag opted	Meter Station eek Blowdown oproved Act 167 F ement Plans. (Us		ssary) □ ⊠
		letter is not required if a v ther sub paragraph 1, 2, or			NOI Instructions. The PC	SM/SR Plan
1.	with all	Plan approvals on or after requirements pertaining to proved by DEP on or after sts.	rate, volume, and	water quality from	m an Act 167 Stormwater I	Management
2. The PCSM/SR Plan meets the standard design criteria from sections 102.8(g)(2) and (3) and the Stormwater BMP Manual. For projects involving oil and gas activities authorized by a permit issued under Chapter 78 or Chapter 78a (well pads) or pipelines and other similar utility infrastructure, post construction stormwater management requirements are met for all areas that are restored to preconstruction conditions or to a condition of meadow in good condition or better. [Note: PCSM plans must meet both the volume and rate requirements in the regulations, which are provided in the 2 sections mentioned in this paragraph].						
3. Alternative Design Standard – The attached PCSM/SR Plan was developed using approaches as provided in 102.8(g)(2)(iv) and 102.8(g)(3)(iii). Demonstrate/explain in the space provided below how this standard will be either more protective than what is required in 102.8(g)(2) and 102.8(g)(3) or will maintain and protect existing water quality and existing and designated uses.						

SITE RESTORATION ONLY - MEET SECTION 102.8(g)(2) and (3)

РС	SM/SR BMP Alternative Standards:
Ha	s the alternative BMP or design standard been approved by the Department?
	Yes
	No – Do not submit the ESCGP-3 application and see Section (H) of the NOI Instructions concerning the alternative BMP approval process.
Wa	ater Quality Compliance:
Do	es the PCSM/SR plan comply with requirements for volume control? 🛛 Yes 🔲 No
lf y	res, is at least 90% of the disturbed area controlled by a PCSM BMP? Yes No
	res, do you have the Standard PCSM Worksheet # 10 attached to show water quality compliance has achieved? Yes □ No
lf n	no, attach Standard PCSM Worksheets # 12 and #13 to show water quality compliance has achieved.
	PCSM/SR plan is not complying with the requirements for volume control, attach Standard PCSM Worksheets # 11, # 12 d #13 to show water quality compliance has achieved.
a.	PCSM/SR Plan Summary
	Provide a summary of proposed BMPs and their performance to manage PCSM/SR for the project.
	All sites will be restored to pre-existing conditions. By limiting the disturbed areas, limiting extent and duration of disturbance and performing site restoration, these practices will eliminate the net change in rate, volume and water quality after construction.
	Check all that apply ☐ PCSM BMPs ☐ SR BMPs
b.	Do you have any information regarding riparian buffer which differs from what was submitted in the Section G, Riparian Buffer?
	☐ Yes No
	Explain:
C.	Thermal Impacts Analysis
	Explain how thermal impacts associated with this project were avoided, minimized, or mitigated. Thermal impacts have been minimized by limiting the disturbed area to the maximum extent practicable. By minimizing the extent of the disturbed area, vegetative clearing has been minimized. Thermal impacts will also be minimizing the duration of disturbance and reseeding and restoring vegetative growth as soon as possible.
d.	Off-Site Discharge Analysis.
	Does the activity propose any off-site discharges to areas other than surface waters? 🖂 Yes 🔲 No If yes, it is the applicant's responsibility to ensure that they have legal authority for any off-site discharge to neighboring properties.
	The Applicant must provide a demonstration in both the E&S and PCSM/SR Plans that the discharge will not cause erosion, damage, or a nuisance to off-site properties.
	See PCSM Narrative, Section XI, Page 15

The remainder of this section (Summary Table for Calculation and Measurement Data) does not need to be completed for areas of projects involving oil and gas activities authorized by Chapter 78 or Chapter 78a (well pads) or pipelines and other similar utility infrastructure which will be restored to meadow in good condition or better or existing conditions.

Watershed Name: Perkiomen Creek						
Volume Control design storm frequency N/A Rainfall amount N/A inches	Pre-construction	Post Construction	Net Change			
Impervious area (acres)	N/A	N/A	N/A			
Volume of stormwater runoff (acrefeet) without planned stormwater BMPs	N/A	N/A	N/A			
Volume of stormwater runoff (acrefeet) with planned stormwater BMPs		N/A	N/A			
Stormwater discharge rate for the design frequency storm	Pre-construction	Post Construction	Net Change			
1) 2-Year/24-Hour	N/A	N/A	N/A			
2) 10-Year/24-Hour	N/A	N/A	N/A			
3) 50-year/24-Hour	N/A	N/A	N/A			
4) 100-year/24-Hour	N/A	N/A	N/A			
f. Summary Description of PCSM	f. Summary Description of PCSM/SR BMPs SITE RESTORATION ONLY					

In the lists below, check the BMPs identified in the PCSM Plan. The primary function(s) of the BMP listed in the functions column (infiltration/recharge; detention/retention; water quality). Additional functions may be added if applicable to that BMP. List the stormwater volume and area of runoff to be treated by each BMP type when calculations are required. If any BMP in the PCSM/SR Plan is not listed below, describe it in the space provided after "Other". A summary table with infiltration testing information (Attachment E, included in the NOI Instructions) must be submitted for all Bio-infiltration BMPs included in PCSM/SR plan.

For Rate control provide the volume of stormwater treated and acres treated for the 100-year/24-hour storm event.

For volume control and water quality provide the volume of stormwater treated and acres treated for the 2-year/24-hour storm event.

ВМР	Function(s)	Purpose(s)	Volume of stormwater treated	Acres treated
Site Restoration ONLY				
Restore Site to Meadow in Good Condition or Better, or Existing Conditions	Infiltration/Recharge Detention/WQ Treatment	□VC □RC □WQ		
Bio-infiltration areas	Infiltration/Recharge			
☐ Infiltration Trench		□ VC □ RC □ WQ		
☐ Infiltration Bed		□ VC □ RC □ WQ		
☐ Infiltration Basin		□ VC □ RC □ WQ		
Rain Garden/ Bioretention		☐ VC ☐ RC ☐ WQ		
☐ Infiltration Berm		□VC □RC □WQ		

8000-PM-OOGM0006 9/2018 Notice of Intent

			•	
Natural Area Conservation Streamside Buffer Zone Wetland Buffer Zone Sensitive Area Buffer Zone Pre-Construction Drainage Pattern Intact	Infiltration/Recharge	VC RC WQ VC RC WQ VC RC WQ VC RC WQ VC RC WQ		
Stormwater Retention	Detention/Retention			
☐ Constructed Wetlands☐ Wet Ponds☐ Retention Basin		<pre></pre>	<u> </u>	
Sediment and Pollutant Removal	Water Quality Treatment			
☐ Vegetated Filter Strips☐ Compost Filter Sock☐ Detention Basins		<pre></pre>	<u>—</u>	
Access Road Design	Infiltration/Recharge			
 ☐ Road Crowning ☐ Ditches ☐ Turnouts ☐ Culverts ☐ Roadside Vegetated Filter Strips 		□ VC □ RC □ WQ □ VC □ RC □ WQ □ VC □ RC □ WQ □ VC □ RC □ WQ		
Stormwater Energy Dissipaters	Infiltration/Recharge			
Level Spreaders Riprap Aprons Upslope Diversions Other	Č	<pre></pre>		
g. Critical PCSM Plan stage	S			
Identify and list critical stages be present on site.	of implementation of t	he PCSM Plan for which	a licensed professional	or designee shall
License professional to be pre	esent during the site res	toration activities as noted	d the in Site Restoration	Schedule.

SECTION H. POST CONSTRUCTION STORMWATER MANAGEMENT (PCSM) AND/OR SITE RESTORATION(SR) PLAN See NOI Instructions for additional guidance with PCSM Plans

See NOT instructions for additional guidance with PCSM Plans					
PCSM/SR BMPs should be designed to use natural measures to eliminate pollution, infiltrate runoff, not require extensive construction/maintenance, promote pollutant reduction, and preserve the integrity of stream channels. All PCSM/SR BMPs proposed in the PCSM/SR Plan must be designed in accordance with Ch. 102, Ch. 78a for unconventional operations, Ch. 78 for conventional operations and the <i>Pennsylvania Stormwater Best Management Practices Manual (Stormwater BMP Manual)</i> (363-0300-002). If alternate design criteria are utilized for the proposed project, they must have prior approval by the Department, or the NOI Application will be returned to the Applicant.					
	ruction is cor conditions?	npleted, how much of the entire distur $oxtime All oxtime $ Partial $ oxtime $ None	bed area will be restored	to meadow in good condition	n or better,
	SM narrative toration plan	e and drawings for remaining imperviol.	ous area. Also include a	map showing the proposed of	contours of
required by	subsection	ages of the project prior to permit tern 'a' to section 'g' for each stage (e.g. p us areas). Upload a narrative for each	artial restoration or chan	ges to the amount of compac	
	EXAMPLE				
	Stage No	Stage Name	PCSM Plan	SR Plan	
	Stage 1	Adelphia Gateway	\boxtimes	\boxtimes	
	Stage 2	Tilghman & Parkway Laterals			
	Stage 3				
	Stage 4				
Act 167 (Consistency	r. Check those that apply.			
	n Act 167 Pl	one.	ertown Compressor St	ation	
☐ The a	attached PCS	SM/SR Plan is consistent with an appli	cable approved Act 167	Plan.	
Complete	the following	g for all approved Act 167 Stormwater	Management Plans. (U	se additional sheets if necess	sary)
·		onsistency Letter Included			
<u>Tohicko</u> ı	n Creek	<u>February 28, 2002</u>	<u>2</u>	erification Report Included	\boxtimes
		/ letter is not required if a verification ither sub paragraph 1, 2, or 3 below.		NOI Instructions. The PCS	M/SR Plan
1. Act 167 Plan approvals on or after January 2005 – The attached PCSM/SR Plan, in its entirety, is consistent with all requirements pertaining to rate, volume, and water quality from an Act 167 Stormwater Management Plan approved by DEP on or after January 2005. Box 1 must be checked if a current, DEP approved Act 167 plan exists.					
2. The PCSM/SR Plan meets the standard design criteria from sections 102.8(g)(2) and (3) and the Stormwater BMP Manual. For projects involving oil and gas activities authorized by a permit issued under Chapter 78 or Chapter 78a (well pads) or pipelines and other similar utility infrastructure, post construction stormwater management requirements are met for all areas that are restored to preconstruction conditions or to a condition of meadow in good condition or better. [Note: PCSM plans must meet both the volume and rate requirements in the regulations, which are provided in the 2 sections mentioned in this paragraph].					
3. Alternative Design Standard – The attached PCSM/SR Plan was developed using approaches as provided in 102.8(g)(2)(iv) and 102.8(g)(3)(iii). Demonstrate/explain in the space provided below how this standard will be either more protective than what is required in 102.8(g)(2) and 102.8(g)(3) or will maintain and protect existing water quality and existing and designated uses.					

PCSM/SR BMP Alternative Standards:	
Has the alternative BMP or design standard been approved by t	he Department?
☐ Yes	
□ No – Do not submit the ESCGP-3 application and see Se BMP approval process.	ction (H) of the NOI Instructions concerning the alternative
Water Quality Compliance:	
Does the PCSM/SR plan comply with requirements for volume of	control? 🛛 Yes 🔲 No
If yes, is at least 90% of the disturbed area controlled by a PCS	M BMP? ☐ Yes ⊠ No
If yes, do you have the Standard PCSM Worksheet # 10 attache ☐ Yes ☐ No	ed to show water quality compliance has achieved?
If no, attach Standard PCSM Worksheets # 12 and #13 to show	water quality compliance has achieved.
If PCSM/SR plan is not complying with the requirements for voland #13 to show water quality compliance has achieved.	ume control, attach Standard PCSM Worksheets # 11, # 12 See PCSM Narrative, Section VII & App. D.1
a. PCSM/SR Plan Summary	
Provide a summary of proposed BMPs and their performance. The following Best Management Practices (BMP), in accordance with Pennsylvania Storr design to reduce runoff volume, reduce peak rates and improve water quality. These stru runoff rate, volume and/or changes in stormwater runoff. Implementing these controls will physical, biological and chemical qualities of the receiving stream.	nwater BMP Manual, dated December 2006, have been integrated into the ctural BMPs will result in the prevention or minimization of increased stormwater
A non-vegetated managed release concept (MRC) BMP will be installed at Quakertown C storage chambers (Storm-tank). A stormwater swale with check dams will be installed up functions of volume reduction, runoff quality and peak rate reduction. Check all that apply PCSM BMPs SR BMPs	
b. Do you have any information regarding riparian buffer which Buffer?	n differs from what was submitted in the Section G, Riparian
☐ Yes ⊠ No	
Explain:	
c. Thermal Impacts Analysis	
Explain how thermal impacts associated with this project we	ere avoided, minimized, or mitigated.
Thermal impacts associated with the project will be minimiz subsurface MRC basin and a stormwater swale with check to the BMPs where the travel time is increased to store run	dams. Runoff from the impervious areas will be directed
The subsurface basin at Quakertown Compressor Station values, away from direct sunlight and will promote the slow	
d. Off-Site Discharge Analysis.	
Does the activity propose any off-site discharges to areas of If yes, it is the applicant's responsibility to ensure that they properties.	ther than surface waters? Yes No have legal authority for any off-site discharge to neighboring
	&S and PCSM/SR Plans that the discharge will not cause
erosion, damage, or a nuisance to off-site properties.	See PCSM Narrative, Section XI, Page 15

e. Summary Table for Supporting Calculation and Measurement Data (See NOI Instructions for additional guidance with this section)

The remainder of this section (Summary Table for Calculation and Measurement Data) does not need to be completed for areas of projects involving oil and gas activities authorized by Chapter 78 or Chapter 78a (well pads) or pipelines and other similar utility infrastructure which will be restored to meadow in good condition or better or existing conditions.

Watershed Name: Tohickon Creek (Site - Quakertown Compressor Site)				
Volume Control design storm frequency 2-yr Rainfall amount 3.16 inches	Pre-construction	Post Construction	Net Change	
Impervious area (acres)	0.00	0.32	+0.32	
Volume of stormwater runoff (acrefeet) without planned stormwater BMPs	0.194	0.287	+0.093	
Volume of stormwater runoff (acrefeet) with planned stormwater BMPs		0.192	-0.098	
Stormwater discharge rate for the design frequency storm	Pre-construction	Post Construction	Net Change	
1) 2-Year/24-Hour	2.94	2.21	-0.73	
2) 10-Year/24-Hour	5.36	3.45	-1.91	
3) 50-year/24-Hour	8.87	5.15	-3.72	
4) 100-year/24-Hour	10.88	7.47	-4.78	

f. Summary Description of PCSM/SR BMPs

In the lists below, check the BMPs identified in the PCSM Plan. The primary function(s) of the BMP listed in the functions column (infiltration/recharge; detention/retention; water quality). Additional functions may be added if applicable to that BMP. List the stormwater volume and area of runoff to be treated by each BMP type when calculations are required. If any BMP in the PCSM/SR Plan is not listed below, describe it in the space provided after "Other". A summary table with infiltration testing information (Attachment E, included in the NOI Instructions) must be submitted for all Bio-infiltration BMPs included in PCSM/SR plan.

For Rate control provide the volume of stormwater treated and acres treated for the 100-year/24-hour storm event.

For volume control and water quality provide the volume of stormwater treated and acres treated for the 2-year/24-hour storm event.

Key for BMP purpose(s): VC = Volume Control; RC = Rate Control; and WQ = Water Quality

ВМР	Function(s)	Purpose(s)	Volume of stormwater treated	Acres treated
Site Restoration ONLY				
Restore Site to Meadow in Good Condition or Better, or Existing Conditions	Infiltration/Recharge Detention/WQ Treatment	□VC □RC □WQ		
Bio-infiltration areas	Infiltration/Recharge			
☐ Infiltration Trench		□ VC □ RC □ WQ		
☐ Infiltration Bed		□ VC □ RC □ WQ		
☐ Infiltration Basin		☐ VC ☐ RC ☐ WQ		
☐ Rain Garden/ Bioretention		☐ VC ☐ RC ☐ WQ		
☐ Infiltration Berm		□VC □RC □WQ		

			1		
Natural Area Conservation Streamside Buffer Zone Wetland Buffer Zone	Infiltration/Recharge				
☐ Sensitive Area Buffer Zone☐ Pre-Construction DrainagePattern Intact		UC RC WQ VC RC WQ			
Stormwater Retention	Detention/Retention				
☐ Constructed Wetlands☐ Wet Ponds☑ Retention Basin (MRC)		<pre></pre>	<u></u> <u>0.192</u>	1.09	
Sediment and Pollutant Removal	Water Quality Treatment				
☐ Vegetated Filter Strips☐ Compost Filter Sock☐ Detention Basins		<pre></pre>	<u> </u>		
Access Road Design	Infiltration/Recharge				
 ☐ Road Crowning ☐ Ditches ☐ Turnouts ☐ Culverts ☐ Roadside Vegetated Filter Strips 		VC RC WQ VC RC WQ VC RC WQ VC RC WQ VC RC WQ			
Stormwater Energy Dissipaters	Infiltration/Recharge				
☐ Level Spreaders☐ Riprap Aprons☐ Upslope Diversions☐ Other	,	 □ VC □ RC □ WQ □ VC □ RC □ WQ □ VC □ RC □ WQ 			
g. Critical PCSM Plan stage Identify and list critical stages be present on site.		he PCSM Plan for which	a licensed professional	or designee shall	
A licensed professional should be present and witness the following stages in construction:					
Excavation and final grading of the BMP.					
Placement of geotextile and a	Placement of geotextile and aggregate within the BMP.				
Construction of the outlet structure and discharging of piping from the BMP.					

SECTION H. POST CONSTRUCTION STORMWATER MANAGEMENT (PCSM) AND/OR SITE RESTORATION(SR) PLAN See NOI Instructions for additional guidance with PCSM Plans

			See NOI Instructions for additi	onal guidance with PC	CSM Plans	
PCSM/SR BMPs should be designed to use natural measures to eliminate pollution, infiltrate runoff, not require extensive construction/maintenance, promote pollutant reduction, and preserve the integrity of stream channels. All PCSM/SR BMPs proposed in the PCSM/SR Plan must be designed in accordance with Ch. 102, Ch. 78a for unconventional operations, Ch. 78 for conventional operations and the <i>Pennsylvania Stormwater Best Management Practices Manual (Stormwater BMP Manual)</i> (363-0300-002). If alternate design criteria are utilized for the proposed project, they must have prior approval by the Department, or the NOI Application will be returned to the Applicant.						
After const or existing			oleted, how much of the entire disturb	ped area will be restored	d to meadow in good conditio	n or better,
Include PC the site res			and drawings for remaining impervio	us area. Also include a	map showing the proposed	contours of
required by	/ subsect	ion 'a'	ges of the project prior to permit term to section 'g' for each stage (e.g. pa areas). Upload a narrative for each a	artial restoration or char	nges to the amount of compa	
	EXAMF	PLE				
	Stage N		Stage Name	PCSM Plan	SR Plan	
	Stage 1		Adelphia Gateway	\boxtimes		
	Stage 2		Tilghman & Parkway Laterals			
	Stage 3	}				
	Stage 4	•				
Is there a	Act 167 Consistency. Check those that apply. Is there an Act 167 Plan? ✓ Yes ✓ No Site: Mainline Valve 1					
			1/SR Plan is consistent with an applic	• •		
Complete Act 167 F		_	for all approved Act 167 Stormwater Date Adopted	•	lse additional sheets if neces: Consistency Letter Included	sary) □
V-H 0 1		erification Report Included	\boxtimes			
Note: A consistency letter is not required if a verification report is provided. See NOI Instructions. The PCSM/SR Plan must satisfy either sub paragraph 1, 2, or 3 below. Check those that apply.				:M/SR Plan		
1. Act 167 Plan approvals on or after January 2005 – The attached PCSM/SR Plan, in its entirety, is consistent with all requirements pertaining to rate, volume, and water quality from an Act 167 Stormwater Management Plan approved by DEP on or after January 2005. Box 1 must be checked if a current, DEP approved Act 167 plan exists.						
2. The PCSM/SR Plan meets the standard design criteria from sections 102.8(g)(2) and (3) and the Stormwater BMP Manual. For projects involving oil and gas activities authorized by a permit issued under Chapter 78 or Chapter 78a (well pads) or pipelines and other similar utility infrastructure, post construction stormwater management requirements are met for all areas that are restored to preconstruction conditions or to a condition of meadow in good condition or better. [Note: PCSM plans must meet both the volume and rate requirements in the regulations, which are provided in the 2 sections mentioned in this paragraph].						
 a. Alternative Design Standard – The attached PCSM/SR Plan was developed using approaches as provided in 102.8(g)(2)(iv) and 102.8(g)(3)(iii). Demonstrate/explain in the space provided below how this standard will be either more protective than what is required in 102.8(g)(2) and 102.8(g)(3) or will maintain and protect existing water quality and existing and designated uses. 						

SITE RESTORATION ONLY - MEET SECTION 102.8(g)(2) and (3)

PCS	SM/SR BMP Alternative Standards:
Has	s the alternative BMP or design standard been approved by the Department?
	Yes
	No – Do not submit the ESCGP-3 application and see Section (H) of the NOI Instructions concerning the alternative BMP approval process.
Wa	ter Quality Compliance:
Doe	es the PCSM/SR plan comply with requirements for volume control? 🛛 Yes 🔲 No
If ye	es, is at least 90% of the disturbed area controlled by a PCSM BMP? Yes No
	es, do you have the Standard PCSM Worksheet # 10 attached to show water quality compliance has achieved? Yes
If no	o, attach Standard PCSM Worksheets # 12 and #13 to show water quality compliance has achieved.
	CSM/SR plan is not complying with the requirements for volume control, attach Standard PCSM Worksheets # 11, # 12 I #13 to show water quality compliance has achieved.
a.	PCSM/SR Plan Summary
	Provide a summary of proposed BMPs and their performance to manage PCSM/SR for the project.
	All sites will be restored to pre-existing conditions. By limiting the disturbed areas, limiting extent and duration of disturbance and performing site restoration, these practices will eliminate the net change in rate, volume and water quality after construction.
	Check all that apply ☐ PCSM BMPs ☐ SR BMPs
b.	Do you have any information regarding riparian buffer which differs from what was submitted in the Section G, Riparian Buffer?
	☐ Yes ⊠ No
	Explain:
	Thermal Impacts Analysis
O.	Explain how thermal impacts associated with this project were avoided, minimized, or mitigated.
	Thermal impacts associated with this project were avoided, minimized, or minimized. Thermal impacts have been minimized by limiting the disturbed area to the maximum extent practicable. By minimizing the extent of the disturbed area, vegetative clearing has been minimized. Thermal impacts will also be minimizing the duration of disturbance and reseeding and restoring vegetative growth as soon as possible.
d.	Off-Site Discharge Analysis.
	Does the activity propose any off-site discharges to areas other than surface waters? \boxtimes Yes \square No If yes, it is the applicant's responsibility to ensure that they have legal authority for any off-site discharge to neighboring properties.
	The Applicant must provide a demonstration in both the E&S and PCSM/SR Plans that the discharge will not cause erosion, damage, or a nuisance to off-site properties.
	See PCSM Narrative, Section XI, Page 15

e. Summary Table for Supporting Calculation and Measurement Data (See NOI Instructions for additional guidance with this section)

The remainder of this section (Summary Table for Calculation and Measurement Data) does not need to be completed for areas of projects involving oil and gas activities authorized by Chapter 78 or Chapter 78a (well pads) or pipelines and other similar utility infrastructure which will be restored to meadow in good condition or better or existing conditions.

Watershed Name: Valley Creek			
Volume Control design storm frequency N/A Rainfall amount N/A inches	Pre-construction	Post Construction	Net Change
Impervious area (acres)	N/A	N/A	N/A
Volume of stormwater runoff (acrefeet) without planned stormwater BMPs	N/A	N/A	N/A
Volume of stormwater runoff (acrefeet) with planned stormwater BMPs		N/A	N/A
Stormwater discharge rate for the design frequency storm	Pre-construction	Post Construction	Net Change
1) 2-Year/24-Hour	N/A	N/A	N/A
2) 10-Year/24-Hour	N/A	N/A	N/A
3) 50-year/24-Hour	N/A	N/A	N/A
4) 100-year/24-Hour	N/A	N/A	N/A
	WAR BUTE DE		

f. Summary Description of PCSM/SR BMPs SITE RESTORATION ONLY

In the lists below, check the BMPs identified in the PCSM Plan. The primary function(s) of the BMP listed in the functions column (infiltration/recharge; detention/retention; water quality). Additional functions may be added if applicable to that BMP. List the stormwater volume and area of runoff to be treated by each BMP type when calculations are required. If any BMP in the PCSM/SR Plan is not listed below, describe it in the space provided after "Other". A summary table with infiltration testing information (Attachment E, included in the NOI Instructions) must be submitted for all Bio-infiltration BMPs included in PCSM/SR plan.

For Rate control provide the volume of stormwater treated and acres treated for the 100-year/24-hour storm event.

For volume control and water quality provide the volume of stormwater treated and acres treated for the 2-year/24-hour storm event.

Key for BMP purpose(s): VC = Volume Control; RC = Rate Control; and WQ = Water Quality

,			•	
ВМР	Function(s)	Purpose(s)	Volume of stormwater treated	Acres treated
Site Restoration ONLY				
Restore Site to Meadow in Good Condition or Better, or Existing Conditions	Infiltration/Recharge Detention/WQ Treatment	⊠ VC ⊠ RC ⊠ WQ		
Bio-infiltration areas	Infiltration/Recharge			
☐ Infiltration Trench		□ VC □ RC □ WQ		
☐ Infiltration Bed		☐ VC ☐ RC ☐ WQ		
☐ Infiltration Basin		□ VC □ RC □ WQ		
Rain Garden/ Bioretention		□ VC □ RC □ WQ		
☐ Infiltration Berm		UVC □RC □WQ		

8000-PM-OOGM0006 9/2018 Notice of Intent

Natural Area Conservation	Infiltration/Recharge			
☐ Streamside Buffer Zone		□ VC □ RC □ WQ		
		□ VC □ RC □ WQ		
Sensitive Area Buffer Zone		□ VC □ RC □ WQ		
☐ Pre-Construction Drainage		□ VC □ RC □ WQ		
Pattern Intact				
Stormwater Retention	Detention/Retention			
☐ Constructed Wetlands		□ VC □ RC □ WQ		
		□ VC □ RC □ WQ		
Retention Basin		☐ VC ☐ RC ☐ WQ		
Sediment and Pollutant	Water Quality			
Removal	Treatment			
□ Vegetated Filter Strips		☐ VC ☐ RC ☐ WQ		
☐ Compost Filter Sock		☐ VC ☐ RC ☐ WQ		
☐ Detention Basins		☐ VC ☐ RC ☐ WQ		
Access Road Design	Infiltration/Recharge			
☐ Road Crowning		□ VC □ RC □ WQ		
Ditches		□ VC □ RC □ WQ		<u> </u>
☐ Turnouts		□ VC □ RC □ WQ		
☐ Culverts		□ VC □ RC □ WQ		<u> </u>
☐ Roadside Vegetated Filter		□ VC □ RC □ WQ		
Strips				
Stormwater Energy Dissipaters	Infiltration/Recharge			
☐ Level Spreaders		□ VC □ RC □ WQ		
☐ Riprap Aprons		☐ VC ☐ RC ☐ WQ		
☐ Upslope Diversions		☐ VC ☐ RC ☐ WQ		
Other		☐ VC ☐ RC ☐ WQ		
g. Critical PCSM Plan stage	s			
Identify and list critical stages	of implementation of t	he PCSM Plan for which	a licensed professional	or designee shall
be present on site.	•		·	
License professional to be pr	esent during the site res	storation activities as note	d the in Site Restoration	n Schedule.

CHESTER CREEK

SECTION I. ANTIDEGRADATION ANALYSIS

This section must be completed where earth disturbance activities will be conducted in the watershed of a surface water with an existing or designated use of exceptional value or high quality pursuant to Chapter 93 (relating to water quality standards), projects where any part is located in an exceptional value wetland in accordance with 25 Pa. Code § 105.17, and projects where any part is located in the watershed of an impaired surface water where the cause of impairment is identified as siltation.

Part 1 - NONDISCHARGE ALTERNATIVES EVALUATION

- Minimize accelerated erosion and sedimentation during the earth disturbance activity
- Achieve no net change from pre-development to post-development volume, rate and concentration of pollutants in

water quality	st-development volume, rate and concentration of pollutants in
E & S Plan	PCSM/SR Plan
Check off the environmentally sound nondischarge Best Management Practices (BMPs) listed below to be used prior to, during, and after earth disturbance activities that have been incorporated into your E & S Plan based on the site analysis. For non-discharge BMPs not checked, provide an explanation of why they were not utilized. Also for BMPs checked, provide an explanation of why they were utilized. (Provide the analysis and attach additional sheets if necessary)	Check off the environmentally sound nondischarge Best Management Practices (BMPs) listed below to be used after construction that have been incorporated into the PCSM/SR Plan based on your site analysis. For non-discharge BMPs not checked, provide an explanation of why they were not utilized. Also for BMPs checked, provide an explanation of why they were utilized. (Provide the analysis and attach additional sheets if necessary)
Nondischarge BMPs Alternative Siting Alternative location Alternative configuration Alternative location of discharge Limited Disturbed Area Limiting Extent & Duration of Disturbance (Phasing, Sequencing) Riparian Buffers (150 ft. min.) Riparian Forest Buffer (150 ft. min.) Other	Nondischarge BMPs Alternative Siting Alternative location Alternative configuration Alternative location of discharge Low Impact Development (LID / BSD) Riparian Buffers (150 ft. min.) Riparian Forest Buffer (150 ft. min.) Infiltration Water Reuse Other Site Restoration
Will the non-discharge alternative BMPs eliminate the net change in rate, volume and quality during construction? ☑ Yes ☐ No	Will the non-discharge alternative BMPs eliminate the net change in rate, volume and quality after construction? ☐ Yes ☐ No
If yes, antidegradation analysis is complete.	If yes, antidegradation analysis is complete.

PERKIOMEN CREEK

SECTION I. ANTIDEGRADATION ANALYSIS

This section must be completed where earth disturbance activities will be conducted in the watershed of a surface water with an existing or designated use of exceptional value or high quality pursuant to Chapter 93 (relating to water quality standards), projects where any part is located in an exceptional value wetland in accordance with 25 Pa. Code § 105.17, and projects where any part is located in the watershed of an impaired surface water where the cause of impairment is identified as siltation.

Part 1 - NONDISCHARGE ALTERNATIVES EVALUATION

- Minimize accelerated erosion and sedimentation during the earth disturbance activity
- Achieve no net change from pre-development to post-development volume, rate and concentration of pollutants in

water quality	st-development volume, rate and concentration of pollutants in
E & S Plan	PCSM/SR Plan
Check off the environmentally sound nondischarge Best Management Practices (BMPs) listed below to be used prior to, during, and after earth disturbance activities that have been incorporated into your E & S Plan based on the site analysis. For non-discharge BMPs not checked, provide an explanation of why they were not utilized. Also for BMPs checked, provide an explanation of why they were utilized. (Provide the analysis and attach additional sheets if necessary)	Check off the environmentally sound nondischarge Best Management Practices (BMPs) listed below to be used after construction that have been incorporated into the PCSM/SR Plan based on your site analysis. For non-discharge BMPs not checked, provide an explanation of why they were not utilized. Also for BMPs checked, provide an explanation of why they were utilized. (Provide the analysis and attach additional sheets if necessary)
Nondischarge BMPs Alternative Siting Alternative location Alternative configuration Alternative location of discharge Limited Disturbed Area Limiting Extent & Duration of Disturbance (Phasing, Sequencing) Riparian Buffers (150 ft. min.) Riparian Forest Buffer (150 ft. min.) Other	Nondischarge BMPs Alternative Siting Alternative location Alternative configuration Alternative location of discharge Low Impact Development (LID / BSD) Riparian Buffers (150 ft. min.) Riparian Forest Buffer (150 ft. min.) Infiltration Water Reuse Other Site Restoration
Will the non-discharge alternative BMPs eliminate the net change in rate, volume and quality during construction? ☑ Yes ☐ No	Will the non-discharge alternative BMPs eliminate the net change in rate, volume and quality after construction? ☐ Yes ☐ No
If yes, antidegradation analysis is complete.	If yes, antidegradation analysis is complete.

RIDLEY CREEK

SECTION I. ANTIDEGRADATION ANALYSIS

This section must be completed where earth disturbance activities will be conducted in the watershed of a surface water with an existing or designated use of exceptional value or high quality pursuant to Chapter 93 (relating to water quality standards), projects where any part is located in an exceptional value wetland in accordance with 25 Pa. Code § 105.17, and projects where any part is located in the watershed of an impaired surface water where the cause of impairment is identified as siltation.

Part 1 - NONDISCHARGE ALTERNATIVES EVALUATION

- Minimize accelerated erosion and sedimentation during the earth disturbance activity
- Achieve no not change from are development to nost-development volume, rate and concentration of pollutants in

water quality	st-development volume, rate and concentration of pollutarits in
E & S Plan	PCSM/SR Plan
Check off the environmentally sound nondischarge Best Management Practices (BMPs) listed below to be used prior to, during, and after earth disturbance activities that have been incorporated into your E & S Plan based on the site analysis. For non-discharge BMPs not checked, provide an explanation of why they were not utilized. Also for BMPs checked, provide an explanation of why they were utilized. (Provide the analysis and attach additional sheets if necessary)	Check off the environmentally sound nondischarge Best Management Practices (BMPs) listed below to be used after construction that have been incorporated into the PCSM/SR Plan based on your site analysis. For non-discharge BMPs not checked, provide an explanation of why they were not utilized. Also for BMPs checked, provide an explanation of why they were utilized. (Provide the analysis and attach additional sheets if necessary)
Nondischarge BMPs Alternative Siting Alternative location Alternative configuration Alternative location of discharge Limited Disturbed Area Limiting Extent & Duration of Disturbance (Phasing, Sequencing) Riparian Buffers (150 ft. min.) Riparian Forest Buffer (150 ft. min.) Other	Nondischarge BMPs Alternative Siting Alternative location Alternative configuration Alternative location of discharge Low Impact Development (LID / BSD) Riparian Buffers (150 ft. min.) Riparian Forest Buffer (150 ft. min.) Infiltration Water Reuse Other Site Restoration
Will the non-discharge alternative BMPs eliminate the net change in rate, volume and quality during construction? ☐ Yes ☐ No	Will the non-discharge alternative BMPs eliminate the net change in rate, volume and quality after construction? ☐ Yes ☐ No
If yes, antidegradation analysis is complete.	If yes, antidegradation analysis is complete.

SCHUYLKILL RIVER

SECTION I. ANTIDEGRADATION ANALYSIS

This section must be completed where earth disturbance activities will be conducted in the watershed of a surface water with an existing or designated use of exceptional value or high quality pursuant to Chapter 93 (relating to water quality standards), projects where any part is located in an exceptional value wetland in accordance with 25 Pa. Code § 105.17, and projects where any part is located in the watershed of an impaired surface water where the cause of impairment is identified as siltation.

Part 1 - NONDISCHARGE ALTERNATIVES EVALUATION

- Minimize accelerated erosion and sedimentation during the earth disturbance activity
- Achieve no net change from pre-development to post-development volume, rate and concentration of pollutants in

water quality	st-development volume, rate and concentration of pollutants in
E & S Plan	PCSM/SR Plan
Check off the environmentally sound nondischarge Best Management Practices (BMPs) listed below to be used prior to, during, and after earth disturbance activities that have been incorporated into your E & S Plan based on the site analysis. For non-discharge BMPs not checked, provide an explanation of why they were not utilized. Also for BMPs checked, provide an explanation of why they were utilized. (Provide the analysis and attach additional sheets if necessary)	Check off the environmentally sound nondischarge Best Management Practices (BMPs) listed below to be used after construction that have been incorporated into the PCSM/SR Plan based on your site analysis. For non-discharge BMPs not checked, provide an explanation of why they were not utilized. Also for BMPs checked, provide an explanation of why they were utilized. (Provide the analysis and attach additional sheets if necessary)
Nondischarge BMPs Alternative Siting Alternative location Alternative configuration Alternative location of discharge Limited Disturbed Area Limiting Extent & Duration of Disturbance (Phasing, Sequencing) Riparian Buffers (150 ft. min.) Riparian Forest Buffer (150 ft. min.) Other	Nondischarge BMPs Alternative Siting Alternative location Alternative configuration Alternative location of discharge Low Impact Development (LID / BSD) Riparian Buffers (150 ft. min.) Riparian Forest Buffer (150 ft. min.) Infiltration Water Reuse Other Site Restoration
Will the non-discharge alternative BMPs eliminate the net change in rate, volume and quality during construction? ☑ Yes ☐ No	Will the non-discharge alternative BMPs eliminate the net change in rate, volume and quality after construction? ☐ Yes ☐ No
If yes, antidegradation analysis is complete.	If yes, antidegradation analysis is complete.

STONY RUN

SECTION I. ANTIDEGRADATION ANALYSIS

This section must be completed where earth disturbance activities will be conducted in the watershed of a surface water with an existing or designated use of exceptional value or high quality pursuant to Chapter 93 (relating to water quality standards), projects where any part is located in an exceptional value wetland in accordance with 25 Pa. Code § 105.17, and projects where any part is located in the watershed of an impaired surface water where the cause of impairment is identified as siltation.

Part 1 - NONDISCHARGE ALTERNATIVES EVALUATION

- Minimize accelerated erosion and sedimentation during the earth disturbance activity
- Achieve no not change from are development to nost-development volume, rate and concentration of pollutants in

water quality	st-development volume, rate and concentration of pollutarits in
E & S Plan	PCSM/SR Plan
Check off the environmentally sound nondischarge Best Management Practices (BMPs) listed below to be used prior to, during, and after earth disturbance activities that have been incorporated into your E & S Plan based on the site analysis. For non-discharge BMPs not checked, provide an explanation of why they were not utilized. Also for BMPs checked, provide an explanation of why they were utilized. (Provide the analysis and attach additional sheets if necessary)	Check off the environmentally sound nondischarge Best Management Practices (BMPs) listed below to be used after construction that have been incorporated into the PCSM/SR Plan based on your site analysis. For non-discharge BMPs not checked, provide an explanation of why they were not utilized. Also for BMPs checked, provide an explanation of why they were utilized. (Provide the analysis and attach additional sheets if necessary)
Nondischarge BMPs Alternative Siting Alternative location Alternative configuration Alternative location of discharge Limited Disturbed Area Limiting Extent & Duration of Disturbance (Phasing, Sequencing) Riparian Buffers (150 ft. min.) Riparian Forest Buffer (150 ft. min.) Other	Nondischarge BMPs Alternative Siting Alternative location Alternative configuration Alternative location of discharge Low Impact Development (LID / BSD) Riparian Buffers (150 ft. min.) Riparian Forest Buffer (150 ft. min.) Infiltration Water Reuse Other Site Restoration
Will the non-discharge alternative BMPs eliminate the net change in rate, volume and quality during construction? ☐ Yes ☐ No	Will the non-discharge alternative BMPs eliminate the net change in rate, volume and quality after construction? ☐ Yes ☐ No
If yes, antidegradation analysis is complete.	If yes, antidegradation analysis is complete.

TOHICKON CREEK

SECTION I. ANTIDEGRADATION ANALYSIS

This section must be completed where earth disturbance activities will be conducted in the watershed of a surface water with an existing or designated use of exceptional value or high quality pursuant to Chapter 93 (relating to water quality standards), projects where any part is located in an exceptional value wetland in accordance with 25 Pa. Code § 105.17, and projects where any part is located in the watershed of an impaired surface water where the cause of impairment is identified as siltation.

Part 1 - NONDISCHARGE ALTERNATIVES EVALUATION

- Minimize accelerated erosion and sedimentation during the earth disturbance activity
- Achieve no net change from pre-development to post-development volume, rate and concentration of pollutants in

water quality								
E & S Plan	PCSM/SR Plan							
Check off the environmentally sound nondischarge Best Management Practices (BMPs) listed below to be used prior to, during, and after earth disturbance activities that have been incorporated into your E & S Plan based on the site analysis. For non-discharge BMPs not checked, provide an explanation of why they were not utilized. Also for BMPs checked, provide an explanation of why they were utilized. (Provide the analysis and attach additional sheets if necessary)	Check off the environmentally sound nondischarge Best Management Practices (BMPs) listed below to be used after construction that have been incorporated into the PCSM/SI Plan based on your site analysis. For non-discharge BMP not checked, provide an explanation of why they were not utilized. Also for BMPs checked, provide an explanation of why they were utilized. (Provide the analysis and attacked additional sheets if necessary)							
Nondischarge BMPs Alternative Siting Alternative location Alternative configuration Alternative location of discharge Limited Disturbed Area Limiting Extent & Duration of Disturbance (Phasing, Sequencing) Riparian Buffers (150 ft. min.) Riparian Forest Buffer (150 ft. min.) Other	Nondischarge BMPs Alternative Siting Alternative location Alternative configuration Alternative location of discharge Low Impact Development (LID / BSD) Riparian Buffers (150 ft. min.) Riparian Forest Buffer (150 ft. min.) Infiltration Water Reuse Other Site Restoration							
Will the non-discharge alternative BMPs eliminate the net change in rate, volume and quality during construction? ☐ Yes ☐ No	Will the non-discharge alternative BMPs eliminate the net change in rate, volume and quality after construction? ☐ Yes ☐ No							
If yes, antidegradation analysis is complete. If no, proceed to Part 2.	If yes, antidegradation analysis is complete. If no, proceed to Part 2.							

TOHICKON CREEK

PART 2 - ANTIDEGRADATION BEST AVAILABLE COMBINATION OF TECHNOLOGIES (ABACT)

If the net change in stormwater discharge from or after construction is not fully managed by nondischarge BMPs, the applicant must utilize ABACT BMPs to manage the difference. The Applicant must specify whether the discharge will occur during construction, post-construction or both, and identify the technologies that will be used to ensure that the discharge will be a non-degrading discharge. ABACT BMPs include but are not limited to:

E & S Plan	PCSM/SR Plan							
☑ Treatment BMPs: ☐ Sediment basin with skimmer ☐ Sediment basin ratio of 4:1 or greater (flow length to basin width) ☐ Sediment basin with 4-7 day detention ☐ Flocculants ☐ Compost Filter Socks ☐ Compost Filter Sock Sediment Basin ☐ RCE w/ Wash Rack ☐ Land disposal: ☐ Vegetated filters ☐ Riparian buffers <150ft.	Treatment BMPs:							
Are the ABACT BMPs selected sufficient to minimize E&S discharges to the extent that existing or designated surface water uses are protected? Yes No If yes, Antidegradation analysis is complete. If no, NOI Application will be returned to the Applicant.	Are the ABACT BMPs selected sufficient to achieve no net change and assure that existing or designated surface water uses are protected? Yes No If yes, Antidegradation analysis is complete. If no, NOI Application will be returned to the Applicant.							

VALLEY CREEK

SECTION I. ANTIDEGRADATION ANALYSIS

This section must be completed where earth disturbance activities will be conducted in the watershed of a surface water with an existing or designated use of exceptional value or high quality pursuant to Chapter 93 (relating to water quality standards), projects where any part is located in an exceptional value wetland in accordance with 25 Pa. Code § 105.17, and projects where any part is located in the watershed of an impaired surface water where the cause of impairment is identified as siltation.

Part 1 - NONDISCHARGE ALTERNATIVES EVALUATION

- Minimize accelerated erosion and sedimentation during the earth disturbance activity
- Achieve no net change from pre-development to post-development volume, rate and concentration of pollutants in

water quality	st-development volume, rate and concentration of pollutants in
E & S Plan	PCSM/SR Plan
Check off the environmentally sound nondischarge Best Management Practices (BMPs) listed below to be used prior to, during, and after earth disturbance activities that have been incorporated into your E & S Plan based on the site analysis. For non-discharge BMPs not checked, provide an explanation of why they were not utilized. Also for BMPs checked, provide an explanation of why they were utilized. (Provide the analysis and attach additional sheets if necessary)	Check off the environmentally sound nondischarge Best Management Practices (BMPs) listed below to be used after construction that have been incorporated into the PCSM/SR Plan based on your site analysis. For non-discharge BMPs not checked, provide an explanation of why they were not utilized. Also for BMPs checked, provide an explanation of why they were utilized. (Provide the analysis and attach additional sheets if necessary)
Nondischarge BMPs Alternative Siting Alternative location Alternative configuration Alternative location of discharge Limited Disturbed Area Limiting Extent & Duration of Disturbance (Phasing, Sequencing) Riparian Buffers (150 ft. min.) Riparian Forest Buffer (150 ft. min.) Other	Nondischarge BMPs Alternative Siting Alternative location Alternative configuration Alternative location of discharge Low Impact Development (LID / BSD) Riparian Buffers (150 ft. min.) Riparian Forest Buffer (150 ft. min.) Infiltration Water Reuse Other Site Restoration
Will the non-discharge alternative BMPs eliminate the net change in rate, volume and quality during construction? ☑ Yes ☐ No	Will the non-discharge alternative BMPs eliminate the net change in rate, volume and quality after construction? ☐ Yes ☐ No
If yes, antidegradation analysis is complete.	If yes, antidegradation analysis is complete.

SECTION J. COMPLIANCE HISTORY REVIEW								
Is/was the applicant(s) in violation of any Department regulation, order, schedule of compliance or permit or in violation of any department regulated activities within the past five years? \square Yes \square No								
	escription of the violation, the compliance schedule (including mpliance status. (Attach additional information on a separate							
Permit Program or Activity: Brief Description of non-compliance:	Permit Number (if applicable):							
Steps taken to achieve compliance	Date(s) compliance achieved							
Current Compliance Status: In-Compliance	☐ In Non-Compliance							
If in non-compliance, attach schedule for achieving compliance	e.							

SECTION K. CERTIFICATION BY PERSON PREPARING E&S AND PCSM/SR PLANS I do hereby certify to the best of my knowledge, information, and belief, that the Erosion and Sediment Control and PCSM/Site Restoration Plans are true and correct, represent actual field conditions, and are in accordance with the 25 Pa. Code Chapters 78/78a and 102 of the Department's rules and regulations. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment. Print Name Shiny Mathew Signature Professional Seal Company JMT

Company JMT

Address 1600 Market Street, Suite 520

Phone 215-496-4780

Most Recent DEP Training Attended Location Date

E&S - Permitting Workshop Montgomery County 5/2016

e-Mail Address smathew@jmt.com

EXPEDITED REVIEW PROCESS

In addition to the certification required above, applicants using the expedited permit review process must attach an E&S and PCSM/Site Restoration Plans developed and sealed by a licensed professional engineer, surveyor or professional geologist. The plans shall contain the following certification:

I do hereby certify to the best of my knowledge, information, and belief, that the E & S Control and PCSM/SR BMPs are true and correct, represent actual field conditions and are in accordance with the 25 Pa. Code Chapters 78 / 78a and 102 of the Department's rules and regulations. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment.

SECTION L. APPLICANT CERTIFICATION

Applicant Certification

I certify under penalty of law, as provided by 18 Pa. C.S.A. § 4904, that this application and all related attachments were prepared by me or under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my own knowledge and on inquiry of the person or persons who manage the system or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate and complete. The responsible official's signature also verifies that the activity is eligible to participate in the ESCGP, and that the applicant agrees to abide by the terms and conditions of the permit. BMP's, E&S Plan, PPC Plan, PCSM Plan, and other controls are being or will be, implemented to ensure that water quality standards and effluent limits are attained.

I grant permission to the agencies responsible for the permitting of this work, or their duly authorized representative to enter the project site for inspection purposes. I will abide by the conditions of the permit if issued and will not begin work prior to permit issuance.

(For individuals no indication of title is necessary, choose the box below. All others proceed to the next paragraph)

☐ Individual; proceed to signature portion.

I hereby certify under penalty of law, as provided by 18 Pa. C.S.A. § 4904, that I am the person who is responsible for decision-making regarding environmental compliance functions for Adelphia Gateway, LLC, the manager of one or more manufacturing, production, or operating facilities of the applicant and am authorized to make management decisions which govern the operation of regulated facility including having explicit or implicit duty of making major capital investment recommendations, and initiating and directing other comprehensive measures to assure the applicant's long term environmental compliance with environmental laws and regulations; and I am responsible for ensuring that the necessary systems are established or actions taken to gather complete and accurate information for permit application requirements.

(choose one of the following; not applicable for individuals):	
ig ig The responsible corporate officer $ig $ president $ig ig $ vice preside	
☐ treasure of C Entity name	Corporation/Company
-	
☐ The ☐ member or ☐ manager of Entity name	LLC
·	
The general partner of partnership/LP. Entity name	/LLP
☐ The principal executive officer or ranking elected official of	Municipality/State/Federal/other public agency
	ity name
Power of Attorney/delegation of contractual authority (documents be provided) for	mentation supporting delegation of contracting authority
Entity name	
Mark F. Valori, Vice President	
Print Name and Title of Applicant	Print Name and Title of Co-Applicant (if applicable)
7 Mic Name and Mile 617 Applicant	This rame and this of so ripplicant (if applicable)
Aw)	
Signature of Applicant	Signature of Co-Applicant
03/11/2019	
Date Application Signed	Date Application Signed
Notarization Sworn to and subscribed to before me this	Commonwealth of Pennsylvania
	·
114 day of March, 20 19	County of
Jani S. Castello	My Commission expires
Notary Public	
AFFIX SEAL	
LORI S. CASTELLO	4)
ID# 2353137	
NOTARY PUBLIC STATE OF NEW JERSEY	
MY COMMISSION EXPIRES 12-4-21	
	2.
at the second se	
	1)

SECTION M. ADDITIONAL CONTACT INFORMATION										
Contact's Last Name	First Name	MI	Phone							
			FAX							
Mailing Address	City		State	ZIP + 4						
e-Mail Address	·		•	•						

Stormwater BMP Information Chart 5.B revised March 15, 2016																		
	Infiltration Information Drainage Information BMP Information																	
			Infilte	ration Info	rmation		Drainage Information					BMP Information						
	Proposed Structural BMPs (site specific)	Measured Infiltration Rate ⁹	Factor of Safety Min. of 2	Design Infiltration Rate	Dewatering Time ¹ hrs.	Elevation of Limiting Zone - Water Table, Bedrock, etc. ²	Total Drainage Area to BMP sg. ft	Total Impervious Drainage Area to BMP sq. ft.	Infiltration BMP Surface Area sq. ft.	Total Drainage Area Loading Ratio ⁶	Impervious Area Loading Ratio ⁷	Volume of Runoff Tributary to BMP During the 2yr/24hr Design Storm ⁵	Calculated Infiltration Volume (from storms up to and including 2yr/24hr)	Calculated Managed Volume (from storms up to and including 2yr/24hr) ⁸	Maximum water surface elevation in BMP from 2yr storm ³	Infiltration Elevation Bottom of Bed/ Basin ³	Elevation of Infiltration Test ⁴	Elevation of E&S Sediment Basin Bottom (if applies)
BMP 6.4.1	Pervious Pavement w/ Infiltration Bed							,										
BMP 6.4.2 BMP 6.4.3 BMP 6.4.4 BMP 6.4.5	Infiltration Basin Subsurface Infiltration Bed Transco Infiltration Trench Rain Garden/Bioretention	o N/A	N/A	N/A	N/A	N/A	27,793	4,668	2075	13	2	4,590.0	N/A	N/A	N/A	N/A	N/A	N/A
BMP 6.4.6	Dry Well / Seepage Pit																	
Other	Vegetated MRC BMP Marcus Hool Non-vegetated MRC: Underground storage chambers Quakertown		N/A N/A	N/A N/A	N/A N/A	N/A N/A	95,504 47,775	21,048 13,960	16833 3875	6 12	1	18,403.0 8,366.0	N/A N/A	N/A N/A	N/A N/A	N/A N/A	N/A N/A	N/A N/A
BMP 6.4.7 BMP 6.4.8 BMP 6.4.9 BMP 6.4.10	Constructed Filter Vegetated Swale Vegetated Filter Strip Infilt. Berm & Ret. Grading						,,,,	. 3,000	3370	.2	,	5,500.0						

All information should be based on the 2-year/24-hour storm

Provide page numbers from the stormwater narrative identifying the location of the above information.

Any deviations from the recommendations above should be adequately justified by a qualified professional and included with the application.

NOTE: This chart is for summary purposes only and should be consistent with all design calculations and worksheets.

BMPs at Marcus Hook and Quakertown are MRC basins due to poor infiltration results.

¹ Can include active infiltration time - dewatering time should not exceed 72 hours after the 2-year/24-hour storm

² Depth to limiting zone is recommended to be at least 2 ft below infiltration testing elevation/proposed infiltration elevation.

³ A maximum of 2 feet of Hydraulic head is recommended.

⁴ Provide supporting field notes/documenation from soil evaluation.

⁵ This value should be greater than or equal to the Volume to be Infiltrated or Managed by the BMP.

⁶ A maximum of 8:1 is recommended.

⁷ A maximum of 5:1 is recommended; however, in carbonate geology areas, a maximum of 3:1 is recommended.

⁸ Calculated runoff volume that is managed in ways other than infiltration to address 25 PA Code Ch 102.8(g)(2)

⁹ The infiltration testing information should be located on the plan view of the PCSM Plan and should include infiltration test elevation and rate.