Version: 2.0 Effective Date: Jul-20-2015 Previous Date: Feb-24-2015



# SAFETY DATA SHEET

# STEAMATE\* LSA1900

## 1. Identification

Product identifier STEAMATE LSA1900

Other means of identification None.

**Recommended use** Steam condensate treatment.

**Recommended restrictions** None known.

### Company/undertaking identification

GE Betz, Inc. 4636 Somerton Road Trevose, PA 19053 T 215 355 3300, F 215 953 5524

### **Emergency telephone**

(800) 877 1940

## 2. Hazard(s) identification

Physical hazards	Flammable liquids	Category 3
Health hazards	Acute toxicity, oral	Category 4
	Acute toxicity, dermal	Category 3
	Acute toxicity, inhalation	Category 3
	Skin corrosion/irritation	Category 1
	Serious eye damage/eye irritation	Category 1
	Reproductive toxicity (fertility)	Category 2

Not classified.

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

## OSHA defined hazards

Label elements



Signal word Danger

**Hazard statement** Flammable liquid and vapor. Harmful if swallowed. Toxic in contact with skin. Causes severe skin burns and eye damage. Causes serious eye damage. Toxic if inhaled. May cause respiratory irritation.

Suspected of damaging fertility.

## Precautionary statement Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting// equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

**Response** If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all

contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor/. Take off immediately all contaminated clothing and wash it before reuse. In case of fire: Use dry chemical,

carbon dioxide or foam to extinguish.

**Storage** Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep

cool. Store locked up.

**Disposal** Dispose of contents/container to an approved facility.

Hazard(s) not otherwise classified

(HNOC)

None known.

Supplemental information

None

## 3. Composition/information on ingredients

#### **Mixtures**

Components	CAS#	Percent
Dimethylaminoethanol (DMAE)	108-01-0	60 - 80
Cyclohexylamine	108-91-8	10 - 20

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Composition comments

Information for specific product ingredients as required by the U.S. OSHA HAZARD COMMUNICATION STANDARD is listed. Refer to additional sections of this SDS for our assessment of the potential hazards of this formulation.

#### 4. First-aid measures

**Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial

respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper

respiratory medical device. Call a POISON CENTER or doctor/physician.

**Skin contact**Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or poison

control center immediately. Chemical burns must be treated by a physician. Wash contaminated

clothing before reuse.

Eye contact URGENT! Immediately flush eyes with water for 30 minutes while removing contact lenses. Hold eyelids

apart. Continue rinsing. Call a physician or poison control center immediately.

**Ingestion** Do not feed anything by mouth to an unconscious or convulsive victim. Do not induce vomiting. Call a

physician or poison control center immediately. Rinse mouth. Dilute contents of stomach using 2-8 fluid ounces (60-240ml) of milk or water. If vomiting occurs, keep head low so that stomach content doesn't

get into the lungs.

Most important

symptoms/effects, acute and

delayed

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed

**General information** 

Take off immediately all contaminated clothing. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

## 5. Fire-fighting measures

Suitable extinguishing media

Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2). Water spray should be used only to cool fire-exposed containers and disperse vapours.

Unsuitable extinguishing media Specific hazards arising from the chemical Do not use water jet as an extinguisher, as this will spread the fire.

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask.

Material name: STEAMATE\* LSA1900

Version number: 2.0

Page: 2 / 9

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk.

Cool containers / tanks with water spray.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

Flammable liquid and vapor.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

**Environmental precautions** 

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. Water contaminated with this product

may be sent to a sanitary sewer treatment facility, or a permitted waste treatment facility, in accordance with any local agreements.

## 7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). Do not freeze. If frozen, thaw completely and mix thoroughly prior to use.

## 8. Exposure controls/personal protection

Occupational exposure limits

### **US. ACGIH Threshold Limit Values**

Components	Туре	Value
Cyclohexylamine (CAS	TWA	10 ppm
100 01 0)		

## US. NIOSH: Pocket Guide to Chemical Hazards

03. MOSH. Focket Guide to Chemical Mazards			
Components	Туре	Value	
Cyclohexylamine (CAS 108-91-8)	TWA	40 mg/m3	
		10 ppm	

**Biological limit values** 

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

### Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles) and a face shield. Eye/face protection

Skin protection

Wear appropriate chemical resistant gloves. The choice of an appropriate glove does not only depend Hand protection

on its material but also on other quality features and is different from one producer to the other. Glove

selection must take into account any solvents and other hazards present.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece. A RESPIRATORY PROTECTION

PROGRAM THAT MEETS OSHA'S 29 CFR 1910.134 AND ANSI Z88.2 REQUIREMENTS MUST BE FOLLOWED

WHENEVER WORKPLACE CONDITIONS WARRANT A RESPIRATOR'S USE.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as General hygiene considerations

washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

**Appearance** 

Color Colorless to yellow

Physical state Liquid Odor **Amine** 

Odor threshold Not available.

12.8 pH (concentrated product)

11.9 (5% SOL.) pH in aqueous solution < -20 °F (< -29 °C) Melting point/freezing point Not available. Initial boiling point and boiling

range

113 °F (45 °C) P-M(CC) Flash point

< 1 (Ether = 1)**Evaporation rate** Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) Not available. Not available. Flammability limit - upper

(%)

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available.

Vapor pressure < 11 mm Hg Vapor pressure temp. 70 °F (21 °C) Vapor density > 1 (Air = 1)

0.91 Relative density

70 °F (21 °C) Relative density temperature

Solubility(ies)

100 % Solubility (water)

**Partition coefficient** Not available.

(n-octanol/water)

Auto-ignition temperature Not available. Not available. **Decomposition temperature** 

Viscosity 20 cps

Material name: STEAMATE\* LSA1900

Page: 4 / 9

Viscosity temperature 70 °F (21 °C)

Other information

90 (Estimated) Percent volatile < -20 °F (< -29 °C) Pour point

Specific gravity 0.91

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. Chemical stability Possibility of hazardous reactions Hazardous polymerization does not occur.

Contact with incompatible materials. Avoid heat, sparks, open flames and other ignition sources. Avoid Conditions to avoid

temperatures exceeding the flash point. Contact with strong acids may cause a violent reaction

releasing heat. Contact with water reactive compounds may cause fire or explosion.

Incompatible materials Acids. Strong oxidizing substances.

Hazardous decomposition

products

Oxides of carbon and nitrogen, ammonia and volatile amines.

## 11. Toxicological information

Information on likely routes of exposure

Toxic if inhaled. Inhalation

Skin contact Toxic in contact with skin. Causes severe skin burns.

Eye contact Causes serious eye damage.

Causes digestive tract burns. Harmful if swallowed. Ingestion

Symptoms related to the physical, chemical and toxicological

characteristics

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness

could result. May cause respiratory irritation.

Information on toxicological effects

Acute toxicity

Acute toxicity	Toxic if inhaled. Toxic in contact v	Toxic if inhaled. Toxic in contact with skin. Harmful if swallowed. May cause respiratory irritation.	
Product	Species	Test Results	
STEAMATE LSA1900 (CAS Mi	ixture)		
Acute			
Dermal			
LD50	Rabbit	868 mg/kg, (Calculated according to GHS additivity formula (Category 3))	
Inhalation			
LC50	Rat	8.15 mg/l, 4 Hours, (Calculated according to GHS additivity formula (Category 3))	
Oral			
LD50	Rat	633 mg/kg, (Calculated according to GHS additivity formula (Category 4))	
Components	Species	Test Results	
Cyclohexylamine (CAS 108-	91-8)		
Acute			
Dermal			
LD50	Rabbit	277 mg/kg	
Oral			
LD50	Rat	156 mg/kg	
Dimethylaminoethanol (DM	AE) (CAS 108-01-0)		
Acuto			

Acute

Dermal

LD50 Rabbit 1220 mg/kg

Inhalation

LC50 Rat 6.1 mg/l, 4 Hour

Material name: STEAMATE\* LSA1900

Page: 5 / 9

 Components
 Species
 Test Results

 Oral
 LD50
 Rat
 1210 mg/kg

\* Estimates for product may be based on additional component data not shown. **Skin corrosion/irritation**Causes severe skin burns and eve damage.

Serious eye damage/eye irritation Causes serious eye damage.

Respiratory or skin sensitization

**Respiratory sensitization**This product is not expected to cause respiratory sensitization. **Skin sensitization**This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are mutagenic or

genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

**Reproductive toxicity**Suspected of damaging fertility. **Specific target organ toxicity -**May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

single exposure

Not classified.

**Aspiration hazard**Based on available data, the classification criteria are not met. Aspiration of this product may cause the

same corrosiveness/irritation impacts as if it were ingested.

**Chronic effects** Prolonged inhalation may be harmful.

### 12. Ecological information

**Ecotoxicity**The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product		Species	Test Results
STEAMATE LSA1900 (CA	AS Mixture)		
	LC50	Fathead Minnow	136.6 mg/l, Static Renewal Bioassay, 96 hour, (pH adjusted)
	NOEL	Fathead Minnow	100 mg/l, Static Renewal Bioassay, 96 hour, (pH adjusted)
Aquatic			
Crustacea	LC50	Daphnia magna	127.5 mg/l, Static Renewal Bioassay, 48 hour, (pH adjusted)
	NOEL	Daphnia magna	100 mg/l, Static Renewal Bioassay, 48 hour, (pH adjusted)

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

**Bioaccumulative potential** No data available.

Partition coefficient n-octanol / water (log Kow)

Cyclohexylamine 1.49

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential,

endocrine disruption, global warming potential) are expected from this component.

**Environmental fate**The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data is available on the degradability of this product.

#### 13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the

material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in

accordance with local/regional/national/international regulations.

Material name: STEAMATE\* LSA1900

Page: 6 / 9

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

D002: Waste Corrosive material [pH <=2 or =>12.5, or corrosive to steel]

The waste code should be assigned in discussion between the user, the producer and the waste disposal

company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product

residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since

emptied containers may retain product residue, follow label warnings even after container is emptied.

## 14. Transport information

DOT

UN number UN2734

UN proper shipping name AMINES, LIQUID, CORROSIVE, FLAMMABLE, N.O.S. (DIMETHYLAMINOETHANOL, CYCLOHEXYLAMINE RQ =

670 LBS

Transport hazard class(es)

Class 8
Subsidiary risk 3, 6.1
Packing group ||

**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

ERG number 132

Some containers may be exempt from Dangerous Goods/Hazmat Transport Regulations, please check BOL for exact container

classification.

IATA

**UN number** Not available.

UN proper shipping name

DO NOT SHIP, NOT CLASSIFIED. CALL PRODUCT COMPLIANCE.

Transport hazard class(es)

**Class** Not available.

Subsidiary risk

Packing group Not applicable.

Environmental hazards No

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.

IMDG

**UN number** Not available.

UN proper shipping name Transport hazard class(es) DO NOT SHIP. NOT CLASSIFIED. CALL PRODUCT COMPLIANCE.

Class Not available.

Subsidiary risk

Packing group Not applicable.

**Environmental hazards** 

Marine pollutant No.

**EmS** Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

DOT



## 15. Regulatory information

**US federal regulations**This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

Material name: STEAMATE\* LSA1900 Page: 7 / 9

Version number: 2.0

#### CERCLA Hazardous Substance List (40 CFR 302.4)

Cyclohexylamine (CAS 108-91-8) Listed.

SARA 304 Emergency release notification

Cyclohexylamine (CAS 108-91-8) 10000 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed

Superfund Amendments and Reauthorization Act of 1986 (SARA)

**Hazard categories** Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Threshold planning Chemical name CAS number Reportable Threshold planning Threshold planning quantity quantity, lower quantity quantity, upper value value Cyclohexylamine 108-91-8 10000 10000 lbs

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Cyclohexylamine (CAS 108-91-8)

Safe Drinking Water Act

Not regulated.

(SDWA)

#### Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

### **US state regulations**

### US - Massachusetts RTK - Substance List

Cyclohexylamine (CAS 108-91-8)

Dimethylaminoethanol (DMAE) (CAS 108-01-0)

### US - Pennsylvania RTK - Hazardous Substances

Cyclohexylamine (CAS 108-91-8)

Dimethylaminoethanol (DMAE) (CAS 108-01-0)

#### US - Rhode Island RTK

Cyclohexylamine (CAS 108-91-8)

### US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

## US. New Jersey Worker and Community Right-to-Know Act

Cyclohexylamine (CAS 108-91-8)

Dimethylaminoethanol (DMAE) (CAS 108-01-0)

#### US. Pennsylvania Worker and Community Right-to-Know Law

Cyclohexylamine (CAS 108-91-8)

Dimethylaminoethanol (DMAE) (CAS 108-01-0)

#### **US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

## US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Aniline (CAS 62-53-3) Listed: January 1, 1990

Material name: STEAMATE\* LSA1900 Page: 8 / 9

US - California Proposition 65 - CRT: Listed date/Developmental toxin

No ingredient listed.

US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

No ingredient listed.

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

No ingredient listed.

## 16. Other information, including date of preparation or last revision

Issue dateFeb-24-2015Revision dateJul-20-2015

Version # 2.0

List of abbreviations

CAS: Chemical Abstract Service Registration Number

TSRN indicates a Trade Secret Registry Number is used in place of the CAS number.

ACGIH: American Conference of Governmental Industrial Hygienists

NOEL: No Observed Effect Level STEL: Short Term Exposure Limit LC50: Lethal Concentration, 50% TWA: Time Weighted Average BOD: Biochemical Oxygen Demand COD: Chemical Oxygen Demand TOC: Total Organic Carbon

IATA: International Air Transport Association

IMDG: International Maritime Dangerous Goods Code

LD50: Lethal Dose, 50%

NFPA: National Fire Protection Association

**References:** No data available

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge, information

and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process,

unless specified in the text.

**Revision Information** Toxicological Information: Toxicological Data

Other information, including date of preparation or last revision: Prepared by

GHS: Classification

**Prepared by**This SDS has been prepared by GE Water & Process Technologies Regulatory Department

(1-215-355-3300).

Material name: STEAMATE\* LSA1900 Version number: 2.0

<sup>\*</sup> Trademark of General Electric Company. May be registered in one or more countries.