



**COMMONWEALTH OF PENNSYLVANIA
DEPARTMENT OF ENVIRONMENTAL PROTECTION
AIR QUALITY PROGRAM**

STATE ONLY NATURAL MINOR OPERATING PERMIT

Issue Date: January 16, 2024

Effective Date: January 16, 2024

Expiration Date: January 16, 2029

In accordance with the provisions of the Air Pollution Control Act, the Act of January 8, 1960, P.L. 2119, as amended, and 25 Pa. Code Chapter 127, the Owner, [and Operator if noted] (hereinafter referred to as permittee) identified below is authorized by the Department of Environmental Protection (Department) to operate the air emission source(s) more fully described in this permit. This Facility is subject to all terms and conditions specified in this permit. Nothing in this permit relieves the permittee from its obligations to comply with all applicable Federal, State and Local laws and regulations.

The regulatory or statutory authority for each permit condition is set forth in brackets. All terms and conditions in this permit are federally enforceable unless otherwise designated.

State Only Permit No: 54-00098

Natural Minor

Federal Tax Id - Plant Code: 95-1901059

Owner Information

Name: MI WINDOWS & DOORS LLC

Mailing Address: 79 PARK LN
HEGINS, PA 17938-9089

Plant Information

Plant: MI WINDOWS AND DOORS - HEGINS

Location: 54 Schuylkill County 54931 Hegins Township
SIC Code: 3089 Manufacturing - Plastics Products, Nec

Responsible Official

Name: DAVE BUFFELEN

Title: ENV. EXCELLENCE MANAGER

Phone: (253) 330 - 0350

Email: davebuffelen@milgard.com

Permit Contact Person

Name: SEAN ERDMAN

Title: SAFETY MANAGER

Phone: (570) 682 - 8381 Ext.6208

Email: Sean.Erdman@miwd.com

[Signature] _____

MARK J. WEJKSZNER, NORTHEAST REGION AIR PROGRAM MANAGER

**SECTION A. Table of Contents****Section A. Facility/Source Identification**

Table of Contents
Site Inventory List

Section B. General State Only Requirements

- #001 Definitions.
- #002 Operating Permit Duration.
- #003 Permit Renewal.
- #004 Operating Permit Fees under Subchapter I.
- #005 Transfer of Operating Permits.
- #006 Inspection and Entry.
- #007 Compliance Requirements.
- #008 Need to Halt or Reduce Activity Not a Defense.
- #009 Duty to Provide Information.
- #010 Revising an Operating Permit for Cause.
- #011 Operating Permit Modifications
- #012 Severability Clause.
- #013 De Minimis Emission Increases.
- #014 Operational Flexibility.
- #015 Reactivation
- #016 Health Risk-based Emission Standards and Operating Practice Requirements.
- #017 Circumvention.
- #018 Reporting Requirements.
- #019 Sampling, Testing and Monitoring Procedures.
- #020 Recordkeeping.
- #021 Property Rights.
- #022 Alternative Operating Scenarios.
- #023 Reporting
- #024 Report Format

Section C. Site Level State Only Requirements

- C-I: Restrictions
- C-II: Testing Requirements
- C-III: Monitoring Requirements
- C-IV: Recordkeeping Requirements
- C-V: Reporting Requirements
- C-VI: Work Practice Standards
- C-VII: Additional Requirements
- C-VIII: Compliance Certification
- C-IX: Compliance Schedule

Section D. Source Level State Only Requirements

- D-I: Restrictions
- D-II: Testing Requirements
- D-III: Monitoring Requirements
- D-IV: Recordkeeping Requirements
- D-V: Reporting Requirements
- D-VI: Work Practice Standards
- D-VII: Additional Requirements

Note: These same sub-sections are repeated for each source!

Section E. Source Group Restrictions

- E-I: Restrictions



SECTION A. Table of Contents

- E-II: Testing Requirements
- E-III: Monitoring Requirements
- E-IV: Recordkeeping Requirements
- E-V: Reporting Requirements
- E-VI: Work Practice Standards
- E-VII: Additional Requirements

Section F. Alternative Operating Scenario(s)

- F-I: Restrictions
- F-II: Testing Requirements
- F-III: Monitoring Requirements
- F-IV: Recordkeeping Requirements
- F-V: Reporting Requirements
- F-VI: Work Practice Standards
- F-VII: Additional Requirements

Section G. Emission Restriction Summary

Section H. Miscellaneous

**SECTION A. Site Inventory List**

Source ID	Source Name	Capacity/Throughput	Fuel/Material
200	INDUSTRIAL SOLVENTS		
201	SEALANTS		
Z200	FUGITIVE EMISSIONS - SOLVENTS		
Z201	FUGITIVE EMISSIONS - SEALANTS		

PERMIT MAPS

PROC
200 → STAC
Z200

PROC
201 → STAC
Z201

**SECTION B. General State Only Requirements****#001 [25 Pa. Code § 121.1]****Definitions.**

Words and terms that are not otherwise defined in this permit shall have the meanings set forth in Section 3 of the Air Pollution Control Act (35 P.S. § 4003) and in 25 Pa. Code § 121.1.

#002 [25 Pa. Code § 127.446]**Operating Permit Duration.**

(a) This operating permit is issued for a fixed term of five (5) years and shall expire on the date specified on Page 1 of this permit.

(b) The terms and conditions of the expired permit shall automatically continue pending issuance of a new operating permit, provided the permittee has submitted a timely and complete application and paid applicable fees required under 25 Pa. Code Chapter 127, Subchapter I and the Department is unable, through no fault of the permittee, to issue or deny a new permit before the expiration of the previous permit.

#003 [25 Pa. Code §§ 127.412, 127.413, 127.414, 127.446 & 127.703(b)]**Permit Renewal.**

(a) The permittee shall submit a timely and complete application for renewal of the operating permit to the appropriate Regional Air Program Manager. The application for renewal of the operating permit shall be submitted at least six (6) months and not more than 18 months before the expiration date of this permit.

(b) The application for permit renewal shall include the current permit number, a description of any permit revisions that occurred during the permit term, and any applicable requirements that were promulgated and not incorporated into the permit during the permit term. An application is complete if it contains sufficient information to begin processing the application, has the applicable sections completed and has been signed by a responsible official.

(c) The permittee shall submit with the renewal application a fee for the processing of the application as specified in 25 Pa. Code § 127.703(b). The fees shall be made payable to "The Commonwealth of Pennsylvania Clean Air Fund" and submitted with the fee form to the respective regional office.

(d) The renewal application shall also include submission of proof that the local municipality and county, in which the facility is located, have been notified in accordance with 25 Pa. Code § 127.413.

(e) The application for renewal of the operating permit shall also include submission of supplemental compliance review forms in accordance with the requirements of 25 Pa. Code § 127.412(b) and § 127.412(j).

(f) The permittee, upon becoming aware that any relevant facts were omitted or incorrect information was submitted in the permit application, shall promptly submit such supplementary facts or corrected information as necessary to address any requirements that become applicable to the source after the permittee submits a complete application, but prior to the date the Department takes action on the permit application.

#004 [25 Pa. Code § 127.703]**Operating Permit Fees under Subchapter I.**

(a) The permittee shall pay the annual operating permit maintenance fee according to the following fee schedule in either paragraph (1) or (2) in accordance with 25 Pa. Code § 127.703(d) on or before December 31 of each year for the next calendar year.

(1) For a synthetic minor facility, a fee equal to:

(i) Four thousand dollars (\$4,000) for calendar years 2021—2025.

(ii) Five thousand dollars (\$5,000) for calendar years 2026—2030.

(iii) Six thousand three hundred dollars (\$6,300) for the calendar years beginning with 2031.

**SECTION B. General State Only Requirements**

(2) For a facility that is not a synthetic minor, a fee equal to:

- (i) Two thousand dollars (\$2,000) for calendar years 2021—2025.
- (ii) Two thousand five hundred dollars (\$2,500) for calendar years 2026—2030.
- (iii) Three thousand one hundred dollars (\$3,100) for the calendar years beginning with 2031.

(b) The applicable fees shall be made payable to "The Commonwealth of Pennsylvania Clean Air Fund" with the permit number clearly indicated and submitted to the respective regional office.

#005 [25 Pa. Code §§ 127.450 (a)(4) and 127.464]**Transfer of Operating Permits.**

(a) This operating permit may not be transferred to another person, except in cases of transfer-of-ownership that are documented and approved by the Department.

(b) In accordance with 25 Pa. Code § 127.450(a)(4), a change in ownership of the source shall be treated as an administrative amendment if the Department determines that no other change in the permit is required and a written agreement has been submitted to the Department identifying the specific date of the transfer of permit responsibility, coverage and liability between the current and the new permittee and a compliance review form has been submitted to, and the permit transfer has been approved by, the Department.

(c) This operating permit is valid only for those specific sources and the specific source locations described in this permit.

#006 [25 Pa. Code § 127.441 and 35 P.S. § 4008]**Inspection and Entry.**

(a) Upon presentation of credentials and other documents as may be required by law, the permittee shall allow the Department or authorized representatives of the Department to perform the following:

(1) Enter at reasonable times upon the permittee's premises where a source is located or emissions related activity is conducted, or where records are kept under the conditions of this permit;

(2) Have access to and copy, at reasonable times, any records that are kept under the conditions of this permit;

(3) Inspect at reasonable times, any facilities, equipment including monitoring and air pollution control equipment, practices, or operations regulated or required under this permit;

(4) Sample or monitor, at reasonable times, any substances or parameters, for the purpose of assuring compliance with the permit or applicable requirements as authorized by the Clean Air Act, the Air Pollution Control Act, or the regulations promulgated under the Acts.

(b) Pursuant to 35 P.S. § 4008, no person shall hinder, obstruct, prevent or interfere with the Department or its personnel in the performance of any duty authorized under the Air Pollution Control Act or regulations adopted thereunder including denying the Department access to a source at this facility. Refusal of entry or access may constitute grounds for permit revocation and assessment of criminal and/or civil penalties.

(c) Nothing in this permit condition shall limit the ability of the EPA to inspect or enter the premises of the permittee in accordance with Section 114 or other applicable provisions of the Clean Air Act.

#007 [25 Pa. Code §§ 127.441 & 127.444]**Compliance Requirements.**

(a) The permittee shall comply with the conditions of this operating permit. Noncompliance with this permit constitutes a violation of the Clean Air Act and the Air Pollution Control Act and is grounds for one or more of the following:

**SECTION B. General State Only Requirements**

- (1) Enforcement action
- (2) Permit termination, revocation and reissuance or modification
- (3) Denial of a permit renewal application

(b) A person may not cause or permit the operation of a source which is subject to 25 Pa. Code Article III unless the source(s) and air cleaning devices identified in the application for the plan approval and operating permit and the plan approval issued for the source is operated and maintained in accordance with specifications in the applications and the conditions in the plan approval and operating permit issued by the Department. A person may not cause or permit the operation of an air contamination source subject to 25 Pa. Code Chapter 127 in a manner inconsistent with good operating practices.

(c) For purposes of Sub-condition (b) of this permit condition, the specifications in applications for plan approvals and operating permits are the physical configurations and engineering design details which the Department determines are essential for the permittee's compliance with the applicable requirements in this State-Only permit. Nothing in this sub-condition shall be construed to create an independent affirmative duty upon the permittee to obtain a predetermination from the Department for physical configuration or engineering design detail changes made by the permittee.

#008 [25 Pa. Code § 127.441]**Need to Halt or Reduce Activity Not a Defense.**

It shall not be a defense for the permittee in an enforcement action that it was necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

#009 [25 Pa. Code §§ 127.442(a) & 127.461]**Duty to Provide Information.**

(a) The permittee shall submit reports to the Department containing information the Department may prescribe relative to the operation and maintenance of each source at the facility.

(b) The permittee shall furnish to the Department, in writing, information that the Department may request to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with the permit. Upon request, the permittee shall also furnish to the Department copies of records that the permittee is required to maintain in accordance with this permit.

#010 [25 Pa. Code § 127.461]**Revising an Operating Permit for Cause.**

This operating permit may be terminated, modified, suspended or revoked and reissued if one or more of the following applies:

- (1) The permittee constructs or operates the source subject to the operating permit so that it is in violation of the Air Pollution Control Act, the Clean Air Act, the regulations thereunder, a plan approval, a permit or in a manner that causes air pollution.
- (2) The permittee fails to properly or adequately maintain or repair an air pollution control device or equipment attached to or otherwise made a part of the source.
- (3) The permittee has failed to submit a report required by the operating permit or an applicable regulation.
- (4) The EPA determines that the permit is not in compliance with the Clean Air Act or the regulations thereunder.

#011 [25 Pa. Code §§ 127.450, 127.462, 127.465 & 127.703]**Operating Permit Modifications**

(a) The permittee is authorized to make administrative amendments, minor operating permit modifications and significant operating permit modifications, under this permit, as outlined below:

**SECTION B. General State Only Requirements**

(b) Administrative Amendments. The permittee shall submit the application for administrative operating permit amendments (as defined in 25 Pa. Code § 127.450(a)), according to procedures specified in § 127.450 unless precluded by the Clean Air Act or its regulations.

(c) Minor Operating Permit Modifications. The permittee shall submit the application for minor operating permit modifications (as defined 25 Pa. Code § 121.1) in accordance with 25 Pa. Code § 127.462.

(d) Significant Operating Permit Modifications. The permittee shall submit the application for significant operating permit modifications in accordance with 25 Pa. Code § 127.465.

(e) The applicable fees shall be made payable to "The Commonwealth of Pennsylvania Clean Air Fund" with the permit number clearly indicated and submitted to the respective regional office.

#012 [25 Pa. Code § 127.441]**Severability Clause.**

The provisions of this permit are severable, and if any provision of this permit is determined by a court of competent jurisdiction to be invalid or unenforceable, such a determination will not affect the remaining provisions of this permit.

#013 [25 Pa. Code § 127.449]**De Minimis Emission Increases.**

(a) This permit authorizes de minimis emission increases in accordance with 25 Pa. Code § 127.449 so long as the permittee provides the Department with seven (7) days prior written notice before commencing any de minimis emissions increase. The written notice shall:

(1) Identify and describe the pollutants that will be emitted as a result of the de minimis emissions increase.

(2) Provide emission rates expressed in tons per year and in terms necessary to establish compliance consistent with any applicable requirement.

(b) The Department may disapprove or condition de minimis emission increases at any time.

(c) Except as provided below in (d), the permittee is authorized to make de minimis emission increases (expressed in tons per year) up to the following amounts without the need for a plan approval or prior issuance of a permit modification:

(1) Four tons of carbon monoxide from a single source during the term of the permit and 20 tons of carbon monoxide at the facility during the term of the permit.

(2) One ton of NO_x from a single source during the term of the permit and 5 tons of NO_x at the facility during the term of the permit.

(3) One and six-tenths tons of the oxides of sulfur from a single source during the term of the permit and 8.0 tons of oxides of sulfur at the facility during the term of the permit.

(4) Six-tenths of a ton of PM₁₀ from a single source during the term of the permit and 3.0 tons of PM₁₀ at the facility during the term of the permit. This shall include emissions of a pollutant regulated under Section 112 of the Clean Air Act unless precluded by the Clean Air Act, the regulations thereunder or 25 Pa. Code Article III.

(5) One ton of VOCs from a single source during the term of the permit and 5.0 tons of VOCs at the facility during the term of the permit. This shall include emissions of a pollutant regulated under Section 112 of the Clean Air Act unless precluded by the Clean Air Act, the regulations thereunder or 25 Pa. Code Article III.

(6) Other sources and classes of sources determined to be of minor significance by the Department.

(d) In accordance with § 127.14, the permittee is authorized to install the following minor sources without the need for a plan approval or permit modification:

**SECTION B. General State Only Requirements**

(1) Air conditioning or ventilation systems not designed to remove pollutants generated or released from other sources.

(2) Combustion units rated at 2,500,000 or less Btu per hour of heat input.

(3) Combustion units with a rated capacity of less than 10,000,000 Btu per hour heat input fueled by natural gas supplied by a public utility or by commercial fuel oils which are No. 2 or lighter, viscosity less than or equal to 5.82 c St, and which meet the sulfur content requirements of 25 Pa. Code §123.22 (relating to combustion units). For purposes of this permit, commercial fuel oil shall be virgin oil which has no reprocessed, recycled or waste material added.

(4) Space heaters which heat by direct heat transfer.

(5) Laboratory equipment used exclusively for chemical or physical analysis.

(6) Other sources and classes of sources determined to be of minor significance by the Department.

(e) This permit does not authorize de minimis emission increases if the emissions increase would cause one or more of the following:

(1) Increase the emissions of a pollutant regulated under Section 112 of the Clean Air Act except as authorized in Subparagraphs (c)(4) and (5) of this permit condition.

(2) Subject the facility to the prevention of significant deterioration requirements in 25 Pa. Code Chapter 127, Subchapter D and/or the new source review requirements in Subchapter E.

(3) Violate any applicable requirement of this permit, the Air Pollution Control Act, the Clean Air Act, or the regulations promulgated under either of the acts.

(f) Emissions authorized under this permit condition shall be included in the monitoring, recordkeeping and reporting requirements of this permit.

(g) Except for de minimis emission increases, installation of minor sources made pursuant to this permit condition and Plan Approval Exemptions under 25 Pa. Code § 127.14 (relating to exemptions), the permittee is prohibited from making changes or engaging in activities that are not specifically authorized under this permit without first applying for a plan approval. In accordance with § 127.14(b), a plan approval is not required for the construction, modification, reactivation, or installation of the sources creating the de minimis emissions increase.

(h) The permittee may not meet de minimis emission threshold levels by offsetting emission increases or decreases at the same source.

#014 [25 Pa. Code § 127.3]**Operational Flexibility.**

The permittee is authorized to make changes within the facility in accordance with the regulatory provisions outlined in 25 Pa. Code § 127.3 (relating to operational flexibility) to implement the operational flexibility requirements provisions authorized under Section 6.1(i) of the Air Pollution Control Act and the operational flexibility terms and conditions of this permit. The provisions in 25 Pa. Code Chapter 127 which implement the operational flexibility requirements include the following:

(1) Section 127.14 (relating to exemptions)

(2) Section 127.447 (relating to alternative operating scenarios)

(3) Section 127.448 (relating to emissions trading at facilities with Federally enforceable emissions caps)

(4) Section 127.449 (relating to de minimis emission increases)

(5) Section 127.450 (relating to administrative operating permit amendments)

**SECTION B. General State Only Requirements**

(6) Section 127.462 (relating to minor operating permit modifications)

(7) Subchapter H (relating to general plan approvals and general operating permits)

#015 [25 Pa. Code § 127.11]**Reactivation**

(a) The permittee may not reactivate a source that has been out of operation or production for at least one year unless the reactivation is conducted in accordance with a plan approval granted by the Department or in accordance with reactivation and maintenance plans developed and approved by the Department in accordance with 25 Pa. Code § 127.11a(a).

(b) A source which has been out of operation or production for more than five (5) years but less than 10 years may be reactivated and will not be considered a new source if the permittee satisfies the conditions specified in 25 Pa. Code § 127.11a(b).

#016 [25 Pa. Code § 127.36]**Health Risk-based Emission Standards and Operating Practice Requirements.**

(a) When needed to protect public health, welfare and the environment from emissions of hazardous air pollutants from new and existing sources, the permittee shall comply with the health risk-based emission standards or operating practice requirements imposed by the Department, except as precluded by §§ 6.6(d)(2) and (3) of the Air Pollution Control Act [35 P.S. § 4006.6(d)(2) and (3)].

(b) A person challenging a performance or emission standard established by the Department has the burden to demonstrate that performance or emission standard does not meet the requirements of Section 112 of the Clean Air Act.

#017 [25 Pa. Code § 121.9]**Circumvention.**

No person may permit the use of a device, stack height which exceeds good engineering practice stack height, dispersion technique or other technique which, without resulting in reduction of the total amount of air contaminants emitted, conceals or dilutes an emission of air contaminants which would otherwise be in violation of 25 Pa. Code Article III, except that with prior approval of the Department, the device or technique may be used for control of malodors.

#018 [25 Pa. Code §§ 127.402(d) & 127.442]**Reporting Requirements.**

(a) The permittee shall comply with the applicable reporting requirements of the Clean Air Act, the regulations thereunder, the Air Pollution Control Act and 25 Pa. Code Article III including Chapters 127, 135 and 139.

(b) The permittee shall submit reports to the Department containing information the Department may prescribe relative to the operation and maintenance of any air contamination source.

(c) Reports, test data, monitoring data, notifications and requests for renewal of the permit shall be submitted to the:

Regional Air Program Manager
PA Department of Environmental Protection
(At the address given in the permit transmittal letter, or otherwise notified)

(d) Any records or information including applications, forms, or reports submitted pursuant to this permit condition shall contain a certification by a responsible official as to truth, accuracy and completeness. The certifications submitted under this permit shall require a responsible official of the facility to certify that based on information and belief formed after reasonable inquiry, the statements and information in the documents are true, accurate and complete.

(e) Any records, reports or information submitted to the Department shall be available to the public except for such

**SECTION B. General State Only Requirements**

records, reports or information which meet the confidentiality requirements of § 4013.2 of the Air Pollution Control Act and §§ 112(d) and 114(c) of the Clean Air Act. The permittee may not request a claim of confidentiality for any emissions data generated for the facility.

#019 [25 Pa. Code §§ 127.441(c) & 135.5]**Sampling, Testing and Monitoring Procedures.**

(a) The permittee shall comply with the monitoring, recordkeeping or reporting requirements of 25 Pa. Code Chapter 139 and the other applicable requirements of 25 Pa. Code Article III and additional requirements related to monitoring, reporting and recordkeeping required by the Clean Air Act and the regulations thereunder including the Compliance Assurance Monitoring requirements of 40 CFR Part 64, where applicable.

(b) Unless alternative methodology is required by the Clean Air Act and regulations adopted thereunder, sampling, testing and monitoring required by or used by the permittee to demonstrate compliance with any applicable regulation or permit condition shall be conducted in accordance with the requirements of 25 Pa. Code Chapter 139.

#020 [25 Pa. Code §§ 127.441(c) and 135.5]**Recordkeeping.**

(a) The permittee shall maintain and make available, upon request by the Department, the following records of monitored information:

- (1) The date, place (as defined in the permit) and time of sampling or measurements.
- (2) The dates the analyses were performed.
- (3) The company or entity that performed the analyses.
- (4) The analytical techniques or methods used.
- (5) The results of the analyses.
- (6) The operating conditions as existing at the time of sampling or measurement.

(b) The permittee shall retain records of any required monitoring data and supporting information for at least five (5) years from the date of the monitoring, sample, measurement, report or application. Supporting information includes the calibration data and maintenance records and original strip-chart recordings for continuous monitoring instrumentation, and copies of reports required by the permit.

(c) The permittee shall maintain and make available to the Department upon request, records including computerized records that may be necessary to comply with the reporting, recordkeeping and emission statement requirements in 25 Pa. Code Chapter 135 (relating to reporting of sources). In accordance with 25 Pa. Code Chapter 135, § 135.5, such records may include records of production, fuel usage, maintenance of production or pollution control equipment or other information determined by the Department to be necessary for identification and quantification of potential and actual air contaminant emissions.

#021 [25 Pa. Code § 127.441(a)]**Property Rights.**

This permit does not convey any property rights of any sort, or any exclusive privileges.

#022 [25 Pa. Code § 127.447]**Alternative Operating Scenarios.**

The permittee is authorized to make changes at the facility to implement alternative operating scenarios identified in this permit in accordance with 25 Pa. Code § 127.447.

**SECTION B. General State Only Requirements****#023 [25 Pa. Code §135.3]****Reporting**

(a) If the facility is a Synthetic Minor Facility, the permittee shall submit by March 1 of each year an annual emissions report for the preceding calendar year. The report shall include information for all active previously reported sources, new sources which were first operated during the preceding calendar year, and sources modified during the same period which were not previously reported. All air emissions from the facility should be estimated and reported.

(b) A source owner or operator of a Synthetic Minor Facility may request an extension of time from the Department for the filing of an annual emissions report, and the Department may grant the extension for reasonable cause.

#024 [25 Pa. Code §135.4]**Report Format**

If applicable, the emissions reports shall contain sufficient information to enable the Department to complete its emission inventory. Emissions reports shall be made by the source owner or operator in a format specified by the Department.

**SECTION C. Site Level Requirements****I. RESTRICTIONS.****Emission Restriction(s).****# 001 [25 Pa. Code §123.1]****Prohibition of certain fugitive emissions**

(a) No person may permit the emission into the outdoor atmosphere of fugitive air contaminant from a source other than the following:

- (1) Construction or demolition of buildings or structures.
- (2) Grading, paving and maintenance of roads and streets.
- (3) Use of roads and streets. Emissions from material in or on trucks, railroad cars and other vehicular equipment are not considered as emissions from use of roads and streets.
- (4) Clearing of land.
- (5) Stockpiling of materials.
- (6) Open burning operations.
- (7) Sources and classes of sources other than those identified above, for which the operator has obtained a determination from the Department that fugitive emissions from the source, after appropriate control, meet the following requirements:
 - (i) the emissions are of minor significance with respect to causing air pollution; and
 - (ii) the emissions are not preventing or interfering with the attainment or maintenance of any ambient air quality standard.

002 [25 Pa. Code §123.2]**Fugitive particulate matter**

No person shall permit the emission of particulate matter into the outdoor atmosphere from a source specified in Section C, Condition #001 if the emissions are visible at the point the emissions pass outside the person's property.

003 [25 Pa. Code §123.31]**Limitations**

No person shall permit the emission into the outdoor atmosphere of any malodorous air contaminants from any source in such a manner that the malodors are detectable outside the property of the person on whose land the source is being operated.

004 [25 Pa. Code §123.41]**Limitations**

The permittee may not allow the emission of visible air contaminants into the outdoor atmosphere in such a manner that the opacity of the emission is either of the following:

- (1) Equal to or greater than 20% for a period or periods aggregating more than three minutes in any one hour.
- (2) Equal to or greater than 60% at any time.

005 [25 Pa. Code §123.42]**Exceptions**

The emission limitations of Section 123.41 shall not apply when:

- (1) The presence of uncombined water vapor is the only reason for failure of the emission to meet the limitations;
- (2) The emission results from the operation of equipment used solely to train and test persons in observing the opacity of visible emissions;
- (3) The emission results from sources specified in Section C, Condition 001 (relating to prohibition of certain fugitive emissions).

006 [25 Pa. Code §127.441]**Operating permit terms and conditions.**

Total facility emissions from all sources, including emissions during start-ups and shutdowns, shall not exceed the

**SECTION C. Site Level Requirements**

following limits during any consecutive a 12-month rolling period:

Facility Emission Limits	tons per year
NOx	99.9
CO	99.9
PM10/PM2.5	99.9
SO2	99.9

007 [25 Pa. Code §129.14]**Open burning operations**

- (a) Air basins. No person may permit the open burning of material in an air basin.
- (b) Outside of air basins. No person may permit the open burning of material in an area outside of air basins in a manner that:
- (1) The emissions are visible, at any time, at the point such emissions pass outside the property of the person on whose land the open burning is being conducted.
 - (2) Malodorous air contaminants from the open burning are detectable outside the property of the person on whose land the open burning is being conducted.
 - (3) The emissions interfere with the reasonable enjoyment of life or property.
 - (4) The emissions cause damage to vegetation or property.
 - (5) The emissions are or may be deleterious to human or animal health.
- (c) Exceptions: The requirements of subsections (a) and (b) do not apply where the open burning operations result from:
- (1) A fire set to prevent or abate a fire hazard, when approved by the Department and set by or under the supervision of a public officer.
 - (2) A fire set for the purpose of instructing personnel in fire fighting, when approved by the Department.
 - (3) A fire set for the prevention and control of disease or pests, when approved by the Department.
 - (4) A fire set in conjunction with the production of agricultural commodities in their unmanufactured state on the premises of the farm operation.
 - (5) A fire set for the purpose of burning domestic refuse, when the fire is on the premises of a structure occupied solely as a dwelling by two families or less and when the refuse results from the normal occupancy of such structure.
 - (6) A fire set solely for recreational or ceremonial purposes.
 - (7) A fire set solely for cooking food.
- (d) Clearing and grubbing wastes. The following is applicable to clearing and grubbing wastes:
- (1) As used in this subsection the following terms shall have the following meanings:

Air curtain destructor -- A mechanical device which forcefully projects a curtain of air across a pit in which open burning is being conducted so that combustion efficiency is increased and smoke and other particulate matter are contained.

Clearing and grubbing wastes -- Trees, shrubs, and other native vegetation which are cleared from land during or prior to the process of construction. The term does not include demolition wastes and dirt laden roots.

(2) Subsection (a) notwithstanding, clearing and grubbing wastes may be burned in a basin subject to the following requirements:

- (i) Air curtain destructors shall be used when burning clearing and grubbing wastes.
- (ii) Each proposed use of air curtain destructors shall be reviewed and approved by the Department in writing with respect to equipment arrangement, design and existing environmental conditions prior to commencement of burning. Proposals approved under this subparagraph need not obtain plan approval or operating permits under Chapter 127 (relating to construction modification, reactivation and operation of sources).
- (iii) Approval for use of an air curtain destructor at one site may be granted for a specified period not to exceed 3 months, but may be extended for additional limited periods upon further approval by the Department.
- (iv) The Department reserves the right to rescind approval granted if a determination by the Department indicates that

**SECTION C. Site Level Requirements**

an air pollution problem exists.

(3) Subsection (b) notwithstanding clearing and grubbing wastes may be burned outside of an air basin, subject to the following limitations:

(i) Upon receipt of a complaint or determination by the Department that an air pollution problem exists, the Department may order that the open burning cease or comply with subsection (b) of this section.

(ii) Authorization for open burning under this paragraph does not apply to clearing and grubbing wastes transported from an air basin for disposal outside of an air basin.

(4) During an air pollution episode, open burning is limited by Chapter 137 (relating to air pollution episodes) and shall cease as specified in such chapter.

II. TESTING REQUIREMENTS.**# 008 [25 Pa. Code §127.441]****Operating permit terms and conditions.**

The Department reserves the right to require exhaust stack testing of the sources and control devices referenced in this permit to measure emissions for purposes including verification of permit condition compliance and estimation of annual air emissions.

009 [25 Pa. Code §139.1]**Sampling facilities.**

Upon the request of the Department, the permittee shall provide adequate sampling ports, safe sampling platforms and adequate utilities for the performance by the Department of tests on such sources. In the request, the Department will set forth the time period in which the facilities shall be provided, as well as the specifications for the facilities.

III. MONITORING REQUIREMENTS.**# 010 [25 Pa. Code §123.43]****Measuring techniques**

Visible emissions may be measured using either of the following:

- (1) A device approved by the Department and maintained to provide accurate opacity measurements.
- (2) Observers, trained and certified in EPA Method 9, to measure plume opacity with the naked eye or with the aid of any devices approved by the Department.

011 [25 Pa. Code §127.441]**Operating permit terms and conditions.**

The permittee shall conduct a weekly inspection during daylight hours when the plant is in production to detect visible, malodor, and fugitive emissions as follows:

- (a) Visible emissions in excess of the limits stated in Section C, Condition #004. Visible emissions may be measured according to the method specified in Section C, Condition #010 or alternatively, plant personnel who observe any visible emissions will report the incident of visible emissions to the Department within four hours of each incident and make arrangements for a certified observer to verify the opacity of the visible emissions.
- (b) The presence of fugitive or malodor emissions detectable beyond the plant boundaries as stated in Section C, Conditions #002 and #003

**SECTION C. Site Level Requirements****IV. RECORDKEEPING REQUIREMENTS.****# 012 [25 Pa. Code §127.441]
Operating permit terms and conditions.**

The permittee shall keep up-to-date records of Certified Product Data Sheets (CPDSs) or Material Safety Data Sheets (MSDSs) that identify the volatile organic compound (VOC) content and hazardous air pollutant (HAP) content of each VOC and/or HAP containing material used at the facility.

V. REPORTING REQUIREMENTS.

No additional reporting requirements exist except as provided in other sections of this permit including Section B (State Only General Requirements).

VI. WORK PRACTICE REQUIREMENTS.**# 013 [25 Pa. Code §123.1]
Prohibition of certain fugitive emissions**

The permittee shall take all reasonable actions to prevent particulate matter from the sources identified in Section C, Condition #001(a)(1) through (a)(7) from becoming airborne. The actions shall include, but are not limited to, the following:

- (1) Use, where possible, of water or chemicals for control of dust in the demolition of buildings or structures, construction operations, the grading of roads or the clearing of land.
- (2) Application of asphalt, oil, water or suitable chemicals on dirt roads, materials stockpiles and other surfaces which may give rise to airborne dusts.
- (3) Paving and maintenance of roadways.
- (4) Prompt removal of earth or other material from paved streets onto which earth or other material has been transported by trucking or earth moving equipment, erosion by water, or other means.

**# 014 [25 Pa. Code §127.441]
Operating permit terms and conditions.**

Industrial solvents and sealant material used in operations must comply with Best Available Technology (BAT) to minimize VOC emissions and must be stored in closed containers except when being used.

**# 015 [25 Pa. Code §127.441]
Operating permit terms and conditions.**

The company shall maintain and operate the sources in accordance with good engineering practices.

VII. ADDITIONAL REQUIREMENTS.**# 016 [25 Pa. Code §127.441]
Operating permit terms and conditions.**

The permittee shall not impose conditions upon or otherwise restrict the Department's access to the sources and/or any associated air cleaning device(s) and shall allow the Department to have access at any time to the sources and associated air cleaning device(s) with such measuring and recording equipment, including equipment recording visual observations, as the Department deems necessary and proper for performing its duties and for the effective enforcement of the Air Pollution Control Act.

**# 017 [25 Pa. Code §127.441]
Operating permit terms and conditions.**

(a) Any changes in the location of any sources, or changes in the process or control equipment would be considered a modification and would require the submittal of an amended application for plan approval in accordance with the provisions of 25 Pa. Code Section 127.11 and 127.12.

(b) Any notification as a result of any condition herein should be directed to:

**SECTION C. Site Level Requirements**

Air Quality Program Manager
2 Public Square
Wilkes-Barre, PA 18701-1915

VIII. COMPLIANCE CERTIFICATION.

No additional compliance certifications exist except as provided in other sections of this permit including Section B (relating to State Only General Requirements).

IX. COMPLIANCE SCHEDULE.


No compliance milestones exist.

**SECTION D. Source Level Requirements**

Source ID: 200

Source Name: INDUSTRIAL SOLVENTS

Source Capacity/Throughput:

**I. RESTRICTIONS.**

No additional requirements exist except as provided in other sections of this permit including Section B (State Only General Requirements).

II. TESTING REQUIREMENTS.

No additional testing requirements exist except as provided in other sections of this permit including Section B (State Only General Requirements).

III. MONITORING REQUIREMENTS.

No additional monitoring requirements exist except as provided in other sections of this permit including Section B (State Only General Requirements).

IV. RECORDKEEPING REQUIREMENTS.

No additional record keeping requirements exist except as provided in other sections of this permit including Section B (State Only General Requirements).

V. REPORTING REQUIREMENTS.

No additional reporting requirements exist except as provided in other sections of this permit including Section B (State Only General Requirements).

VI. WORK PRACTICE REQUIREMENTS.

No additional work practice requirements exist except as provided in other sections of this permit including Section B (State Only General Requirements).

VII. ADDITIONAL REQUIREMENTS.**# 001 [25 Pa. Code §129.63a]****Control of VOC emissions from industrial cleaning solvents.**

(a) Applicability. This section applies to the owner and the operator of a facility at which an industrial cleaning solvent is used or applied in a cleaning activity at a cleaning unit operation, a work production-related work area or a part, product, tool, machinery, equipment, vessel, floor or wall.

(b) Definitions [INCLUDED BY REFERENCE]

(c) Exceptions and exemptions.

(1) This section does not apply to all of the following:

(i) [N/A - CLEANING UNITS NOT SUBJECT TO PA.129.63 OR 40 CFR PART 63, SUBPART T]

(ii) An owner or operator of a cleaning unit operation associated with a following category: [NA - FACILITY IS NOT INCLUDED IN EXEMPT CATEGORIES]

(2) The VOC emission limitations in subsection (e) do not apply to the use or application of an industrial cleaning solvent by the owner or operator of a cleaning unit operation at a facility subject to subsection (a) under either of the following

**SECTION D. Source Level Requirements**

circumstances:

- (i) [N/A - NOT FEDERAL GOVERNMENT]
- (ii) [N/A - NO SCREEN PRINTING EQUIPMENT]

(3) The VOC emission limitations in subsection (e) and the work practice requirements in subsection (f) do not apply to the owner or operator of a facility subject to subsection (a) if the total combined actual VOC emissions from all subject cleaning unit operations at the facility are less than 2.7 tons (2,455 kilograms) per 12-month rolling period, before consideration of controls. An owner or operator claiming this exemption shall maintain records in accordance with subsection (h)(4).

(d) [N/A - NO RACT PERMIT]

(e) Emissions limitations. Beginning August 11, 2018, the owner or operator of a facility at which the total combined actual VOC emissions from all subject cleaning unit operations at the facility are equal to or greater than 2.7 tons (2,455 kilograms) per 12-month rolling period, before consideration of controls, may not cause or permit the emission into the outdoor atmosphere of VOCs from an industrial cleaning solvent used or applied in a cleaning unit operation subject to this section at the facility, unless one of the following limitations is met:

- (1) Compliant solvents. The industrial cleaning solvent meets one of the following VOC limits:
 - (i) A VOC content less than or equal to 0.42 lb VOC/gal (50 g VOC/l) as applied.
 - (ii) A VOC composite vapor pressure less than or equal to 8 mm mercury at 68°F (20°C) as applied.
- (2) [N/A - NO VOC CAPTURE AND CONTROL DEVICE]

(f) Work practice requirements for industrial cleaning solvents, used shop towels and waste materials. The owner or operator of a facility subject to subsection (e) shall comply with all of the following work practices for industrial cleaning solvents and shop towels used in the cleaning unit operation cleaning activity:

- (1) Store all VOC-containing industrial cleaning solvents, used shop towels and related waste materials in closed containers.
- (2) Ensure that mixing and storage containers used for VOC-containing industrial cleaning solvents and related waste materials are kept closed at all times except when depositing or removing these materials.
- (3) Minimize spills of VOC-containing industrial cleaning solvents and related waste materials and clean up spills immediately.
- (4) Convey VOC-containing industrial cleaning solvents and related waste materials from one location to another in closed containers or pipes.
- (5) Minimize VOC emissions from cleaning of storage, mixing and conveying equipment.
- (6) Minimize air circulation around cleaning unit operations.

(g) Compliance demonstration. The owner or operator of a cleaning unit operation subject to this section shall demonstrate compliance as follows:

- (1) The owner or operator of a facility at which the total combined actual VOC emissions from all subject cleaning unit operations at the facility are equal to or greater than 2.7 tons (2,455 kilograms) per 12-month rolling period, before consideration of controls, shall do either of the following:
 - (i) Ensure that industrial cleaning solvents used or applied in the subject cleaning unit operations at the facility meet the applicable emissions limitation in subsection (e)(1) and maintain records in accordance with subsection (h)(1)(i).
 - (ii) [N/A - NO VOC CAPTURE AND CONTROL DEVICE]
- (2) The owner or operator of a cleaning unit operation subject to this section claiming exemption under:
 - (i) [N/A - SUBSECTION (c)(2)(i) EXEMPTION NOT CLAIMED]
 - (ii) [N/A - SUBSECTION (c)(2)(ii) EXEMPTION NOT CLAIMED]
 - (iii) Subsection (c)(3) shall maintain records in accordance with subsection (h)(4).
- (3) The owner or operator of a cleaning unit operation subject to this section shall determine the VOC content of the industrial cleaning solvent as applied by conducting sampling and testing of the industrial cleaning solvent in accordance with the procedures and test methods specified in subsections (i) and (j) and Chapter 139.
- (4) The owner or operator of a cleaning unit operation subject to paragraph (3) may use other test methods or documentation to demonstrate compliance with this section if approved in advance in writing by the Department and the EPA.

(h) Recordkeeping and reporting requirements. The owner or operator of a cleaning unit operation subject to this section shall comply with all of the following applicable recordkeeping and reporting requirements:

- (1) The owner or operator of a facility at which the total combined actual VOC emissions from all subject cleaning unit

**SECTION D. Source Level Requirements**

operations at the facility are equal to or greater than 2.7 tons (2,455 kilograms) per 12-month rolling period, before consideration of controls, shall maintain all of the applicable records:

(i) For an owner or operator that complies with this section by using a complying industrial cleaning solvent under subsection (e)(1), records of all of the following parameters for each cleaning unit operation industrial cleaning solvent:

(A) The name and identification number.

(B) The weight percent of total volatiles, water and exempt solvents, as supplied.

(C) The VOC content or composite vapor pressure, as supplied. The composite vapor pressure as supplied shall be determined in accordance with subsections (i) and (j).

(D) The VOC content or composite vapor pressure, as applied. The composite vapor pressure as applied shall be determined in accordance with subsections (i) and (j).

(E) The volume used or applied on a monthly basis.

(ii) [N/A - NO VOC CAPTURE AND CONTROL DEVICE]

(2) [N/A - SUBSECTION (c)(2)(i) EXEMPTION NOT CLAIMED]

(3) [N/A - SUBSECTION (c)(2)(ii) EXEMPTION NOT CLAIMED]

(4) The owner or operator of a facility claiming exemption under subsection (c)(3) shall maintain monthly records of the industrial cleaning solvents used or applied at the subject cleaning unit operations sufficient to demonstrate that the total combined actual VOC emissions from all subject cleaning unit operations at the facility are less than 2.7 tons (2,455 kilograms) per 12-month rolling period, before consideration of controls.

(5) Records shall be maintained onsite for 2 years, unless a longer period is required under Chapter 127 (relating to construction, modification, reactivation and operation of sources) or a plan approval, operating permit, consent decree or order issued by the Department.

(6) Records shall be submitted to the Department in an acceptable format upon receipt of a written request from the Department.

(i) Composite vapor pressure. The composite vapor pressure of organic compounds in cleaning unit operation industrial cleaning solvents shall be determined by one or more of the following procedures:

(1) Quantifying the amount of each compound in the blend using gas chromatographic analysis, using one or more of the following methods:

(i) An appropriate and current ASTM test method with prior written approval from the Department and the EPA.

(ii) Another test method demonstrated to provide results that are acceptable for purposes of determining compliance with this section if prior approval is obtained in writing from the Department and the EPA.

(2) Calculating the composite vapor pressure using the following equation:

[REFERENCE REGULATION FOR EQUATION]

(3) Providing documentation from the manufacturer of the industrial cleaning solvent that indicates the composite vapor pressure. The documentation may include an MSDS, CPDS or other data certified by the manufacturer.

(j) Vapor pressure of single component compound. The vapor pressure of each single component compound in a cleaning unit operation industrial cleaning solvent shall be determined from one or more of the following:

(1) An appropriate and current ASTM test method with prior written approval from the Department and the EPA.

(2) The most recent edition of one or more of the following sources:

(i) Vapour Pressures of Pure Substances, Boublik, Elsevier Scientific Publishing Company.

(ii) Perry's Chemical Engineers' Handbook, Green and Perry, McGraw-Hill Book Company.

(iii) CRC Handbook of Chemistry and Physics, CRC Press.

(iv) Lange's Handbook of Chemistry, McGraw-Hill Book Company.

(3) Documentation provided by the manufacturer of the single component compound that indicates the vapor pressure of the single component compound. The documentation may include an MSDS, CPDS or other data certified by the manufacturer.


(k) ASTM method references. References to ASTM methods in this section pertain to test methods developed by ASTM International, 100 Barr Harbor Drive, Post Office Box C700, West Conshohocken, Pennsylvania 19428-2959, www.astm.org.

**SECTION D. Source Level Requirements**

Source ID: 201

Source Name: SEALANTS

Source Capacity/Throughput:

**I. RESTRICTIONS.****Emission Restriction(s).****# 001 [25 Pa. Code §129.77.]****Control of emissions from the use or application of adhesives, sealants, primers and solvents.**

(a) On or after January 1, 2012, an owner or operator of a facility may not use or apply at the facility an adhesive, sealant, adhesive primer or sealant primer that exceeds the applicable VOC content limits, expressed as lbs VOC / gallon product, less water and exempt compounds, as specified in Tables V & VI of 25 Pa Code 129.77:

Table V - VOC Content Limits for Adhesives, Sealants, Adhesive Primers and Sealant Primers, As Applied:

(A) Architectural Sealant - 2.1 (250 grams VOC per liter, less water and exempt compounds)

Note: Reference Tables V & VI from the regulation for the complete list of adhesives, sealants, adhesive primers, sealant primers and substrates.

II. TESTING REQUIREMENTS.

No additional testing requirements exist except as provided in other sections of this permit including Section B (State Only General Requirements).

III. MONITORING REQUIREMENTS.

No additional monitoring requirements exist except as provided in other sections of this permit including Section B (State Only General Requirements).

IV. RECORDKEEPING REQUIREMENTS.

No additional record keeping requirements exist except as provided in other sections of this permit including Section B (State Only General Requirements).

V. REPORTING REQUIREMENTS.

No additional reporting requirements exist except as provided in other sections of this permit including Section B (State Only General Requirements).

VI. WORK PRACTICE REQUIREMENTS.

No additional work practice requirements exist except as provided in other sections of this permit including Section B (State Only General Requirements).

VII. ADDITIONAL REQUIREMENTS.**# 002 [25 Pa. Code §129.77.]****Control of emissions from the use or application of adhesives, sealants, primers and solvents.**

**SECTION D. Source Level Requirements**

- (a) This section applies to the owner or operator of a facility that uses or applies one or more of the following at the facility on or after January 1, 2012:
- (1) An adhesive, sealant, adhesive primer or sealant primer subject to the VOC content limits in Table V.
 - (2) An adhesive or sealant product applied to the listed substrate subject to the VOC content limits in Table VI.
 - (3) A surface preparation solvent or cleanup solvent.
- (b) On or after January 1, 2012, an owner or operator of a facility may not use or apply at the facility an adhesive, sealant, adhesive primer or sealant primer that exceeds the applicable VOC content limit in Table V or VI, except as provided elsewhere in this section.
- (c) On or after January 1, 2012, an owner or operator of a facility may not use or apply at the facility a surface preparation or cleanup solvent that exceeds the applicable VOC content limit or composite partial vapor pressure requirements of this section, except as provided elsewhere in this section.
- (d) The VOC content limits in Table VI for adhesives or sealants applied to particular substrates apply as follows:
- (1) If an owner or operator of a facility uses or applies at the facility an adhesive or sealant subject to a specific VOC content limit in Table V, the specific limit is applicable rather than the adhesive-to-substrate limit in Table VI.
 - (2) If an owner or operator of a facility uses or applies at the facility an adhesive to bond dissimilar substrates together, the applicable substrate category with the highest VOC content limit is the limit for this use.
- (e) An owner or operator of a facility subject to this section using or applying a surface preparation solvent or cleanup solvent at the facility may not:
- (1) Except as provided in paragraph (2) for single-ply roof membrane, use materials containing VOCs for surface preparation, unless the VOC content of the surface preparation solvent is less than 70 grams per liter of material or 0.6 pound of VOC per gallon of material.
 - (2) Use materials containing VOCs for surface preparation or cleanup when applying single-ply roof membrane, unless the composite partial vapor pressure, excluding water and exempt compounds, of the surface preparation solvent or cleanup solvent is less than or equal to 45 mm mercury at 20° C.
 - (3) Except as provided in subsection (f), use cleanup solvent materials containing VOCs for the removal of adhesives, sealants, adhesive primers or sealant primers from surfaces, other than from the parts of spray application equipment, unless the composite partial vapor pressure of the solvent is less than or equal to 45 mm mercury at 20° C.
- (f) Removal of an adhesive, sealant, adhesive primer or sealant primer from the parts of spray application equipment shall be performed by one or more of the following methods:
- (1) Using an enclosed cleaning system, or an equivalent cleaning system as determined by the test method identified in subsection (z).
 - (2) Using a solvent with a VOC content less than or equal to 70 grams of VOC per liter of material or 0.6 pound of VOC per gallon of material.
 - (3) Soaking parts containing dried adhesive in a solvent if the composite partial vapor pressure of the solvent, excluding water and exempt compounds, is less than or equal to 9.5 mm mercury at 20° C and the parts and solvent are in a closed container that remains closed except when adding parts to or removing parts from the container.
- (g) N/A - ADD-ON CONTROL EQUIPMENT NOT USED
- (h) An owner or operator of a facility subject to this section shall store or dispose of all absorbent materials, including cloth or paper, which are moistened with adhesives, sealants, primers, surface preparation solvents or cleanup solvents subject to this section, in nonabsorbent containers at the facility that are kept closed except when placing materials in or removing materials from the container.
- (i) An owner or operator of a facility subject to this section may not solicit, require or specify the use or application of an adhesive, sealant, adhesive primer, sealant primer, surface preparation solvent or cleanup solvent if the use or application would result in a violation of this section, unless the emissions are controlled through the use of add-on air pollution control equipment as specified in subsection (g). The prohibition of this subsection applies to all written or oral contracts created on or after January 1, 2012, under which an adhesive, sealant, adhesive primer, sealant primer, surface preparation solvent or cleanup solvent subject to this section is to be used or applied at a facility in this Commonwealth.

**SECTION D. Source Level Requirements**

(j) An owner or operator of a facility subject to this section who uses or applies an adhesive, sealant, adhesive primer or sealant primer subject to this section may not add solvent to the adhesive, sealant, adhesive primer or sealant primer in an amount in excess of the manufacturer's recommendation for application, if this addition causes the adhesive, sealant, adhesive primer or sealant primer to exceed the applicable VOC content limit listed in Table V or VI, unless the emissions are controlled through the use of add-on air pollution control equipment as specified in subsection (g).

(k) This section does not apply to the use or application of the following compounds or products:

(1) Adhesives, sealants, adhesive primers or sealant primers being tested or evaluated in a research and development, quality assurance or analytical laboratory, if records are maintained as required in subsections (p) and (q).

(2) Adhesives, sealants, adhesive primers or sealant primers that are subject to § 129.73 (relating to aerospace manufacturing and rework) or Chapter 130, Subchapter B or C (relating to consumer products; and architectural and industrial maintenance coatings).

(3) Adhesives and sealants that contain less than 20 grams of VOC per liter of adhesive or sealant, less water and less exempt compounds, as applied.

(4) Cyanoacrylate adhesives.

(5) Adhesives, sealants, adhesive primers or sealant primers that are sold or supplied by the manufacturer or supplier in containers with a net volume of 16 fluid ounces or less, or a net weight of 1 pound or less, except plastic cement welding adhesives and contact adhesives.

(6) Contact adhesives that are sold or supplied by the manufacturer or supplier in containers with a net volume of 1 gallon or less.

(l) This section does not apply to the use of adhesives, sealants, adhesive primers, sealant primers, surface preparation solvents or cleanup solvents in the following operations:

(1) Tire repair operations, if the label of the adhesive states, "For tire repair only."

(2) The assembly, repair and manufacture of aerospace components or undersea-based weapons systems.

(3) The manufacture of medical equipment.

(4) Plaque laminating operations in which adhesives are used to bond clear, polyester acetate laminate to wood with lamination equipment installed prior to July 1, 1992. An owner or operator claiming an exemption under this paragraph shall record and maintain operational records sufficient to demonstrate compliance with this exemption, in accordance with subsections (o) thru (q).

(m) This section does not apply if the total VOC emissions from all adhesives, sealants, adhesive primers and sealant primers used or applied at the facility are less than 200 pounds or an equivalent volume, per calendar year. An owner or operator of a facility claiming exemption under this subsection shall record and maintain operational records sufficient to demonstrate compliance with this exemption, in accordance with subsections (o) thru (q).

(n) This section does not apply to the use or application of a noncomplying adhesive, sealant, adhesive primer, sealant primer, surface preparation solvent or cleanup solvent if the total volume of noncomplying adhesives, sealants, primers, surface preparation and cleanup solvents used or applied facility-wide does not exceed 55 gallons per calendar year. An owner or operator of a facility claiming exemption under this subsection shall record and maintain operational records sufficient to demonstrate compliance with this exemption, in accordance with subsections (o) thru (q).

(o) Except as provided in subsection (p), each owner or operator subject to this section shall maintain records demonstrating compliance with this section, including the following information:

(1) A list of each adhesive, sealant, adhesive primer, sealant primer, surface preparation solvent and cleanup solvent product in use and in storage.

(2) A data sheet or material list which provides the product name, manufacturer identification and use or material application for each product included on the list required under paragraph (1).

(3) The VOC content of each product on the list required under paragraph (1), as supplied.

(4) Catalysts, reducers or other components used and the mix ratio.

(5) The VOC content or vapor pressure of each product on the list required by paragraph (1), as applied, if solvent or other VOC is added to the product before application.

(6) The volume purchased or produced of each product on the list required under paragraph (1).

(7) The monthly volume used or applied as part of a manufacturing process at the facility of each product on the list required under paragraph (1).

**SECTION D. Source Level Requirements**

(p) For an adhesive, sealant, adhesive primer and sealant primer product subject to the laboratory testing exemption of subsection (k)(1), the person conducting the testing shall make and maintain records of all products used, including the following information:

- (1) The product name.
- (2) The product category of the material or type of application.
- (3) The VOC content of the material.

(q) Records made to determine compliance with this section shall be:

- (1) Maintained onsite for 5 years from the date the record is created.
- (2) Made available to the Department upon receipt of a written request.

(r) Except as otherwise provided in this section, the VOC and solids content of nonaerosol adhesives (including one-part moisture cure urethane adhesives and silicone adhesives), sealants, adhesive primers, sealant primers, surface preparation solvents and cleanup solvents shall be determined using one of the following:

- (1) EPA Reference Method 24, Determination of Volatile Matter Content, Water Content, Density, Volume Solids, and Weight Solids of Surface Coatings, found at 40 CFR 60, Subpart D, Appendix A, including updates and revisions.
- (2) SCAQMD Method 304, Determination of Volatile Organic Compounds (VOC) in Various Materials, SCAQMD, 21865 Copley Drive, Diamond Bar, CA 91765 USA, including updates and revisions.

(s) The weight volatile matter content and weight solids content for one-part or multiple part reactive adhesives, except one-part moisture cure urethane adhesives and silicone adhesives, shall be determined using the EPA Reference Method, Determination of Weight Volatile Matter Content and Weight Solids Content of Reactive Adhesives, found at 40 CFR 63, Subpart P, Appendix A, including updates and revisions.

(t) The identity and concentration of exempt organic compounds shall be determined using one of the following:

- (1) ASTM D4457, Standard Test Method for Determination of Dichloromethane and 1,1,1-Trichloroethane in Paints and Coatings by Direct Injection into a Gas Chromatograph, ASTM International, 100 Barr Harbor Drive, P. O. Box C700, West Conshohocken, PA 19428-2959 USA including updates and revisions.
- (2) SCAQMD Method 303, Determination of Exempt Compounds, SCAQMD, 21865 Copley Drive, Diamond Bar, CA 91765 USA, including updates and revisions.

(u) The VOC content of a plastic cement welding adhesive or primer shall be determined using SCAQMD Method 316A, Determination of Volatile Organic Compounds (VOC) in Materials Used for Pipes and Fittings, SCAQMD, 21865 Copley Drive, Diamond Bar, CA 91765 USA, including updates and revisions.

(v) To determine if a diluent is a reactive diluent, the percentage of the reactive organic compound that becomes an integral part of the finished material shall be determined using SCAQMD Method 316A, Determination of Volatile Organic Compounds (VOC) in Materials Used for Pipes and Fittings, SCAQMD, 21865 Copley Drive, Diamond Bar, CA 91765 USA, including updates and revisions.

(w) The composite partial vapor pressure of organic compounds in cleaning materials shall be determined by the following procedure:

- (1) Quantifying the amount of each compound in the blend using gas chromatographic analysis, using the following methods:
 - (i) ASTM E260, Standard Practice for Packed Column Gas Chromatography, ASTM International, 100 Barr Harbor Drive, P. O. Box C700, West Conshohocken, PA 19428-2959 USA, for organic content, including updates and revisions.
 - (ii) ASTM D3792, Standard Test Method for Water Content of Coatings by Direct Injection Into a Gas Chromatograph, ASTM International, 100 Barr Harbor Drive, P. O. Box C700, West Conshohocken, PA 19428-2959 USA, for water content, including updates and revisions.
- (2) Calculating the composite partial vapor pressure using the following equation:

REFER TO REGULATION FOR EQUATION

(x) The vapor pressure of each single component compound shall be determined from one or more of the following:

- (1) ASTM D2879, Standard Test Method for Vapor Pressure-Temperature Relationship and Initial Decomposition Temperature of Liquids by Isoteniscope, ASTM International, 100 Barr Harbor Drive, P. O. Box C700, West Conshohocken,

**SECTION D. Source Level Requirements**

PA 19428-2959 USA, including updates and revisions.

(2) The most recent edition of one or more of the following sources:

- (i) Vapour Pressures of Pure Substances, Boublik, Elsevier Scientific Publishing Company, New York.
- (ii) Perry's Chemical Engineers Handbook, Green and Perry, McGraw-Hill Book Company.
- (iii) CRC Handbook of Chemistry and Physics, CRC Press.
- (iv) Lange's Handbook of Chemistry, McGraw-Hill Book Company.
- (v) Additional sources approved by the SCAQMD or other California air districts.

(y) N/A - ADD-ON CONTROL EQUIPMENT NOT USED

(z) The active and passive solvent losses from the use of an enclosed spray gun cleaning system or equivalent cleaning system, as listed in subsection (f)(1), shall be determined using the SCAQMD method, General Test Method for Determining Solvent Losses from Spray Gun Cleaning Systems, dated October 3, 1989, SCAQMD, 21865 Copley Drive, Diamond Bar, CA 91765 USA, including updates and revisions.

(1) The test solvent for this determination shall be a lacquer thinner with a minimum vapor pressure of 105 mm of mercury at 20° C.

(2) The minimum test temperature shall be 15° C.

(aa) Another test method may be used to determine the VOC or solids content of a product if the request for approval of the test method meets the following requirements:

- (1) The request is submitted to the Department in writing.
- (2) The request demonstrates that the test method provides results that accurately determine the concentration of VOCs in the product or its emissions.
- (3) The Department approves the request in writing.

(bb) For adhesive, sealant, adhesive primer or sealant primer products that do not contain reactive diluents, grams of VOC per liter of product thinned to the manufacturer's recommendation, less water and exempt compounds, shall be calculated according to the following equation:

Grams of VOC per liter of product, as applied = $(W_s - W_w - W_e)/(V_m - V_w - V_e)$

Where:

W_s = weight of volatile compounds, in grams.

W_w = weight of water, in grams.

W_e = weight of exempt compounds, in grams.

V_m = volume of material, in liters.

V_w = volume of water, in liters.

V_e = volume of exempt compounds, in liters.

(cc) For adhesive, sealant, adhesive primer or sealant primer products that contain reactive diluents, the VOC content of the product is determined after curing. The grams of VOC per liter of product thinned to the manufacturer's recommendation, less water and exempt compounds, shall be calculated according to the following equation:

Grams of VOC per liter of product, as applied = $(W_{rs} - W_{rw} - W_{re})/(V_{rm} - V_{rw} - V_{re})$

Where:

W_{rs} = weight of volatile compounds not consumed during curing, in grams.

W_{rw} = weight of water not consumed during curing, in grams.

W_{re} = weight of exempt compounds not consumed during curing, in grams.

V_{rm} = volume of material not consumed during curing, in liters.

V_{rw} = volume of water not consumed during curing, in liters.

V_{re} = volume of exempt compounds not consumed during curing, in liters.

(dd) For low-solids adhesive, sealant, adhesive primer or sealant primer products, grams of VOC per liter of product thinned to the manufacturer's recommendation, including the volume of water and exempt compounds, shall be calculated according to the following equation:

**SECTION D. Source Level Requirements**

Grams of VOC per liter of product, as applied = $(W_s - W_w - W_e)/V_m$

Where:

W_s = weight of volatile compounds, in grams.

W_w = weight of water, in grams.

W_e = weight of exempt compounds, in grams.

V_m = volume of material, in liters.

(ee) Percent VOC by weight shall be calculated according to the following equation:

% VOC by weight = $[(W_v/W)] \times 100$

Where:

W_v = weight of VOCs, in grams.

W = weight of material, in grams.

(ff) To convert from grams per liter (g/l) to pounds per gallon (lb/gal), multiply the result (VOC content) by 8.345×10^{-3} (lb/gal/g/l).



SECTION E. Source Group Restrictions.



SECTION F. Alternative Operation Requirements.

No Alternative Operations exist for this State Only facility.



SECTION G. Emission Restriction Summary.

No emission restrictions listed in this section of the permit.

**SECTION H. Miscellaneous.**

(a) The Department received the operating permit application for this facility on 03/20/23. The facility is required to pay an Annual Operating Permit Maintenance Fee in accordance with Pennsylvania Code, Title 25, Chapter 127, Section 127.703(d). The Annual Maintenance Fee is due on or before December 31 of each year for the next calendar year.

(b) This permit is a new permit and includes conditions from Plan Approval # 54-00098A issued January 30, 2023.

(c) This is a Natural Minor Operating Permit facility.

(d) Insignificant sources.

The following sources do not require any restrictions, work practice standards or testing, monitoring, recordkeeping and reporting requirements:

(1) Welding Booth - it is not subject to 40 CFR Part 63, Subpart XXXXXX since the facility's NAICS code is not applicable.

(2) Maintenance Shop parts washer - the washer fluid does not contain VOCs.

(3) Quanex Duralite window spacer tape - does not contain VOCs.



***** End of Report *****
