

*E&S Plan Drawings*

[illegible]

JULY 02, 2025

SHEET INDEX				
EROSION AND SEDIMENT CONTROL DRAWINGS				
NO.	TITLE	SHEET	REVISION	
0-001-1001	EAC COVER SHEET			
0-001-1002	GENERAL NOTES	1	A	
C144-001	VERTICAL CURVING CHORD PLAN	1	A	
C144-002	OVERALL EROSION & SEDIMENT CONTROL PLAN	1	A	
C144-002	ROADWAY EROSION & SEDIMENT CONTROL PLANS	1	A	
C144-002	ROADWAY EROSION & SEDIMENT CONTROL PLANS	2	A	
C144-002	ROADWAY EROSION & SEDIMENT CONTROL PLANS	3	A	
C144-002	ROADWAY EROSION & SEDIMENT CONTROL PLANS	4	A	
C144-001	ROADWAY PROFILES	1	A	
C144-002	ROADWAY PROFILES	1	A	
C144-003	ROADWAY PROFILES	1	A	
C144-004	CHANNEL PROFILES	1	A	
C144-005	CHANNEL PROFILES	1	A	
C144-006	CULVERT PROFILES	1	A	
C144-001	EIS NOTES & DETAILS	1	A	
C144-002	EIS NOTES & DETAILS	1	A	
C144-003	EIS NOTES & DETAILS	1	A	
C144-004	EIS NOTES & DETAILS	1	A	
C144-005	EIS NOTES & DETAILS	1	A	




	<b>Michael Baker International</b>			<b>MICHAEL BAKER INTERNATIONAL, LLC</b> 1000 WILSON ROAD ANN ARBOR, MI 48106		
<b>HOMER CITY STATION</b>						
				1000 POWER PLANT ROAD HOMER CITY, PA 15120		
(DWG. TYPE)				<b>GENERAL</b>		
(TITLE)				<b>E&amp;S COVER SHEET</b>		
PROJECT NAME: POWER PLANT ROAD RELOCATION						
MTS	PPR1	C-001-1001			A	A
SCALE	PROJECT NO.	DRAWING NUMBER	SHEET	RE		

### SANITARY UTILITY NOTES

1. ALL SANITARY SEWER AND ASSOCIATED DEVICES WORK MUST BE COORDINATED WITH THE UTILITY OWNER.
2. ALL SANITARY SEWER BUILDING CONNECTIONS ARE TO BE MADE USING 6.00 INCH LINES UNLESS INDICATED OTHERWISE.
3. ALL SANITARY LINES ARE TO BE Laid AT A UNIFORM SLOPE FROM THE BUILDING CONNECTIONS TO THE CONNECTING SEWER AND BETWEEN UTILITY STRUCTURES.
4. SEWER LINES SHALL BE INSTALLED A MINIMUM OF 10.00 FEET HORIZONTALLY FROM ADJACENT WATER LINES UNLESS INDICATED OTHERWISE. SEE SPECIFICATIONS FOR ADDITIONAL CLEARANCE REQUIREMENTS FOR SANITARY PIPING.
5. SEWER LINES SHALL BE INSTALLED BELOW WATER LINES WITH A MINIMUM VERTICAL SEPARATION OF 18 INCHES UNLESS INDICATED OTHERWISE. WHERE SANITARY SEWER WILL BE INSTALLED ABOVE WATER LINES, IT SHALL BE ENCASED IN CONCRETE DETAILS.
6. IF MANHOLES ARE INDICATED ON SANITARY LINES, A 3.00 INCH DROP IN ELEVATION BETWEEN THE INCOMING AND OUTGOING SEWER SHALL BE PROVIDED IN EACH MANHOLE UNLESS INDICATED OTHERWISE. FOR 90°-TYPE MANHOLE ORIENTATIONS, THE MINIMUM DROP ACROSS MANHOLE CHANNELS IS 12 INCHES. INVERT FLOW CHANNELS SHALL BE CONSTRUCTED TO PROVIDE SMOOTH AND UNIFORM FLOW WITH GRADUAL TRANSITION SECTIONS.
7. CONTRACTOR SHALL BE RESPONSIBLE FOR ANY NECESSARY BRIDGING OR TANKER TRUCKS NEEDED DURING SANITARY SEWER INSTALLATION TO MAINTAIN ACCESS TO ALL ADJACENT PROPERTIES.
8. ALL EXISTING STRUCTURES TO REMAIN THAT ARE BEING ALTERED OR ADJUSTED SHALL BE INSPECTED PRIOR TO WORK. STRUCTURES SHALL BE REPLACED IF THE STRUCTURE IS IN POOR CONDITION.


1. ALL UTILITY STRUCTURES ARE TO BE H400 RATED UNLESS INDICATED OTHERWISE.
2. MANHOLE RIM ELEVATIONS SHALL BE FLUSH WITH ADJACENT FINAL OR EXISTING GRADE ACCORDING TO THE PROVIDED STORM PROFILES AND STRUCTURE TABLES.
3. COVERS AND CASTINGS OF MANHOLES AND STRUCTURES SHALL BE STAMPED PER THE APPROPRIATE UTILITY TYPE OR PER THE LOCAL STANDARDS.
4. COVERS AND CASTINGS SHALL BE TAMPER-PROOF FOR STRUCTURES LOCATED IN PEDESTRIAN SPACES, EASEMENT AREAS, AND AREAS WITH SPECIAL SECURITY RESTRICTIONS.
5. ANY LIFT LOOPS FOR UTILITY STRUCTURES SHALL BE GROUDED FLUSH AFTER INSTALLATION.
6. PIPE MAY EXTEND 2 INCHES MAXIMUM BEYOND INTERIOR MANHOLE WALL.

**PROJECT SERIAL NUMBER:**










- NOTES
- EXISTING SITE, AND UTILITY INFORMATION COMPILED FROM HOMER CITY GENERATION LP TAX MAP NO. 12-017-103.00. LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND SHOULD BE LOCATED IN THE FIELD PRIOR TO CONSTRUCTION. SURVEY OF EXISTING SITE AND UTILITY INFORMATION WAS COMPLETED ON SEPTEMBER 2, 2024.
  - EXISTING CONDITIONS ARE BASED ON AVAILABLE PAST DATA. CONTAIN INFORMATION AND SHOULD BE CONSIDERED APPROPRIATE.
  - EXISTING STREAMS AND WETLANDS WERE DELINEATED BY MICHAEL BAKER INTERNATIONAL, INC. IN JUNE 2024.
  - HORIZONTAL DATUM IS BASED ON HOMER CITY STATION GRID SYSTEM.




<b>Michael Baker International, Inc.</b>	
<b>HOMER CITY STATION</b>	
1200 PINE HILL ROAD HOMER CITY, IN 47301	
DWG. TYPE: CIVIL	
TITLE: OVERALL EROSION & SEDIMENT CONTROL PLAN	
PROJECT NAME: POWER PLANT ROAD RELOCATION	
SCALE: PROJECT NOT	DRAWING NUMBER: C-744-3001
SHEET: 1	SHEET TOTAL: 1



- NOTES**
1. EXISTING SITE, AND UTILITY INFORMATION COMPILED FROM HOMER CITY GENERATIONS AS-BUILTS AND PLANT DESIGN DRAWINGS. LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND SHOULD BE LOCATED IN THE FIELD PRIOR TO CONSTRUCTION. SURVEY OF EXISTING SITE AND UTILITY INFORMATION WAS COMPLETED ON SEPTEMBER 2, 2024.
  2. EXISTING CONDITIONS ARE BASED ON AVAILABLE PASDA CONTOUR INFORMATION AND SHOULD BE CONSIDERED APPROXIMATE.
  3. EXISTING STREAMS AND WETLANDS WERE DELINEATED BY MICHAEL BAKER INTERNATIONAL, INC IN JUNE 2024.
  4. HORIZONTAL DATUM IS BASED ON HOMER CITY STATION GRID SYSTEM.



### KEY PLAN



**Michael Baker**  
INTERNATIONAL

**MICHAEL BAKER**  
INTERNATIONAL, LLC  
100 ARSIDE DRIVE  
MOON TOWNSHIP, PA 15108

**HOMER CITY STATION**

1100 POWER PLANT ROAD  
POWER CITY, IN 45960


2. TYPE: CIVIL

### E) ROADWAY EROSION & SEDIMENT CONTROL PLANS

1990-1991 1991-1992 1992-1993 1993-1994 1994-1995 1995-1996 1996-1997 1997-1998 1998-1999 1999-2000 2000-2001 2001-2002 2002-2003 2003-2004 2004-2005 2005-2006 2006-2007 2007-2008 2008-2009 2009-2010 2010-2011 2011-2012 2012-2013 2013-2014 2014-2015 2015-2016 2016-2017 2017-2018 2018-2019 2019-2020 2020-2021 2021-2022 2022-2023 2023-2024 2024-2025 2025-2026 2026-2027 2027-2028 2028-2029 2029-2030 2030-2031 2031-2032 2032-2033 2033-2034 2034-2035 2035-2036 2036-2037 2037-2038 2038-2039 2039-2040 2040-2041 2041-2042 2042-2043 2043-2044 2044-2045 2045-2046 2046-2047 2047-2048 2048-2049 2049-2050 2050-2051 2051-2052 2052-2053 2053-2054 2054-2055 2055-2056 2056-2057 2057-2058 2058-2059 2059-2060 2060-2061 2061-2062 2062-2063 2063-2064 2064-2065 2065-2066 2066-2067 2067-2068 2068-2069 2069-2070 2070-2071 2071-2072 2072-2073 2073-2074 2074-2075 2075-2076 2076-2077 2077-2078 2078-2079 2079-2080 2080-2081 2081-2082 2082-2083 2083-2084 2084-2085 2085-2086 2086-2087 2087-2088 2088-2089 2089-2090 2090-2091 2091-2092 2092-2093 2093-2094 2094-2095 2095-2096 2096-2097 2097-2098 2098-2099 2099-2100 2100-2101 2101-2102 2102-2103 2103-2104 2104-2105 2105-2106 2106-2107 2107-2108 2108-2109 2109-2110 2110-2111 2111-2112 2112-2113 2113-2114 2114-2115 2115-2116 2116-2117 2117-2118 2118-2119 2119-2120 2120-2121 2121-2122 2122-2123 2123-2124 2124-2125 2125-2126 2126-2127 2127-2128 2128-2129 2129-2130 2130-2131 2131-2132 2132-2133 2133-2134 2134-2135 2135-2136 2136-2137 2137-2138 2138-2139 2139-2140 2140-2141 2141-2142 2142-2143 2143-2144 2144-2145 2145-2146 2146-2147 2147-2148 2148-2149 2149-2150 2150-2151 2151-2152 2152-2153 2153-2154 2154-2155 2155-2156 2156-2157 2157-2158 2158-2159 2159-2160 2160-2161 2161-2162 2162-2163 2163-2164 2164-2165 2165-2166 2166-2167 2167-2168 2168-2169 2169-2170 2170-2171 2171-2172 2172-2173 2173-2174 2174-2175 2175-2176 2176-2177 2177-2178 2178-2179 2179-2180 2180-2181 2181-2182 2182-2183 2183-2184 2184-2185 2185-2186 2186-2187 2187-2188 2188-2189 2189-2190 2190-2191 2191-2192 2192-2193 2193-2194 2194-2195 2195-2196 2196-2197 2197-2198 2198-2199 2199-2200 2200-2201 2201-2202 2202-2203 2203-2204 2204-2205 2205-2206 2206-2207 2207-2208 2208-2209 2209-2210 2210-2211 2211-2212 2212-2213 2213-2214 2214-2215 2215-2216 2216-2217 2217-2218 2218-2219 2219-2220 2220-2221 2221-2222 2222-2223 2223-2224 2224-2225 2225-2226 2226-2227 2227-2228 2228-2229 2229-2230 2230-2231 2231-2232 2232-2233 2233-2234 2234-2235 2235-2236 2236-2237 2237-2238 2238-2239 2239-2240 2240-2241 2241-2242 2242-2243 2243-2244 2244-2245 2245-2246 2246-2247 2247-2248 2248-2249 2249-2250 2250-2251 2251-2252 2252-2253 2253-2254 2254-2255 2255-2256 2256-2257 2257-2258 2258-2259 2259-2260 2260-2261 2261-2262 2262-2263 2263-2264 2264-2265 2265-2266 2266-2267 2267-2268 2268-2269 2269-2270 2270-2271 2271-2272 2272-2273 2273-2274 2274-2275 2275-2276 2276-2277 2277-2278 2278-2279 2279-2280 2280-2281 2281-2282 2282-2283 2283-2284 2284-2285 2285-2286 2286-2287 2287-2288 2288-2289 2289-2290 2290-2291 2291-2292 2292-2293 2293-2294 2294-2295 2295-2296 2296-2297 2297-2298 2298-2299 2299-2300 2300-2301 2301-2302 2302-2303 2303-2304 2304-2305 2305-2306 2306-2307 2307-2308 2308-2309 2309-2310 2310-2311 2311-2312 2312-2313 2313-2314 2314-2315 2315-2316 2316-2317 2317-2318 2318-2319 2319-2320 2320-2321 2321-2322 2322-2323 2323-2324 2324-2325 2325-2326 2326-2327 2327-2328 2328-2329 2329-2330 2330-2331 2331-2332 2332-2333 2333-2334 2334-2335 2335-2336 2336-2337 2337-2338 2338-2339 2339-2340 2340-2341 2341-2342 2342-2343 2343-2344 2344-2345 2345-2346 2346-2347 2347-2348 2348-2349 2349-2350 2350-2351 2351-2352 2352-2353 2353-2354 2354-2355 2355-2356 2356-2357 2357-2358 2358-2359 2359-2360 2360-2361 2361-2362 2362-2363 2363-2364 2364-2365 2365-2366 2366-2367 2367-2368 2368-2369 2369-2370 2370-2371 2371-2372 2372-2373 2373-2374 2374-2375 2375-2376 2376-2377 2377-2378 2378-2379 2379-2380 2380-2381 2381-2382 2382-2383 2383-2384 2384-2385 2385-2386 2386-2387 2387-2388 2388-2389 2389-2390 2390-2391 2391-2392 2392-2393 2393-2394 2394-2395 2395-2396 2396-2397 2397-2398 2398-2399 2399

507	PPRR1	C-744-3002	1	A
-----	-------	------------	---	---



FILE	PROJECT NO.	DRAWING NUMBER	SHEET	REV
FILES\202955_CE1XX.DWG PLOT DATE:7/21/2025 1:12 PM				



- ### NOTES
1. EXISTING SITE, AND UTILITY INFORMATION COMPILED FROM HOMER CITY GENERATION AS-BUILTS AND PLANT DESIGN DRAWINGS. LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND SHOULD BE LOCATED IN THE FIELD PRIOR TO CONSTRUCTION. SURVEY OF EXISTING SITE AND UTILITY INFORMATION WAS COMPLETED ON SEPTEMBER 2, 2024.
  2. EXISTING CONDITIONS ARE BASED ON AVAILABLE PASTORAL CONDITION INFORMATION AND SHOULD BE CONSIDERED APPROXIMATE.
  3. EXISTING STREAMS AND WETLANDS WERE DELINEATED BY MICHAEL BAKER INTERNATIONAL, INC. IN JUNE 2024.
  4. HORIZONTAL DATUM IS BASED ON HOMER CITY STATION GR SYSTEM.



### KEY PLAN




**Michael Baker**  
INTERNATIONAL

**HOMER CITY STATION**  
1700 POWER PLANT ROAD  
HOMER CITY, PA. 15106

DWG. TYPE:	CIVIL
TITLE:	ROADWAY EROSION & SEDIMENT CONTROL PLANS

PROJECT NAME: POWER PLANT ROAD RELOCATION			
1" = 50'	PPRR1	C-744-3002	2
SCALE	PROJECT NO.	DRAWING NUMBER	SHEET



**NOTES**

1. EXISTING SITE, AND UTILITY INFORMATION COMPILED FROM HOMER CITY GENERATION AS-BUILTS AND PLANT DESIGN DRAWINGS. LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND SHOULD BE LOCATED IN THE FIELD PRIOR TO CONSTRUCTION. SURVEY OF EXISTING SITE, AND UTILITY INFORMATION WAS COMPLETED ON SEPTEMBER 2, 2024.
2. EXISTING CONDITIONS ARE BASED ON AVAILABLE PAIQA CONTOUR INFORMATION AND SHOULD BE CONSIDERED APPROXIMATE.
3. EXISTING STREAMS AND WETLANDS WERE DELINEATED BY MICHAEL BAKER INTERNATIONAL, INC IN JUNE 2024.
4. HORIZONTAL DATUM IS BASED ON HOMER CITY STATION GRID SYSTEM.



### KEY PLAN



0' 50' 100' 150'

Scale in Feet


**Michael Baker International, LLC**

**HOMER CITY STATION**  
1730 POWER PLANT ROAD  
HOMER CITY, PA. 15106

TYPE: CIVIL

CT NAME: POWER PLANT ROAD RELOCATION

PROJECT NO. DRAWING NUMBER SHEET REV  
S\202965\_CEXXX.DWG PLOT DATE:7/21/2025 1:12 PM



**NOTES**



- EXISTING SITE AND UTILITY INFORMATION COMPILED FROM HOMER CITY GENERATION LP SURVEY AND PLANT DESIGN DRAWINGS. LOCATIONS OF EXISTING UTILITIES ARE APPROXIMATE AND SHOULD BE LOCATED IN THE FIELD PRIOR TO CONSTRUCTION. SURVEY OF EXISTING SITE AND UTILITY INFORMATION WAS COMPLETED ON SEPTEMBER 1, 2021. EXISTING CONDITIONS ARE BASED ON AVAILABLE PAST DATA. CONSTRUCTION INFORMATION SHOULD BE CHECKED FOR APPROXIMATE.
- EXISTING STREAMS AND WETLANDS WERE DELINEATED BY MICHAEL BAKER INTERNATIONAL, INC. IN JUNE 2021.
- HORIZONTAL DATUM IS BASED ON HOMER CITY 15-10-10N GRID SYSTEM.

**KEY PLAN**

0' 50' 100' 150'  
Scale in Feet

**Michael Baker International, Inc.**  
MICHAEL BAKER INTERNATIONAL, LLC  
1000 WEST 10TH AVE  
HOMER CITY, OH 43924  
419.326.1000

HOMER CITY STATION			
DWG. TYPE: CIVIL			
TITLE: ROADWAY EROSION & SEDIMENT CONTROL PLANS			
PROJECT NAME: POWER PLANT ROAD RELOCATION			
1" = 80'	PPR01	C-744-3002	4 A
SCALE	PROJECT NO.	DRAWING NUMBER	SHEET NO.



PROFESSIONAL ENGINEER  
MICHAEL THOMAS SLATTS  
STATE OF FLORIDA  
LICENSE NO. 12543  
EXPIRATION DATE 12/31/2025

LEGEND

PROPOSED GRADE  
EXISTING GRADE

Scale in Feet (Vert.)  
0' 10' 20' 30'

Scale in Feet (Horiz.)  
0' 30' 60' 90'




Michael Baker International, LLC

HOMER CITY STATION

DWG. TYPE: CIVIL  
TITLE: ROADWAY PROFILES

PROJECT NAME: POWER PLANT ROAD RELOCATION  
SCALE: PROJECT NO. C-744-3201  
DRAWING NUMBER 1  
SHEET 1A

10 9 8 7 6 5 4 3 2 1



Michael Baker International, LLC

HOMER CITY STATION

PROJECT NAME: POWER PLANT ROAD RELOCATION


DWG. TYPE: CIVIL

TITLE: ROADWAY PROFILES






PROJECT NO: C-744-3202

DRAWING NUMBER: 1


SHEET: 1







<b>Michael Baker International, Inc.</b>	
<b>HOMER CITY STATION</b>	
100 WEST MAIN STREET HOMER CITY, PA 15043	
DWG. TYPE: CIVIL	
TITLE: CHANNEL PROFILES	
PROJECT NAME: POWER PLANT ROAD RELOCATION	
1" = 30'	PPRR1
C-744-3204	1 A
SCALE	PROJECT NO.
DRAWING NUMBER	SHEET NO.



**Michael Baker**  
INTERNATIONAL, LLC

HOMER CITY STATION

1730 POWER PLANE ROAD  
POWER CITY, PA 15140

© 2006 The Authors  
Journal compilation © 2006 Blackwell Publishing Ltd

NO. 100	CIVIL
FILE	CHANNEL PROFILES

---


PROJECT NAME: POWER PLANT ROAD RELOCATION

" = 30'	PPRR1	C-744-3205	1	A
SCALE	PROJECT NO.	DRAWING NUMBER	SHEET	NO.

FILES\202965\_CS2XX.DWG PLOT DATE:6/27/2025 1:01



STORM STRUCTURES TABLE			
STRUCTURE ID	DATA	LOCATION	
FOREBAY DCS	STANDARD BOX INLET WITH TRASH RACK RM=101.45 IN V. OUT=101.50 E. 1900279.89	N. 420814.83 E. 1900279.89	
HH-1	TYPE D-4 ENDWALL RM=106.71 IN V. OUT=107.15 E. 1900255.34	N. 420873.08 E. 1900255.34	
HH-2	TYPE D ENDWALL RM=102.71 IN V. OUT=103.15 E. 1900258.52	N. 420818.84 E. 1900258.52	
HH-4	TYPE D ENDWALL RM=102.37 IN V. OUT=102.75 E. 1900258.52	N. 420818.84 E. 1900258.52	
HH-5	TYPE D ENDWALL RM=110.37 IN V. OUT=110.75 E. 1900279.89	N. 420818.84 E. 1900279.89	
HH-6	TYPE D ENDWALL RM=110.37 IN V. OUT=110.75 E. 1900279.89	N. 420818.84 E. 1900279.89	
HH-7	TYPE D ENDWALL RM=110.37 IN V. OUT=110.75 E. 1900279.89	N. 420818.84 E. 1900279.89	
HH-8	TYPE D ENDWALL RM=110.37 IN V. OUT=110.75 E. 1900279.89	N. 420818.84 E. 1900279.89	
HH-9	TYPE D ENDWALL RM=110.37 IN V. OUT=110.75 E. 1900279.89	N. 420818.84 E. 1900279.89	
HH-10	TYPE D ENDWALL RM=110.37 IN V. OUT=110.75 E. 1900279.89	N. 420818.84 E. 1900279.89	
HH-11	TYPE D ENDWALL RM=110.37 IN V. OUT=110.75 E. 1900279.89	N. 420818.84 E. 1900279.89	
HH-12	TYPE D ENDWALL RM=110.37 IN V. OUT=110.75 E. 1900279.89	N. 420818.84 E. 1900279.89	
HH-13	TYPE D ENDWALL RM=110.37 IN V. OUT=110.75 E. 1900279.89	N. 420818.84 E. 1900279.89	
HH-01	TYPE M STANDARD BOX INLET RM=101.31 IN V. OUT=101.75 E. 1900279.89	N. 420818.84 E. 1900279.89	
HH-02	TYPE M STANDARD BOX INLET RM=101.31 IN V. OUT=101.75 E. 1900279.89	N. 420818.84 E. 1900279.89	
HH-03	TYPE M STANDARD BOX INLET RM=101.31 IN V. OUT=101.75 E. 1900279.89	N. 420818.84 E. 1900279.89	
HH-04	STANDARD BOX INLET WITH TRASH RACK RM=105.50 IN V. OUT=105.95 E. 1900255.34	N. 420818.84 E. 1900255.34	
HH-05	STANDARD BOX INLET WITH TRASH RACK RM=105.50 IN V. OUT=105.95 E. 1900255.34	N. 420818.84 E. 1900255.34	
HH-01	TYPE 4 MANHOLE RM=104.12 IN V. OUT=104.55 E. 1900255.34	N. 420818.84 E. 1900255.34	
HH-02	TYPE 4 MANHOLE RM=104.12 IN V. OUT=104.55 E. 1900255.34	N. 420818.84 E. 1900255.34	
HH-03	TYPE 4 MANHOLE RM=104.12 IN V. OUT=104.55 E. 1900255.34	N. 420818.84 E. 1900255.34	
HH-04	TYPE 4 MANHOLE RM=104.12 IN V. OUT=104.55 E. 1900255.34	N. 420818.84 E. 1900255.34	
HH-05	TYPE 4 MANHOLE RM=104.12 IN V. OUT=104.55 E. 1900255.34	N. 420818.84 E. 1900255.34	
OUTLET CONTROL STRUCTURE	STANDARD BOX INLET WITH TRASH RACK RM=101.31 IN V. OUT=101.75 E. 1900279.89	N. 420818.84 E. 1900279.89	

STORM STRUCTURES TABLE			
STRUCTURE ID	DATA	LOCATION	
BEND-01	18" 10' RCP BEND IN V. OUT=101.50 E. 1900279.89	N. 420814.83 E. 1900279.89	
BEND-02	18" 10' RCP BEND IN V. OUT=101.50 E. 1900279.89	N. 420814.83 E. 1900279.89	
BEND-03	18" 10' RCP BEND IN V. OUT=101.50 E. 1900279.89	N. 420814.83 E. 1900279.89	
BEND-04	18" 10' RCP BEND IN V. OUT=101.50 E. 1900279.89	N. 420814.83 E. 1900279.89	
BEND-05	18" 10' RCP BEND IN V. OUT=101.50 E. 1900279.89	N. 420814.83 E. 1900279.89	
BEND-06	18" 10' RCP BEND IN V. OUT=101.50 E. 1900279.89	N. 420814.83 E. 1900279.89	
BEND-07	18" 10' RCP BEND IN V. OUT=101.50 E. 1900279.89	N. 420814.83 E. 1900279.89	
BEND-08	18" 10' RCP BEND IN V. OUT=101.50 E. 1900279.89	N. 420814.83 E. 1900279.89	
BEND-09	18" 10' RCP BEND IN V. OUT=101.50 E. 1900279.89	N. 420814.83 E. 1900279.89	
BEND-10	18" 10' RCP BEND IN V. OUT=101.50 E. 1900279.89	N. 420814.83 E. 1900279.89	












PROPERTY	TEST METHOD	MINIMUM STANDARD
AUG. WIND HIGH STRENGTH	ASTM D-4864	100 LB
TEAR TENSILE	ASTM D-4864	100 LB
PUNCTURE	ASTM D-4864	100 LB
WALL TENSILE	ASTM D-4864	100 LB
UV RESISTANCE	ASTM D-4864	100%
AGE RETAINED	ASTM D-4864	80%

NOTES:


- LOW VOLUME FILTER BAGS SHALL BE MADE FROM NON-WOVEN GEOTEXTILE MATERIAL, SEWN WITH HIGH STRENGTH DOUBLE STITCHED "Y" TYPE SEAMS. THEY SHALL BE CAPABLE OF TRAPPING PARTICLES LARGER THAN 10 MICRONS. HIGH VOLUME FILTER BAGS SHALL BE MADE FROM NON-WOVEN GEOTEXTILES THAT MEET THE FOLLOWING STANDARDS:
- A SUITABLE MEANS OF ACCESSING THE BAG WITH MACHINERY REQUIRED FOR DISPOSAL PURPOSES SHALL BE PROVIDED. FILTER BAGS SHALL BE REPLACED IMMEDIATELY WHEN THEY BECOME INOPERABLE. SPARE BAGS SHALL BE KEPT AVAILABLE FOR REPLACEMENT OF THOSE THAT HAVE FAILED OR ARE FILLED. BAGS SHALL BE PLACED ON STRIPS TO FACILITATE REMOVAL, UNLESS BAGS COME WITH LIFTING STRAPS ALREADY ATTACHED.
- BAGS SHALL BE LOCATED IN WELL-VEGETATED GRASSY AREA, AND DISCHARGE INTO STABLE, EROSION RESISTANT AREAS. WHERE THIS IS NOT POSSIBLE, A GEOTEXTILE UNDERLAMENT AND LOW KEY SHALL BE PROVIDED. BAGS MAY BE PLACED ON FILTER STONE TO INCREASE DISCHARGE CAPACITY. BAGS SHALL NOT BE PLACED ON SLOPES GREATER THAN 10% FOR SLOPES EXCEEDING 10% CLEAN ROCK OR OTHER NON-ERODIBLE AND NON-POLLUTING MATERIAL MAY BE PLACED UNDER THE BAG TO REDUCE SLOPE STEEPNESS.
- NO DOWNHOLE SEDIMENT BARRIER IS REQUIRED FOR MOST INSTALLATIONS. COMPOST BERM OR COMPOST FILTER ROCK SHALL BE INSTALLED BELOW BAGS LOCATED IN HIGH OR VERY WATERSHEDS, WITHIN 5 FEET OF ANY RECEIVING SURFACE WATER OR WHERE GRASSY AREA IS NOT AVAILABLE.
- THE PUMP DISCHARGE HOSE SHALL BE INSERTED INTO THE BAGS IN THE MANNER SPECIFIED BY THE MANUFACTURER AND SECURELY CLAMPED. A PIECE OF PVC PIPE IS RECOMMENDED FOR THIS PURPOSE.
- THE PUMPING RATE SHALL BE NO GREATER THAN 750 GPM OR 10% THE MAXIMUM SPECIFIED BY THE MANUFACTURER, WHICHEVER IS LESS. PUMP INTAKES SHALL BE FLUSHING AND SCREENED.
- FILTER BAGS SHALL BE INSPECTED DAILY. IF ANY PROBLEM IS DETECTED, PUMPING SHALL CEASE IMMEDIATELY AND NOT RESUME UNTIL THE PROBLEM IS CORRECTED.

TEMPORARY (EROSION CONTROL)	PERMANENT (STEEP SLOPES) (EROSION CONTROL)
SPECIES	SPECIES
% PURE LIVE SEED	% PURE LIVE SEED
SEED RATE (PER ACRE)	SEED RATE (PER ACRE)
FERTILIZER TYPE	FERTILIZER TYPE
WILCHIT TYPE	WILCHIT TYPE
WILCHIT RATE	WILCHIT RATE
WILCHIT METHOD	WILCHIT METHOD
WILCHIT MATERIAL	WILCHIT MATERIAL
WILCHIT RATE	WILCHIT RATE
WILCHIT METHOD	WILCHIT METHOD
WILCHIT MATERIAL	WILCHIT MATERIAL
WILCHIT RATE	WILCHIT RATE
WILCHIT METHOD	WILCHIT METHOD
WILCHIT MATERIAL	WILCHIT MATERIAL



OUTLET NO.	PIPE DIA. (IN)	RIPRAP SIZE (IN)	THICK. (IN)	LENGTH (FT)	INITIAL WIDTH (FT)	TERMINAL WIDTH (FT)
RA-1	18	8-16	8	8	4.5	12.0
RA-2	18	8-16	8	8	4.5	12.0
RA-3	18	8-16	8	8	4.5	12.0
RA-4	18	8-16	8	8	4.5	12.0
RA-5	12	8-16	8	3	3	9
RA-6	12	8-16	8	3	3	9
RA-7	12	8-16	8	3	3	9
RA-8	12	8-16	8	3	3	9
RA-9	12	8-16	8	3	3	9
RA-10	12	8-16	8	3	3	9
RA-11	12	8-16	8	3	3	9
RA-12	24	8-16	18	12	6	18
RA-13	12	8-16	8	3	3	9
RA-14	12	8-16	8	3	3	9
RA-15	18	8-16	8	4.5	12.0	
RA-16	12	8-16	8	3	3	9
RA-17	24	8-16	18	12	6	18

TEMPORARY (EROSION CONTROL)	PERMANENT (STEEP SLOPES) (EROSION CONTROL)
SPECIES	SPECIES
% PURE LIVE SEED	% PURE LIVE SEED
SEED RATE (PER ACRE)	SEED RATE (PER ACRE)
FERTILIZER TYPE	FERTILIZER TYPE
WILCHIT TYPE	WILCHIT TYPE
WILCHIT RATE	WILCHIT RATE
WILCHIT METHOD	WILCHIT METHOD
WILCHIT MATERIAL	WILCHIT MATERIAL
WILCHIT RATE	WILCHIT RATE
WILCHIT METHOD	WILCHIT METHOD
WILCHIT MATERIAL	WILCHIT MATERIAL
WILCHIT RATE	WILCHIT RATE
WILCHIT METHOD	WILCHIT METHOD
WILCHIT MATERIAL	WILCHIT MATERIAL



SECTION A-A SECTION B-B

**SEDIMENT BASIN CONSTRUCTION NOTES:**

- SEDIMENT BASIN, INCLUDING ALL APPURTENANT WORKS, SHALL BE CONSTRUCTED TO THE DETAIL AND DIMENSIONS SHOWN ON THE E&S PLANDRAWINGS.
- ACCESS FOR SEDIMENT REMOVAL AND OTHER REQUIRED MAINTENANCE ACTIVITIES SHALL BE PROVIDED.
- CONCRETE BASE SHALL BE POURED IN SUCH A MANNER AS TO INSURE THAT CONCRETE FILL BOTTOM OF RISER TO INVERT OF THE OUTLET PIPE TO PREVENT RISER FROM BREAKING AWAY FROM THE BASE OR PRECAST EXTENDED BASE.
- THE AREA UNDER EMANKMENT SHALL BE CLEARED, GRUBBED, AND STRIPPED OF TOPSOIL TO A DEPTH OF TWO FEET PRIOR TO ANY PLACEMENT AND COMPACTION OF EARTHWORK.
- THE EMANKMENT SHALL BE COMPACTED IN LAYERED LIFTS OF NOT MORE THAN 8" TO 10". THE MAXIMUM ROCK SIZE SHALL BE NO GREATER THAN 30 THE LIFT THICKNESS. FIVE PASSES OF THE COMPACTION EQUIPMENT OVER THE ENTIRE SURFACE OF EACH LIFT IS REQUIRED. EMANKMENT COMPACTION TO VISIBLE NONMOVEMENT IS ALSO REQUIRED.
- SOILS ACCEPTABLE FOR EMANKMENT CONSTRUCTION SHOULD BE LIMITED TO GC, GW, SC, SM, CL, OR ML AS DESCRIBED IN ASTM 2487 (UNIFIED SOILS CLASSIFICATION). FILL MATERIAL FOR THE EMANKMENTS SHALL BE FREE OF ROOTS, OR OTHER WOODY VEGETATION, ORGANIC MATERIAL, LARGE STONES, AND OTHER OBSTRUCTABLE MATERIALS.
- THE KEY TRENCH SHALL HAVE A MINIMUM TRENCH DEPTH + 2, MINIMUM WIDTH + 4, MAXIMUM SIDE SLOPE STEEPNESS IS 1H:1V. THE TRENCH SHALL EXTEND UP BOTH ABUTMENTS TO THE RISER CREST ELEVATION. COMPACTION REQUIREMENTS SHALL BE THE SAME AS THOSE FOR THE EMANKMENT. THE TRENCH SHALL BE Dewatered DURING BACKFILLING AND COMPACTION OPERATIONS.
- ANY SPRINGS ENCOUNTERED IN THE FOUNDATION AREA OF THE ROAD EMANKMENT SHALL BE DRAINED TO THE OUTSIDE DOWNSTREAM TOE OF THE EMANKMENT WITH A DRAIN SECTION TWO FEET BY TWO FEET IN DIMENSION CONSISTING OF PERFORATED TYPE A SAND, COMPACTED BY HAND TAMPER. NO GEOTEXTILES ARE TO BE USED AROUND THE SAND THE LAST THREE FEET OF TWO DRAIN AT THE OUTSIDE DOWNSTREAM SLOPE SHALL BE CONSTRUCTED WITH AGGREGATE MATERIAL.
- A CLEAN OUT STAKE SHALL BE PLACED NEAR THE CENTER OF EACH BASIN. ACCUMULATED SEDIMENT SHALL BE REMOVED IMMEDIATELY HAS REACHED THE CLEAN OUT ELEVATION ON THE STAKE AND RESTORE THE BASIN TO ITS ORIGINAL DIMENSIONS. DISPOSE OF MATERIALS REMOVED FROM THE BASIN IN THE MANNER DESCRIBED IN THE E&S PLAN.
- TYPE OF PIPE SHALL BE SLOPP (SMOOTH LINED CORRUGATED PLASTIC PIPE).
- INSPECT ALL SEDIMENT BASIN ON AT LEAST A WEEKLY BASIS AFTER EACH RUNOFF EVENT. CHECK BASIN EMANKMENTS, SPILLWAYS, AND OUTLETS FOR EROSION, PIPING AND SETTLEMENT. NECESSARY REPAIRS SHALL BE MADE IMMEDIATELY. DISPLACED RIPRAP WITHIN THE OUTLET ENERGY DISSIPATOR SHALL BE REPLACED IMMEDIATELY. ACCUMULATED SEDIMENT SHALL BE REMOVED AND DISTURBED AREAS SHALL BE STABILIZED INSIDE THE BASIN BEFORE CONVERSION TO A STORMWATER MANAGEMENT FACILITY.
- CHECK EMANKMENTS, SPILLWAYS, AND OUTLETS FOR EROSION, PIPING AND SETTLEMENT. CLOGGED OR DAMAGED SPILLWAYS AND/OR EMANKMENTS SHALL BE RESTORED TO THE DESIGN SPECIFICATIONS.
- CLOGGED OR DAMAGED SPILLWAYS SHALL BE REPAIRED IMMEDIATELY. TRASH AND OTHER DEBRIS SHALL BE REMOVED FROM THE BASIN AND RISER.
- PROVIDE WANGLE STEPS IN FOREBAY RISER WHEN THE DEPTH BETWEEN THE TOP OF RISER BOX AND THE TOP OF BOTTOM SLAB ELEVATION IS GREATER THEN 5'-0". PROVIDE WANGLE STEPS TO WITHIN 18" OF THE BOTTOM SLAB. WANGLE STEPS SHALL BE IN ACCORDANCE WITH PERFORATED PUBLICATION, 408 (SECTION B&C).

**TABLE 1: SEDIMENT BASIN**

SNP	EMANKMENT TOP ELEV A	EMERGENCY SPILLWAY CREST ELEV B	TOP OF RISER ELEV C	SEGMENT STORAGE ELEVATION ELEV D	SEGMENT BASIN BOTTOM ELEV E	INVERT ELEV F	INVERT ELEV G
SNP 1: SEDIMENT BASIN	1008.00	1008.00	1007.50	1005.00	1004.00	1003.50	1002.00

**SEDIMENT BASIN SKIMMER**

SCALE: N.T.S.

**PERMANENT OUTLET RISER**

SCALE: N.T.S.

**TABLE 2: POWER PLANT ROAD RELOCATION**

M&BE	Skimmer Size	Outlet Size Dia.	Outlet R&D	Required Basin Volume	Days To Drain
SNP 1: SEDIMENT BASIN	5"	2 1/2"	1.50'	5400	4

**SEDIMENT BASIN SKIMMER**

SCALE: N.T.S.

**PERMANENT OUTLET RISER**

SCALE: N.T.S.

**SEDIMENT BASIN CONSTRUCTION NOTES:**

- SEDIMENT BASIN, INCLUDING ALL APPURTENANT WORKS, SHALL BE CONSTRUCTED TO THE DETAIL AND DIMENSIONS SHOWN ON THE E&S PLANDRAWINGS.
- ACCESS FOR SEDIMENT REMOVAL AND OTHER REQUIRED MAINTENANCE ACTIVITIES SHALL BE PROVIDED.
- CONCRETE BASE SHALL BE POURED IN SUCH A MANNER AS TO INSURE THAT CONCRETE FILL BOTTOM OF RISER TO INVERT OF THE OUTLET PIPE TO PREVENT RISER FROM BREAKING AWAY FROM THE BASE OR PRECAST EXTENDED BASE.
- THE AREA UNDER EMANKMENT SHALL BE CLEARED, GRUBBED, AND STRIPPED OF TOPSOIL TO A DEPTH OF TWO FEET PRIOR TO ANY PLACEMENT AND COMPACTION OF EARTHWORK.
- THE EMANKMENT SHALL BE COMPACTED IN LAYERED LIFTS OF NOT MORE THAN 8" TO 10". THE MAXIMUM ROCK SIZE SHALL BE NO GREATER THAN 30 THE LIFT THICKNESS. FIVE PASSES OF THE COMPACTION EQUIPMENT OVER THE ENTIRE SURFACE OF EACH LIFT IS REQUIRED. EMANKMENT COMPACTION TO VISIBLE NONMOVEMENT IS ALSO REQUIRED.
- SOILS ACCEPTABLE FOR EMANKMENT CONSTRUCTION SHOULD BE LIMITED TO GC, GW, SC, SM, CL, OR ML AS DESCRIBED IN ASTM 2487 (UNIFIED SOILS CLASSIFICATION). FILL MATERIAL FOR THE EMANKMENTS SHALL BE FREE OF ROOTS, OR OTHER WOODY VEGETATION, ORGANIC MATERIAL, LARGE STONES, AND OTHER OBSTRUCTABLE MATERIALS.
- THE KEY TRENCH SHALL HAVE A MINIMUM TRENCH DEPTH + 2, MINIMUM WIDTH + 4, MAXIMUM SIDE SLOPE STEEPNESS IS 1H:1V. THE TRENCH SHALL EXTEND UP BOTH ABUTMENTS TO THE RISER CREST ELEVATION. COMPACTION REQUIREMENTS SHALL BE THE SAME AS THOSE FOR THE EMANKMENT. THE TRENCH SHALL BE Dewatered DURING BACKFILLING AND COMPACTION OPERATIONS.
- ANY SPRINGS ENCOUNTERED IN THE FOUNDATION AREA OF THE ROAD EMANKMENT SHALL BE DRAINED TO THE OUTSIDE DOWNSTREAM TOE OF THE EMANKMENT WITH A DRAIN SECTION TWO FEET BY TWO FEET IN DIMENSION CONSISTING OF PERFORATED TYPE A SAND, COMPACTED BY HAND TAMPER. NO GEOTEXTILES ARE TO BE USED AROUND THE SAND THE LAST THREE FEET OF TWO DRAIN AT THE OUTSIDE DOWNSTREAM SLOPE SHALL BE CONSTRUCTED WITH AGGREGATE MATERIAL.
- A CLEAN OUT STAKE SHALL BE PLACED NEAR THE CENTER OF EACH BASIN. ACCUMULATED SEDIMENT SHALL BE REMOVED IMMEDIATELY HAS REACHED THE CLEAN OUT ELEVATION ON THE STAKE AND RESTORE THE BASIN TO ITS ORIGINAL DIMENSIONS. DISPOSE OF MATERIALS REMOVED FROM THE BASIN IN THE MANNER DESCRIBED IN THE E&S PLAN.
- TYPE OF PIPE SHALL BE SLOPP (SMOOTH LINED CORRUGATED PLASTIC PIPE).
- INSPECT ALL SEDIMENT BASIN ON AT LEAST A WEEKLY BASIS AFTER EACH RUNOFF EVENT. CHECK BASIN EMANKMENTS, SPILLWAYS, AND OUTLETS FOR EROSION, PIPING AND SETTLEMENT. NECESSARY REPAIRS SHALL BE MADE IMMEDIATELY. DISPLACED RIPRAP WITHIN THE OUTLET ENERGY DISSIPATOR SHALL BE REPLACED IMMEDIATELY. ACCUMULATED SEDIMENT SHALL BE REMOVED AND DISTURBED AREAS SHALL BE STABILIZED INSIDE THE BASIN BEFORE CONVERSION TO A STORMWATER MANAGEMENT FACILITY.
- CHECK EMANKMENTS, SPILLWAYS, AND OUTLETS FOR EROSION, PIPING AND SETTLEMENT. CLOGGED OR DAMAGED SPILLWAYS AND/OR EMANKMENTS SHALL BE RESTORED TO THE DESIGN SPECIFICATIONS.
- CLOGGED OR DAMAGED SPILLWAYS SHALL BE REPAIRED IMMEDIATELY. TRASH AND OTHER DEBRIS SHALL BE REMOVED FROM THE BASIN AND RISER.
- PROVIDE WANGLE STEPS IN FOREBAY RISER WHEN THE DEPTH BETWEEN THE TOP OF RISER BOX AND THE TOP OF BOTTOM SLAB ELEVATION IS GREATER THEN 5'-0". PROVIDE WANGLE STEPS TO WITHIN 18" OF THE BOTTOM SLAB. WANGLE STEPS SHALL BE IN ACCORDANCE WITH PERFORATED PUBLICATION, 408 (SECTION B&C).

**TABLE 1: SEDIMENT BASIN**

SNP	EMANKMENT TOP ELEV A	EMERGENCY SPILLWAY CREST ELEV B	TOP OF RISER ELEV C	SEGMENT STORAGE ELEVATION ELEV D	SEGMENT BASIN BOTTOM ELEV E	INVERT ELEV F	INVERT ELEV G
SNP 1: SEDIMENT BASIN	1008.00	1008.00	1007.50	1005.00	1004.00	1003.50	1002.00

**SEDIMENT BASIN SKIMMER**


SCALE: N.T.S.

**PERMANENT OUTLET RISER**

SCALE: N.T.S.


**TABLE 2: POWER PLANT ROAD RELOCATION**

M&BE	Skimmer Size	Outlet Size Dia.	Outlet R&D	Required Basin Volume	Days To Drain
SNP 1: SEDIMENT BASIN	5"	2 1/2"	1.50'	5400	4




NOTES:

1. MINIMUM DISTANCE TO PIPE JOINT SHALL BE 2 FEET.
2. ALL COLLARS SHALL BE INSTALLED SO AS TO BE WATERTIGHT.




12" DRAIN BASIN




**NOTES:**

1. A ROCK FILTER OUTLET SHALL BE INSTALLED WHERE FAILURE OF A COMPOST FILTER SOCK HAS OCCURRED DUE TO CONCENTRATED FLOW.
2. SEDIMENT MUST BE REMOVED WHEN ACCUMULATIONS REACH 1/3 THE HEIGHT OF THE OUTLET.



**NOTES:**

1. PIPE TO BE INSTALLED PER MANUFACTURERS RECOMMENDATIONS.
2. ANCHORS SHALL BE PLACED EVERY JOINT.
3. VELOCITY REDUCTION METHODS SHALL BE TAKEN WHEN SLOPE CREATES VELOCITY GREATER THAN 20 FPS



**NOTES:**

1. MAXIMUM DRAINAGE AREA = 1 ACRE
2. EROSION PROTECTION SHALL NOT BE REQUIRED FOR INLET TRIBUTARY TO SEGMENT BASIN OR TRAP. REINFS SHALL BE REQUIRED FOR ALL INSTALLATIONS NOT LOCATED AT A FLOWPOINT
3. FOLDED ENTRENCH BERM IN CHANNEL SHALL BE PROVIDED AND MAINTAINED IMMEDIATELY DOWNGRAD OF THE INLET. EROSION PROTECTION SHALL BE REQUIRED FOR ALL SEGMENTS OF ROAD SUBJECT TO EROSION. EROSION PROTECTION SHALL BE REQUIRED FOR ALL SEGMENTS OF ROAD SUBJECT TO EROSION. EROSION PROTECTION SHALL BE REQUIRED FOR ALL SEGMENTS OF ROAD SUBJECT TO EROSION.
4. TOP OF BLOCK SHALL BE AT LEAST 6 INCHES BELOW ADJACENT ROADS IF PAVED WATER WOULD POSE A SAFETY HAZARD TO TRAFFIC.
5. SEGMENT SHALL BE REMOVED WHEN IT REACHES HALF THE HEIGHT OF THE TOWER. DAMAGE ON CLOSSED INSTALLATIONS SHALL BE REPAIRED OR REPLACED IMMEDIATELY.
6. THE BOTTOM CHAMBER TO BE SURFACE WATER, A RATCH BACK COMPACT LAYER SHALL BE SECURELY INCHORED FOR ON OUTSIDE AND OVER TOP OF TOWER. COMPACT SHALL MEET THE STANDARDS IN TABLE 4 OF THE PAPER DESIGN.

STONE AND CONCRETE BLOCK INLET PROTECTION (TYPE M)



		SCALE: N.T.S.	
		<b>Michael Baker INTERNATIONAL</b>	<b>MICHAEL BAKER INTERNATIONAL, LLC</b> <small>600 WEST WISCONSIN AVENUE SUITE 700 MILWAUKEE, WI 53233</small>
		<b>HOMER CITY STATION</b> <small>1700 POWER PLANT ROAD HOMER CITY, PA 15106</small>	
		DWG. TYPE:	CIVIL
		TITLE:	E&S NOTIS & DETAILS
		PROJECT NAME: POWER PLANT ROAD RELOCATION	
		MS	PPR01
		C - 744 - 3505	SHEET
		DRAWING NUMBER	1