



NOTE: REFER TO TEST BORING LOG <u>S2-0081</u> OR COMPLETE SOIL MATERIAL DESCRIPTION 20" x 0.456" W.T., X-65, API5L, PSL2, ERW, BFW
COATING: 14-16 MILS FBE WITH 30-35 MIL ARO (POWERCRETE R95) REF. DRAWING REVISIONS NOTES 1. ALL COORDINATES SHOWN ARE IN LATITUDE AND LONGITUDE. ALL MSL ELEVATIONS ARE NAD83
2. STATIONING IS BASED ON HORIZONTAL DISTANCES.
3. ROONEY ENGINEERING, INC. AND SUNOCO PIPELINE, LP ARE NOT RESPONSIBLE FOR LOCATION OF FOREIGN UTILITIES SHOWN IN PLOT PLAN OR PROFILE. THE INFORMATION SHOWN HEREON IS FURNISHED WITHOUT LIABILITY ON THE PART OF ROONEY ENGINEERING, INC. AND SUNOCO PIPELINE. EROSION & SEDIMENT PLAN EP1 REVISED PER PADEP COMMENTS DLM | 05/09/16 | RMB | 05/09/16 | AAW | 05/09/16 DLM 11/13/15 RMB 11/13/15 AAW 11/13/15 C ADDED GEOTECH INFO/DESIGN ADJUSTMENT LP, FOR ANY DAMAGES RESULTING FROM ERRORS OR OMISSIONS THEREIN.
4. CONTRACTOR IS RESPONSIBLE FOR LOCATING ALL UTILITIES. CONTACT ONE CALL AT 811 PRIOR TO B ISSUED FOR BID MRS 07/31/15 RMB 07/31/15 AAW 07/31/15 DIGGING.
5. SUNOCO EMERGENCY HOTLINE NUMBER IS #1-800-786-7440. A ISSUED FOR FOR REVIEW KB 04/15/15 RMB 04/15/15 AAW 04/15/15 DWG NO DWG NO DESCRIPTION NO. DESCRIPTION BY DATE CHK DATE APP DATE

PIPELINE.
DESIGNED IN ACCORDANCE WITH CFR 49 195 & ASME B31.4

CROSSING PIPE SPECIFICATION: HDD HORZ. LENGTH (L=):2645' HDD PIPE LENGTH (S=):2657'

-CL (16.5' - 21.0') -SC (21.0' - 30.0') -COMPLETION

-SC (21.0' - 30.0')

DEPTH EL. 709'

- CARRIER PIPE NOT ENCASED. PIPE / AMBIENT TEMPERATURE MUST BE NO LESS THAN 30°F DURING PULLBACK WITHOUT PRIOR WRITTEN APPROVAL FROM THE ENGINEER

 10. CONDUCT 4-HOUR PRE-INSTALLATION HYDROTEST OF HDD PIPE STRING TO MINIMUM ISSO PSIG.

 11. SEE SUNDOCO PENNSYLVANIA PIPELINE PROJECT ESRI WEBMAP FOR ACCESS ROAD ALIGNMENT.



(303) 792-5911

SUNOCO PIPELINE, L.P.

20-INCH HORIZONTAL DIRECTIONAL DRILL WOODBINE DRIVE PENNSYLVANIA PIPELINE PROJECT

TETRA TECH ROONEY

SCALE: 1"=250' DWG. NO: PA-DA-0063.0000-RD