

### COMMONWEALTH OF PENNSYLVANIA DEPARTMENT OF ENVIRONMENTAL PROTECTION BUREAU OF CLEAN WATER

## NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM (NPDES) DISCHARGES OF STORMWATER ASSOCIATED WITH CONSTRUCTION ACTIVITIES POST-CONSTRUCTION STORMWATER MANAGEMENT (PCSM) MODULE 2

Ар	Applicant: Project Site Name:							
	PRE-DEVELOPMENT SITE CHARACTERIZATION							
1.	Was a pre-development site characterization completed for this project?							
	If Yes, describe the activities undertaken.							
2.	No. Test Pits completed:  No. Boreholes completed:							
3.	Number of Infiltration Tests completed: Method(s):							
4.	Project Site Area: acres Area investigated for infiltration capabilities: acres							
5.	5. DEP's Pre-Development Site Characterization Spreadsheet has been completed and is attached.   Yes  No							
6.	The infiltration potential of the site is:							
7.	If the infiltration potential of the site is limited or is otherwise not advised, explain the limitations.							
8.	Is the project site located in an area with known karst features?							
	If Yes, was a subsurface geotechnical investigation conducted and is a report attached?							
9.	Are there natural stormwater features on-site that will be protected?							
	If Yes, describe the features and any increase or decrease in stormwater runoff volume to the features.							

# POINTS OF ANALYSIS (POAs) (CONTINUED) 1. Identify all POAs used for the stormwater analysis and provide the information requested. All runoff from the site must be accounted for. POA No. Longitude DA (acres) **Surface Water Name** DA (acres) Latitude

			PCSM SCM IN	NVENTORY		
1. Identify	all PCSM SCMs planned for the project	ect site and prov	ide the informati	on requested.		
SCM ID	SCM Name	Latitude	Longitude	DA Treated (acres)	PCSM Objective	Deviations from PCSM Manual
	ot treated by an SCM, Earth Disturbar			Area not treated	d by an SCM, Pro	eject Site Area (acres):
3. 🗌 On	e or more SCMs will be located off-site	e. SCM	IDs:			

#### **PCSM SCM INVENTORY**

4. List the critical stages for each SCM and identify the licensed professional and/or company that will sign SCM Construction Certification forms for the SCM.

SCM ID	Critical Stages	LP Name	Company	LP Employed by Company	Contract

STORMWATER ANALYSIS – RUNOFF VOLUME											
Surface Wat	ter Name:							POA(s)	:		
1.	design stand	ard is bas	ed on volume ma	nagement re	quirements in	an Act 167 Pla	ın approv	ed by DEP withi	n the past five ye	ars.	
2.	design stand	lard is bas	ed on managing	the net chanç	ge for storms ι	up to and includ	ling the 2	2-year/24-hour st	orm.		
3.	Iternative de	sign stand	ard is being used	l.							
4. A printout of DEP's PCSM Spreadsheet – Volume Worksheet is attached.											
5. 2-Year/24-Hour Storm Event: inches Source of precipitation data:											
6. Stormwater Runoff Volume @ 2-Year/24-Hour Storm, Pre-Construction: CF											
7. Stormwater Runoff Volume @ 2-Year/24-Hour Storm, Post-Construction: CF											
8. Net Change (Post-Construction – Pre-Construction Volumes):											
9. Identify a	all selected s	tructural P	CSM SCMs and	provide the in	nformation rec	quested. [	Calcu	lations attached			
SCM II)   SOVICE   MIDE						ET Credit (CF)					
											<u> </u>
								Tota	ıl Infiltration & E	T Credits (CF):	
	Other Credits (CF) (Attach Calculations):										
Managed Release Credits (CF) (Attach MRC Design Summary):											
								Vol	ume Required to	o Manage (CF):	
Total Credits (CF):											

	STORMWATER ANALYSIS – PEAK RATE									
Su	rface Water Name:	:				POA	\(s):			
1.	☐ The design sta	andard is base	d on rate re	quirements i	n an Act 167	' Plan appro	ved by DEF	within the	past five ye	ears.
2.	☐ The design sta	andard is base	d on manag	ging the net o	change for 2	-, 10-, 50-, a	nd 100-yea	r/24-hour st	torms.	
3.	. An alternative design standard is being used.									
4.										
5.	Alternative rate		-							
6.	Identify precipitation			e of precipita	etion data:					
0.			Source	e or precipite						
	2-Year/24-Hour St					r/24-Hour St				
	50-Year/24-Hour S	Storm:			100-Ye	ar/24-Hour S	Storm			
7.	Identify all SCMs to	used to mitigat	e peak rate	differences	and provide	the requeste	ed information	on.		
	SCM ID		Inflow to SCM (cfs)				Outflow from SCM (cfs)			
			2-Yr	10-Yr	50-Yr	100-Yr	2-Yr	10-Yr	50-Yr	100-Yr
8.	Report peak rates	for pre-constr	uction and r	ost-construc	tion with SC	Ms and ider	ntify the diffe	erences		
<u> </u>	Pro-Construction Pook Pato   Post-Construction Pook Pato									
	Design Storm (cfs) (with SCMs) (cfs) (with SCMs)									
	2-Year/24-Hour									
	10-Year/24-Hour									
	50-Year/24-Hour									
1	00-Year/24-Hour									

	STORMWATER ANALYSIS – WATER QUALITY										
	A pri	rintout of DEP's PCSM Spreadsheet – Quality Worksheet is attached for all surface waters receiving discharges.									
	OTHER INFORMATION										
1.		A long-term operation a legal instrument for each			ared for each SCM	I and will be recorded with a					
2.		PCSM Plan Drawings h	ave been developed fo	r the project and are att	ached to the NOI/a	application.					
3.		The PCSM Plan has be	en planned, designed,	and will be implemented	d to be consistent v	with the E&S Plan.					
4.		Recycling and proper disposal of materials associated with PCSM SCMs are addressed as part of long-term operation and maintenance of the PCSM SCMs.									
5.		There are pre-construc	ction stormwater discha	rges to wetlands from t	he project site.						
		Pre-Con	struction		Post-Construc	tion					
		Drainage Area (ac)	Volume (CF)	Drainage Area (ac)	Volume (CF)	Ponding Depth Increase (%)					
7.	7. Describe the sequence of PCSM SCM implementation in relation to earth disturbance activities.										
8.	Identify naturally occurring geologic formations or soil conditions that may have the potential to cause pollution after earth disturbance activities are completed and PCSM SCMs are operational and the applicant's plan to avoid or minimize potential pollution and its impacts.										
9.	Ther	rmal Impacts: check the	appropriate box(es) if a	ny of the following are t	rue:						
		A peak rate control SCN impervious surface that				ontaining more than 25%					
		A Wet Basin or Engineer reversed slope outlet pi		nent Wetland is propose	ed that does not inc	clude shading and/or a					
		An impervious undetain	ed area exceeds 10%	of the receiving water's	watershed area.						
		A quantitative thermal in	mpact analysis is attach	ned.							

	IMPERVIOUS SURFACES (MULTI-LOT DEVELOPMENT ONLY)							
Tax Faicei / Lot		Treat Lot Stormwater	1 at A === (CE)	Planned	Maximum Allowable	Maximum Allowable Impervious, Per	Objective Met? 4	
ID No.	Rate	Volume / WQ	20171104 (017	Impervious (SF) <sup>1</sup>	Impervious, As Designed <sup>2</sup>	Ordinance (SF) <sup>3</sup>	Met? 4	

- 1 Enter the impervious area as presented on PCSM Plan Drawings.
- 2 Report the maximum allowable impervious on the lot according to the stormwater analysis and SCM design.
- 3 List the maximum allowable impervious on the lot to meet requirements of a zoning ordinance, if applicable.
- 4 Check the box if either 1) Maximum Allowable Impervious, As Designed is at least 110% of Planned Impervious or 2) Planned Impervious is equal to Maximum Allowable Impervious, Per Ordinance. If the box is checked the permittee will not be responsible for identifying any new impervious added to a lot on record drawings after a lot is sold during the term of permit coverage.

PCSM PLAN PREPARER								
☐ I am trained and experienced	in PCSM methods.	☐ I am a licensed professiona	al.					
No. years of experience preparing	g PCSM Plans:							
Name:		Title:						
Company:		Phone No.:						
Address:		Email:						
City, State, ZIP:		License No.:						
License Type:		Exp. Date						
	_							
PCSM Plan F	Preparer Signature	Date						
Identify those who assisted the in	dividual identified above in prep	aring the PCSM Plan:						
Name	Company	Field	LP?	License Type				

### **Version History**

Date	Version	Revision Reason
	1.1	Updated for reissuance of PAG-02 General Permit.
12/8/2019	1.0	Original

