

SAFETY DATA SHEET

Section 1. Identification

Product name

: BPB 59455 CORROSION INHIBITOR

Product code

: BPB59455

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Validation date

: Boiler water treatment.

Print date

: 4/10/2017 : 4/10/2017

Version

: 1.01

Supplier's details

: Baker Petrolite LLC

12645 W. Airport Blvd. Sugar Land, TX 77478

For Product Information/SDSs Call: 800-231-3606

(8:00 a.m. - 5:00 p.m. CST, Monday - Friday) 281-276-5400

Emergency telephone

number (with hours of

operation)

: CHEMTREC: 800-424-9300 (U.S. 24 hour)

Baker Petrolite: 800-231-3606

(001)281-276-5400

CANUTEC: 613-996-6666 (Canada 24 hours)

CHEMTREC Int'l 01-703-527-3887 (International 24 hour)

Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the substance or mixture

: FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 4

ACUTE TOXICITY (inhalation) - Category 4 SKIN CORROSION - Category 1

SERIOUS EYE DAMAGE - Category 1

TOXIC TO REPRODUCTION (Fertility) - Category 2

GHS label elements

Hazard pictograms









Signal word

: Danger

Hazard statements

: Flammable liquid and vapor.

Harmful if swallowed, in contact with skin or if inhaled.

Causes severe skin burns and eye damage.

Suspected of damaging fertility.

Precautionary statements

Section 2. Hazards identification

Prevention

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves: > 8 hours (breakthrough time): Neoprene gloves.. Wear eye or face protection. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Avoid breathing vapor. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.

Response

: IF exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or physician. IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or physician. IF ON SKIN: Wash with plenty of soap and water. Call a POISON CENTER or physician if you feel unwell. Take off contaminated clothing and wash it before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.

Storage

: Store locked up. Store in a well-ventilated place. Keep cool.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise classified

: None known.

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Ingredient name	%	CAS number
Morpholine	10 - 20	110-91-8
Cyclohexylamine	10 - 20	108-91-8

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Get medical attention immediately. Call a poison center or physician. Immediately flush the eye(s) continuously with lukewarm, gently flowing water for at least 20-60 minutes while holding the eyelid(s) open. Check for and remove any contact lenses. Chemical burns must be treated promptly by a physician.

Inhalation

: Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

: Get medical attention immediately. Call a poison center or physician. Wash affected area with soap and mild detergent for at least 20 - 60 minutes. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Section 4. First aid measures

Indestion

: Call a poison center or physician. Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. If yomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact

: Causes serious eye damage.

Inhalation

: Harmful if inhaled.

Skin contact

: Causes severe burns. Harmful in contact with skin.

Ingestion

: Harmful if swallowed.

Over-exposure signs/symptoms

Eye contact

: pain,watering,redness

Inhalation

: reduced fetal weight, increase in fetal deaths, skeletal malformations

Skin contact

: pain or irritation, redness, blistering may occur, reduced fetal weight, increase in fetal

deaths, skeletal malformations

Ingestion

: stomach pains, reduced fetal weight, increase in fetal deaths, skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments

: No specific treatment.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water

before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

: Use dry chemical, CO2, water spray (fog) or foam.

Unsuitable extinguishing

media

: Do not use water jet.

Specific hazards arising from the chemical

: Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products : carbon dioxide,carbon monoxide,nitrogen oxides

BPB 59455 CORROSION INHIBITOR

Section 5. Fire-fighting measures

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

te No.

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk, Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Dike spill area and do not allow product to reach sewage system or surface or ground water. Notify any reportable spill to authorities. (See section 12 for environmental risks and 13 for disposal information.) Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Avoid exposure obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist, Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Keep away from acids. Empty containers retain product residue and can be hazardous. Do not reuse container.

Section 7. Handling and storage

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from acids. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits	
Morpholine	skin. TWA: 71 mg/m³, 0 t TWA: 20 ppm, 0 tim OSHA PEL (United S skin. TWA: 70 mg/m³, 0 t TWA: 20 ppm, 0 tim OSHA PEL 1989 (Un through skin. STEL: 105 mg/m³, 0 STEL: 30 ppm, 0 tim TWA: 70 mg/m³, 0 t	States, 3/2015). Absorbed through imes per shift, 8 hours. States, 2/2013). Absorbed through imes per shift, 8 hours. Sees per shift, 8 hours. Sees per shift, 8 hours. Sited States, 3/1989). Absorbed of times per shift, 15 minutes. Sees per shift, 15 minutes. Sees per shift, 15 minutes. Sees per shift, 8 hours. Sees per shift, 8 hours.
Cyclohexylamine	TWA: 10 ppm, 0 tim OSHA PEL 1989 (Un TWA: 40 mg/m³, 0 t	States, 3/2015). imes per shift, 8 hours. les per shift, 8 hours. lited States, 3/1989). imes per shift, 8 hours. les per shift, 8 hours.

Consult local authorities for acceptable exposure limits.

If OSHA permissible exposure levels are shown above they are the OSHA 1989 levels or are from subsequent OSHA regulatory actions. Although the 1989 levels have been vacated the 11th Circuit Court of Appeals, Baker Hughes recommends that these lower exposure levels be observed as reasonable worker protection.

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Section 8. Exposure controls/personal protection

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before

eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing.

Wash contaminated clothing before reusing.

Eye/face protection : Wear chemical safety goggles. When transferring material wear face-shield in addition

to chemical safety goggles. If inhalation hazards exist, a full-face respirator may be

required instead.

Hand protection Chemical-resistant gloves: Neoprene gloves.

Skin protection : Wear long sleeves and chemical resistant apron to prevent repeated or prolonged skin

contact.

Respiratory protection : If a risk assessment indicates it is necessary, use a properly fitted, air purifying or

> supplied air respirator complying with an approved standard. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the

safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid.

Color : Yellow. [Light] Odor Amine like.

Odor threshold Not available.

рΗ 12.7

: Neat-without dilution.

Melting/freezing point : -1.1°C (30°F)

Boiling point : 102°C (215.6°F) : Not available.

Initial Boiling Point

Flash point

: Closed cup: 53°C (127.4°F) [SFCC]

Burning time Not applicable. Burning rate : Not applicable. Not available.

Evaporation rate Flammability (solid, gas)

: Flammable in the presence of the following materials or conditions: open flames, sparks

and static discharge and heat.

Lower and upper explosive

(flammable) limits

: Not available.

Vapor pressure : 2.3 kPa (17.5 mm Hg) @ 21.1°C (Calculated Value for all Components.)

Vapor density : >1 [Air = 1] Relative density : 1.001 (15.6°C) Density : 8.34 (lbs/gal) Solubility in water : Soluble Partition coefficient: n-

octanol/water

Pour Point

: Not available.

: Not available.

Auto-ignition temperature : Not available. Decomposition temperature : Not available. : Not available. Viscosity VOC : Not available.

Section 10. Stability and reactivity

Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability

: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid

: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.

Incompatible materials

: Reactive or incompatible with the following materials: oxidizing materials and acids.

Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Morpholine	LD50 Dermal	Rabbit	0.5 g/kg	-
·	LD50 Oral	Rat	1.05 g/kg	-
	LD50 Oral	Rat	1450 mg/kg	_
Cyclohexylamine	LC50 Inhalation Vapor	Mouse	1070 mg/m ³	4 hours
	LC50 Inhalation Vapor	Rat	2.3 mg/l	4 hours
	LC50 Inhalation Vapor	Rat	7500 mg/m³	4 hours

Irritation/Corrosion

No applicable toxicity data

Sensitization

No applicable toxicity data

<u>Mutagenicity</u>

No applicable toxicity data

Carcinogenicity

Product/ingredient name	OSHA	IARC	NTP
Morpholine	н	3	-
Cyclohexylamine	-	3	-

Reproductive toxicity

No applicable toxicity data

Teratogenicity

No applicable toxicity data

Specific target organ toxicity (single exposure)

Not applicable.

Specific target organ toxicity (repeated exposure)

Not applicable.

Aspiration hazard

BPB 59455 CORROSION INHIBITOR

Section 11. Toxicological information

Not available.

Information on the likely routes of exposure

: Routes of entry anticipated: Dermal, Inhalation.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

General

No known significant effects or critical hazards.No known significant effects or critical hazards.

Carcinogenicity

Mutagenicity

: No known significant effects or critical hazards.

Teratogenicity

: No known significant effects or critical hazards.

Developmental effects

: No known significant effects or critical hazards.

Fertility effects

: Suspected of damaging fertility.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Dermal	1872.9 mg/kg 1181.1 mg/kg 15 mg/l

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure	
Morpholine	Acute EC50 28 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours	
	Acute LC50 1000 μg/l	Fish - Danio rerio	96 hours	
Cyclohexylamine	Acute EC50 20 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours	
	Acute LC50 44 mg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours	
BPB 59455 CORROSION INHIBITOR	Acute LC50 68 ppm	Daphnia	48 hours	
	Acute LC50 148 mg/l Acute LC50 152 mg/l	Daphnia Fish	48 hours 96 hours	

Persistence and degradability

Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	IATA
UN number	UN2920	UN2920	UN2920	UN2920
UN proper shipping name	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Contains: Morpholine, Cyclohexylamine)	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Contains: Morpholine, Cyclohexylamine)	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Contains: Morpholine, Cyclohexylamine)	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Contains: Morpholine, Cyclohexylamine)
Transport hazard class(es)	8 (3)	8 (3)	8 (3)	8 (3)
Packing group		11	II	111
Environmental hazards	No.	No.	No.	No.
Additional information		Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.40-2.42 (Class 8), 2.18-2.19 (Class 3).	Emergency schedules (EmS) F-E S-C	-

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according: Not available. to Annex II of MARPOL and

the IBC Code

DOT Reportable

Not applicable.

Quantity

Marine pollutant

Not available.

North-America NAERG

: 132

Section 15. Regulatory information

U.S. Federal regulations

: TSCA 12(b) one-time export: No products were found.

TSCA 12(b) annual export notification: No products were found.

United States inventory (TSCA 8b): All components are listed or exempted.

Clean Water Act (CWA) 307: No products were found.
Clean Water Act (CWA) 311: No products were found.

Clean Air Act (CAA) 112 regulated toxic substances: Cyclohexylamine

United States - Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs):

List name	Status	Ingredient name	Name on list	Conc.
None of the components are listed.				

SARA 302/304

			e e E e		SARA 302 TPQ		SARA 304 RQ	
Name			%	EHS	(lbs)	(gallons)	(lbs)	(gallons)
Cyclohexylamine	· · · · · · · · · · · · · · · · · · ·	ilani i	10 - 20	Yes.	10000	1386.5	10000	1386.5

SARA 311/312

Classification

: Fire hazard

Immediate (acute) health hazard Delayed (chronic) health hazard

SARA 313

Supplier notification

: No products were found.


<u>Canada</u>

Canada (CEPA DSL):

: All components are listed or exempted.

Section 16. Other information

National Fire Protection Association (U.S.A.)



History

Date of printing

: 4/10/2017

Notice to reader

NOTE: The information on this SDS is based on data which is considered to be accurate. Baker Hughes, however, makes no guarantees or warranty, either expressed or implied of the accuracy or completeness of this information.

The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of this product.

This SDS was prepared and is to be used for this product. If the product is used as a component in another product, this SDS information may not be applicable.