



Material Safety Data Sheet

Issue Date: 05-JUL-2013 Supercedes: 22-MAR-2011

FOAMTROL AF2290

1 Identification

Identification of substance or preparation FOAMTROL AF2290

Product Application Area Antifoam.

Company/Undertaking Identification GE Betz, Inc. 4636 Somerton Road Trevose, PA 19053 T 215 355-3300, F 215 953 5524

Emergency Telephone (800) 877-1940

Prepared by Product Stewardship Group: T 215-355-3300 Prepared on: 05-JUL-2013

2 Hazard(s) identification

CAUTION

May cause slight irritation to the skin. May cause slight irritation to the eyes. Vapors, gases, mists and/or aerosols may cause irritation to upper respiratory tract.

DOT hazard is not applicable Odor: Slight; Appearance: White, Emulsion

POTENTIAL HEALTH EFFECTS

ACUTE SKIN EFFECTS:

Primary route of exposure; May cause slight irritation to the skin.

ACUTE EYE EFFECTS:

May cause slight irritation to the eyes.

ACUTE RESPIRATORY EFFECTS:

Vapors, gases, mists and/or aerosols may cause irritation to upper respiratory tract.

INGESTION EFFECTS:

No evidence of adverse effects from available information.

TARGET ORGANS:

No evidence of potential chronic effects.

MEDICAL CONDITIONS AGGRAVATED:

Not known.

SYMPTOMS OF EXPOSURE:

May cause redness or itching of skin.

3 Composition / information on ingredients

Information for specific product ingredients as required by the U.S. OSHA HAZARD COMMUNICATION STANDARD is listed. Refer to additional sections of this MSDS for our assessment of the potential hazards of this formulation. This product is subject to the Pennsylvania and New Jersey Worker and Community Right to Know Law.

HAZARDOUS INGREDIENTS:

This product is not hazardous as defined by OSHA regulations.

No component is considered to be a carcinogen by the National Toxicology Program, the International Agency for Research on Cancer, or the Occupational Safety and Health Administration at Pennsylvania thresholds for carcinogens. NON-HAZARDOUS INGREDIENTS:

CAS# CHEMICAL NAME

7732-18-5	WATER		
PROPRIETARY	SILICA	FILLED	POLYDIMETHYLSILOXANE

4 First-aid measures

SKIN CONTACT:

Wash thoroughly with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

EYE CONTACT:

Remove contact lenses. Hold eyelids apart. Immediately flush eyes with plenty of low-pressure water for at least 15 minutes. Get medical attention if irritation persists after flushing.

INHALATION:

If nasal, throat or lung irritation develops - remove to fresh air and get medical attention.

INGESTION:

Do not feed anything by mouth to an unconscious or convulsive victim. Do not induce vomiting. Immediately contact physician. Dilute contents of stomach using 2-8 fluid ounces (60-240 mL) of milk or water.

NOTES TO PHYSICIANS:

No special instructions

5 Fire-fighting measures

```
FIRE FIGHTING INSTRUCTIONS:
```

```
Fire fighters should wear positive pressure self-contained breathing apparatus (full face-piece type).
```

EXTINGUISHING MEDIA:

```
dry chemical, carbon dioxide, foam or water
```

```
HAZARDOUS DECOMPOSITION PRODUCTS:
```

```
oxides of silicon
FLASH POINT:
```

> 200F > 93C P-M(CC)

6 Accidental release measures

PROTECTION AND SPILL CONTAINMENT:

Ventilate area. Use specified protective equipment. Contain and absorb on absorbent material. Place in waste disposal container. Flush area with water. Wet area may be slippery. Spread sand/grit.

DISPOSAL INSTRUCTIONS:

Water contaminated with this product may be sent to a sanitary sewer treatment facility, in accordance with any local agreement, a permitted waste treatment facility or discharged under a permit. Product as is - Incinerate or land dispose in an approved landfill.

7 Handling and storage

```
HANDLING:
```

Normal chemical handling. **STORAGE:** Keep containers closed when not in use. Protect from freezing. If frozen, thaw and mix completely prior to use. Shelf life 270 days.

8 Exposure controls / personal protection

EXPOSURE LIMITS

This product is not hazardous as defined by OSHA regulations.

ENGINEERING CONTROLS: adequate ventilation PERSONAL PROTECTIVE EQUIPMENT: Use protective equipment in accordance with 29CFR 1910 Subpart I RESPIRATORY PROTECTION: A RESPIRATORY PROTECTION PROGRAM THAT MEETS OSHA'S 29 CFR 1910.134 AND ANSI Z88.2 REQUIREMENTS MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT A RESPIRATOR'S USE. USE AIR PURIFYING RESPIRATORS WITHIN USE LIMITATIONS ASSOCIATED WITH THE EQUIPMENT OR ELSE USE SUPPLIED AIR-RESPIRATORS. If air-purifying respirator use is appropriate, use any of the following particulate respirators: N95, N99, N100, R95, R99, R100, P95, P99 or P100. SKIN PROTECTION:

butyl or viton gloves -- Wash off after each use. Replace as necessary. EYE PROTECTION: splash proof chemical goggles

9 Physical and chemical properties

Spec. Grav.(70F,21C) 1.001 Vapor Pressure (mmHG) ~ 18.0 Freeze Point (F)27Freeze Point (C)-3 Vapor Density (air=1) < 1.00 % Solubility (water) Viscosity(cps 70F,21C) 1588 0.0 Odor Slight Appearance White Physical State Flash Point Emulsion P-M(CC) > 200F > 93C 7.5 pH As Is (approx.) < 1.00 Evaporation Rate (Ether=1) Percent VOC: 0.0

NA = not applicable ND = not determined

10 Stability and reactivity

```
CHEMICAL STABILITY:
```

```
Stable under normal storage conditions.

POSSIBILITY OF HAZARDOUS REACTIONS:

Contact with water reactive compounds may cause fire or explosion.

INCOMPATIBILITIES:

May react with strong oxidizers.

DECOMPOSITION PRODUCTS:

oxides of silicon
```

11 Toxicological information

Oral LD50 RAT:	>5000 mg/kg
Dermal LD50 RABBIT:	>5000 mg/kg
Skin Irritation Score RABBIT:	0
Eye Irritation Score RABBIT:	0

12 Ecological information

AQUATIC TOXICOLOGY

Daphnia magna 48 Hour Static Screen 10% Mortality= 5000; 0% Mortality= 1000 mg/L Fathead Minnow 96 Hour Static Bioassay with 48-Hour Renewal 0% Mortality= 5000 mg/L Rainbow Trout 48 Hour Static Screen 100% Mortality= 5000; 0% Mortality= 1000 mg/L

BIODEGRADATION

BOD-28 (mg/g): 0 BOD-5 (mg/g): 0 COD (mg/g): 219 TOC (mg/g): 41

13 Disposal considerations

If this undiluted product is discarded as a waste, the US RCRA hazardous waste identification number is : Not applicable.

Please be advised; however, that state and local requirements for waste disposal may be more restrictive or otherwise different from federal regulations. Consult state and local regulations regarding the proper disposal of this material.

14 Transport information

```
Transportation Hazard: Not Applicable
DOT: Not Regulated
DOT EMERGENCY RESPONSE GUIDE #: Not applicable
Note: Some containers may be DOT exempt, please check BOL for
exact container classification
IATA: Not Regulated
IMDG: Not Regulated
```

15 Regulatory information

```
TSCA:
          All components of this product are included on or are in
          compliance with the U.S. TSCA regulations.
    CERCLA AND/OR SARA REPORTABLE QUANTITY (RQ):
          Treat as oil spill
    FOOD AND DRUG ADMINISTRATION:
          21 CFR 176.210 & 176.200 (antifoams approved for use in wet end
          applications and in coating formulations) and 21 CFR 175.105
          (adhesives)
    NSF Registered and/or meets USDA (according to 1998 Guidelines):
          Registration number: 147598
          Category Code(s):
       G5
             Cooling and retort water treatment products - all
             food processing areas
       G7
             Boiler treatment products - all food processing
             areas/nonfood contact
    SARA SECTION 312 HAZARD CLASS:
          Product is non-hazardous under Section 311/312
    SARA SECTION 302 CHEMICALS:
          No regulated constituent present at OSHA thresholds
    SARA SECTION 313 CHEMICALS:
          No regulated constituent present at OSHA thresholds
CALIFORNIA REGULATORY INFORMATION
    CALIFORNIA SAFE DRINKING WATER AND TOXIC
    ENFORCEMENT ACT (PROPOSITION 65):
       No regulated constituents present
```

MICHIGAN REGULATORY INFORMATION

No regulated constituent present at OSHA thresholds

16 Other information

HMIS VII

CODE TRANSLATION

Health	1	Slight Hazard
Fire	0	Minimal Hazard
Reactivity	0	Minimal Hazard
Special	NONE	No special Hazard
(1) Protective Equipment	В	Goggles,Gloves

(1) refer to section 8 of MSDS for additional protective equipment recommendations.

CHANGE LOG

EFFECTIVE DATE	REVISIONS TO SECTION:	SUPERCEDES
15-JAN-1998		** NEW **
24-FEB-1998	2	15-JAN-1998
12-OCT-2001	4,16	24-FEB-1998
30-AUG-2007	4,5,7,8,10	12-OCT-2001
29-JUN-2010	4,8,10	30-AUG-2007
22-MAR-2011	11	29-JUN-2010
05-JUL-2013	15	22-MAR-2011
	DATE 15-JAN-1998 24-FEB-1998 12-OCT-2001 30-AUG-2007 29-JUN-2010 22-MAR-2011	DATE REVISIONS TO SECTION: 15-JAN-1998 24-FEB-1998 2 12-OCT-2001 4,16 30-AUG-2007 4,5,7,8,10 29-JUN-2010 4,8,10 22-MAR-2011 11