

Trade Name: METSO PENTABEAD® 20 Sodium Metasilicate, pentahydrate Date Prepared: 09/12/06

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: Product description:

Manufacturer:

METSO PENTABEADO 20 Sodium Metaslikate, pentahydrate

Granular sodlum metasilicate, pentabydrate

PQ Corporation P. O. Box \$40

Valley Forge, PA 19482 USA

610-651-4200

Telephone: in case of emergency call: 610-651-4200 For transportation emergency Call CHEMTREC:

800-424-9300

GEFIRING-MONTGOMERY, INC.

710 Louis Orive Tel:(215)957-1234 Warminster, PA 18974 Fax:(215)957-1311

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical and Common Name Na Silicie acid, dirodium snit;

1a

CAS Registry Number 6834-92-0

W1. % OSHA PEL ACGIH TLV

~58% Not Established*

Not Established*

Disodium frioxosilicater Sodium metasilicate

Water

7732-18-5

-42% Not Established Not Established

Manufacturer's recommended exposure limit is 2 mg/m3 Ceiling Limit,

3. HAZARDS IDENTIFICATION

Emergency Overview:

White, eduriess, granular powder. Corrosive to eyes, skin, and digestive tract. Dust corrollve to respiratory tract. Due to high pH of product, release into surface water is harmful to aquatic life. Noncombustible. Reacts with acids and some organics.

Eye contact: Skin contact: Inhalation:

Corrosive. Causes eye burns. Corrosive. Causes skin burnt. Dust corrosive to respiratory tract.

Ingastion: Chronic hazards:

Corrosive. Causes burns to mouth, exophagus, and stomach. No known chronic hazards. Not listed by NTP, IARC or OSHA

Physical hatards:

as a carcinogen. Can etch glass if not promptly removed.

4. FIRST AID MEASURES

Eye

in case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

Skin:

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. Thoroughly ciean shoes before reuse.

Trade Name: METSO PENTABEAD® 20 Sodium Metasilicate, pentahydrate Date Prepared: 09/12/06 Page; 2 of 5

Inholation:

Ingestion:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention. If swallowed, DO NOT induce vomiling. Get medical attention

immediately, if victim is fully conscious, give a cupful of water. Never

give anything by mouth to an unconscious person.

5. FIRE FIGHTING MEASURES

Flammable limits:

Extinguishing Media: Hazards to fire-fighters:

This material is noncombustible, This material is compatible with all extinguishing media. See Section 3 for information on hazards when this material

is present in the area of a fire.

Fire-fighting equipment:

The following protective equipment for fire fighters is recommended when this material is present in the area of a fire: chemical goggles, body-covering protective clothing, chemical resistant gloves, and rubber boots.

6. ACCIDENTAL RELEASE MEASURES

Personal protection:

Wear chemical goggles, body-covering protective clothing, chemical resistant gloves, and rubber boots, NIOSH-approved dust respirator

Environmental Hazards:

where dust occurs. See section 8. Sinks and mixes with water. High pH of this material is harmful to aquatic life, see Section 12.

Small spill cleanup:

Large spill cleanup:

Carefully shovel or sweep up spilled material and place in aultable container. Avoid generating dust. Use appropriate Personal Protective

Equipment (PPE). See section 8. Keep unnecessary people away; isolate hazard area and deny entry. Do not fouch or walk through spilled material. Carefully shovel or sweep up

spilled material and place in suitable container. Avoid generating dust. Use appropriate Personal Protective Equipment (PPE). Sea section 8. In case of contact with water, prevent runoff from entering into storm sewers and ditches which lead to natural waterways. Neutralize contaminated area and flush with large quantities of water. Comply with applicable environmental regulations.

CERCLA RQ:

There is no CERCLA Reportable Quantity for this material. If a spill goes offsite, notification of sinte and local authorities is recommended.

7. HANDLING AND STORAGE

Handling:

Do not get in eyes, on skin, or on clothing. Do not breathe dust. Keep container closed. Promptly clean up spills. Wash thoroughly after

Storage:

Store at temperatures below 150°F (65°C), Keep containers closed. Store in clean, tightly closed steel, liber, or plastic containers. Separate from acids, reactive metals, and ammonium saits. Do not store in aluminum, fiberglass, copper, brass, zinc or galvanized containers. This product can absorb water from the air. In case of high humidity or storage for extended periods of time, use plastic bags to enclose product containers to

Trade Name: METSO PENTABEAD® 20 Sodium Metasilicate, pentahydrate Date Prepared: 09/12/06

> avoid taking. Packaged inventory should be used on a first in, first out (FIFO) basis. Bulk storage bins should be painted white or siuminum to minimiza sum heat absorption which can cause melling of this material at about 160 P.

& EXPOSURE CONTROL SPERSONAL PROTECTION

Engineering controls;

Use only with adequate ventilation. Keep containers closed. Safety shower and eyewash fountain should be within direct access.

Respiratory protection:

Use a NIOSH-approved dust respirator where dust occurs. Observe

OSHA regulations for respirator use (29 C.F.R. §1910.134)

Skin protection: Eye protection:

Wear body-covering protective clothing and gloves.

Wear chemical goggles.

2. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Granular powder,

Color:

White.

Odor;

Odorless or musty odor.

pH:

Approximately 14

Bulk density: Solubility in water:

Approximately 49 lbs/ft2 untamped, 59 lbs/ft2 tamped.

Soluble.

10. STABILITY AND REACTIVITY

Stability:

Conditions to avoid: Materials to avoid:

This material is stable under all conditions of use and storage.

Generates heat when mixed with acid. May react with ammonium saft solutions resulting in evolution of ammonia gas. Flammable hydrogen gas may be produced on contact with aluminum, tin, lead, and zinc. Carbon monoxide gas may be produced on confact with reducing sugars.

Hazardous decomposition

products:

Hydrogen,

11. TOXICOLOGICAL INFORMATION

Acute Data:

This material has not been tested for primary eye irritation potential. However, on the basis of its high degree of alkalinity, it is regarded as

corrosive to the eyes.

When this material was tested for skin corresion/irritation potential according to OECD Guidelines Section 404, if produced dermal

corresion.

The acute oral toxicity of this product has not been tested. When sodium silicates were tested on a 100% solids basis, their single dose acute oral LDs in rais ranged from 1500 mg/kg to 3200 mg/kg. The acule oral leibality resulted from nonspecific causes.

Subchronic Data:

In a study of rate fed sodium silicate in drinking water for three months, at 200, 600 and 1800 ppm, changes were reported in the blood chemistry



to sodium silicate administration were observed in any of the dosage groups. Another study reported adverge effects to the kidneys of dogs fed sodium silicate in their diet at 2.4g/kg/day for 4 weeks, whereas rati fed. the same dotage did not develop any tresiment-related effects. Decreased numbers of births and survival to meaning was reported for rate fed sodlum silicate in their drinking water at 600 and 1200 ppm.

of some animals, but no specific changes to the organs of the animals due

Sodium alleage was not mulagenic to the hacterium E. Coll when tested

in a mutagenicity bioassay. There are no known reports of carcinogenicity of sodium slikestes. Frequent ingestion over extended periods of time of gram quantities of allicates is associated with the formation kidney atones and other siticeous urinary calcult in humans. Sodium silicate is not listed by IARC, NTP or OSHA as a carcinogen.

12. ECOLOGICAL INFORMATION

Special Studies:

Eco toxicity:

The following data is reported for sodium silicates on a 100% solids basis: A 96 hour median tolerance for fish (Gambusia affiib) of 2320 ppm; a 96 hour median tolerance for water fless (Daphnit magne) of 247 ppm; a 96 hour median tolerance for small eggs (Lymnes) of 632 ppm; and a 96 hour median tolerance for Amphipoda of 160 ppm.

Environmental Fate:

This material is not persistent in aquatic systems, but its high phi when undiluted or unneutralized is acutely harmful to aquatic life. Dliuted material yields dissolved allica in a form that is indistinguishable from natural dissolved silica. It does not contribute to BOD. This material does not bloaccumulate except in apecies that use allica as a aiructural material such as diatoms and alliceous sponges. Where abnormally low natural silica concentrations exist (less than 0.1 ppm), dissolved silica may be a limiting nutrient for distoms and a few other aquatic signi species. However, the addition of excess dissolved silics over the limiting concentration will not atimulate the growth of diatom populations; their growth rate is independent of silica concentration once the limiting concentration is exceeded. Neither silica nor sodium will appreciably

Physical/Chemical:

blocoucentrate up the food chain. Sinks and dissolves in water.

Tracke Name: METSO PENTABEAD 20 Sodium Metasilicate, pentahydrate Date Prepared: 09/12/06

13. DISPOSAL CONSIDERATIONS

Classiscation:

Disposed dry/solld material is not classified as a RCRA Hazardous waste. However, disposed water/wet solutions containing this material are classified as RCRA hazardous waste if they exhibit the correstve characteristic (pli greater than or equal fol 2.5) as defined in EPA suies at 40 C.F.R. \$261,22 (a)(1).

Disposal Method:

Dispose in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

DOT UN Status:

This material is a regulated bazardous material.

UN PROPER SHIPPING NAME: UN HAZARD CLASS/DIVISION

Disodium trioxosilicate

UN IDENTIFICATION NUMBER: UN3253 UN PACKING GROUP:

PG III

15. REGULATORY INFORMATION

CERCLA: SARA TITLE !!!;

No CERCLA Reportable Quantity has been established for this material, Not an Extremely Hazardous Substance under \$302. Not a Toxic

TSCA: FDA:

Chemical under §313. Hazard Categories under §\$311/317: Acute All ingredients of this material are listed on the TSUA inventory. The use of sodium metasilicate is authorized by FDA as a boiler water additive for the production of steam that will contact food pursuant to 21 CFR §173.310; and as a GRAS substance pursuant to 21 CFR

§184,1769afor use in washing and lye pecling of fruits, vegetables, and nuts; as a denuding agent for trips; a hog scald agent in removing hair; and as a corrosion preventative in canned and bottled water.

16. OTHER INFORMATION

Prepared by:

John G. Blumberg

Supersedes revision of: 01/24/06

The information on this safety data sheet is believed to be accurate and it is the dest INFORMATION AVAILABLE TO PQ CORPORATION THIS DOCUMENT IS INTENDED ONLY AS A GUIDE TO THE appropriate precautions for handling a chemical by a person trained in Chemical Handling. PQ CORPORATION MAKES NO WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR implied with respect to such information or the product to winch it relates, and we assume no liability resulting from the use or handling of the product to which this safety data sheet relates. Users and handlers of this product should make their own investigations to determine the suitability of the information provided herein for their own purposes.