

Material Safety Data Sheet



TRACTOR BRITE

1. Product and company identification

Product name	: TRACTOR BRITE									
Supplier/Manufacturer	: DuBois Chemicals, Inc. 3630 E. Kemper Rd. Cincinnati, OH 45241 USA Phone: 1-800-438-2647 DuBois Chemicals Canada, Inc. 1155 North Service Road West Unit 6 Oakville, Ontario, L6M 3E3 Canada Phone: 1-866-861-3603									
Recommended use	: Industrial applications: Cleaning solutions. Alkaline Cleaner This product is intended to be diluted prior to use									
MSDS #	: DUB00076									
Product code	: 11822150, 11822330, 11822470									
Validation date	: 8/19/2014.									
Version	: 4									
Responsible name	: Regulatory Department 1-800-438-2647									
In case of emergency	: 1-866-923-4919 (US and Canada) 01-651-523-0314 (Int'l and Mexico)									
Hazardous Material Information System (U.S.A.)	: <table border="1"><tr><td>Health</td><td>*</td><td>3</td></tr><tr><td>Flammability</td><td></td><td>0</td></tr><tr><td>Physical hazards</td><td></td><td>0</td></tr></table>	Health	*	3	Flammability		0	Physical hazards		0
Health	*	3								
Flammability		0								
Physical hazards		0								

2. Hazards identification

Physical state	: Liquid. [Aqueous solution]
OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Emergency overview	: DANGER! CORROSIVE. CAUSES EYE AND SKIN BURNS. HARMFUL IF SWALLOWED. Do not breathe vapor or mist. Do not ingest. Do not get in eyes or on skin or clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.
Routes of entry	: Dermal contact. Eye contact. Inhalation.
Potential acute health effects	
Inhalation	: May give off gas, vapor or dust that is very irritating or corrosive to the respiratory system. Serious effects may be delayed following exposure.
Ingestion	: May cause burns to mouth, throat and stomach.
Skin	: Corrosive to the skin. Causes burns.
Eyes	: Corrosive to eyes. Causes burns.
Potential chronic health effects	
Carcinogenicity	: No known significant effects or critical hazards.
Target organs	: Contains material which may cause damage to the following organs: lungs, upper respiratory tract, skin, eye, lens or cornea.

2. Hazards identification

Medical conditions aggravated by over-exposure : Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

See toxicological information (Section 11)

3. Composition/information on ingredients

Name	CAS number	% by weight
sodium hydroxide	1310-73-2	5 - 10
tetrasodium ethylene diamine tetraacetate	64-02-8	1 - 5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
- Skin contact** : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
- Inhalation** : Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
- Ingestion** : Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

5. Fire-fighting measures

Flammability of the product : In a fire or if heated, a pressure increase will occur and the container may burst.

Extinguishing media

Suitable : Use an extinguishing agent suitable for the surrounding fire.

Not suitable : None known.

Special exposure hazards : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
metal oxide/oxides

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. Handling and storage

Handling : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Keep away from acids. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Separate from acids. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

Occupational exposure limits

Ingredient	Exposure limits
sodium hydroxide	ACGIH TLV (United States, 3/2012). C: 2 mg/m ³ NIOSH REL (United States, 1/2013). CEIL: 2 mg/m ³ OSHA PEL (United States, 6/2010). TWA: 2 mg/m ³ 8 hours.

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

8. Exposure controls/personal protection

- Engineering measures** : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Personal protection**
- Respiratory** : If a risk assessment indicates this is necessary, use a properly fitted, air-purifying or airfed respirator complying with an approved standard. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Recommended: nitrile rubber
- Eyes** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
Recommended: splash goggles
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
- Personal protective equipment (Pictograms)** :



9. Physical and chemical properties

- Physical state** : Liquid. [Aqueous solution]
- Flash point** : Closed cup: Not applicable. [Product does not sustain combustion.]
- Color** : Clear Amber.
- Odor** : Alkaline.
- pH** : 13.6
- Dilution pH** : 12.4 [Conc. (% w/w): 1%]
- Boiling/condensation point** : Not available.
- Melting/freezing point** : Not available.
- Specific gravity** : 1.14
- Density** : 9.5133 lbs/gal
- Vapor pressure** : Not available.
- Vapor density** : Not available.
- Odor threshold** : Not available.
- Evaporation rate** : Not available.
- Solubility** : Easily soluble in the following materials: cold water and hot water.
- Elemental Phosphorus** : 0 %
- Partition coefficient: n-octanol/water** : Not available.

10. Stability and reactivity

- Chemical stability** : The product is stable.
- Conditions to avoid** : No specific data.
- Materials to avoid** : Reactive or incompatible with the following materials:
acids
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

11. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
tetrasodium ethylene diamine tetraacetate	LD50 Oral	Rat	10 g/kg	-

Conclusion/Summary

TRACTOR BRITE : Oral LD50 estimated to be 1000 - 2000 mg/kg. Dermal LD50 estimated to be > 2000 mg/kg.

Carcinogenicity

None known.

Acute toxicity estimates

Not available.

12. Ecological information

Ecotoxicity : No known significant effects or critical hazards.

Aquatic ecotoxicity

None known.

13. Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

RCRA classification : D002 [corrosive]

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

IATA/IMDG/DOT/TDG: Please refer to the Bill of Lading/receiving documents for up to date shipping information.

15. Regulatory information

United States

U.S. Federal regulations

- TSCA 12(b) one-time export** : TSCA 12(b) one-time export: No products were found.
- TSCA 12(b) annual export notification** : TSCA 12(b) annual export notification: No products were found.
- United States inventory (TSCA 8b)** : All components are listed or exempted.
- SARA 311/312 Hazards identification**: Immediate (acute) health hazard
- SARA 302/304**: No products were found.
- CERCLA**: Hazardous substances.: sodium hydroxide: 1000 lbs. (454 kg);

SARA 313

None identified.

State regulations

- Massachusetts** : The following components are listed: SODIUM HYDROXIDE
- Rhode Island** : None of the components are listed.
- New Jersey** : The following components are listed: SODIUM HYDROXIDE; CAUSTIC SODA
- Pennsylvania** : The following components are listed: SODIUM HYDROXIDE (NA(OH))
- California Prop. 65**

None of the components are listed.

Canada

- WHMIS (Canada)** : Class E: Corrosive material
- WHMIS (Pictograms)** :



Canadian lists

- Canadian NPRI** : None of the components are listed.
- Canada inventory** : All components are listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

International regulations

- International lists** :
- Australia inventory (AICS)**: Not determined.
 - China inventory (IECSC)**: Not determined.
 - Japan inventory**: Not determined.
 - Korea inventory**: Not determined.
 - Malaysia Inventory (EHS Register)**: Not determined.
 - New Zealand Inventory of Chemicals (NZIoC)**: Not determined.
 - Philippines inventory (PICCS)**: Not determined.
 - Taiwan inventory (CSNN)**: Not determined.
- Europe inventory** : Not determined.

16. Other information

Hazardous Material Information System (U.S.A.) :

Health	*	3
Flammability		0
Physical hazards		0

16. Other information

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

Date of issue : 8/19/2014.

Date of previous issue : 7/21/2014.

Version : 4

✔ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.