3850-PM-BCW0015d 3/2016 Permit



COMMONWEALTH OF PENNSYLVANIA DEPARTMENT OF ENVIRONMENTAL PROTECTION BUREAU OF CLEAN WATER

PERMIT NO. <u>6419402</u>	
AMENDMENT NO.	

APS ID. 1008550

AUTH. ID. 1300322

WATER QUALITY MANAGEMENT			
PERMIT			

A.	PERMITTEE (Name and Address):	CLIENT ID#: 354335		B. PROJECT/FACILITY (Na	me):		
	LT Realty, Inc.			Bethany Village Senior I	_iving STP		
	150 Noble Lane						
	Bethany, PA_18431						
C.	LOCATION (Municipality, County):			SITE ID#: 825385			
	Dyberry Township, Wayne County	,					
D.	This permit approves the construction/operation of sewage facilities consisting of:						
	A new 6,500 gpd (0.0065 MGD) WW malfunctioning on-lot sewage dispos		Bethany '	/illage Senior Living Center. T	his facility wil	I replace an existin	ıg
	Sewage from the 70-bed facility will filter. Approximately 850 feet of new packaged extended aeration WWTP surge tank, a 1,707-gallon aerated sl are air diffusers, effluent trough, retu motor housing with baseplates, international statements of the second statement of the second statements of th	6-inch sewer line will convey filtered. The plant will be a welded steel reludge holding tank, a 9,000-gallon acrn sludge air lift, skimmer air lift, rota	d sewage ectangular eration ta ary blowe	from the existing septic tank to tank structure divided into four nk and a 1,083-gallon clarifier. is complete with necessary mo	the new Pur major sectio Included in t	restream Model PT ons: a 4,270-gallon the packaged plant	
	Treated effluent from the Purestream pumps will dose Yardney MM-1460-3 same pumps will be used to backwas system is an Ultra-Violet (UV) Pure r will be in parallel for redundancy. Installed after the media filter.	3A pressure filters. A throttling globe sh the filters and backwash water wi nodel Halett 500-W with 4-20 mA. T	e valve w ill be supp The syste	Il be provided to limit the flow to blied by the wet well of the dupl m is rated for up to 22 gpm @6	o the tertiary ex pump stat 5% UVT, 30	filters to 16 gpm. tion. The disinfection mJ/cm2. Two units	The ion is
	A type-DW concrete endwall with concencasing a 1.5' x 8' R-3 rip rap pad.				wall will be a	6" x 6" timber restr	raint
Pun	np Stations: <u>N/A</u>	Manure Storage: N/A		Sewage Treatment Facility:			
Des	ign Capacity: GPM	Volume: MG		Annual Average Flow:	0.0065	MGD	
		Freeboard: inches		Design Hydraulic Capacity:	0.0065	MGD	
				Design Organic Capacity:	17.35	lbs/day	
E.	APPROVAL GRANTED BY THIS PE	L RMIT IS SUBJECT TO THE FOLLO	OWING.			<u> </u>	
1.	New Permits: All construction, ope December 20, 2019, its supporting of	erations and procedures shall be in	accordar				ated
2.	Permit Conditions Relating to Sewers	age are attached and made part of t	this permi	t.			
3.	Special Condition $\underline{\mathbf{A}}$ is attached and	made part of this permit.					
F.	THE AUTHORITY GRANTED BY TH	HIS PERMIT IS SUBJECT TO THE F	FOLLOW	ING FURTHER QUALIFICATION	DNS:		
1.	If there is a conflict between the appl shall apply.	lication or its supporting documents	and ame	ndments and the attached cond	litions, the at	tached conditions	
2.	Failure to comply with the rules and by the issuance of this permit.	regulations of DEP or with the terms	or condi	ions of this permit shall void the	e authority giv	ven to the permitte	е
3.	This permit is issued pursuant to the shall not relieve the permittee of any		1937, P.L	. 1987, as amended 35 P.S. §6	91.1 et seq.	Issuance of this pe	rmit
	PERMIT ISSUED:		BY:	BR Patel			
_	July 8, 2020		TITLE:	Bharat Patel, P.E. Environmental Program I Northeast Regional Office	-		



COMMONWEALTH OF PENNSYLVANIA DEPARTMENT OF ENVIRONMENTAL PROTECTION BUREAU OF POINT AND NON-POINT SOURCE MANAGEMENT

PERMIT CONDITIONS RELATING TO SEWERAGE

For use in Water Quality Management Permits

The Department of Environmental Protection (DEP) considers the licensed Professional Engineer whose seal

is affixed to the design documents to be fully responsible for the adequacy of all aspects of the facility design.

The permittee shall adopt and enforce an ordinance requiring the abandonment of privies, cesspools or similar

(Check boxes that apply)

General

1.

2.

 \bowtie

		receptacles for human waste and onlot sewage disposal systems on the premises of occupied structures accessible to public sewers. All such structures must be connected to the public sewers.
	3.	The outfall sewer or drain shall be extended to the low water mark of the receiving body of water. Where necessary to ensure proper mixing and waste assimilation, an outfall sewer or drain may be extended with appurtenances below the low water mark and into the bed of a navigable stream provided that the permittee has secured an easement, right-of-way, license or lease from DEP in accordance with Section 15 of the Dam Safety and Encroachments Act, the Act of November 26, 1978, P.L. 1375, as amended.
	4.	The approval is specifically made contingent on the permittee acquiring all necessary property rights, by easement or otherwise, providing for the satisfactory construction, operation, maintenance and replacement of all sewers or sewerage structures in, along or across private property with full rights of ingress, egress and regress.
\boxtimes	5.	When construction of the approved sewerage facilities is completed and before they are placed in operation, the permittee shall notify DEP in writing so that a DEP representative may inspect the facilities.
	6.	The approval of the plans, and the authority granted in this permit, if not specifically extended, shall cease and be null and void 5 years from the issuance date of this permit unless construction or modification of the facilities covered by this permit has begun on or before the fifth anniversary of the permit date.
	7.	If, at any time, the sewerage facilities covered by this permit create a public nuisance, including but not limited to, causing malodors or causing environmental harm to waters of the Commonwealth, DEP may require the permittee to adopt appropriate remedial measures to abate the nuisance or harm.
	8.	If, after the issuance of this permit, DEP approves a municipal sewage facilities official plan or an amendment to an official plan under Act 537 (Pennsylvania Sewage Facilities Act, the Act of January 24, 1966, P.L. 1535 as amended) in which sewage from the herein approved facilities will be treated and disposed of at other planned facilities, the permittee shall, upon notification from the municipality or DEP, provide for the conveyance of its sewage to the planned facilities, abandon use and decommission the herein approved facilities including the proper disposal of solids, and notify DEP accordingly. The permittee shall adhere to schedules in the approved official plan, amendments to the plan, or other agreements between the permittee and municipality. This permit shall then, upon notice from DEP, terminate and become null and void and shall be relinquished to DEP.
\boxtimes	9.	This permit does not relieve the permittee of its obligations to comply with all federal, interstate, state or local laws, ordinances and regulations applicable to the sewerage facilities.
	10.	This permit does not give any real or personal property rights or grant any exclusive privileges, nor shall it be construed to grant or confirm any right, easement or interest in, on, to or over any lands which belong to the Commonwealth.

Construction

12. This permit is issued under the authorization of The Clean Streams Law and 25 Pa. Code Chapter 91. The permittee shall obtain all necessary permits, approvals and/or registrations under 25 Pa. Code Chapters 102, 105 and 106 prior to commencing construction of the facilities authorized by this permit, as applicable. The permittee should contact the DEP office that issued this permit if there are any questions concerning the applicability of additional permits.

11. The authority granted by this permit is subject to all effluent requirements, monitoring requirements and other conditions as set forth in the NPDES Permit and all subsequent amendments and renewals. No discharge is

authorized from these facilities unless approved by an NPDES Permit.

- 13. The facilities shall be constructed under the supervision of a Pennsylvania licensed Professional Engineer in accordance with the approved reports, plans and specifications.
- 14. A Pennsylvania licensed Professional Engineer shall certify that construction of the permitted facilities was completed in accordance with the application and design plans submitted to DEP, using the "Post Construction Certification" form (3800-PM-WSFR0179a). It is the permittee's responsibility to ensure that a Professional Engineer is on-site to provide the necessary oversight and/or inspections to certify the facilities. The certification must be submitted to DEP before the facility is placed in operation. As-built drawings, photographs (if available) and a description of all deviations from the application and design plans must be submitted to DEP within 30 days of certification.
- Manhole inverts shall be formed to facilitate the flow of the sewage and to prevent the stranding of sewage solids. The manhole structure shall be built to prevent undue infiltration, entrance of street wash or grit and provide safe access to facilitate manhole maintenance activities.
- 16. The local Waterways Conservation Officer of the Pennsylvania Fish and Boat Commission (PFBC) shall be notified when the construction of any stream crossing and/or outfall is started and completed. A written permit must be secured from the PFBC if the use of explosives in any waterways is required and the permittee shall notify the local Waterways Conservation Officer when explosives are to be used.

Operation and Maintenance

- □ 17. The permittee shall maintain records of "as-built" plans showing all the treatment facilities as actually constructed together with facility operation and maintenance (O&M) manuals and any other relevant information that may be required. Upon request, the "as-built" plans and O&M manuals shall be filed with DEP.
- 18. The sewers shall have adequate foundation support as soil conditions require. Trenches shall be back-filled to ensure that sewers will have proper structural stability, with minimum settling and adequate protection against breakage. Concrete used in connection with these sewers shall be protected from damage by water, freezing, drying or other harmful conditions until cured.
- 19. Stormwater from roofs, foundation drains, basement drains or other sources shall not be admitted directly to the sanitary sewers.
- 20. The approved sewers shall be maintained in good condition, kept free of deposits by flushing or other cleaning methods and repaired when necessary.
- 21. The sewerage facilities shall be properly operated and maintained to perform as designed.
- 22. The attention of the permittee is called to the highly explosive nature of certain gases generated by the digestion of sewage solids when these gases are mixed in proper proportions with air and to the highly toxic character of certain gases arising from such digestion or from sewage in poorly ventilated compartments or sewers. Therefore, at all places throughout the sewerage facilities where hazard of fire, explosion or danger from toxic gases may occur, the permittee shall post conspicuous permanent and legible warnings. The permittee shall instruct all employees concerning the aforesaid hazards, first aid and emergency methods of meeting such hazards and shall make all necessary equipment and material accessible.
- 23. An operator certified in accordance with the Water and Wastewater Systems Operator Certification Act of February 21, 2002, 63 P.S. §§1001, *et seq.* shall operate the sewage treatment plant.
- 24. The permittee shall properly control any industrial waste discharged into its sewerage system by regulating the rate and quality of such discharge, requiring necessary pretreatment and excluding industrial waste, if necessary, to protect the integrity or operation of the permittee's sewerage system.
- 25. There shall be no physical connection between a public water supply system and a sewer or appurtenance to it which would permit the passage of any sewage or polluted water into the potable water supply. No water pipe shall pass through or come in contact with any part of a sewer manhole.
- 26. All connections to the approved sanitary sewers must be in accordance with the official Act 537 Plan and, if applicable, a corrective action plan as contained in the approved Title 25 Pa. Code Chapter 94 Municipal Wasteload Management Annual Report.
- 27. Collected screenings, slurries, sludge and other solids shall be handled and disposed of in compliance with Title 25 Pa. Code Chapters 271, 273, 275, 283 and 285 (related to permits and requirements for land filling, land application, incineration and storage of sewage sludge), Federal Regulations 40 CFR 257 and the Federal Clean Water Act and its amendments.



COMMONWEALTH OF PENNSYLVANIA DEPARTMENT OF ENVIRONMENTAL PROTECTION BUREAU OF CLEAN WATER

WATER QUALITY MANAGEMENT POST CONSTRUCTION CERTIFICATION

PERMITTEE IDENTIFIER

Permittee	LT Realty, Inc.	
Municipality	Dyberry Township	
County	Wayne	
WQM Permit No.	6419402	
Facility Type	Sewage	
	CEI	RTIFICATION
WQM permit within	n 30 days of completion of the prophotographs (if available) and a	to the permits section of the DEP's regional office issuing the oject and received by DEP prior to operation, and if requested, a discussion of any DEP-approved deviations from the design
belief, based upon	personal observation and interv mit has been constructed in a	nnsylvania, do hereby certify to the best of my knowledge and riews, that the above facility approved under the Water Quality ccordance with the plans, specifications and modifications
Construction Com	pletion Date (MM/DD/YYYY): _	
		Professional Engineer
		Name
		(Please Print or Type)
		Signature
		Date
		License Expiration Date
		Firm or Agency
		Telephone
		Permittee or Authorized Representative
		Name(Please Print or Type)
	Engineer's	Signature
	Seal	Title
	nor 40 300 to	Telephone