

Application Type New
Facility Type Industrial
Major / Minor Minor

**NPDES PERMIT FACT SHEET
INDIVIDUAL INDUSTRIAL WASTE (IW)
AND IW STORMWATER**

Application No. PA0267627
APS ID 1049903
Authorization ID 1373265

Applicant and Facility Information

Applicant Name	<u>Texas Eastern Transmission LP</u>	Facility Name	<u>Texas Eastern Perulack Compressor Station</u>
Applicant Address	<u>890 Winter Street</u> <u>Waltham, MA 02451-1470</u>	Facility Address	<u>3318 Pumping Station Road</u> <u>East Waterford, PA 17021-7187</u>
Applicant Contact	<u>Ivana Pejatovic</u>	Facility Contact	<u></u>
Applicant Phone	<u>(617) 560-1364</u>	Facility Phone	<u></u>
Client ID	<u>82786</u>	Site ID	<u>442911</u>
SIC Code	<u>4922</u> <u>Trans. & Utilities - Natural Gas</u> <u>Transmission</u>	Municipality	<u>Lack Township</u>
SIC Description		County	<u>Juniata</u>
Date Application Received	<u>October 15, 2021</u>	EPA Waived?	<u>Yes</u>
Date Application Accepted	<u>October 27, 2021</u>	If No, Reason	<u></u>
Purpose of Application	<u>New NPDES individual permit application for discharge of industrial wastewater, specifically discharges from hydrostatic testing of new pipelines</u>		

Summary of Review

SWCA on behalf of Texas Eastern submitted this permit application for the proposed discharge of hydrostatic test water either through the water treatment system or directly to ground surface and vegetated uplands.

The discharges of hydrostatic testing water are from new natural gas pipeline facilities to be installed as part of the construction work at the Perulack Compressor Station. The construction work is part of a project designed to ensure continued compliance with PADEP's air emissions regulation.

At this time, the PAG-10 NPDES General Permit for discharges from hydrostatic testing of tanks and pipelines expired July 10, 2020 and has been administratively extended a second time through July 10, 2022 (see Notice of Extension of National Pollutant Discharge Elimination System General Permit for Discharges from Hydrostatic Testing of Tanks and Pipelines (PAG-10) in Volume 51, Issue 24, Saturday, June 12, 2021 issue of the Pa Bulletin [Pennsylvania Bulletin \(pacodeandbulletin.gov\)](http://pacodeandbulletin.gov)). During this period of administrative extension, no new coverage under the PAG-10 General Permit may be authorized by the Department. Therefore, Texas Eastern has applied for an individual NPDES Permit to Discharge Industrial Wastewater. If the PAG-10 was available, they would qualify and fall under Part A I.A. Effluent Limitations and Monitoring Requirements for discharges of hydrostatic test water from new tanks and pipelines.

Note: A Public Notice of Draft NPDES General Permit for Discharges from Hydrostatic Testing of Tanks and Pipelines (PAG-10) was published in Volume 51, Issue 43 (51 Pa.B. 6706), Saturday, October 23, 2021 issue of the PA Bulletin [Pennsylvania Bulletin \(pacodeandbulletin.gov\)](http://pacodeandbulletin.gov)

The project will include the installation of new natural gas piping, followed by the hydrostatic testing of the new pipe. The municipal water used for hydrostatic testing will be clean of any pollutants, since all piping to be tested at the station will be new. Hydrostatic test water samples will be collected at the beginning of discharge as well as at the end of discharge to

Approve	Deny	Signatures	Date
x		<i>Brenda J Fruchtl</i> Brenda J. Fruchtl, P.G. / Licensed Professional Geologist	December 9, 2021
x		<i>Scott M Arwood</i> Scott M. Arwood, P.E. / Environmental Engineer Manager	12/13/2021

Summary of Review

verify compliance with NPDES Individual permit limits. If elevated sampling parameters exist prior to discharge onsite, the hydrostatic test water will be treated via the on-site water filtration system before being discharged onsite.

The water, either treated or directly released, will be discharged to uplands at the project site through a filter bag placed within a straw bale enclosure underlain by a geotextile fabric. Water will be discharged at a controlled rate to prevent scouring and erosion at the discharge point. The filter bag and straw bales will help to remove, retain, and filter any suspended solids from the water before it infiltrates into the surrounding uplands.

Approximately 21,200 linear feet of 2-inch to 36-inch diameter piping will be hydrostatically tested throughout the course of the project.

The system is designed for a flow rate of 100 gpm (0.06 mgd) but will likely operate at a lower flow rate. Hydrostatic test water is anticipated to be discharged for 10 hours per day for an estimated six days per year for a total of approximately 120,000 gallons each year.

The discharges are anticipated to occur during 2022 and 2023.

See **Figure 1** for project location and outfall locations.

TIMELINE

1. October 29, 2021. PADEP sent an email outlining technical deficiencies that need addressed.
2. November 10, 2021. Texas Eastern (SWCA) addressed the technical deficiencies.
3. November 17, 2021. PADEP sent an email asking some additional questions.
4. December 1, 2021. Texas Eastern (SWCA) responded to the additional questions.

Public Participation

DEP will publish notice of the receipt of the NPDES permit application and a tentative decision to issue the individual NPDES permit in the *Pennsylvania Bulletin* in accordance with 25 Pa. Code § 92a.82. Upon publication in the *Pennsylvania Bulletin*, DEP will accept written comments from interested persons for a 30-day period (which may be extended for one additional 15-day period at DEP's discretion), which will be considered in making a final decision on the application. Any person may request or petition for a public hearing with respect to the application. A public hearing may be held if DEP determines that there is significant public interest in holding a hearing. If a hearing is held, notice of the hearing will be published in the *Pennsylvania Bulletin* at least 30 days prior to the hearing and in at least one newspaper of general circulation within the geographical area of the discharge.

Discharge, Receiving Waters and Water Supply Information			
Outfall No.	<u>001</u>	Design Flow (MGD)	<u>.06</u>
Latitude	<u>40° 21' 17"</u>	Longitude	<u>-77° 39' 7"</u>
Wastewater Description: <u>Hydrostatic Test Water</u>			
Receiving Waters	<u>Lick Run (CWF, MF)</u>	Stream Code	<u>12119</u>
NHD Com ID	<u>66209841</u>	RMI	<u>1.0</u>
Drainage Area	<u>8.15</u>	Elevation (ft)	<u>726</u>
Watershed No.	<u>12B</u>	Chapter 93 Class.	<u>CWF, MF</u>
Assessment Status <u>Attaining Use(s)</u>			
Nearest Downstream Public Water Supply Intake		<u>Newport Boro Water Authority</u>	
PWS Waters	<u>Juniata River</u>	Location	<u>Newport Boro, Perry Co</u>
PWS RMI	<u>12</u>	Distance from Outfall (mi)	<u>53</u>

Other Comments:
 The discharge will flow overland approximately 400 ft to the east before reaching Lick Run.

Discharge, Receiving Waters and Water Supply Information			
Outfall No.	<u>002</u>	Design Flow (MGD)	<u>.06</u>
Latitude	<u>40° 21' 13"</u>	Longitude	<u>-77° 39' 11"</u>
Wastewater Description: <u>Hydrostatic Test Water</u>			
Receiving Waters	<u>Unnamed Tributary to Lick Run (CWF, MF)</u>	Stream Code	<u>12120</u>
NHD Com ID	<u>66209937</u>	RMI	<u>0.2600</u>
Drainage Area	<u>0.15</u>	Elevation (ft)	<u>790</u>
Watershed No.	<u>12B</u>	Chapter 93 Class.	<u>CWF, MF</u>
Assessment Status <u>Attaining Use(s)</u>			
Nearest Downstream Public Water Supply Intake		<u>Newport Boro Water Authority</u>	
PWS Waters	<u>Juniata River</u>	Location	<u>Newport Boro, Perry Co</u>
PWS RMI	<u>12</u>	Distance from Outfall (mi)	<u>53</u>

Other Comments:
 The discharge will flow overland approximately 200 feet to the south before reaching Trib 12120 to Lick Run.

Discharge, Receiving Waters and Water Supply Information			
Outfall No.	<u>003</u>	Design Flow (MGD)	<u>.06</u>
Latitude	<u>40° 21' 27"</u>	Longitude	<u>-77° 39' 24"</u>
Wastewater Description: <u>Hydrostatic Test Water</u>			
Receiving Waters	<u>Lick Run (CWF, MF)</u>	Stream Code	<u>12119</u>
NHD Com ID	<u>66209841</u>	RMI	<u>1.2</u>
Drainage Area	<u>8.1</u>	Elevation (ft)	<u>770</u>
Watershed No.	<u>12B</u>	Chapter 93 Class.	<u>CWF, MF</u>
Assessment Status	<u>Attaining Use(s)</u>		
Nearest Downstream Public Water Supply Intake		<u>Newport Boro Water Authority</u>	
PWS Waters	<u>Juniata River</u>	Location	<u>Newport Boro, Perry Co</u>
PWS RMI	<u>12</u>	Distance from Outfall (mi)	<u>53</u>

Other Comments:

The discharge will flow overland approximately 800 ft east before reaching Lick Run.

Treatment Facility Summary

Treatment Facility Name: Hydrostatic Test Water Dewatering.

Texas Eastern requested an approval of both potential water discharge methods for the hydrostatic water, directly to ground surface and uplands or through the onsite water treatment system.

The hydrostatic test water will be sampled prior to, and at the beginning of, and at the end of discharge to verify compliance with NPDES Individual permit limits. If hydrostatic test water does not meet the permit threshold related to specific sampling parameters levels, it can be treated via an onsite water treatment system. Texas Eastern will have a water treatment system located at the northwest side of the Compressor Station to address water generated during the hydrovac excavation procedure, whose discharge is covered by a temporary discharge approval.

The water, either treated or directly released, will be discharged to uplands at the project site through a filter bag placed within a straw bale enclosure underlain by a geotextile fabric. Water will be discharged at a controlled rate to prevent scouring and erosion at the discharge point.

Design Flow = 0.06 MGD
Average Flow = 0.04 MGD
Maximum Flow = 0.07 MGD

Discharge will be for 10 hours a day for approximately 6 days a year.

Texas Eastern has developed an erosion and sediment control plan in accordance with the Pennsylvania Erosion and Sedimentation Pollution Control Program Manual (PA E&S Manual 363-2134-008) as part of the Individual Permit Application. An ESCGP-3 coverage was obtained from the Berks County Conservation District and the PADEP. The components of the erosion and sediment control plan (e.g., rock construction entrances, filter socks, diversion fencing, sediment traps, and inlet protections) were designed and sized based on the PA E&S Manual. Texas Eastern has also prepared a post-construction stormwater management plan as part of its ESCGP-3 NOI submittal. The PCSM was designed in accordance with 25 Pa. Code Chapter 102 and the Pennsylvania Stormwater.

See **Attachment A** for the BMPs in place to address erosion and sedimentation.

Development of Effluent Limitations

Outfall No.	001	Design Flow (MGD)	.06
Latitude	40° 21' 17.00"	Longitude	-77° 39' 7.00"
Outfall No.	002	Design Flow (MGD)	.06
Latitude	40° 21' 13.00"	Longitude	-77° 39' 11.00"
Outfall No.	003	Design Flow (MGD)	.06
Latitude	40° 21' 27.00"	Longitude	-77° 39' 24.00"

Wastewater Description: Hydrostatic Test Water

Parameters, Monitoring Frequency, and Limits

Parameters, monitoring frequency, and the limits were taken directly from the NPDES PAG-10 General Permit for discharges from hydrostatic testing of tanks and pipelines (effective July 11, 2015) for new tanks and pipelines since the facility would be eligible for the PAG-10 General Permit if it were currently available for new dischargers. See Table below taken from the PAG-10 General Permit (effective July 11, 2015):

PART A

EFFLUENT LIMITATIONS, MONITORING, RECORDKEEPING AND REPORTING REQUIREMENTS

I. EFFLUENT LIMITATIONS AND MONITORING REQUIREMENTS

A. The permittee shall comply with the following effluent limitations and monitoring requirements for discharges of hydrostatic test water from new tanks and pipelines.

Parameter	Effluent Limitations			Monitoring Requirements ⁽¹⁾	
	Minimum	Average Monthly	Instant. Maximum	Minimum Measurement Frequency ^{(2),(3)}	Sample Type
Flow (GPM) ⁽⁴⁾	XXX	Report	XXX	1/discharge	Measured
Duration of Discharge (Hours) ⁽⁴⁾	XXX	Report	XXX	1/discharge	Measured
Total Volume Discharged (Gallons) ⁽⁴⁾	XXX	Report Total Monthly	XXX	1/month	Calculated
Dissolved Oxygen (mg/L)	5.0	XXX	XXX	2/discharge	Grab
pH (S.U.)	6.0	XXX	9.0	2/discharge	Grab
Total Residual Chlorine (TRC) (mg/L) ⁽⁵⁾	XXX	Report	0.05	2/discharge	Grab
Total Suspended Solids (TSS) (mg/L)	XXX	30	60	1/discharge	Grab
Oil and Grease (mg/L)	XXX	15	30	1/discharge	Grab
Dissolved Iron (mg/L)	XXX	XXX	7.0	1/discharge	Grab

Part A – Effluent Limitations, Monitoring, Recordkeeping and Reporting Requirements

The following applicable footnotes, obtained from the PAG-10 NPDES General Permit for Discharges from Hydrostatic Testing of Tanks and Pipelines, effective 7/11/15, were added to Part A.1:

- Footnote (2) or Minimum Measurement Frequency in Part A.1:
(2) This is the minimum number of sampling events required. Permittees are encouraged, and it may be advantageous in demonstrating compliance, to perform more than the number of sampling events.
- Footnote (3) for Minimum Measurement Frequency in Part A.1:
(3) The permittee shall collect samples at the point of discharge (outfall) prior to the discharge entering the receiving

waters. For measurement frequencies of 1/discharge, the permittee shall collect samples within the first 30 minutes of commencing a discharge. For measurement frequencies of 2/discharge, the permittee shall collect one sample at the start of a discharge and one sample at the end of a discharge.

3. Footnote (4) for Flow (GPM), Duration of Discharge (hours), and Total Volume (Gallons) in Part A.I.
(4) *The permittee shall report the average monthly flow, in gallons per minute (GPM), for all discharges occurring during the month. The permittee shall measure the flow and the duration of the discharge (in hours) for each discharge and shall report this information to DEP in the Annual Report as specified in Part C II of this permit. The permittee shall report the total volume discharged each month, in gallons.*
4. Footnote (5) for Total Residual Chlorine (TRC) in Part A.I:
(5) *The permittee shall comply with the effluent limitations and monitoring requirements for Total Residual Chlorine (TRC) only when a public water supply or other source of chlorinated water is used in hydrostatic testing.*

PART C SPECIAL CONDITIONS

*Indicates the Special Condition was obtained / adapted from Part C of the PAG-10 NPDES General Permit for Discharges from Hydrostatic Testing of Tanks and Pipelines, effective 7/11/15.

^ Indicates the Special Condition was obtained / adapted from Part A.III.C.1. of the PAG-10 NPDES General Permit for Discharges from Hydrostatic Testing of Tanks and Pipelines, effective 7/11/15.

I. OTHER REQUIREMENTS

- A. The approval herein given is specifically made contingent upon the permittee acquiring all necessary property rights by easement or otherwise, providing for the satisfactory construction, operation, maintenance or replacement of all structures associated with the herein approved discharge in, along, or across private property, with full rights of ingress, egress and regress.
- B. Collected screenings, slurries, sludges, and other solids shall be handled, recycled and/or disposed of in compliance with the Solid Waste Management Act (35 P.S. §§ 6018.101 – 6018.1003), 25 Pa. Code Chapters 287, 288, 289, 291, 295, 297, and 299 (relating to requirements for landfilling, impoundments, land application, composting, processing, and storage of residual waste), Chapters 261a, 262a, 263a, and 270a (related to identification of hazardous waste, requirements for generators and transporters, and hazardous waste, requirements for generators and transporters, and hazardous waste permit programs), federal regulation 40 CFR Part 257, The Clean Streams Law, and the Federal Clean Water Act and its amendments. Screenings collected at intake structures shall be collected and managed and not be returned to the receiving waters.

The permittee is responsible to obtain or assure that contracted agents have all necessary permits and approvals for the handling, storage, transport and disposal of solid waste materials generated as a result of wastewater treatment.

- C. If the applicable standard or effluent guideline limitation relating to the application for Best Available Technology (BAT) Economically Achievable or to Best Conventional Technology (BCT) is developed by DEP or EPA for this type of industry, and if such standard or limitation is more stringent than the corresponding limitations of this permit (or if it controls pollutants not covered by this permit), DEP may modify or revoke and reissue the permit to conform with that standard or limitation.
- *D. The permittee shall not discharge any other wastewaters such as cleaning wastewaters, tank bottom water, sewage, raw product, etc. to waters of the Commonwealth. The permittee may discharge these other wastewaters to an available sanitary sewer system, if the permittee obtains permission from the owner. If discharge to a local sanitary sewer system is not an option, the permittee shall properly dispose of these other wastewaters off-site, unless otherwise authorized by DEP.
- *E. The permittee shall not introduce chemical additives, including but not limited to corrosion inhibitors, bactericides and dyes, into hydrostatic test water unless the permittee completely removes the constituents of such additives from the effluent prior to discharge (i.e., the permittee shall analyze the effluent for the constituents of such additives using the analytical method available that achieves the lowest quantitation limit, and the constituents shall not be detectable). The permittee shall notify DEP prior to introducing chemical additives to the hydrostatic test water.

^II. ANNUAL REPORT – The permittee shall submit a complete Annual Report to the DEP office that issued the permit by March 1 each year using DEP’s Annual Report template, attached to this permit. The Annual Report shall address activities under the permit for the previous calendar year. The permittee shall submit the Annual Report electronically if notified by DEP in writing. (25 Pa. Code § 92a.61(g))

***III. BEST MANAGEMENT PRACTICES (BMPs)**

A. General

1. The permittee shall not discharge in a manner that causes erosion of stream banks or scouring of stream beds. The permittee shall properly direct the discharge of all water discharged so that it does not cause nuisance conditions and does not pool or pond prior to reaching surface waters.
2. The permittee shall implement erosion and sedimentation control practices at the discharge point in accordance with 25 Pa. Code Chapter 102 (relating to Erosion and Sediment Control) and DEP’s Erosion and Sedimentation Pollution Control Manual (DEP ID: 363-2134-008).
3. Wherever possible, the permittee shall not use water that has been chlorinated for hydrostatic testing. If no alternatives to chlorinated water exist, the permittee shall retain the water in the tank or pipeline for at least 24 hours prior to discharge and shall sample the water prior to discharge to confirm that the Total Residual Chlorine limits in Part A of this permit will be achieved. Dechlorination of discharges may be required.
4. If the permittee withdraws water from a stream to conduct its hydrostatic testing, the permittee shall not withdraw a volume of water that exceeds 25 percent of the volume of the stream at the time of withdrawal. The permittee shall not discharge a volume of test water that increases the volume of the receiving stream by more than 25 percent downstream regardless of the source of the test water. The permittee shall not dewater the stream to the extent that downstream users, including aquatic life, are impacted during pipe filling operations. The permittee shall prevent the impingement and entrainment of fish when withdrawing water from surface waters.
5. The permittee shall limit the volume to be discharged to the lowest possible rate to minimize any potential impact on aquatic life and to reduce the potential for erosion. In addition, the permittee shall avoid withdrawals and discharges during critical stream conditions such as low flow, trout stocking season, spawning seasons, recreational seasons, etc. The permittee shall not discharge to trout stocked streams from March 1 to June 15. The listing of trout stock streams can be found on the Pennsylvania Fish and Boat Commission’s website: www.fish.state.pa.us.
6. The permittee shall clean all tanks and pipelines prior to hydrostatic testing and discharge under this General Permit. The permittee shall collect wastewaters and solids from the cleaning process and shall transport them to an authorized disposal facility.
7. The permittee shall not discharge hydrostatic test water and cleaning wastewaters into a combined sewer system or a separate sanitary sewer.
8. The permittee shall develop and implement a Preparedness, Prevention and Contingency (PPC) Plan in accordance with 25 Pa. Code § 91.34 following the guidance contained in DEP’s “Guidelines for the Development and Implementation of Environmental Emergency Response Plans” (DEP ID 400-2200-001), and its NPDES-specific addendum. The permittee shall evaluate and, if necessary, update the PPC Plan on an annual basis, at a minimum, and when one or more of the following occur:
 - a. The PPC Plan fails in an emergency;
 - b. A change in design, industrial process, operation, maintenance, or other circumstance occurs in a manner that materially increases the potential for fires, explosions or releases of toxic or hazardous constituents; or which changes the response necessary in an emergency;
 - c. The list of emergency coordinators or equipment changes; or
 - d. When notified in writing by DEP.

The PPC Plan must be maintained on-site at the location of hydrostatic testing and be made available to DEP upon request.

B. Hydrostatic Testing of Pipelines

For pipelines, the permittee shall, at a minimum, place hay bales in a circular fashion at the discharge point with oil absorbent pads and a decant pipe for sampling purposes. The permittee shall install an energy dissipater in the containment areas and shall line the bottom of the containment areas with an impermeable material.


Proposed Effluent Limitations and Monitoring Requirements

The limitations and monitoring requirements specified below are proposed for the draft permit, and reflect the most stringent limitations amongst technology, water quality and BPJ. Instantaneous Maximum (IMAX) limits are determined using multipliers of 2 (conventional pollutants) or 2.5 (toxic pollutants). Sample frequencies and types are derived from the "NPDES Permit Writer's Manual" (362-0400-001), SOPs and/or BPJ.

Outfalls 001, 002, and 003, Effective Period: Permit Effective Date through Permit Expiration Date.

Parameter	Effluent Limitations						Monitoring Requirements	
	Mass Units (lbs/day) ⁽¹⁾		Concentrations (mg/L)				Minimum ⁽²⁾ Measurement Frequency	Required Sample Type
	Average Monthly	Average Weekly	Minimum	Average Monthly	Maximum	Instant. Maximum		
Flow (GPM)	Report	XXX	XXX	XXX	XXX	XXX	1/discharge	Measured
Total Flow (M Gal)	Report Total Mo	XXX	XXX	XXX	XXX	XXX	1/month	Calculation
Duration of Discharge (hours)	XXX	XXX	XXX	Report	XXX	XXX	1/discharge	Measured
pH (S.U.)	XXX	XXX	6.0 Inst Min	XXX	XXX	9.0	2/discharge	Grab
DO	XXX	XXX	5.0 Inst Min	XXX	XXX	XXX	2/discharge	Grab
TRC	XXX	XXX	XXX	Report	XXX	0.05	2/discharge	Grab
TSS	XXX	XXX	XXX	30.0	XXX	60.0	1/discharge	Grab
Oil and Grease	XXX	XXX	XXX	15.0	XXX	30.0	1/discharge	Grab
Dissolved Iron	XXX	XXX	XXX	XXX	XXX	7.0	1/discharge	Grab

Compliance Sampling Location: At the Outfall








 <p>PERULACK COMPRESSOR STATION FIGURE 1: PROJECT OVERVIEW MAP USGS 7.5' TOPOGRAPHIC QUADRANGLE BLAIRS MILLS, PENNSYLVANIA JUNIATA COUNTY, PENNSYLVANIA OCTOBER 2020</p>	<ul style="list-style-type: none"> ★ Compressor Station ● Outfall Location ▭ Limit of Disturbance ▭ USGS Quadrangle Boundary 		 <p>SWCA ENVIRONMENTAL CONSULTANTS</p> <p>1:24,000</p> <p>Created by: E. Smith Project Number: 43174 Date: 10/20/20 MTD: 09810742/Perulack</p> 
--	--	--	--

Figure 1. Topographic map showing Outfall locations


Attachment A

Discharge Structure Details and BMPs

G:\S-U\SPE\2013-200,00\AutoCAD\Final\es0025.dwg
 Wayne Sicora
 5/29/2014 1:56 PM
 I.C. ES0025.DWG



PLAN VIEW



CROSS-SECTION

NOTES:


1. THE FILTER BAG OR STRUCTURE MUST BE MANNED WHEN THE PUMPING IS INITIATED TO ENSURE PROPER OPERATION AND FUNCTIONALITY.
2. REMOVE DEWATERING STRUCTURE AS SOON AS PRACTICABLE AFTER COMPLETION OF DEWATERING ACTIVITIES.
3. PLACEMENT OF FILTERBAGS SHOULD BE IN A MANNER THAT BAG USE DOES NOT CAUSE EROSION. IF SITE CONDITIONS ALLOW, PLACE FILTER BAG IN WELL-VEGETATED AREA, A MINIMUM OF 50 FEET FROM WETLANDS OR WATERBODIES.

	<p>FILTER BAG</p>	<p>FIGURE WD-1</p>
	<p>DWG. ES-0025</p>	<p>REV.</p>

Q:\S-U\SPE\2013-200.00\AutoCAD\Final\es0026.dwg

Wayne Sicora
5/29/2014 1:58 PM

I.d. ES0026.DWG



PLAN VIEW



OPTION 1

OPTION 2

CROSS SECTION VIEWS

NOTES:


1. SIZE AND DIMENSION OF DEWATERING STRUCTURE WILL VARY DEPENDING ON THE VOLUME AND RATE OF DISCHARGE, STAGGER PLACEMENT OF STRAW BALES WHEN TWO ROWS ARE USED.
2. COVER THE BASE OF THE DISCHARGE STRUCTURE EITHER WITH STRAW BALES (OPTION 1) OR LINE WITH GEOTEXTILE FABRIC (OPTION 2).
3. PROVIDE SUPPORT TO ENSURE THAT DISCHARGE PIPE DOES NOT REST ON STRAW BALES.
4. PLASTIC SHEETING, WOODEN MATS OR STEEL PLATES MAY ALSO BE USED, AS DIRECTED BY THE ENVIRONMENTAL INSPECTOR, TO PREVENT EROSION, STREAMBED SCOUR, SUSPENSION OF SEDIMENTS OR EXCESSIVE STREAMFLOW.
5. ABSORBENT BOOMS MUST BE USED DURING DISCHARGES FROM EXISTING / USED PIPE OR AS DIRECTED BY PERMIT REQUIREMENTS.
6. PREVENT EROSION, STREAMBED SCOUR, SUSPENSION OF SEDIMENTS AND EXCESSIVE STREAMFLOW BY PROPER DESIGN OF STRUCTURE, REGULATING THE WATER DISCHARGE RATE AS WELL AS USE OF ENERGY DISSIPATION DEVICE(S) AND SEDIMENT BARRIERS, AS NECESSARY.

DISCHARGE STRUCTURE FOR
 HYDROSTATIC TEST WATER

FIGURE WD-2

DWG. ES-0026

REV.



PLAN VIEW
 NOT TO SCALE

NOTES:


1. SIZE AND DIMENSION OF DEWATERING STRUCTURE, INCLUDING NUMBER OF STRAW BALES USED, WILL VARY DEPENDING ON VOLUME OF WATER DISCHARGED, RATE OF DISCHARGE AND SITE CONDITIONS, SUCH AS THE TYPE AND AMOUNT OF SEDIMENT WITHIN THE DISCHARGE WATER.
2. PREVENT EROSION, STREAMBED SCOUR, SUSPENSION OF SEDIMENTS AND EXCESSIVE STREAMFLOW BY PROPER DESIGN OF STRUCTURE, REGULATING THE WATER DISCHARGE RATE AS WELL AS USE OF ENERGY DISSIPATION DEVICE(S) AND SEDIMENT BARRIERS, AS NECESSARY.
3. MONITOR AND CONDUCT DISCHARGES IN A MANNER THAT DOES NOT CAUSE EROSION AND DOES NOT RESULT IN SILT-LADEN WATER FLOWING INTO ANY WATERBODY OR WETLAND.
4. DO NOT DEPOSIT SAND, SILT, AND/OR SEDIMENT INTO SENSITIVE ENVIRONMENTAL RESOURCE AREAS, INCLUDING WETLANDS, WATERBODIES, CULTURAL RESOURCE SITES, AND SENSITIVE SPECIES HABITATS. STOP DEWATERING ACTIVITIES IF SUCH DEPOSITION IS OCCURRING AND ENSURE THE DESIGN OF THE DISCHARGE IS CHANGED TO PREVENT REOCCURRENCE.
5. ABSORBENT BOOMS MUST BE USED DURING DISCHARGES FROM EXISTING / USED PIPE OR AS DIRECTED BY PERMIT REQUIREMENTS.
6. FILTER BAGS SHOULD BE INSTALLED ACCORDING TO THE DETAILS SHOWN IN "FILTER BAG" FIGURE.
7. REMOVE STRUCTURE AS SOON AS PRACTICABLE AFTER COMPLETION OF WATER DISCHARGES.

G:\S-U\SPE\2013-200,00\AutoCAD\Final\es0027.dwg

Wayne Sidor 5/29/2014 2:09 PM

I.G. ES0027.DWG

OPTIONS FOR SMALL WATER DISCHARGES		FIGURE WD-3	
		DWG. ES-0027	REV.



G:\S-U\SPE\2013-200.00\AutoCAD\Final\es0028.dwg

Wayne Sica
6/9/2014 4:22 PM

I.C. ES0028.DWG

NOTES:

1. USE BACKHOE BUCKET OR DOZER BLADE TO ANCHOR DISCHARGE PIPE.
2. ON FLAT TERRAIN, USE STACKED STRAW BALES AND SILT FENCE AS NEEDED TO DIVERT WATER AWAY FROM DISTURBED RIGHT-OF-WAY.

	<p>DISCHARGE OF HYDROSTATIC TEST WATER TO A SURFACE WATER</p>	<p>FIGURE WD-4</p>	
		<p>DWG. ES-0028</p>	<p>REV.</p>