

Application Type New  
Facility Type Storm Water  
Major / Minor Minor

**NPDES PERMIT FACT SHEET  
INDIVIDUAL INDUSTRIAL WASTE (IW)  
AND IW STORMWATER**

Application No. PA0284955  
APS ID 1066746  
Authorization ID 1403441

**Applicant and Facility Information**

Applicant Name	<u>Gold Bond Building Products, LLC</u>	Facility Name	<u>Shippingport Plant</u>
Applicant Address	<u>2001 Rexford Road</u> <u>Charlotte, NC 28211-3415</u>	Facility Address	<u>168 Shippingport Road</u> <u>Shippingport, PA 15077</u>
Applicant Contact	<u>Trey Jackson</u>	Facility Contact	<u>Same as applicant</u>
Applicant Phone	<u>thjackson@goldbondbuilding.com</u>	Facility Phone	<u>Same as applicant</u>
Client ID	<u>91710</u>	Site ID	<u>464337</u>
SIC Code	<u>3275</u>	Municipality	<u>Shippingport Borough</u>
SIC Description	<u>Manufacturing - Gypsum Products</u>	County	<u>Beaver</u>
Date Application Received	<u>June 28, 2022</u>	EPA Waived?	<u>Yes</u>
Date Application Accepted	<u>July 14, 2022</u>	If No, Reason	<u></u>
Purpose of Application	<u>NPDES permit coverage of Stormwater associated with Industrial Activities</u>		

**Summary of Review**



The Department received a new Individual NPDES permit application for Industrial Stormwater Discharges from the Gold Bond Building Products, LLC Shippingport Plant on June 28, 2022. The site is currently covered under the PAG-03 General Stormwater permit (PAR216143) but due to the site storing gypsum outdoors uncovered, exposed to precipitation, the site no longer qualifies for the PAG-03 general permit and must apply for the Individual permit.

The facility manufactures raw materials (gypsum) into wallboard. Most of the gypsum that the plant uses is stored in a large dome located behind the manufacturing building. The storage dome is incapable of storing the entire volume of gypsum and some of it is stored outside. This practice of exterior storage is the primary source and concern for contamination of stormwater runoff from the site. The external storage area is bermed, so that all runoff must flow to one corner of the storage area. The runoff first enters a primary settling pond (gypsum sedimentation pond), which has been designed for easy and frequent clean-out. From there the water enters a large sediment pond with an upright "castle" weir. There are no other wastewater discharges from the site.

Stormwater is conveyed from the site by a combination of sheet flow, stormwater drainage channels, and underground piping. Paved areas at the facility are sloped to route run-off into storm drains, which lead to stormwater drainage channels and pipes that drain into two storm water retention ponds and a gypsum sedimentation pond. A site diagram depicting the site stormwater drainage network is in Attachment A of this Fact Sheet. All of the stormwater at the facility is collected in a large retention basin at the front of the building and discharges to Haden Run, designated in 25 PA Code Chapter 93 as a Warm Water Fishery, via Outfall 002.

The site was last inspected on May 28, 2021, no violations were noted. The Permittee has no open violations.

Draft Permit Issuance is recommended.

Approve	Deny	Signatures	Date
X		 Adam Olesnanik / Project Manager	7/19/2022
X		 Michael E. Fifth, P.E. / Environmental Engineer Manager	7/29/2022

**Summary of Review**

Public Participation

DEP will publish notice of the receipt of the NPDES permit application and a tentative decision to issue the individual NPDES permit in the *Pennsylvania Bulletin* in accordance with 25 Pa. Code § 92a.82. Upon publication in the *Pennsylvania Bulletin*, DEP will accept written comments from interested persons for a 30-day period (which may be extended for one additional 15-day period at DEP's discretion), which will be considered in making a final decision on the application. Any person may request or petition for a public hearing with respect to the application. A public hearing may be held if DEP determines that there is significant public interest in holding a hearing. If a hearing is held, notice of the hearing will be published in the *Pennsylvania Bulletin* at least 30 days prior to the hearing and in at least one newspaper of general circulation within the geographical area of the discharge.

**Discharge, Receiving Waters and Water Supply Information**

Outfall No.	<u>002</u>	Design Flow (MGD)	<u>0</u>
Latitude	<u>40° 37' 43"</u>	Longitude	<u>-80° 25' 11"</u>
Quad Name	<u>Midland</u>	Quad Code	<u>1302</u>
Wastewater Description: <u>Stormwater</u>			
Receiving Waters	<u>Haden Run (WWF)</u>	Stream Code	<u>33523</u>
NHD Com ID	<u>99681430</u>	RMI	<u>0.36</u>
Drainage Area	<u>2.44</u>	Yield (cfs/mi <sup>2</sup> )	<u>0.009</u>
Q <sub>7-10</sub> Flow (cfs)	<u>0.0224</u>	Q <sub>7-10</sub> Basis	<u>USGS StreamStats</u>
Elevation (ft)	<u>690</u>	Slope (ft/ft)	<u>0.001</u>
Watershed No.	<u>20-D</u>	Chapter 93 Class.	<u>WWF</u>
Existing Use	<u></u>	Existing Use Qualifier	<u></u>
Exceptions to Use	<u></u>	Exceptions to Criteria	<u></u>
Assessment Status	<u>Impaired</u>		
Cause(s) of Impairment	<u>Siltation</u>		
Source(s) of Impairment	<u>Highway/Road/Bridge Runoff (Non-Construction Related), Removal Of Riparian Vegetation</u>		
TMDL Status	<u></u>	Name	<u></u>

**Development of Effluent Limitations**

<b>Outfall No.</b> <u>002</u>	<b>Design Flow (MGD)</b> <u>0</u>
<b>Latitude</b> <u>40° 37' 43"</u>	<b>Longitude</b> <u>-80° 25' 11"</u>
<b>Wastewater Description:</b> <u>Stormwater</u>	

**Technology-Based Limitations**

Stormwater Technology Limits

Outfall 002 will be subject to PAG-03 General Stormwater Permit conditions as a minimum requirement because the outfall receives stormwater. The SIC code for the site is 3275 (Manufacturing - Gypsum Products) and the corresponding appendix of the PAG-03 that would apply to the facility is Appendix N (Glass, Clay, Cement, Concrete and Gypsum Products). The reporting requirements applicable to stormwater discharges are shown in Table 1 below. Along with the monitoring requirements, sector specific BMPs included in Appendix N of the PAG-03 will also be included in Part C of the Draft Permit.

**Table 1: PAG-03 Appendix (N) Monitoring Requirements**

Parameter	Max Daily Concentration
pH	Monitor and Report
Total Suspended Solids (TSS)	Monitor and Report
Total Aluminum	Monitor and Report
Total Iron	Monitor and Report

Best Professional Judgment (BPJ) Technology Limitation Analysis

There are no Effluent Limitation Guidelines (ELGs) developed for stormwater discharges from this class of industrial activity. In the absence of any ELG's, technology limitations are developed based on Best Professional Judgment. In order to ensure that adequate BMPs are in place and effective, the Department proposes effluent limitations which are in line with the EPA's stormwater benchmark goals, based on EPA'S 2021 Multisector General Permit (MSGP) document. These values are typical of the Department's PAG-03 Action Levels; above which, permittees are required to reduce their discharge concentrations. A daily maximum Total Suspended Solids limitation of 100 mg/L is proposed, consistent with the MSGP and the PAG-03 benchmark goal. Since the gypsum piles will lack cover and be exposed to precipitation, the facility must achieve an actual effluent limit instead of a benchmark goal. In establishing effluent limitations on a case-by-case basis, various pollutant controls are considered. When evaluating appropriate BPJ limits for a permittee, the Department considers six factors as required by 40 CFR § 125.3.

The six factors are: (1) the age of the equipment and facility, (2) the process employed, (3) the engineering aspects of the application of various types of control technique, (4) process changes, (5) the cost of achieving such effluent reduction and, (6) non-water quality environmental impact (including energy requirements). Factors specific to each level of control technology include costs, pollutant reduction benefits and economic achievability. Each of these factors are discussed below as they relate to the Gold Bond Building Products Shippingport Plant.

1. Equipment and Facility Age – Stormwater pollutants are typically controlled through the implementation of Best Management Practices (BMPs) and housekeeping. Only in rare cases should an industrial wastewater treatment system be considered. Gold Bond Building Products may need to invest resources into specialized pollution control equipment including more sediment covers, catch basin sediment traps and/or structural controls if stormwater discharges from the site are contaminated by the exposed gypsum pile runoff.
2. The Process Employed – As mentioned in the previous paragraph, the Department anticipates compliance with the proposed effluent limitations through implementation of BMPs and housekeeping.
3. Engineering Aspects of Control Techniques – Additional BMPs and/or engineering solutions may be necessary if the facility is unable to meet its proposed effluent limitations. Although immediate BMP pollutant controls including sediment covers, increased frequency of changing covers and booms at catch basins, and more frequent street sweeping may be achieved without an engineer, additional structural solutions may require engineering design

expertise. If a treatment system is necessary to meet the effluent limits, the Department and Gold Bond Building Products will evaluate the engineering aspects of the project at that time.

4. Process Changes – There are no proposed operational changes at the site.
5. The Cost of Achieving Effluent Reduction – Compliance with the proposed effluent limitations is likely achievable through implementation of BMPs and housekeeping. As such, any expenses associated with BMP implementation are minimal.
6. Non-Water Quality Environmental Impacts (Including Energy Requirements) – There are no known non-water quality environmental impacts or energy requirements associated with the installation of BMPs. The proposed effluent limits are appropriate and attainable using widely available BMPs and housekeeping measures.

The proposed 100 mg/L TSS effluent limitation is readily achievable using a combination of site-specific BMPs and general housekeeping procedures such as the utilization of sediment covers over catch basins, increased frequency of changing covers and booms at the catch basins and outfall, removal of solids from the sedimentation basin, and street sweeping, silt fencing, and sediment traps. If Gold Bond Building Products is unable to meet the TSS effluent limitation, the construction of additional sedimentation technologies may be necessary.

**Water Quality-Based Limitations**

Stormwater WQBELs

Water quality analyses are typically performed under low-flow (Q7-10) conditions. Stormwater discharges occur at variable rates and frequencies but not however during Q7-10 conditions. Since the discharge from Outfall 002 is composed entirely of stormwater, a formal water quality analysis cannot be accurately conducted. Accordingly, water quality-based effluent limitations based on water quality analyses are not proposed.

**Anti-Backsliding**

The limitations in the site’s current permit, PAR216143, can be used pursuant to EPA’s anti-backsliding regulation, 40 CFR 122.44(l) and are displayed in Table 2 below.

**Table 2: PAR216143 Monitoring Requirements**

<b>Parameter</b>	<b>Max Daily Concentration</b>
pH	Monitor and Report
Total Suspended Solids (TSS)	Monitor and Report
Total Aluminum	Monitor and Report
Total Iron	Monitor and Report

**Proposed Effluent Limitations and Monitoring Requirements**

The proposed effluent monitoring requirements for Outfall 002 are displayed in Table 3 below, they are the most stringent values from the above effluent limitation development.

**Table 3: Proposed Effluent Monitoring Requirements**

<b>Parameter</b>	<b>Daily Maximum (mg/L)</b>	<b>Measurement Frequency</b>	<b>Sample Type</b>
Total Suspended Solids (TSS)	100.0	1/6 Months	Grab
Total Aluminum	Report	1/6 Months	Grab
Total Iron	Report	1/6 Months	Grab
pH (S.U.)	Report	1/6 Months	Grab

Tools and References Used to Develop Permit	
<input type="checkbox"/>	WQM for Windows Model (see Attachment [redacted])
<input type="checkbox"/>	Toxics Management Spreadsheet (see Attachment [redacted])
<input type="checkbox"/>	TRC Model Spreadsheet (see Attachment [redacted])
<input type="checkbox"/>	Temperature Model Spreadsheet (see Attachment [redacted])
<input type="checkbox"/>	Water Quality Toxics Management Strategy, 361-0100-003, 4/06.
<input type="checkbox"/>	Technical Guidance for the Development and Specification of Effluent Limitations, 362-0400-001, 10/97.
<input type="checkbox"/>	Policy for Permitting Surface Water Diversions, 362-2000-003, 3/98.
<input type="checkbox"/>	Policy for Conducting Technical Reviews of Minor NPDES Renewal Applications, 362-2000-008, 11/96.
<input type="checkbox"/>	Technology-Based Control Requirements for Water Treatment Plant Wastes, 362-2183-003, 10/97.
<input type="checkbox"/>	Technical Guidance for Development of NPDES Permit Requirements Steam Electric Industry, 362-2183-004, 12/97.
<input type="checkbox"/>	Pennsylvania CSO Policy, 385-2000-011, 9/08.
<input type="checkbox"/>	Water Quality Antidegradation Implementation Guidance, 391-0300-002, 11/03.
<input type="checkbox"/>	Implementation Guidance Evaluation & Process Thermal Discharge (316(a)) Federal Water Pollution Act, 391-2000-002, 4/97.
<input type="checkbox"/>	Determining Water Quality-Based Effluent Limits, 391-2000-003, 12/97.
<input type="checkbox"/>	Implementation Guidance Design Conditions, 391-2000-006, 9/97.
<input type="checkbox"/>	Technical Reference Guide (TRG) WQM 7.0 for Windows, Wasteload Allocation Program for Dissolved Oxygen and Ammonia Nitrogen, Version 1.0, 391-2000-007, 6/2004.
<input type="checkbox"/>	Interim Method for the Sampling and Analysis of Osmotic Pressure on Streams, Brines, and Industrial Discharges, 391-2000-008, 10/1997.
<input type="checkbox"/>	Implementation Guidance for Section 95.6 Management of Point Source Phosphorus Discharges to Lakes, Ponds, and Impoundments, 391-2000-010, 3/99.
<input type="checkbox"/>	Technical Reference Guide (TRG) PENTOXSD for Windows, PA Single Discharge Wasteload Allocation Program for Toxics, Version 2.0, 391-2000-011, 5/2004.
<input type="checkbox"/>	Implementation Guidance for Section 93.7 Ammonia Criteria, 391-2000-013, 11/97.
<input type="checkbox"/>	Policy and Procedure for Evaluating Wastewater Discharges to Intermittent and Ephemeral Streams, Drainage Channels and Swales, and Storm Sewers, 391-2000-014, 4/2008.
<input type="checkbox"/>	Implementation Guidance Total Residual Chlorine (TRC) Regulation, 391-2000-015, 11/1994.
<input type="checkbox"/>	Implementation Guidance for Temperature Criteria, 391-2000-017, 4/09.
<input type="checkbox"/>	Implementation Guidance for Section 95.9 Phosphorus Discharges to Free Flowing Streams, 391-2000-018, 10/97.
<input type="checkbox"/>	Implementation Guidance for Application of Section 93.5(e) for Potable Water Supply Protection Total Dissolved Solids, Nitrite-Nitrate, Non-Priority Pollutant Phenolics and Fluorides, 391-2000-019, 10/97.
<input type="checkbox"/>	Field Data Collection and Evaluation Protocol for Determining Stream and Point Source Discharge Design Hardness, 391-2000-021, 3/99.
<input type="checkbox"/>	Implementation Guidance for the Determination and Use of Background/Ambient Water Quality in the Determination of Wasteload Allocations and NPDES Effluent Limitations for Toxic Substances, 391-2000-022, 3/1999.
<input type="checkbox"/>	Design Stream Flows, 391-2000-023, 9/98.
<input type="checkbox"/>	Field Data Collection and Evaluation Protocol for Deriving Daily and Hourly Discharge Coefficients of Variation (CV) and Other Discharge Characteristics, 391-2000-024, 10/98.
<input type="checkbox"/>	Evaluations of Phosphorus Discharges to Lakes, Ponds and Impoundments, 391-3200-013, 6/97.
<input type="checkbox"/>	Pennsylvania's Chesapeake Bay Tributary Strategy Implementation Plan for NPDES Permitting, 4/07.
<input type="checkbox"/>	SOP: [redacted]
<input type="checkbox"/>	Other: [redacted]

ATTACHMENT A: Site Plan

