

Application Type New
Wastewater Type Sewage
Facility Type SRSTP

**NPDES PERMIT FACT SHEET
INDIVIDUAL SFTF/SRSTP**

Application No. PA0285293
APS ID 1107582
Authorization ID 1473444

Applicant, Facility and Project Information

| | | | |
|---------------------------|---|------------------|--|
| Applicant Name | <u>Sara Godley</u> | Facility Name | <u>Godley Properties SRSTP</u> |
| Applicant Address | <u>226 Rankin Road</u> <u>Washington, PA 15301-3182</u> | Facility Address | <u>370 Rankin Road</u> <u>Washington, PA 15301-3180</u> |
| Applicant Contact | <u>Ryan Allinder</u> | Facility Contact | <u></u> |
| Applicant Phone | <u>(724) 825-9723</u> | Facility Phone | <u></u> |
| Client ID | <u>383839</u> | Site ID | <u>870757</u> |
| SIC Code | <u>8800</u> | Municipality | <u>South Strabane Township</u> |
| SIC Description | <u>Private Households</u> | County | <u>Washington</u> |
| Date Application Received | <u>February 14, 2024</u> | WQM Required | <u>Yes</u> |
| Date Application Accepted | <u>February 20, 2024</u> | WQM App. No. | <u>6324400</u> |
| Project Description | <u>NPDES application to discharge from a proposed Single Residence Sewage Treatment Plant (SRSTP)</u> | | |

Summary of Review



PA DEP received an application package for an NPDES Permit for a new 400 GPD SRSTP to replace a malfunctioning onlot system. The facility will serve an existing three-bedroom dwelling on the property. The proposed facility will be in the South Strabane Twp., Washington County. The package submitted to DEP included an application for a water quality management permit, WQM Permit No. 6324400, which will be issued concurrently with the NPDES Permit.

The proposed discharge drains into an Unnamed Tributary to Little Chartiers Creek, a High-Quality Warm Water Fishery in Watershed 20-F.

NPDES Permit No. PA0285196 will approve the operation and discharge of treated sewage effluent from an SRSTP. The facility consists of:

- One Norweco Singulair Bio-Kinetic Model 960-500 Three-Chamber Extended Aeration treatment system.
- One Norweco Hydro-Kinetic Bio-Film Reactor for further treatment, with dosing chamber.
- One Norweco Model AT 1500 UV Disinfection system within the dosing chamber.
- Approximately 135 feet of outfall sewer draining to an Unnamed Tributary to Little Chartiers Creek (HQ-WWF).

The Singulair Hydro-Kinetic Bio-Film Reactor is approved by DEP for replacement of onlot systems.

| Approve | Deny | Signatures | Date |
|---------|------|---|--------------|
| x | |  Jack Price / Environmental Engineering Specialist | May 21, 2024 |
| x | |  Mahbuba Iasmin, Ph.D., P.E./Environmental Engineer Manager | May 21, 2024 |

Summary of Review

Sheet 3 of 4 in the plans submitted to DEP shows the system profile of the building sewers, treatment tanks, and outfall sewer as they conform to the requirements of the SFTF Manual. Additional details of the proposed treatment plant are discussed in the Internal Review & Recommendations document accompanying the WQM permit.

Act 537 Planning was approved for this project on January 16, 2024 filed under DEP Code No. 63956-23-019

Act 14 Notification was provided to South Strabane Twp. and Washington County in the letters both dated January 23, 2024.

The application was sealed by Fred Brant, an engineer licensed in the Commonwealth of Pennsylvania, License No. PA054366E.

Public Participation

DEP will publish notice of the receipt of the NPDES permit application and a tentative decision to issue the individual NPDES permit in the *Pennsylvania Bulletin* in accordance with 25 Pa. Code § 92a.82. Upon publication in the *Pennsylvania Bulletin*, DEP will accept written comments from interested persons for a 30-day period (which may be extended for one additional 15-day period at DEP's discretion), which will be considered in making a final decision on the application. Any person may request or petition for a public hearing with respect to the application. A public hearing may be held if DEP determines that there is significant public interest in holding a hearing. If a hearing is held, notice of the hearing will be published in the *Pennsylvania Bulletin* at least 30 days prior to the hearing and in at least one newspaper of general circulation within the geographical area of the discharge.

Discharge and Stream Data – 2 - Receiving Waters and PWS

| Discharge, Receiving Waters and Water Supply Information | | | |
|--|---|------------------------------|---|
| Outfall No. | <u>001</u> | Design Flow (MGD) | <u>0.0004</u> |
| Latitude | <u>40° 9' 29.35"</u> | Longitude | <u>-80° 8' 48.05"</u> |
| Quad Name | <u>Washington East</u> | Quad Code | <u>40080B2</u> |
| Wastewater Description: <u>Sewage Effluent</u> | | | |
| Receiving Waters | <u>Unnamed Tributary of Little Chartiers Creek (HQ-WWF)</u> | Stream Code | <u>UNT 37013</u> |
| NHD Com ID | <u>99694588</u> | RMI | <u>0.68</u> |
| Drainage Area | <u>1.55 mi²</u> | Yield (cfs/mi ²) | <u>0.0094</u> |
| Q ₇₋₁₀ Flow (cfs) | <u>0.01452</u> | Q ₇₋₁₀ Basis | <u>USGS StreamStats (Attachment 1)</u> |
| Elevation (ft) | <u>1040.67</u> | Slope (ft/ft) | <u>0.0091</u> |
| Watershed No. | <u>20-F</u> | Chapter 93 Class. | <u>HQ-WWF</u> |
| Existing Use | <u></u> | Existing Use Qualifier | <u></u> |
| Exceptions to Use | <u></u> | Exceptions to Criteria | <u></u> |
| Assessment Status | <u>Attaining Use(s)</u> | | |
| Cause(s) of Impairment | <u></u> | | |
| Source(s) of Impairment | <u></u> | | |
| TMDL Status | <u>Final, Final</u> | Name | <u>Chartiers Creek, Chartiers Creek Watershed</u> |
| Background/Ambient Data | | Data Source | |
| pH (SU) | <u></u> | | <u></u> |
| Temperature (°F) | <u></u> | | <u></u> |
| Hardness (mg/L) | <u></u> | | <u></u> |
| Other: | <u></u> | | <u></u> |
| Nearest Downstream Public Water Supply Intake | <u>West View Water Authority PWSID 5020043 (40 MGD)</u> | | |
| PWS Waters | <u>Ohio River</u> | Flow at Intake (cfs) | <u>4,730</u> |
| PWS RMI | <u>35.38</u> | Distance from Outfall (mi) | <u>42.17 River Miles</u> <u>23.40 Linear Miles</u> |

Changes Since Last Permit Issuance: N/A, this is a proposed facility

Other Comments: N/A

Technology-Based Limitations (TBELs)

The following effluent limitations and monitoring requirements, at a minimum, will be established in all new and renewed SFTF permits based on the requirements of DEP’s “Standard Operating Procedure (SOP) for Clean Water Program New and Reissuance Small Flow Treatment Facility Individual NPDES Permit Application” (SOP No. BCW-PMT-003, Version 1.8, Final, November 9, 2012, Revised May 17, 2019).

| Parameter | Avg | IMAX | Sample Type | Frequency: SFTFs | Frequency: SRSTPs |
|-----------------------------|---|----------|---------------------------------------|------------------|-------------------|
| Flow (GPD) | Report | XXX | Estimate (SRSTPs) Measured (SFTFs) | 1/month | 1/year |
| BOD5 (mg/L) | 10 | 20 | Grab | 1/month | 1/year |
| TSS (mg/L) | 10 | 20 | Grab | 1/month | 1/year |
| pH* | 6.0 S.U. Inst. Min. | 9.0 S.U. | Grab | 1/month | 1/year |
| TRC (mg/L) | Report for SRSTPs; Use TRC Spreadsheet to determine WQBELs or 0.02 mg/L for SFTFs | | Grab | 1/month | 1/year |
| Fecal Coliform (No./100 ml) | 200 Geometric Mean (SFTFs) / Average (SRSTPs) | | Grab | 1/month | 1/year |

* Technology-Based effluent limits for pH will be imposed based upon Federal Regulation 133.102(c) and State Regulation 95.2(1).

Comments: This is a new SRSTP with UV disinfection. The facility will not be required to measure TRC due to the absence of chlorination facilities.

Anti-Degradation Best Available Combination of Technology (ABACT) TBELs

Outfall 001 discharges to an Unnamed Tributary to Little Chartiers Creek, a HQ-WWF. The proposed discharge for this SRSTP is a treated residential sewage flow of 400 GPD. This discharge is proposed in order to repair a malfunctioning onlot system at an existing dwelling.

The following Antidegradation Best Available Combination of Technologies (ABACT) effluent limits, at a minimum, will be established based on the requirements of DEP’s “Water Quality Antidegradation Implementation Guidance” (Doc. No. 391-0300-002; November 29, 2003).

| Parameter | Treatment Process Performance Expectations (mg/L) | | |
|---------------------------------------|--|------------------|-------------|
| | <2,000 gpd | 2,000-50,000 gpd | >50,000 gpd |
| CBOD ₅ (May 1 – Oct. 31) | 10 | 10 | 10 |
| CBOD ₅ (Nov. 1 – Apr. 30) | 20 | 20 | 10 |
| Suspended Solids | 20 | 10 | 10 |
| NH ₃ -N (May 1 – Oct. 31) | 5.0 | 3.0 | 1.5 |
| NH ₃ -N (Nov. 1 – Apr. 30) | 15.0 | 9.0 | 4.5 |
| Effective disinfection | Disinfection should be accomplished using a method that leaves no detectable residual. Disinfection using ultra-violet light or other non-chlorine based systems is encouraged and must be considered. | | |
| Other parameters, as needed | <i>Determined by the size and characteristics of the proposed discharge, may include – NO₂/NO₃-N, Total Phosphorus, Copper, Lead, Zinc</i> | | |

Development of effluent limitations:

Effluent limitations were derived from ABACT in the Antidegradation Implementation Guidance and from SFTF SOP BCW-PMT-003; for each parameter, the more stringent of either document was selected as the limitation.

Flow monitoring:

Flow monitoring will be placed in this permit in accordance with BCW-PMT-003. The reporting frequency set forth is once a year and sample type is "Estimate" (for SRSTP.)

Biochemical Oxygen Demand (BOD₅)

An average annual BOD₅ limit of 10 mg/l and IMAX limit of 20 mg/l will be placed in this permit. These limits are consistent with the SOP and are more stringent than antidegradation guidance.

Total Suspended Solids (TSS)

An average annual BOD₅ limit of 10 mg/l and IMAX limit of 20 mg/l will be placed in this permit. These limits are consistent with the SOP and are more stringent than the antidegradation ABACT.

Fecal Coliform:

A year-round annual average and IMAX limit of 200 No./100 ml will be placed in this permit. This limit is consistent with the SOP and antidegradation ABACT.

Ammonia Nitrogen:

An average annual Summer limit of 5.0 mg/l and IMAX limit of 10.0 mg/l will be placed in this permit. An average annual Summer limit of 5.0 mg/l and IMAX limit of 10.0 mg/l will be placed in this permit. The SOP for SFTFs does not require monitoring of Ammonia-Nitrogen. Antidegradation ABACT sets a limit of 5.0 mg/L in summer months, and 15.0 mg/L in winter months. The ABACT is the more stringent, therefore ABACT is chosen.

pH:

Daily minimum pH of 6.0 and Daily Maximum pH of 9.0 S.U. will be applied in this permit per Pa Code 25 Ch. 95.2(1).

UV:

The SOP indicates that it is not necessary to require UV intensity or transmittance monitoring in the permit for SRSTPs/SFTFs. This is also consistent with Antidegradation ABACT requirements for effective disinfection.

Additional Considerations:

Monitoring Frequency

Chapter 6.B. of the Permit Writer’s Manual (DEP Document No. 386-0400-001, Revised June 28, 2023) describes the self-monitoring requirements for NPDES Permits. Table 6-3 outlines minimum flow-based monitoring frequencies. The SOP does not list a minimum frequency for Ammonia-Nitrogen monitoring, so Table 6-3 was used to determine 2/yr monitoring frequency.

Chapter 6.B. lists impact of discharge on receiving stream and the expense of monitoring as a factor that should be considered in establishing self-monitoring requirements. For this discharge to a High-Quality stream, the 2/yr monitoring of CBOD₅, Total Suspended Solids, Fecal Coliform, pH, and Flow was selected.

2/yr monitoring is established for CBOD₅, Total Suspended Solids, pH, Flow, and Fecal Coliform based on the following factors:

- The impact and quality of the receiving stream.
- The fact that an effluent sample will be collected at least twice per year due to Ammonia-Nitrogen monitoring per Table 6-3.

Table 6-3 – Self-Monitoring Requirements for SEWAGE Discharges

| Plant Design Flow (MGD) | Flow Monitoring | C-BOD ₅ or BOD ₅ | Suspended Solids | pH | Fecal Coliform | Chlorine Residual | NH ₃ -N | Phosphorus | DO | Toxics |
|--------------------------------------|---|--|------------------|------------|----------------|-------------------|--------------------|------------|----------|------------|
| Single Residence (Individual Permit) | 2/year by estimate | 2/year* | 2/year* | 1/month h* | 2/year* | 1/month* | 2/year* | 2/year* | 2/year* | N/A |
| .0005 to .002 | weekly, using average pump rate or weir (a) | 1/month* | 1/month* | daily* | 1/month* | daily* | 1/month* | 1/month* | daily* | N/A |
| .002 to .01 | weekly, using average pump rate or weir (a) | 2/month* | 2/month* | daily* | 2/month* | daily* | 2/month* | 2/month* | daily* | N/A |
| 0.01 to 0.1 | weekly, using average pump rate or weir (a) | 2/month* | 2/month* | daily* | 2/month* | daily* | 2/month* | 2/month* | Daily* | 1/week* |
| 0.1 to 1.0 | meter | 1/week** | 1/week** | daily* | 1/week* | daily* | 1/week** | 1/week** | daily* | 1/week**** |
| 1.0 to 5.0 | meter | 2/week*** | 2/week*** | daily* | 2/week* | daily* | 2/week*** | 2/week*** | daily* | 1/week**** |
| 5.0 to 25.0 | meter | daily*** | daily*** | daily* | daily* | 1/shift* | daily*** | daily*** | daily* | 1/week**** |
| over 25.0 | meter | daily*** | daily*** | 1/shift* | daily* | 1/shift* | 1/shift*** | 1/shift*** | 1/shift* | 1/week**** |

* Grab sample-these should be most representative of the effluent and are to be taken at a time when the normal daily maximum flow would reach the sampling point.

** 8-hour composite sample.

*** 24-hour composite sample.

**** Same sample type as for Industrial Process Wastewater (See Table 6-4).

DEP Classification of Technology

The technical specifications for the Singulair Bio-Kinetic Model 960-1000 and the Hydro-Kinetic Bio-Film systems are NSF approved to treat 500 gpd and 800 gpd respectively. Furthermore, this combination of systems is classified by the DEP for use as an alternative onlot sewage systems when constructed and operated for flows ranging between 400 gpd and 800 gpd. The alternate technology listings may be found on the following web page:

<https://www.dep.pa.gov/Business/Water/CleanWater/WastewaterMgmt/Act537/OnlotDisposal/Pages/OnlotAlternateTechnologyListings.aspx>

Treatment Facility Summary

Treatment Facility Name: Godley Properties SRSTP

| WQM Permit No. | Issuance Date |
|----------------|---------------|
| 6324400 | Processing |

| Waste Type | Degree of Treatment | Process Type | Disinfection | Avg Annual Flow (MGD) |
|------------|---------------------|-------------------|--------------|-----------------------|
| Sewage | Tertiary | Extended Aeration | Ultraviolet | 0.0004 |

| Hydraulic Capacity (MGD) | Organic Capacity (lbs/day) | Load Status | Biosolids Treatment | Biosolids Use/Disposal |
|--------------------------|----------------------------|----------------|---------------------|---------------------------|
| 0.0004 | 0.90 | Not Overloaded | Aerobic Tank | None/Semi Annual Cleaning |

Proposed Effluent Limitations and Monitoring Requirements

The limitations and monitoring requirements specified below are proposed for the draft permit, and reflect the most stringent limitations amongst technology, water quality and BPJ. Instantaneous Maximum (IMAX) limits are determined using multipliers of 2 (conventional pollutants) or 2.5 (toxic pollutants). Sample frequencies and types are derived from the "NPDES Permit Writer's Manual" (362-0400-001), SOPs and/or BPJ.

Outfall 001, Effective Period: Permit Effective Date through Permit Expiration Date.

| Parameter | Effluent Limitations | | | | | | Monitoring Requirements | |
|-----------------------------|-------------------------------------|-------------------|-----------------------|--------------------|---------|---------------------|--|----------------------------|
| | Mass Units (lbs/day) ⁽¹⁾ | | Concentrations (mg/L) | | | | Minimum ⁽²⁾ Measurement Frequency | Required Sample Type |
| | Average Monthly | Average Weekly | Minimum | Average Monthly | Maximum | Instant. Maximum | | |
| Flow (MGD) | Report | XXX | XXX | XXX | XXX | XXX | 2/year | Estimate |
| pH (S.U.) | XXX | XXX | 6.0 Inst Min | XXX | XXX | 9.0 | 2/year | Grab |
| CBOD5 | XXX | XXX | XXX | 10.0 | XXX | 20.0 | 2/year | Grab |
| TSS | XXX | XXX | XXX | 10.0 | XXX | 20.0 | 2/year | Grab |
| Fecal Coliform (No./100 ml) | XXX | XXX | XXX | 200 Geo Mean | XXX | XXX | 2/year | Grab |
| Ammonia Nov 1 - Apr 30 | XXX | XXX | XXX | 15.0 | XXX | 30.0 | 2/year | Grab |
| Ammonia May 1 - Oct 31 | XXX | XXX | XXX | 5.0 | XXX | 10.0 | 2/year | Grab |

Compliance Sampling Location: Outfall 001

Other Comments:

Attachment 1-StreamStats Report

StreamStats Upstream Report

Region ID: PA
Workspace ID: PA20240517184400102000
Clicked Point (Latitude, Longitude): 40.15774, -80.14595
Time: 2024-05-17 14:44:21 -0400



Discharge for PA0285293 Outlet Elevation: 1040.67

Collapse All

Basin Characteristics

| Parameter Code | Parameter Description | Value | Unit |
|----------------|---|-------|--------------|
| DRNAREA | Area that drains to a point on a stream | 1.55 | square miles |
| ELEV | Mean Basin Elevation | 1212 | feet |

› Low-Flow Statistics

Low-Flow Statistics Parameters [Low Flow Region 4]

| Parameter Code | Parameter Name | Value | Units | Min Limit | Max Limit |
|----------------|----------------------|-------|--------------|-----------|-----------|
| DRNAREA | Drainage Area | 1.55 | square miles | 2.26 | 1400 |
| ELEV | Mean Basin Elevation | 1212 | feet | 1050 | 2580 |

Low-Flow Statistics Disclaimers [Low Flow Region 4]

One or more of the parameters is outside the suggested range. Estimates were extrapolated with unknown errors.

Low-Flow Statistics Flow Report [Low Flow Region 4]

| Statistic | Value | Unit |
|-------------------------|--------|--------------------|
| 7 Day 2 Year Low Flow | 0.0467 | ft ³ /s |
| 30 Day 2 Year Low Flow | 0.0882 | ft ³ /s |
| 7 Day 10 Year Low Flow | 0.0142 | ft ³ /s |
| 30 Day 10 Year Low Flow | 0.0294 | ft ³ /s |
| 90 Day 10 Year Low Flow | 0.059 | ft ³ /s |

Low-Flow Statistics Citations

Stuckey, M.H., 2006, Low-flow, base-flow, and mean-flow regression equations for Pennsylvania streams: U.S. Geological Survey Scientific Investigations Report 2006-5130, 84 p. (<http://pubs.usgs.gov/sir/2006/5130/>)

USGS Data Disclaimer: Unless otherwise stated, all data, metadata and related materials are considered to satisfy the quality standards relative to the purpose for which the data were collected. Although these data and associated metadata have been reviewed for accuracy and completeness and approved for release by the U.S. Geological Survey (USGS), no warranty expressed or implied is made regarding the display or utility of the data for other purposes, nor on all computer systems, nor shall the act of distribution constitute any such warranty.

USGS Software Disclaimer: This software has been approved for release by the U.S. Geological Survey (USGS). Although the software has been subjected to rigorous review, the USGS reserves the right to update the software as needed pursuant to further analysis and review. No warranty, expressed or implied, is made by the USGS or the U.S. Government as to the functionality of the software and related material nor shall the fact of release constitute any such warranty. Furthermore, the software is released on condition that neither the USGS nor the U.S. Government shall be held liable for any damages resulting from its authorized or unauthorized use.